



972 980 198



WhatsApp

699 593 253



info@ilogo.es



www.ilogo.es

OPTONICA

LED Lighting for Everyone

Catalogue 2024_{v2}



PORTABLE POWER STATION

PURE SINE WAVE AC OUTPUT

OPTONICA
 SOLAR


400W

Cell Capacity: 400W/320Wh
 DC Input: 12V-24V/0-10A (120W Max)
 AC Output: 230Vac 400W
 DC Output: 12V/0-10A
 Cigar Socket Output: 13.3V/10A
 USB-A Output: 5V/2.4A
 USB-C Output: 20V/3A max
 LED Flashlight: 3W

SKU: 9418

600W

Cell Capacity: 600W/512Wh
 DC Input: 12V-24V/0-10A (120W Max)
 AC Output: 230Vac 600W
 DC Output: 12V/0-10A
 Cigar Socket Output: 13.3V/10A
 USB-A Output: 5V/2.4A
 USB-C Output: 20V/5A max
 LED Flashlight: 3W

SKU: 9419

1000W

Cell Capacity: 1000W/1036.8Wh
 DC Input: 12V-24V/0-10A (200W Max)
 AC Output: 230Vac 1000W
 DC Output: 12V/0-10A
 Cigar Socket Output: 13.3V/10A
 USB-A Output: 5V/2.4A
 USB-C Output: 20V/5A max
 LED Flashlight: 3W

SKU: 9420

2000W

Cell Capacity: 2000W/2096Wh
 DC Input: 12V-65V/0-10A (650W Max)
 AC Output: 230Vac 2000W
 DC Output: 12V-65V/0-10A
 Cigar Socket Output: 13V/10A
 USB-A Output: 5V/2.4A
 USB-C Output: 20V/5A max
 LED Flashlight: 3W
 Wireless Charge: (20W Max)

SKU: 9421


Bags for Portable Starion

For 400W - SKU: 9429
 For 600W - SKU: 9428
 For 1000W - SKU: 9422
 For 2000W - SKU: 9423


IDEAL FOR OUTDOOR & RECREATION
OPTONICA
 SOLAR


MONOCRYSTALLINE PORTABLE SOLAR PANEL 120W

Convert Efficiency: up to 21%
 ETFE high Light Transmittance Film
 Output: 1. MC4 18V/6.6A Max
 2. USB-A QC 3.0 24W Max
 3. Type-C: PD45W Max
 Material: PET Monocrystalline solar panel
 Intelligent charging chip

SKU: 9400


MONOCRYSTALLINE PORTABLE SOLAR PANEL 200W

Convert Efficiency: up to 21%
 ETFE high Light Transmittance Film
 Output: 1. MC4 18V/11.1A Max
 2. USB-A QC 3.0 24W Max
 3. Type-C: PD45W Max
 Material: PET Monocrystalline solar panel
 Intelligent charging chip

SKU: 9401


MONOCRYSTALLINE PORTABLE SOLAR PANEL 400W

Convert Efficiency: up to 21%
 ETFE high Light Transmittance Film
 Output: MC4 36V/6.6A Max
 Material: PET Monocrystalline solar panel
 Intelligent charging chip

SKU: 9402

OPTONICA
 SOLAR

OPTONICA PV SOLAR PANELS

OPTONICA
 SOLAR

OPTONICA PV SOLAR PANELS

**MONOCRYSTALLINE
SOLAR PV MODULE**
410W

PV Model	FV410-A1	SKU:9404
Rated Maximum Power (Pmax)	410W	
Power Sorting	0~+5W	
Voltage at Pmax (Vmp)	31.40V	
Current at Pmx (IMP)	13.06A	
Open-Circuit Current (Voc)	37.30V	
Short-Circuit Current (Isc)	13.93A	
Pv Module Clasification	CLASS II	
Maximum System Voltage	1500V	
Maximum Series Fuse Rating	25A	
Operating Temperature	-40~85° C	
Dimensions (mm)	1722x1134x30mm	
Pmax /Voc / Isc Tolerance	± 3%	

Tested at STC:1000W/m ; AM1.5; Cell temperature 25C°


**MONOCRYSTALLINE
SOLAR PV MODULE**
450W

PV Model	FV450-A1	SKU:9403
Rated Maximum Power (Pmax)	450W	
Power Sorting	0~+5W	
Voltage at Pmax (Vmp)	42.10V	
Current at Pmx (IMP)	10.69A	
Open-Circuit Current (Voc)	49.84V	
Short-Circuit Current (Isc)	11.20A	
Pv Module Clasification	CLASS II	
Maximum System Voltage	1500V	
Maximum Series Fuse Rating	15A	
Operating Temperature	-40~85° C	
Dimensions (mm)	2094x1038x35mm	
Pmax /Voc / Isc Tolerance	± 3%	

Tested at STC:1000W/m ; AM1.5; Cell temperature 25C°


Micro Inverter

1. Input: 2*MC4 / PV 2*210-400W
2. Output: 230Vac 600W
3. MPPT 25-55V 2*13A
4. Unit: 212*230*40mm 3.15kg
5. IP67


SKU: 9431
SKU: 9424

SKU: 9425

SKU: 9426

SKU: 9427


PV SOLAR PANELS



MONOCRYSTALLINE SOLAR PV MODULE

410W

PV Model	FV410-A1	SKU:9406
Rated Maximum Power (Pmax)	410W	
Power Sorting	0~+5W	
Voltage at Pmax (Vmp)	34.89V	
Current at Pmx (IMP)	11.76A	
Open-Circuit Current (Voc)	41.90V	
Short-Circuit Current (Isc)	12.47A	
Pv Module Clasification	CLASS II	
Maximum System Voltage	1500V	
Maximum Series Fuse Rating	20A	
Operating Temperature	-40~85° C	
Dimensions (mm)	1754x1096x30mm	
Pmax /Voc / Isc Tolerance	± 3%	

Tested at STC:1000W/m ; AM1.5; Cell temperature 25C°



SKU: 9451,9453



4 mm² ; 6 mm²

SKU: 9452,9454



4 mm² ; 6 mm²

SKU: 9457



SKU: 9458



PV SOLAR PANELS



MONOCRYSTALLINE SOLAR PV MODULE

450W

PV Model	FV450-A1	SKU:9407
Rated Maximum Power (Pmax)	450W	
Power Sorting	0~+5W	
Voltage at Pmax (Vmp)	41.30V	
Current at Pmx (IMP)	10.90A	
Open-Circuit Current (Voc)	49.70V	
Short-Circuit Current (Isc)	11.50A	
Pv Module Clasification	CLASS II	
Maximum System Voltage	1500V	
Maximum Series Fuse Rating	20A	
Operating Temperature	-40~85° C	
Dimensions (mm)	2108x1048x35mm	
Pmax /Voc / Isc Tolerance	± 3%	

Tested at STC:1000W/m ; AM1.5; Cell temperature 25C°



SKU: 9455 ; 9456



SKU: 9434



PV POWER OPTIMIZER



SKU: 9464

PV SOLAR PANELS



MONOCRYSTALLINE SOLAR PV MODULE

445W

PV Model	FV445-A1	SKU:9408
Rated Maximum Power (Pmax)		445W
Power Sorting		0~+5W
Voltage at Pmax (Vmp)		45.09V
Current at Pmx (IMP)		12.57A
Open-Circuit Current (Voc)		37.54V
Short-Circuit Current (Isc)		11.86A
Pv Module Clasification		CLASS I
Maximum System Voltage		1500V
Maximum Series Fuse Rating		20A
Operating Temperature		-40~85° C
Dimensions (mm)		1894x1096x30mm
Pmax /Voc / Isc Tolerance		± 3%

Tested at STC:1000W/m ; AM1.5; Cell temperature 25C°



PV SOLAR PANELS



MONOCRYSTALLINE SOLAR PV MODULE

550W

PV Model	FV550-A1	SKU:9405
Rated Maximum Power (Pmax)		550W
Power Sorting		0~+5W
Voltage at Pmax (Vmp)		42.20V
Current at Pmx (IMP)		13.04A
Open-Circuit Current (Voc)		49.80V
Short-Circuit Current (Isc)		13.94A
Pv Module Clasification		CLASS II
Maximum System Voltage		1500V
Maximum Series Fuse Rating		25A
Operating Temperature		-40~85° C
Dimensions (mm)		2279x1134x35mm
Pmax /Voc / Isc Tolerance		± 3%

Tested at STC:1000W/m ; AM1.5; Cell temperature 25C°



PV SOLAR PANELS



MONO HALF-CUT MODULE BLACK FRAME **405W**

UL-405-108HV
MBB 182mm Cell

PV Model	SKU:9411
Rated Maximum Power (Pmax)	405W
Power Sorting	0~+5W
Voltage at Pmax (Vmp)	31.3V
Current at Pmx (IMP)	12.94A
Open-Circuit Current (Voc)	37.3V
Short-Circuit Current (Isc)	13.69A
Module Efficiency STC	20.74
Maximum System Voltage	1500V
Maximum Series Fuse Rating	25A
Operating Temperature	-40~85° C
Dimensions (mm)	2279/1134/35mm
Pmax /Voc / Isc Tolerance	± 3%

Tested at STC:1000W/m ; AM1.5; Cell temperature 25C°




Lower LCOE
 Lower shading and resistive loss
 Lower temperature coefficient



Anti-PID(potential induced degradation)
 Passed anti-PID test under 85% damp heat,
 85% relative humidity for 96 hours



PV SOLAR PANELS



MONO HALF-CUT MODULE SILVER FRAME **455W**

UL-455M-144HV
MBB 166mm Cell

PV Model	SKU:9410
Rated Maximum Power (Pmax)	455W
Power Sorting	0~+5W
Voltage at Pmax (Vmp)	41.1V
Current at Pmx (IMP)	11.07A
Open-Circuit Current (Voc)	49.9V
Short-Circuit Current (Isc)	11.64A
Module Efficiency STC	20.93
Maximum System Voltage	1500V
Maximum Series Fuse Rating	20A
Operating Temperature	-40~85° C
Dimensions (mm)	2094x1038x35mm
Pmax /Voc / Isc Tolerance	± 3%

Tested at STC:1000W/m ; AM1.5; Cell temperature 25C°



Lower LCOE
 Lower shading and resistive loss
 Lower temperature coefficient



Anti-PID(potential induced degradation)
 Passed anti-PID test under 85% damp heat,
 85% relative humidity for 96 hours



PV SOLAR PANELS



BIFACIAL MONO PERC MODULE

550W

UL-550M-144HV
MBB 182mm Cell

PV Model	SKU:9412
Rated Maximum Power (Pmax)	550W
Power Sorting	0~+5W
Voltage at Pmax (Vmp)	41.9V
Current at Pmx (IMP)	13.13A
Open-Circuit Current (Voc)	50V
Short-Circuit Current (Isc)	13.75A
Module Efficiency STC	21.28
Maximum System Voltage	1500V
Maximum Series Fuse Rating	30A
Operating Temperature	-40~85° C
Dimensions (mm)	2279/1134/35mm
Pmax /Voc / Isc Tolerance	± 3%

Tested at STC:1000W/m ; AM1.5; Cell temperature 25C°




Lower LCOE
 Lower shading and resistive loss
 Lower temperature coefficient



Anti-PID(potential induced degradation)
 Passed anti-PID test under 85% damp heat,
 85% relative humidity for 96 hours

PRODUCT
 GUARANTEE
 UP TO
25
 YEARS

PV SOLAR PANELS



DOUBLE-GLASS BIFACIAL MODULE

N-TYPE 570 TOPCON

UL-570M-144DG
MBB 182mm Cell

PV Model	SKU:9413
Rated Maximum Power (Pmax)	570W
Power Sorting	0~+5W
Voltage at Pmax (Vmp)	42.2/
Current at Pmx (IMP)	13.51
Open-Circuit Current (Voc)	50.7
Short-Circuit Current (Isc)	14.23
Module Efficiency STC	22.07%
Maximum System Voltage	1500V
Maximum Series Fuse Rating	30A
Operating Temperature	-40~85° C
Dimensions (mm)	2278/1134/35mm
Pmax /Voc / Isc Tolerance	± 3%

Tested at STC:1000W/m ; AM1.5; Cell temperature 25C°



Lower LCOE
 Lower shading and resistive loss
 Lower temperature coefficient



Anti-PID(potential induced degradation)
 Passed anti-PID test under 85% damp heat,
 85% relative humidity for 96 hours

PRODUCT
 GUARANTEE
 UP TO
25
 YEARS



Double Headed Electric Photovoltaic Brush 5.5M Glass Fiber Handle AC220 or 110V AC

Applicable Voltage	110-240V	Material	Alu/Carbon fiber
Utilization Voltage	24V	Wall thickness	1-1.2mm
Power	52.8W*2	Diameter	43mm
Speed	128rpm	Length	5.5m
Torsion	1.2 N.m	Brush Size	280mm

SKU: 9656



SKU: 9657 - DC24 Supply(Battery)



Accessories

Battery*1
Adapter*1
Water pipe and accessories*1
Backpack*1
Push button switch spring wire*1
Telescopic rod*1
Brush head assembly*1 set
(including 1 pcs brush discs)



Solar Panel Cleaning Robot - Watering



SINGLE SOLAR PANEL CLEANING ROBOT 2384mm 150W 24V10Ah

SKU: 9658

PV Module Range	2384mm Single PV Panel
Traveling Speed	15-20 m/min
Generator Power	150W
Water Used Per Hour	330L/H
Solar Panel(W)	27W
Battery Capacity(Ah)	24V/10Ah
Cleaning Mode	Dry/Watering Cleaning
Other Functions	Speed Adjust/Direction Adjust

DOUBLE SOLAR PANEL CLEANING ROBOT 2384mm 200W 24V20Ah

SKU: 9659

PV Module Range	2384mm Double PV Panel
Traveling Speed	15-20 m/min
Generator Power	200W
Water Used Per Hour	330L/H
Solar Panel(W)	27W
Battery Capacity(Ah)	24V/10Ah
Cleaning Mode	Dry/Watering Cleaning
Other Functions	Speed Adjust/Direction Adjust



ONE-PHASE HYBRID INVERTERS

3.6kW

5kW

6kW



Model	SKU: 9446	SKU: 9437	SKU: 9438
Battery Input Data			
Battery Type	Lead-acid or Lithium-ion		
Battery Voltage Range (V)	40-60		
Max. Charging Current (A)	90	120	135
Max. Discharging Current (A)	90	120	135
Charging Strategy for Li-ion Battery	Self-adaption to BMS		
PV String Input Data			
Max. DC Input Power (W)	4680	6500	7800
Max. DC Input Voltage (V)	500	(125-500)	
Start-up Voltage (V)	125		
MPPT Voltage Range (V)	150-425		
Rated DC Input Voltage (V)	370		
Max. Operating PV Input Current (A)	13+13		
Max. Input Short-Circuit Current (A)	17+17		
No. of MPP Trackers/ No. of Strings per MPP Tracker	2/1+1		
AC Input/Output Data			
Rated AC Input/Output Active Power (W)	3600	5000	6000
Max. AC Input/Output Apparent Power (VA)	3960	5500	6000
Rated AC Input/Output Current (A)	16.4/15.7	22.7/21.7	27.3/26.1
Max. AC Input/Output Current (A)	18/17.2	25/23.9	30/28.7
Max. Continuous AC Passthrough (grid to load) (A)	35	40	40
Peak Power (off-grid) (W)	2 times of rated power, 10s		
Power Factor Adjustment Range	0.8 leading to 0.8 lagging		
Rated Input/Output Voltage/Range (V)	220/230 0.85Un-1.1Un		
Rated Input/Output Grid Frequency/Range(Hz)	50/45-55 , 60/55-65		
Grid Connection Form	L+N+PE		
Total Current Harmonic Distortion THDi	<3% (of nominal power)		
DC Injection Current	<0.5% In		



THREE-PHASE HYBRID INVERTERS

8kW

10kW



Model	SKU: 9436	SKU: 9435
Battery Input Data		
Battery Type	Lead-acid or Li-Ion	
Battery Voltage Range (V)	40~60	
Max. Charging Current (A)	190	210
Max. Discharging Current (A)	190	210
External Temperature Sensor	Yes	
Charging Curve	3 Stages / Equalization	
Charging Strategy for Li-Ion Battery	Self-adaption to BMS	
PV String Input Data		
Max. DC Input Power (W)	10400	13000
Rated PV Input Voltage (V)	550 (160~800)	
Start-up Voltage (V)	160	
MPPT Voltage Range (V)	200-650	
Full Load DC Voltage Range (V)	350-650	
PV Input Current (A)	13+13	26+13
Max. PV I _{sc} (A)	17+17	34+17
No. of MPP Trackers	2	
No. of Strings per MPP Tracker	1	2+1
AC Output Data		
Rated AC Output and UPS Power (W)	8000	10000
Max. AC Output Power (W)	8800	11000
AC Output Rated Current (A)	12.1/11.6	15.2/14.5
Max. AC Current (A)	18.2/17.4	22.7/21.7
Max. Continuous AC Passthrough (A)	45	
Peak Power (off grid)	2 time of rated power, 10 S	
Power Factor	0.8 leading to 0.8 lagging	
Output Frequency and Voltage	50/60Hz; 3L/N/PE 220/380, 230/400Vac	
Grid Type	Three Phase	
Total Harmonic Distortion (THD)	<3% (of nominal power)	
DC current injection	<0.5% In	

THREE-PHASE HYBRID INVERTERS

20kW 30kW 50kW



Model	SKU: 9442	SKU: 9443	SKU: 9444
Battery Input Data			
Battery Type	Lithium-ion		
Battery Voltage Range (V)	160~700	160-800	
Max. Charging Current (A)	37	50+50	
Max. Discharging Current (A)	37	50+50	
Number of Battery Input	1	2	
Charging Strategy for Li-Ion Battery	Self-adaption to BMS		
PV String Input Data			
Max. DC Input Power (W)	26000	39000	65000
Max. DC Input Voltage (V)	1000		
Start-up Voltage (V)	180		
MPPT Range (V)	150-850		
Full Load DC Voltage Range (V)	500-850	360-850	450-850
Rated DC Input Voltage (V)	600		
PV Input Current (A)	26+26	36+36+36	36+36+36+36
Max. PV I _{sc} (A)	39+39	55+55+55	55+55+55+55
No. of MPP Trackers	2	3	4
No. of Strings per MPP Tracker	2+2	2+2+2	2+2+2+2
AC Output Data			
Rated AC Output Active Power (W)	20000	30000	50000
Max AC Output Active Power (W)	22000	33000	55000
AC Output Rated Current (A)	30.4/29	45.5/43.5	75.8/72.5
Max. AC Output Current (A)	33.4/31.9	50/47.8	83.4/79.7
Max. Three-phase Unbalanced Output Current (A)	35	60	83.3
Max. Continuous AC Passthrough (A)	80	200	
Peak Power (Off Grid)	1.5 time of rated power, 10 S		
Generator Input/Smart Load /AC Couple Current (A)	30.4/80/30.4	45.5 / 200 / 45.5	75.8 / 200 / 75.8
Power Factor Adjustment Range	0.8 leading to 0.8 lagging		
Output Frequency and Voltage	50/60Hz; 3L/N/PE 220/380, 230/400Vac		
Grid Type	Three Phase		
Total Harmonics Current Distortion (THDi)	<3% (of nominal power)		
DC Current Injection	<0.5% I _n		

KSTAR

Three Phase On-Grid Solar Inverter



MODEL	SKU:9491	SKU:9492	SKU:9493	SKU:9494
Input(DC)	10KW	30KW	40KW	120KW
Max. DC Voltage	1100V	1100V	1100V	1100V
Nominal Voltage	620V	600V	600V	620V
Start Voltage	180V	180V	180V	250V
MPPT Voltage Range	140V~1000V	200V~1000V	200V~1000V	200V~1000V
Number of MPPT Tracker	2	3	2	10
Strings Per MPPT Tracker	1	2	1	2
Max. Input Current Per MPPT	15A	30A	30A	30A
Max. Short-circuit Current Per MPPT	20A	50A	50A	50A
Output(AC)				
Nominal AC Output Power	10000W	30000W	40000W	120kW
Maximum AC Output Power	11000Va	33000Va	44000Va	121kVa
Nominal AC Voltage	400V 3L+N	400V 3L+N	400V 3L+N	480V 3W+PE
AC Grid Frequency Range	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Maximum Output Current	16.0A	47.7A	63.6A	174.6A
Power Factor(Φ)	0.8leading-0.8lagging	0.8leading-0.8lagging	0.8leading-0.8lagging	0.8leading-0.8lagging
THDi	<3%	<3%	<3%	<3%
Efficiency				
Max. Efficiency	98.6%	98.7%	98.7%	98.7%
General Specifications				
Dimensions W x H x D	380x483x161mm	380x483x227mm	380x483x227mm	1055x700x336mm
Operating Temperature Range	-25°C~+60°C	-25°C~+60°C	-25°C~+60°C	-25°C~+60°C
Cooling Type	Natural cooling	Fan cooling	Fan cooling	Fan cooling
IP Class	IP66	IP66	IP66	IP66

Three Phase On-Grid Solar Inverter



MODEL	SKU:9480	SKU:9481	SKU:9482
Input(DC)	Max 9.6KW	Max 12.8KW	Max 16KW
Max. DC Voltage	1100V	1100V	1100V
Nominal Voltage	600V	600V	600V
Start Voltage	160V	160V	160V
MPPT Voltage Range	250~850V	180V~1000V	180V~1000V
Number of MPPT Tracker	2	2	2
Strings Per MPPT Tracker	1	1	1
Max. Input Current Per MPPT	14A/14A	14A/14A	14A/14A
Max. Short-circuit Current Per MPPT	18A/18A	18A/18A	18A/18A
Output(AC)			
Nominal AC Output Power	6kW	8kW	10kW
Maximum AC Output Power	6.6kVA	8.8kVA	11kVA
Nominal AC Voltage	400Vac 3L/N/PE	400Vac 3L/N/PE	400Vac 3L/N/PE
AC Grid Frequency Range	50/60Hz	50/60Hz	50/60Hz
Maximum Output Current	12.8A	12.8A	15.9A
Power Factor(Φ)	0.8leading-0.8lagging	0.8leading-0.8lagging	0.8leading-0.8lagging
THDi	<3%	<3%	<3%
Efficiency			
Max. Efficiency	98.4%	98.7%	98.7%
General Specifications			
Dimensions W x H x D	481x395x195mm	481x395x195mm	481x395x195mm
Operating Temperature Range	-30°C~+60°C	-30°C~+60°C	-25°C~+60°C
Cooling Type	Natural cooling	Natural cooling	Natural cooling
IP Class	IP66	IP66	IP66

Three Phase On-Grid Solar Inverter



MODEL	SKU:9483	SKU:9484	SKU:9485
Input(DC)	Max 48KW	Max 80KW	Max 150kW
Max. DC Voltage	1100V	1100V	1100V
Nominal Voltage	600V	600V	620V
Start Voltage	250V	250V	250V
MPPT Voltage Range	200V~1000V	200V~1000V	180V~1000V
Number of MPPT Tracker	3	4	9
Strings Per MPPT Tracker	2	3/2/3/2	2
Max. Input Current Per MPPT	26A	39A/26A/39A/26A	26A
Max. Short-circuit Current Per MPPT	32A	48A/32A/48A/32A	40A
Output(AC)			
Nominal AC Output Power	30kW	50kW	100kW
Maximum AC Output Power	33kVA	55kVA	110kVa
Nominal AC Voltage	400Vac 3L/N/PE	230Vac/400Vac	400Vac 3L/N/PE
AC Grid Frequency Range	50/60Hz	50/60Hz	50/60Hz
Maximum Output Current	48.3A	79.7A	158.8A
Power Factor(Φ)	0.8leading-0.8lagging	0.8leading-0.8lagging	0.8leading-0.8lagging
THDi	<3%	<3%	<3%
Efficiency			
Max. Efficiency	98.6%	98.7%	98.7%
General Specifications			
Dimensions W x H x D	600x430x230mm	650x450x260mm	1050x660x330mm
Operating Temperature Range	-25°C~+60°C	-25°C~+60°C	-25°C~+60°C
Cooling Type	Smart Cooling	Smart Cooling	Smart Cooling
IP Class	IP66	IP66	IP66

ONE-PHASE HYBRID INVERTERS

XG8KTL




MODEL	SKU:9486
Input(DC)	Max 12KW
Max. DC Voltage	600V
Start Voltage	80V
MPPT Voltage Range	50~550V
Number of MPPT Tracker	2
Strings Per MPPT Tracker	1/1
Max. Input Current Per MPPT	20A
Max. Short-circuit Current Per MPPT	26A
Output(AC)	
Nominal AC Output Power	8kW
Maximum AC Output Power	8.8kVA
Nominal AC Voltage	220Vac/230Vac/240Vac
AC Grid Frequency Range	50/60Hz
Max. Efficiency	98.1%
General Specifications	
Dimensions W x H x D	380x380x160mm
Operating Temperature Range	-30°C~+60°C
Cooling Type	Natural cooling
IP Class	IP66



Standard 19inch Rack for 12pcs Batteries / 1pcs Controller

SKU: 9475

Dimensions: 589x590x2240mm



High Voltage Battery cluster control box

SKU: 9476



Operating Voltage	120~750Vdc
Nominal Charge/Discharge Current	100A
Max.Charge/Discharge Current	125A
DC Input Rating	12±2%V/4.15A
Operating Temperature Range	-20~65°C
Ingress Protection	IP20
Dimension (W/D/H)	440*570*150mm
Weight Approximate	15.5kg

5.12 kWh Battery module

SKU: 9477



Battery Type	LiFePO4(LFP)
Nominal Voltage	51.2Vdc
Rated Capacity	100Ah
Rated Energy	5.12kWh
Nominal Charge/Discharge Current	100A
Peak.Discharge Current	125A
Charge Temperature	0~55°C
Discharge Temperature	-20~55°C
Storage Temperature	0°C~35°C
Ingress Protection	IP20
Dimension (W/D/H)	440*570*133mm
Weight Approximate	44kg

OPTONICA
 SOLAR 
RECHARGEABLE LITHIUM BATTERY SYSTEM
BATTERY LiFePo4

10.94kWh

Model	SKU:9471
Nominal Capacity	228Ah
Nominal Energy	10.94kWh
Nominal Voltage	48Vdc
Discharge Current	150A
Cell	BYD
Ingress Protection	IP65
Weight	90kg


10.24kWh

Model	SKU:9472
Nominal Capacity	200Ah
Nominal Energy	10.24kWh
Nominal Voltage	51.2Vdc
Discharge Current	150A
Cell	EVE
Ingress Protection	IP65
Weight	90kg


5.12kWh

Model	SKU:9473
Nominal Capacity	100Ah
Nominal Energy	5.12kWh
Nominal Voltage	51.2Vdc
Discharge Current	100A
Cell	EVE
Ingress Protection	IP65
Weight	42.2kg


SKU: 9465 - Cables Red/Black for Battery
9471-9473 - Length 1500mm
Deye
RECHARGEABLE LITHIUM BATTERY SYSTEM

BATTERY LiFePo4
6.14kWh


Model	SKU:9439
Nominal Capacity	120Ah
Nominal Energy	6.14kWh
Nominal Voltage	51.2Vdc
Operating Voltage Range	43.2~57.6Vdc
Nominal Charge/Discharge Current	60A
Ingress Protection	IP65
Operating Temperature(Charge)	0~+55 C°
Operating Temperature(Discharge)	-20~+55 C°
Storage Temperature	-20~+35 C°
DimensionS	475x720x145mm
Weight Approximate	58 Kg

MULTI-FUNCTION ELECTRICAL ENERGY METERS



Single-phase Multi-Function electrical energy meter

230V/100A/RS485/MID Certification
SKU: 9461

Three-phase Multi-Function electrical energy meter

3x230V/100A/RS485/MID certification
SKU: 9462



CT Three-phase Multi-Function electrical energy meter

3x230V/1A or 5A/RS485/MID certification
SKU: 9463

STD670V Smart Meters Kits for INVT 3-Phase Inverters (Including wires and CT SDT024TS)

SKU: 9460



Technical Feature	Parameters
Wiring	2P3L, 3P3L, 3P4L
Voltage	2x110V/220V, 3x57.7/100V, 3x127/220V, 3x230V/400V, 3x240/415V, 3x400/690V 3x100V, 3x230V, 3x400V, 3x690V
	Rated 0.9 ~ 1.1Un; Max 0.7 ~ 1.2Un
Current	3x5A(Ext. CT), 3x16A, 3x32A, 3x63A, 3x100A
	Consumption \leq 4VA / line
Frequency	50 / 60Hz
Accuracy	U,I,P 0.2%, kWh 0.5%, kVarh 1.0%
Thermal drift	<200ppm
Energy Impulse	kWh impulse (open-collector)
	VCC<48V, Iz<50mA Constant: 10imp/kWh
Isolation	2kVAC/min (input / output / power supply)
	input / housing and output / housing >50M Ω
Installation	Standard 35mm DIN rail

CT Clamp for SMART METER

SKU: 9466



SKU: 9601 Rail 27*45mm 2.2m



SKU: 9602 Rail 27*45mm 1.2m



SKU: 9603 End Clamp for 35mm Panel



SKU: 9604 Middle Clamp



SKU: 9617 Ballasted Strip



SKU: 9618 Mini Rail - 300mm



SKU: 9619 Rail - 2400mm



SKU: 9620 Rail+Rubber Pad 70x22x380mm



SKU: 9605 Rooftop Hook



SKU: 9606 TT Nut



SKU: 9607 Screw ST6.3*80mm



SKU: 9608 Wood Screw M6.3*80mm



SKU: 9621 End Clamps M8x25mm for 30mm Panel



SKU: 9622 Middle Clamps Wide 20mm



SKU: 9623 End Clamp for 30mm Panel



SKU: 9624 Middle Clamp for 30mm Panel



SKU: 9609 L-Foot with M8*25mm



SKU: 9610 Rail Joiner 200mm



SKU: 9611 Hanger Bolt with L-Foot



SKU: 9612 Adjustable front Leg



SKU: 9625 INNER HEXAGONAL BOLT 40mm



SKU: 9626 INNER HEXAGONAL BOLT 25mm



SKU: 9627 M8 Hexagonal Nut



SKU: 9628 M8 Square Nut



SKU: 9613 Adjustable rear Leg 10-15° 200mm



SKU: 9614 Adjustable rear Leg 15-30° 320mm



SKU: 9615 Grounding Plate



SKU: 9616 Adjustable Tilt Mount Bracket



SKU: 9629 Expansion Bolt 60mm



SKU: 9630 Ball Nut



SKU: 9631 Self Tapping Screw





LED BULBS GOLDEN GLASS



Innovative line of half-glass covered bulbs combine the classic retro appearance with modern power-saving technology and creating a cosy ambience in both homes, villa or restaurants and bars.

Features:

- Up to 80% power saving impact
- 2500K warm white light
- Half silver or half golden cover
- E27 socket
- Stylish retro look
- Standard bulb head – A60 or G95

Application:

- Home use on standard sockets
- Outdoor use in enclosed fixtures
- Discrete or additional lighting






LED Bulbs PS160 Filament

8W E27

GOLDEN GLASS

Watts	8W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	810lm	Dimension	ø160x315 mm
Beam Angle	270°	Body Type	PS160


 SKU: 1790
 1800K


LED Bulbs BD200 Filament

8W E27

GOLDEN GLASS

Watts	8W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	810lm	Dimension	ø200x410 mm
Beam Angle	270°	Body Type	BD200
Socket	E27	Dimmable	YES


 SKU: 1791
 1800K


LED Bulbs G200 Filament

8W E27

GOLDEN GLASS

Watts	8W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	810lm	Dimension	ø200x300 mm
Beam Angle	270°	Body Type	G200
Socket	E27	Dimmable	YES


 SKU: 1792
 1800K


LED Bulbs MS200 Filament

8W E27

GOLDEN GLASS

Watts	8W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	810lm	Dimension	ø200x210 mm
Beam Angle	270°	Body Type	MS200
Socket	E27	Dimmable	YES


 SKU: 1793
 1800K


LED Bulbs Filament

4W E27

HALF GOLDEN GLASS

Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø95x135 mm
Beam Angle	180°	Body Type	G95
Socket	E27	Dimmable	NO


 SKU: 1889
 1800K


LED Bulbs Filament

4W E27

HALF SILVER GLASS

Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø95x135 mm
Beam Angle	180°	Body Type	G95
Socket	E27	Dimmable	NO

 SKU: 1887
 1800K



LED Bulbs Filament

7W E27

HALF GOLDEN GLASS

Watts	7W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	800lm	Dimension	ø95x135 mm
Beam Angle	180°	Body Type	G95
Socket	E27	Dimmable	NO

SKU: 1890 Warm White 2700K 3800156618909




LED Bulbs Filament

7W E27

HALF SILVER GLASS

Watts	7W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	800lm	Dimension	ø95x135 mm
Beam Angle	180°	Body Type	G95
Socket	E27	Dimmable	NO

 SKU: 1888
 1800K

 SKU: 1890
 1800K




LED Bulbs Filament


4W E27

HALF GOLDEN GLASS

Watts 4W
 Input Voltage AC : 175-265V
 Flux 400lm
 Beam Angle 180°
 Socket E27

SKU: 1893
 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ø60x105 mm
 Body Type A60
 Dimmable NO



LED Bulbs Filament


4W E27

HALF SILVER GLASS

Watts 4W
 Input Voltage AC : 175-265V
 Flux 400lm
 Beam Angle 180°
 Socket E27

SKU: 1879
 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ø60x105 mm
 Body Type A60
 Dimmable NO



LED Bulbs Filament


7W E27

HALF GOLDEN GLASS

Watts 7W
 Input Voltage AC : 175-265V
 Flux 800lm
 Beam Angle 180°
 Socket E27

SKU: 1896
 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ø60x105 mm
 Body Type A60
 Dimmable NO



LED Bulbs Filament


7W E27

HALF SILVER GLASS

Watts 7W
 Input Voltage AC : 175-265V
 Flux 800lm
 Beam Angle 180°
 Socket E27

SKU: 1880
 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ø60x105 mm
 Body Type A60
 Dimmable NO



LED ST64 Bulbs Filament


4W E27

GOLDEN GLASS

Watts 4W
 Input Voltage AC : 220-240V
 Flux 400lm
 Beam Angle 270°
 Socket E27

SKU: 1795
 2500K

CRI Ra>80
 IP Rating IP20
 Dimension ø64x140 mm
 Body Type ST64
 Dimmable NO



LED ST64 Bulbs Filament


6W E27

GOLDEN GLASS

Watts 6W
 Input Voltage AC : 220-240V
 Flux 540lm
 Beam Angle 270°
 Socket E27

SKU: 1306
 2500K

CRI Ra>80
 IP Rating IP20
 Dimension ø64x140 mm
 Body Type ST64
 Dimmable NO



LED ST64 Bulbs Filament


8W E27

GOLDEN GLASS

Watts 8W
 Input Voltage AC : 220-240V
 Flux 700lm
 Beam Angle 270°
 Socket E27

SKU: 1305
 2500K

CRI Ra>80
 IP Rating IP20
 Dimension ø64x140 mm
 Body Type ST64
 Dimmable NO



LED ST64 Bulbs Filament


8W E27

GOLDEN GLASS

Watts 8W
 Input Voltage AC : 220-240V
 Flux 700lm
 Beam Angle 270°
 Socket E27

SKU: 1322
 2500K

CRI Ra>80
 IP Rating IP20
 Dimension ø64x140 mm
 Body Type ST64
 Dimmable YES





LED A60 Bulbs Filament
4W E27

Watts 4W
 Input Voltage AC : 175-265V
 Flux 470lm
 Beam Angle 300°
 Socket E27

SKU: 1857 6000K
 SKU: 1858 4500K
 SKU: 1859 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø60x100 mm
 Body Type A60
 Dimmable NO


LED A60 Bulbs Filament
8W E27

Watts 8W
 Input Voltage AC : 220-240V
 Flux 810lm
 Beam Angle 300°
 Socket E27

SKU: 1310 6000K
 SKU: 1311 4500K
 SKU: 1312 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø60x110 mm
 Body Type A60
 Dimmable NO


LED A60 Bulbs Filament
4W E27

Watts 4W
 Input Voltage AC : 175-265V
 Flux 400lm
 Beam Angle 300°
 Socket E27

SKU: 1899
 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø60x106 mm
 Body Type A60
 Dimmable YES


LED A60 Bulbs Filament
8W E27

Watts 8W
 Input Voltage AC : 220-240V
 Flux 810lm
 Beam Angle 300°
 Socket E27

SKU: 1323
 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø60x110 mm
 Body Type A60
 Dimmable YES


LED A60 Bulbs Filament
5W E27

Watts 5W
 Input Voltage AC : 175-265V
 Flux 600lm
 Beam Angle 300°
 Socket E27

SKU: 1854 6000K
 SKU: 1855 4500K
 SKU: 1856 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø60x106 mm
 Body Type A60
 Dimmable NO


LED A60 Bulbs Filament
8W E27
GOLDEN GLASS

Watts 8W
 Input Voltage AC : 220-240V
 Flux 700lm
 Beam Angle 300°
 Socket E27

SKU: 1796
 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø60x105 mm
 Body Type A60
 Dimmable NO


LED A60 Bulbs Filament
6W E27

Watts 6W
 Input Voltage AC : 220-240V
 Flux 630lm
 Beam Angle 300°
 Socket E27

SKU: 1308 4000K
 SKU: 1309 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø60x105 mm
 Body Type A60
 Dimmable NO


LED A60 Bulbs Filament
8W E27
GOLDEN GLASS

Watts 8W
 Input Voltage AC : 220-240V
 Flux 720lm
 Beam Angle 300°
 Socket E27

SKU: 1324
 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ø60x105 mm
 Body Type A60
 Dimmable YES




LED A60 Bulbs Filament
10W E27


Watts	10W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	1350lm	Dimension	ø60x110 mm
Beam Angle	300°	Body Type	A60
Socket	E27	Dimmable	NO

SKU: 1313 SKU: 1314 SKU: 1315
 6000K 4500K 2700K

1350
Lumens

300°

E27


LED G45 Bulbs Filament
4W E27


Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø45x78 mm
Beam Angle	300°	Body Type	G45
Socket	E27	Dimmable	NO

SKU: 1867 SKU: 1868 SKU: 1869
 6000K 4500K 2700K

400
Lumens

300°

E27


LED A65 Bulbs Filament
12W E27


Watts	12W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	1500lm	Dimension	ø65x126 mm
Beam Angle	300°	Body Type	A60
Socket	E27	Dimmable	NO

SKU: 1316 SKU: 1317 SKU: 1318
 6000K 4500K 2700K

1500
Lumens

300°

E27


LED A65 Bulbs Filament
14W E27


Watts	14W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	2000lm	Dimension	ø65x126 mm
Beam Angle	300°	Body Type	A60
Socket	E27	Dimmable	NO

SKU: 1319 SKU: 1320 SKU: 1321
 6000K 4500K 2700K

2000
Lumens

300°

E27


LED G45 Bulbs Filament
2W E27


Watts	2W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	200lm	Dimension	ø45x78 mm
Beam Angle	300°	Body Type	G45
Socket	E27	Dimmable	NO

SKU: 1864 SKU: 1865 SKU: 1866
 6000K 4500K 2700K

200
Lumens

300°

E27


LED G45 Bulbs Filament
4W E27


Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø45x78 mm
Beam Angle	300°	Body Type	G45
Socket	E27	Dimmable	NO

SKU: 1325
 2700K

400
Lumens

Dimmable

E27


LED G45 Bulbs Filament
4W E27
GOLDEN GLASS


Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	320lm	Dimension	ø45x78 mm
Beam Angle	300°	Body Type	G45
Socket	E27	Dimmable	YES

SKU: 1326
 2700K

320
Lumens

Dimmable

E27


LED G125 Bulbs Filament
4W E27
GOLDEN GLASS


Watts	4W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	400lm	Dimension	ø95x135 mm
Beam Angle	270°	Body Type	G95
Socket	E27	Dimmable	NO

SKU: 1794
 2700K

400
Lumens

270°


E27




**LED G125 Bulbs Filament
4W E27**


Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø125x165 mm
Beam Angle	300°	Body Type	G125
Socket	E27	Dimmable	NO

SKU: 1863 SKU: 1862
 ■ 4500K ■ 2700K


**LED G45 Bulbs Filament
4W E14**


Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø45x78 mm
Beam Angle	300°	Body Type	G45
Socket	E14	Dimmable	YES

SKU: 1417
 ■ 2700K


**LED G125 Bulbs Filament
6.5W E27**


Watts	6.5W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	810lm	Dimension	ø125x165 mm
Beam Angle	300°	Body Type	G125
Socket	E27	Dimmable	NO

SKU: 1861 SKU: 1860
 ■ 4500K ■ 2700K


**LED G45 Bulbs Filament
4W E14
GOLDEN GLASS**


Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø45x78 mm
Beam Angle	300°	Body Type	G45
Socket	E14	Dimmable	NO

SKU: 1492
 ■ 2500K


**LED G45 Bulbs Filament
2W E14**


Watts	2W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	200lm	Dimension	ø45x78 mm
Beam Angle	300°	Body Type	G45
Socket	E14	Dimmable	NO

SKU: 1474 SKU: 1475 SKU: 1476
 ■ 6000K ■ 4500K ■ 2700K


**LED G45 Bulbs Filament
4W E14
GOLDEN GLASS**


Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	350lm	Dimension	ø45x78 mm
Beam Angle	300°	Body Type	G45
Socket	E14	Dimmable	YES

SKU: 1418
 ■ 2500K


**LED G45 Bulbs Filament
4W E14**


Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø45x78 mm
Beam Angle	300°	Body Type	G45
Socket	E14	Dimmable	NO

SKU: 1477 SKU: 1478 SKU: 1479
 ■ 6000K ■ 4500K ■ 2700K


**LED R50 Bulbs Filament
5W E14**

Watts	5W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	600lm	Dimension	ø50x86 mm
Beam Angle	70°	Body Type	R50
Socket	E14	Dimmable	NO


SKU: 1872
 ■ 2700K




**LED C35 Candle Filament
4W E14**

Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø35x98 mm
Beam Angle	300°	Body Type	C35
Socket	E14	Dimmable	NO

SKU: 1470 SKU: 1471 SKU: 1472
 6000K 4500K 2700K


**LED C35 Candle Filament
4W E14**

Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø35x98 mm
Beam Angle	300°	Body Type	C35
Socket	E14	Dimmable	YES

SKU: 1469 SKU: 1473
 4500K 2700K


**LED C35 Candle Filament
4W E14
GOLDEN GLASS**


Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø35x98 mm
Beam Angle	300°	Body Type	C35
Socket	E14	Dimmable	NO

SKU: 1490
 2500K


**LED C35 Twist Candle Filament
4W E14**


Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø35x98 mm
Beam Angle	300°	Body Type	C35 Twist
Socket	E14	Dimmable	NO

SKU: 1413
 2700K


**LED C35 Tip Candle Filament
4W E14**

Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø35x115 mm
Beam Angle	300°	Body Type	C35 Tip
Socket	E14	Dimmable	NO

SKU: 1480 SKU: 1481 SKU: 1482
 6000K 4500K 2700K


**LED C35 Tip Candle Filament
4W E14**


Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø35x115 mm
Beam Angle	300°	Body Type	C35 Tip
Socket	E14	Dimmable	YES

SKU: 1415
 2700K


**LED C35 Tip Candle Filament
4W E14
GOLDEN GLASS**

Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø35x120 mm
Beam Angle	300°	Body Type	C35 Tip
Socket	E14	Dimmable	YES

SKU: 1416
 2500K


**LED C35 Tip Candle Filament
4W E14
GOLDEN GLASS**

Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø35x120 mm
Beam Angle	300°	Body Type	C35 Tip
Socket	E14	Dimmable	NO

SKU: 1491
 2500K






LED C35 Candle Twist Bulbs Filament
4W E14

Watts	4W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	400lm	Dimension	ø35x115 mm
Beam Angle	300°	Body Type	C35T Twist
Socket	E14	Dimmable	NO


SKU: 1414
■ 2700K



LED C35 Candle Filament
6W E14

Watts	6W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	730lm	Dimension	ø35x98 mm
Beam Angle	300°	Body Type	C35
Socket	E14	Dimmable	NO

SKU: 1410 ■ 6000K SKU: 1411 ■ 4500K SKU: 1412 ■ 2700K



LED Bulb A60 Motion Sensor
7W E27

Watts	7W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	560lm	Dimension	ø60x123 mm
Beam Angle	270°	Body Type	A60
Socket	E27	Dimmable	NO

SKU: 1710 ■ 6000K SKU: 1711 ■ 4500K



LED Bulb A60
8.5W E27

Watts	8.5W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	806lm	Dimension	ø60x108 mm
Beam Angle	270°	Body Type	A60
Socket	E27	Dimmable	NO

SKU: 1351 ■ 6000K SKU: 1352 ■ 4500K SKU: 1353 ■ 2700K



LED BULB T80
24W E27

Watts	24W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	2700lm	Dimension	ø80x138 mm
Beam Angle	150°	Body Type	T80
Socket	E27	Dimmable	NO

SKU: 11891 ■ 6000K SKU: 11892 ■ 4000K



SKU: 11899
Adaptor E27>E40
NOT INCLUDED



LED BULB T100
30W E27

Watts	30W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3200lm	Dimension	ø100x165 mm
Beam Angle	150°	Body Type	T100
Socket	E27	Dimmable	NO

SKU: 11893 ■ 6000K SKU: 11894 ■ 4000K



SKU: 11899
Adaptor E27>E40
NOT INCLUDED



LED BULB T120
40W E27

Watts	40W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	4000lm	Dimension	ø120x191 mm
Beam Angle	150°	Body Type	T120
Socket	E27	Dimmable	NO

SKU: 11895 ■ 6000K SKU: 11896 ■ 4000K



SKU: 11899
Adaptor E27>E40
NOT INCLUDED



LED BULB T140
50W E27

Watts	50W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	5000lm	Dimension	ø140x220 mm
Beam Angle	100°	Body Type	T140
Socket	E27	Dimmable	NO

SKU: 11897 ■ 6000K SKU: 11898 ■ 4000K



SKU: 11899
Adaptor E27>E40
NOT INCLUDED




LED Bulb A60

8.5W E27

Watts 8.5W
 Input Voltage AC : 220-240V
 Flux 806lm
 Beam Angle 270°
 Socket E27

SKU: 1341 SKU: 1342 SKU: 1343
 ■ 6000K ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ø60x108 mm
 Body Type A60
 Dimmable NO




LED Bulb A60

9W E27

Watts 9W
 Input Voltage AC : 220-240V
 Flux 806lm
 Beam Angle 270°
 Socket E27

SKU: 1701 SKU: 1702 SKU: 1703
 ■ 6000K ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ø60x108 mm
 Body Type A60
 Dimmable YES




LED Bulb A60

10W E27

Watts 10W
 Input Voltage AC : 220-240V
 Flux 806lm
 Beam Angle 270°
 Socket E27

SKU: 1849
 ■ 6000K

CRI Ra>80
 IP Rating IP20
 Dimension ø60x110 mm
 Body Type A60
 Dimmable YES




LED Bulb A60

10.5W E27

Watts 10.5W
 Input Voltage AC : 220-240V
 Flux 1055lm
 Beam Angle 270°
 Socket E27

SKU: 1354 SKU: 1355 SKU: 1356
 ■ 6000K ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ø60x108 mm
 Body Type A60
 Dimmable NO




LED Bulb A60

11W E27

Watts 11W
 Input Voltage AC : 220-240V
 Flux 1055lm
 Beam Angle 270°
 Socket E27

SKU: 1704 SKU: 1705 SKU: 1706
 ■ 6000K ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ø60x110mm
 Body Type A60
 Dimmable YES




LED Bulb A60

14W E27

Watts 14W
 Input Voltage AC : 220-240V
 Flux 1380lm
 Beam Angle 270°
 Socket E27

SKU: 1357 SKU: 1358 SKU: 1359
 ■ 6000K ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ø60x108 mm
 Body Type A60
 Dimmable NO




LED Bulb A65

17W E27

Watts 17W
 Input Voltage AC : 220-240V
 Flux 1710lm
 Beam Angle 270°
 Socket E27

SKU: 1360 SKU: 1361 SKU: 1362
 ■ 6000K ■ 4500K ■ 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø65x134 mm
 Body Type A65
 Dimmable NO




LED Bulb A65
19W E27


Watts	19W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	1950lm	Dimension	ø65x138 mm
Beam Angle	270°	Body Type	A65
Socket	E27	Dimmable	NO

SKU: 1363 SKU: 1364 SKU: 1365
 ■ 6000K ■ 4500K ■ 2700K


LED Bulb G95
12W E27


Watts	12W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1155lm	Dimension	ø95x138 mm
Beam Angle	270°	Body Type	A60
Socket	E27	Dimmable	NO

SKU: 1841 SKU: 1842 SKU: 1843
 ■ 6000K ■ 4500K ■ 2700K


LED Bulb G45
3.5W E27


Watts	3.5W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	300lm	Dimension	ø45x75 mm
Beam Angle	180°	Body Type	G45
Socket	E27	Dimmable	NO

SKU: 1344 SKU: 1345 SKU: 1346
 ■ 6000K ■ 4500K ■ 2700K


LED Bulb G45
5.5W E27


Watts	5.5W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	450lm	Dimension	ø45x75 mm
Beam Angle	180°	Body Type	G45
Socket	E27	Dimmable	NO

SKU: 1327 SKU: 1328 SKU: 1329
 ■ 6000K ■ 4500K ■ 2700K


LED Bulb G45
8W E27


Watts	8W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	710lm	Dimension	ø45x75 mm
Beam Angle	180°	Body Type	G45
Socket	E27	Dimmable	NO

SKU: 1336 SKU: 1337 SKU: 1338
 ■ 6000K ■ 4500K ■ 2700K


LED Bulb G120
15W E27


Watts	15W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1500lm	Dimension	ø120x155 mm
Beam Angle	270°	Body Type	G120
Socket	E27	Dimmable	NO

SKU: 1845 SKU: 1846 SKU: 1847
 ■ 6000K ■ 4500K ■ 2700K


LED Bulb G120
18W E27

Watts	18W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1820lm	Dimension	ø125x172 mm
Beam Angle	270°	Body Type	120
Socket	E27	Dimmable	NO

SKU: 1884 SKU: 1885 SKU: 1886
 ■ 6000K ■ 4500K ■ 2700K





LED Bulb G63
6W E27


Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	480lm	Dimension	ø63x100 mm
Beam Angle	200°	Body Type	A60
Socket	E27	Dimmable	NO

SKU: 1876 SKU: 1877 SKU: 1878
■ 6000K ■ 4500K ■ 2700K

480
Lumens

200°

E27



LED Spot PAR30
30W E27


Watts	30W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	2400lm	Dimension	ø95x130 mm
Beam Angle	30°	Body Type	PAR30
Socket	E27	Dimmable	NO

SKU: 1528 SKU: 1529 SKU: 1530
■ 6000K ■ 4500K ■ 2700K

2400
Lumens

30°

E27



PORTABLE LED SOLAR BULB
Solar Panel Power: 6V 2.3W

Voltage	6V	CRI	Ra>80
Flux	650lm	IP Rating	IP20
Beam Angle	360°	Body Color	White
Battery	3.2V 10Ah	Dimension	ø110x195 mm

SKU: 229
■ 6000K

650
Lumens

IP20

Battery

Solar Power



LED Bulb P45
3.5W E14


Watts	3.5W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	300lm	Dimension	ø45x78 mm
Beam Angle	240°	Body Type	P45
Socket	E14	Dimmable	NO

SKU: 1407 SKU: 1408 SKU: 1409
■ 6000K ■ 4500K ■ 2700K

300
Lumens

240°

E14



LED Candle C37
3.7W E14


Watts	3.7W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	320lm	Dimension	ø37x100 mm
Beam Angle	180°	Body Type	C37
Socket	E14	Dimmable	NO

SKU: 1422 SKU: 1423 SKU: 1424
■ 6000K ■ 4500K ■ 2700K

320
Lumens

180°

E14



LED Candle C37
5.5W E14


Watts	5.5W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	450lm	Dimension	ø37x100 mm
Beam Angle	180°	Body Type	C37
Socket	E14	Dimmable	NO

SKU: 1425 SKU: 1426 SKU: 1427
■ 6000K ■ 4500K ■ 2700K

450
Lumens

180°

E14



LED Candle C37
6W E14


Watts	6W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	480lm	Dimension	ø37x100 mm
Beam Angle	180°	Body Type	C37
Socket	E14	Dimmable	YES

SKU: 1464 SKU: 1465 SKU: 1463
■ 6000K ■ 4500K ■ 2700K

480
Lumens

180°

E14




Dimmable



LED Candle C37
8W E14

Watts	8W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	710lm	Dimension	ø37x112 mm
Beam Angle	180°	Body Type	C37
Socket	E14	Dimmable	NO


SKU: 1428 6000K
SKU: 1429 4500K
SKU: 1430 2700K



LED Candle C37
5.5W E14

Watts	5.5W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	450lm	Dimension	ø37x125 mm
Beam Angle	180°	Body Type	C37
Socket	E14	Dimmable	NO

SKU: 1435 6000K
SKU: 1436 4500K
SKU: 1437 2700K




NEW



LED Spotlight E14
7W SMD

Watts	7W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	820lm	Dimension	ø19x71 mm
Beam Angle	360°	Material	Alu+PC
Socket	E14	Dimmable	NO


SKU: 1499
4500K



LED Bulb P45
5.5W E14

Watts	5.5W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	450lm	Dimension	ø45x78 mm
Beam Angle	240°	Body Type	P45
Socket	E14	Dimmable	NO


SKU: 1401 6000K
SKU: 1402 4500K
SKU: 1403 2700K



LED Bulb P45
8W E14

Watts	8W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	710lm	Dimension	ø45x78 mm
Beam Angle	240°	Body Type	P45
Socket	E14	Dimmable	NO


SKU: 1404 6000K
SKU: 1405 4500K
SKU: 1406 2700K



LED Bulb P45
8.5W E14

Watts	8.5W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	800lm	Dimension	ø45x78 mm
Beam Angle	240°	Body Type	P45
Socket	E14	Dimmable	NO


SKU: 1493 6000K
SKU: 1494 4500K



LED Bulb R50
6W E14

Watts	6W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	450lm	Dimension	ø50x85 mm
Beam Angle	200°	Body Type	R50
Socket	E14	Dimmable	NO

SKU: 1438 6000K
SKU: 1439 4500K
SKU: 1440 2700K





**LED Bulb A60 High Lumen
9W B22**

Watts 9W
 Input Voltage AC : 220-240V
 Flux 820lm
 Beam Angle 270°
 Socket B22

SKU: 1918 6000K
 SKU: 1919 4500K
 SKU: 1920 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø60x110 mm
 Body Type A60
 Dimmable NO


**LED Bulb A60
10W B22**

Watts 10W
 Input Voltage AC : 220-240V
 Flux 800lm
 Beam Angle 270°
 Socket B22

SKU: 1910
 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø60x110 mm
 Body Type A60
 Dimmable YES


**LED Bulb A60 High Lumen
11W B22**

Watts 11W
 Input Voltage AC : 220-240V
 Flux 1055lm
 Beam Angle 270°
 Socket B22

SKU: 1921 6000K
 SKU: 1922 4500K
 SKU: 1923 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø60x110 mm
 Body Type A60
 Dimmable NO


**LED Bulb A65
12W B22**

Watts 12W
 Input Voltage AC : 220-240V
 Flux 960lm
 Beam Angle 270°
 Socket B22

SKU: 1914
 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø65x110 mm
 Body Type A65
 Dimmable YES


**LED Bulb A65
15W B22**

Watts 15W
 Input Voltage AC : 220-240V
 Flux 1200lm
 Beam Angle 270°
 Socket B22

SKU: 1915 6000K
 SKU: 1916 4500K
 SKU: 1917 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø65x110 mm
 Body Type A65
 Dimmable NO


**LED Candle C37
6W B22**

Watts 6W
 Input Voltage AC : 220-240V
 Flux 480lm
 Beam Angle 180°
 Socket B22

SKU: 1950 6000K
 SKU: 1951 4500K
 SKU: 1952 2700K


CRI Ra>80
 IP Rating IP20
 Dimension ø37x90 mm
 Body Type C37
 Dimmable NO


**LED Candle C37
6W B22**

Watts 6W
 Input Voltage AC : 220-240V
 Flux 480lm
 Beam Angle 180°
 Socket B22

SKU: 1953
 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ø37x90 mm
 Body Type C37
 Dimmable YES



NEW



5 PCS
BLISTER


**LED Spotlight G4
2W SMD**

Watts 2W
Input Voltage AC;DC 12V
Flux 180lm
Beam Angle 300°
Socket G4

SKU: 1601 6000K
SKU: 1602 4500K
SKU: 1603 2800K

CRI Ra>80
IP Rating IP20
Dimension ø12x29 mm
Material Plastic
Dimmable NO

180 Lumens
300°
G4



5 PCS
BLISTER




**LED Spotlight G9
3W SMD**

Watts 3W
Input Voltage AC:170-265V
Flux 220lm
Beam Angle 360°
Socket G9

SKU: 1638 6000K
SKU: 1639 4500K
SKU: 1640 2700K

CRI Ra>80
IP Rating IP20
Dimension ø16x48 mm
Material Plastic
Dimmable NO

220 Lumens
360°
G9




**LED Spotlight G4
2W SMD**

Watts 2W
Input Voltage AC;DC 12V
Flux 170lm
Beam Angle 360°
Socket G4

SKU: 1615 6000K
SKU: 1616 4500K
SKU: 1617 2700K

CRI Ra>80
IP Rating IP20
Dimension ø10x30 mm
Material Plastic
Dimmable NO

170 Lumens
320°
G4



5 PCS
BLISTER




**LED Spotlight G9
3.5W SMD**

Watts 3.5W
Input Voltage AC:220-240V
Flux 400lm
Beam Angle 360°
Socket G9

SKU: 1651 6000K
SKU: 1652 4500K
SKU: 1653 2700K

CRI Ra>80
IP Rating IP20
Dimension ø16x50 mm
Material Ceramic
Dimmable NO

400 Lumens
320°
G9



5 PCS
BLISTER


**LED Spotlight G4/MR11
3W SMD**

Watts 3W
Input Voltage AC;DC 12V
Flux 210lm
Beam Angle 38°
Socket G4

SKU: 1066 6000K
SKU: 1067 4500K
SKU: 1068 2700K

CRI Ra>80
IP Rating IP20
Dimension ø35x45 mm
Material Plastic
Dimmable NO

210 Lumens
38°
G4



5 PCS
BLISTER




**LED Spotlight G9
4W SMD**

Watts 4W
Input Voltage AC:220-240V
Flux 400lm
Beam Angle 360°
Socket G9

SKU: 1654 6000K
SKU: 1655 4500K
SKU: 1656 2700K

CRI Ra>80
IP Rating IP20
Dimension ø16x50 mm
Material Ceramic
Dimmable YES

400 Lumens
Dimmable
G9






LED Spotlight G9
6W SMD

Watts 6W
Input Voltage AC:170-265V
Flux 550lm
Beam Angle 360°
Socket G9

CRI Ra>80
IP Rating IP20
Dimension ø18x64 mm
Material Plastic
Dimmable YES

SKU: 1644 6000K
SKU: 1645 4500K
SKU: 1646 2700K




LED Spotlight G9
7W SMD

Watts 7W
Input Voltage AC:220-240V
Flux 820lm
Beam Angle 360°
Socket G9

CRI Ra>80
IP Rating IP20
Dimension ø19x68 mm
Material Plastic
Dimmable NO

SKU: 1647
2800K




LED Spotlight G9
7W SMD

Watts 7W
Input Voltage AC:220-240V
Flux 950lm
Beam Angle 360°
Socket G9

CRI Ra>80
IP Rating IP20
Dimension ø19x68 mm
Material Plastic
Dimmable NO

SKU: 1648
2800K




LED Spotlight G5.3
15W AR11

Watts 15W
Input Voltage AC ; DC 12V
Flux 1050lm
Beam Angle 30°
Socket G5.3

CRI Ra>80
IP Rating IP20
Dimension ø111x58 mm
Material Plastic
Dimmable NO

SKU: 1517 4500K
SKU: 1516 2700K



LED Spotlight G5.3
15W AR11

Watts 15W
Input Voltage AC ; DC 12V
Flux 1050lm
Beam Angle 120°
Socket G5.3

CRI Ra>80
IP Rating IP20
Dimension ø111x58 mm
Material Plastic
Dimmable NO

SKU: 1519 4500K
SKU: 1518 2700K




LED Spotlight GX53
7W Recessed

Watts 7W
Input Voltage AC:220-240V
Flux 560lm
Beam Angle 180°
Socket GX53

CRI Ra>80
IP Rating IP20
Dimension ø74x25 mm
Material Plastic
Dimmable NO

SKU: 1541 6000K
SKU: 1542 4500K
SKU: 1543 2700K




**LED Spotlight GU10
9W AR111**

Watts 9W
 Input Voltage AC: 170-265V
 Flux 820lm
 Beam Angle 120°
 Socket GU10


SKU: 1531 SKU: 1532
 ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ϕ 111x58 mm
 Material Plastic
 Dimmable NO

820
Lumens

120°

GU10


**LED Spotlight GU10
15W AR111**

Watts 15W
 Input Voltage AC: 170-265V
 Flux 1200lm
 Beam Angle 30°
 Socket GU10


SKU: 1533 SKU: 1534
 ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ϕ 111x58 mm
 Material Aluminium
 Dimmable NO

1200
Lumens

30°

GU10


**LED Spotlight GU10
15W AR111**

Watts 15W
 Input Voltage AC: 170-265V
 Flux 1100lm
 Beam Angle 30°
 Socket GU10


SKU: 1535 SKU: 1536
 ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ϕ 111x58 mm
 Material Aluminium
 Dimmable YES

1100
Lumens

Dimmable

GU10


**LED Spotlight GU5.3/MR16
5W SMD**

Watts 5W
 Input Voltage DC : 12V
 Flux 400lm
 Beam Angle 110°
 Socket GU5.3


SKU: 1191 SKU: 1192 SKU: 1193
 ■ 6000K ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ϕ 50x47 mm
 Material Plastic
 Dimmable NO

400
Lumens

110°

GU5.3


**LED Spotlight GU5.3/MR16
7W SMD**

Watts 7W
 Input Voltage DC : 12V
 Flux 600lm
 Beam Angle 110°
 Socket GU5.3


SKU: 1194 SKU: 1195 SKU: 1196
 ■ 6000K ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ϕ 50x47 mm
 Material Plastic
 Dimmable NO

600
Lumens

110°

GU5.3


**LED Spotlight GU5.3/MR16
4W COB**

Watts 4W
 Input Voltage AC;DC 12V
 Flux 320lm
 Beam Angle 50°
 Socket GU5.3


SKU: 1167 SKU: 1164
 ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ϕ 50x55 mm
 Material Plastic
 Dimmable NO

320
Lumens

50°

GU5.3


**LED Spotlight GU5.3/MR16
6W COB**

Watts 6W
 Input Voltage AC;DC 12V
 Flux 400lm
 Beam Angle 50°
 Socket GU5.3


SKU: 1168 SKU: 1169 SKU: 1170
 ■ 6000K ■ 4500K ■ 2700K

CRI Ra>80
 IP Rating IP20
 Dimension ϕ 50x55 mm
 Material Plastic
 Dimmable NO

400
Lumens


50°

GU5.3




NEW
LED Spotlight GU10 VINTAGE
6W Glass - PREMIUM DIMMING
700
Lumens
 0-100% Dimming
 GU10


Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	700lm	Dimension	ø50x55 mm
Beam Angle	120°	Body Color	Glass
Socket	GU10	Dimmable	YES

 SKU: 1925 SKU:1926 SKU: 1927
 6000K 4500K 2800K

LED Spotlight GU10
4W COB
320
Lumens
 50°
 GU10


Watts	4W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	320lm	Dimension	ø50x60 mm
Beam Angle	50°	Body Color	Gray
Socket	GU10	Dimmable	NO

 SKU: 1263 SKU:1264 SKU: 1265
 6000K 4500K 2700K

LED Spotlight GU10
4W COB
320
Lumens
 50°
 GU10


Watts	4W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	320lm	Dimension	ø50x55 mm
Beam Angle	50°	Body Color	White
Socket	GU10	Dimmable	NO

 SKU: 1957 SKU:1958 SKU: 1959
 6000K 4500K 2700K

LED Spotlight GU10
4W COB
320
Lumens
 Dimmable
 GU10


Watts	4W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	320lm	Dimension	ø50x60 mm
Beam Angle	50°	Body Color	Gray
Socket	GU10	Dimmable	YES

 SKU: 1266 SKU:1267
 6000K 4500K

LED Spotlight GU10
6W COB
480
Lumens
 50°
 GU10


Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	480lm	Dimension	ø50x55 mm
Beam Angle	50°	Body Color	White
Socket	GU10	Dimmable	NO

 SKU: 1960 SKU:1961 SKU: 1962
 6000K 4500K 2700K

LED Spotlight GU10
6W COB
480
Lumens
 50°
 GU10


Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	480lm	Dimension	ø50x60 mm
Beam Angle	50°	Body Color	Gray
Socket	GU10	Dimmable	NO

 SKU: 1269 SKU:1270 SKU: 1271
 6000K 4500K 2700K

LED Spotlight GU10
6W COB
480
Lumens
 Dimmable
 GU10

Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	480lm	Dimension	ø50x55 mm
Beam Angle	50°	Body Color	White
Socket	GU10	Dimmable	YES

 SKU: 1963 SKU:1964 SKU: 1965
 6000K 4500K 2700K

LED Spotlight GU10
6W COB
480
Lumens
 Dimmable
 GU10

Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	480lm	Dimension	ø50x60 mm
Beam Angle	50°	Body Color	Gray
Socket	GU10	Dimmable	YES

 SKU: 1272 SKU:1273 SKU: 1274
 6000K 4500K 2700K



LED Spotlight GU10
4.5W SMD

320
Lumens


110°

GU10

Watts 4.5W
 Input Voltage AC : 220-240V
 Flux 320lm
 Beam Angle 110°
 Socket GU10

CRI Ra>80
 IP Rating IP20
 Dimension ø50x57 mm
 Material Plastic
 Dimmable NO

SKU: 1901 SKU:1902 SKU: 1903
 6000K 4500K 2700K


LED Spotlight GU10
7W SMD

Dimmable

560
Lumens


38°

GU10

Watts 7W
 Input Voltage AC : 175-265V
 Flux 560lm
 Beam Angle 38°
 Socket GU10

CRI Ra>80
 IP Rating IP20
 Dimension ø50x57 mm
 Material Plastic
 Dimmable YES

SKU:1943
 4500K


LED Spotlight GU10
5W SMD

400
Lumens


38°

GU10

Watts 5W
 Input Voltage AC : 175-265V
 Flux 400lm
 Beam Angle 38°
 Socket GU10

CRI Ra>80
 IP Rating IP20
 Dimension ø50x57 mm
 Material Plastic
 Dimmable NO

SKU: 1935 SKU:1936 SKU: 1937
 6000K 4500K 2700K


LED Spotlight GU10
7W SMD

Dimmable

500
Lumens


110°

GU10

Watts 7W
 Input Voltage AC : 175-265V
 Flux 500lm
 Beam Angle 110°
 Socket GU10

CRI Ra>80
 IP Rating IP20
 Dimension ø50x57 mm
 Material Plastic
 Dimmable YES

SKU: 1945 SKU:1946 SKU: 1947
 6000K 4500K 2700K


LED Spotlight GU10
6.5W SMD

550
Lumens


110°

GU10

Watts 6.5W
 Input Voltage AC : 220-240V
 Flux 550lm
 Beam Angle 110°
 Socket GU10

CRI Ra>80
 IP Rating IP20
 Dimension ø50x57 mm
 Material Plastic
 Dimmable NO

SKU: 1904 SKU:1905 SKU: 1906
 6000K 4500K 2700K


LED Spotlight GU10
9.5W SMD

880
Lumens


110°

GU10

Watts 9.5W
 Input Voltage AC : 220-240V
 Flux 880lm
 Beam Angle 110°
 Socket GU10

CRI Ra>80
 IP Rating IP20
 Dimension ø50x57 mm
 Material Plastic
 Dimmable NO

SKU: 1907 SKU:1908 SKU: 1909
 6000K 4500K 2700K


LED Spotlight GU10
7W SMD

560
Lumens


38°

GU10

Watts 7W
 Input Voltage AC : 175-265V
 Flux 560lm
 Beam Angle 38°
 Socket GU10

CRI Ra>80
 IP Rating IP20
 Dimension ø50x57 mm
 Material Plastic
 Dimmable NO

SKU: 1938 SKU:1939 SKU: 1940
 6000K 4500K 2700K





LED Bulbs Premium Line

5 Years Warranty



5 Years Warranty

**LED Bulb G95
12W E27**

Watts 12W
Input Voltage AC : 175-265V
Flux 1055lm
Beam Angle 270°
Socket E27


SKU: 1742 6000K
SKU: 1743 4500K

CRI Ra>80
IP Rating IP20
Dimension ø95x127 mm
Body Type G95
Dimmable NO

1055 Lumens

270°

E27



5 Years Warranty

**LED Bulb G120
15W E27**

Watts 15W
Input Voltage AC : 175-265V
Flux 1320lm
Beam Angle 270°
Socket E27


SKU: 1745 6000K
SKU: 1746 4500K
SKU: 1747 2700K

CRI Ra>80
IP Rating IP20
Dimension ø120x155 mm
Body Type G120
Dimmable NO

1320 Lumens

270°

E27



**LED Bulb A60
10W E27**

Watts 10W
Input Voltage AC : 175-265V
Flux 950lm
Beam Angle 270°
Socket E27


SKU: 1718 6000K
SKU: 1719 4500K
SKU: 1720 2700K

CRI Ra>80
IP Rating IP20
Dimension ø60x109 mm
Body Type A60
Dimmable NO

950 Lumens

5 Years Warranty

E27



**LED Bulb A60
12W E27**

Watts 12W
Input Voltage AC : 175-265V
Flux 1155lm
Beam Angle 270°
Socket E27


SKU: 1721 6000K
SKU: 1722 4500K
SKU: 1723 2700K

CRI Ra>80
IP Rating IP20
Dimension ø60x112 mm
Body Type A60
Dimmable NO

1155 Lumens

5 Years Warranty

E27



**LED Bulb A60
15W E27**

Watts 15W
Input Voltage AC : 175-265V
Flux 1500lm
Beam Angle 270°
Socket E27


SKU: 1724 6000K
SKU: 1725 4500K
SKU: 1726 2700K

CRI Ra>80
IP Rating IP20
Dimension ø60x127 mm
Body Type A60
Dimmable NO

1500 Lumens

5 Years Warranty

E27



**LED Bulb A70
18W E27**

Watts 18W
Input Voltage AC : 175-265V
Flux 1880lm
Beam Angle 270°
Socket E27


SKU: 1748 6000K
SKU: 1749 4500K
SKU: 1750 2700K

CRI Ra>80
IP Rating IP20
Dimension ø70x145 mm
Body Type A70
Dimmable NO

1880 Lumens

5 Years Warranty

E27






5 Years
Warranty

LED Spotlight GU5.3/MR16
5W SMD

Watts 5W
Input Voltage DC : 12V
Flux 320lm
Beam Angle 110°
Socket GU5.3

SKU: 1761 6000K
SKU: 1762 4500K
SKU: 1763 2700K

CRI Ra>80
IP Rating IP20
Dimension ø50x47 mm
Material Plastic
Dimmable NO




5 Years
Warranty

LED Spotlight GU5.3/MR16
7W SMD

Watts 7W
Input Voltage DC : 12V
Flux 500lm
Beam Angle 110°
Socket GU5.3

SKU: 1764 6000K
SKU: 1765 4500K
SKU: 1766 2700K

CRI Ra>80
IP Rating IP20
Dimension ø50x47 mm
Material Plastic
Dimmable NO




5 Years
Warranty

LED Spotlight GU10
5W SMD

Watts 5W
Input Voltage AC : 175-265V
Flux 320lm
Beam Angle 110°
Socket GU10

SKU: 1767 6000K
SKU: 1768 4500K
SKU: 1769 2700K

CRI Ra>80
IP Rating IP20
Dimension ø50x57 mm
Material Plastic
Dimmable NO




5 Years
Warranty

LED Spotlight GU10
7W SMD

Watts 7W
Input Voltage AC : 175-265V
Flux 600lm
Beam Angle 110°
Socket GU10

SKU: 1772 6000K
SKU: 1770 4500K
SKU: 1773 2700K

CRI Ra>80
IP Rating IP20
Dimension ø50x57 mm
Material Plastic
Dimmable NO



SKU: 5081 WHITE BODY
Dimension 180x180x42 mm



SKU: 5083 WHITE BODY
Dimension 330x180x42 mm



SKU: 5085 WHITE BODY
Dimension 480x180x42 mm



Accessories
AR111 Fitting Adjustable



SKU: 5082 SILVER BODY
Dimension 180x180x42 mm



SKU: 5084 SILVER BODY
Dimension 330x180x42 mm



SKU: 5086 SILVER BODY
Dimension 480x180x42 mm



Accessories
AR111 Fitting Adjustable





SKU: 5070 WHITE BODY

Dimension ø82x30 mm

SKU: 5071 INOX BODY

Dimension ø82x30 mm

SKU: 5072 CHROME BODY

Dimension ø82x30 mm

Accessories

GU10,MR16 Fitting



GU10



2 PCS
BOX



ø72mm



SKU: 5170 WHITE BODY Aluminium

Dimension ø83x29 mm

SKU: 5171 INOX BODY Aluminium

Dimension ø83x29 mm

SKU: 5172 CHROME BODY Aluminium

Dimension ø83x29 mm

SKU: 5097 WHITE BODY

Dimension ø83x29 mm

SKU: 5098 INOX BODY

Dimension ø83x29 mm

SKU: 5099 CHROME BODY

Dimension ø83x29 mm

Accessories

GU10,MR16 Fitting Adjustable



GU10



2 PCS
BOX



45°



ø72mm



SKU: 5073 WHITE BODY

Dimension 83x83x30 mm

SKU: 5074 INOX BODY

Dimension 83x83x30 mm

SKU: 5075 CHROME BODY

Dimension 83x83x30 mm

Accessories

GU10,MR16 Fitting



GU10



2 PCS
BOX



ø72mm



SKU: 5076 WHITE BODY

Dimension ø83x29 mm

SKU: 5077 INOX BODY

Dimension ø83x29 mm

SKU: 5078 CHROME BODY

Dimension ø83x29 mm

Accessories

GU10,MR16 Fitting Adjustable



GU10



2 PCS
BOX



45°



ø72mm


**Spotlight Fixture - Waterproof
GU10 Fitting**


Product code	OT1-A2	IP Rating	IP65
Socket	GU10	Dimension	Φ80x54 ; 83x83x54 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Satin Nickel
Material	Aluminium	Max Power	35W

SKU: 2009 White Body - Round

SKU: 2011 White Body - Square

**Spotlight Fixture - Aluminium
GU10 Fitting**


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ79x32 mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Aluminium+PC	Max Power	35W

SKU: 2048 Black Reflector

SKU: 2047 White Reflector

SKU: 2049 Rose Gold Reflector

**Spotlight Fixture - Waterproof
GU10 Fitting**


Product code	OT1-A2	IP Rating	IP65
Socket	GU10	Dimension	Φ80x54 ; 83x83x54 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Satin Nickel
Material	Aluminium	Max Power	35W

SKU: 2010 Satin Nickel - Round

SKU: 2012 Satin Nickel - Square

**Spotlight Fixture - Plastic
GU10 Fitting**


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	102x102x42 mm
Input Voltage	AC : 220-240V	Body Colors	White,Black,White-Black
Material	Plastic	Max Power	35W

SKU: 2050 White Body

SKU: 2051 Black Body

SKU: 2052 White-Black Body


**Spotlight Fixture - Aluminium
2xGU10 Fitting Adjustable**


Product code	OT1-A2	IP Rating	IP20
Socket	2xGU10	Dimension	80x160x85
Input Voltage	AC : 220-240V	Body Colors	White-Black
Material	Aluminium	Max Power	35W

SKU: 2080 White- 2xGU10

SKU: 2081 Black- 2XGu10


ø90mm



90x90mm

**Spotlight Fixture - Aluminium
GU10 Fitting Adjustable**


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	ø100x38 mm ;100x100x38mm
Input Voltage	AC : 220-240V	Body Colors	White-Black
Material	Aluminium	Max Power	35W

SKU: 2013 White/Black- Round

SKU: 2014 White/Black- Square

**Spotlight Fixture - Aluminium
GU10 Fitting**


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ120x80mm;120x120x80mm
Input Voltage	AC : 220-240V	Body Colors	Black
Material	Aluminium	Max Power	35W

SKU: 2082 Black-Round

SKU: 2083 Black-Sqyare


175x90mm



260x90mm

**Spotlight Fixture - Aluminium
GU10 Fitting Adjustable**


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	185x100x38mm , 270x100x38 mm
Input Voltage	AC : 220-240V	Body Colors	White-Black
Material	Aluminium	Max Power	35W

SKU: 2015 2xGU10 Holder

SKU: 2016 3xGU10 Holder


**Spotlight Fixture - Round
GU10 Fitting**


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ80x42 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Aluminium+PC	Max Power	35W

SKU: 2031 White
SKU: 2032 Black


**Spotlight Fixture - Round
GU10 Fitting**


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ80x42 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Aluminium+PC	Max Power	35W

SKU: 2035 Round
SKU: 2036 Black


**Spotlight Fixture - Round
GU10 Fitting**


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ80x42 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Aluminium+PC	Max Power	35W

SKU: 2033 White
SKU: 2034 Black


**Spotlight Fixture - Round
GU10 Fitting**


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ80x42 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Aluminium+PC	Max Power	35W

SKU: 2037 White
SKU: 2038 Black



Spotlight Fixture
GU10 Fitting



Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	75x75x140 mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Aluminium	Max Power	35W

- SKU: 2039 Black Reflector
- SKU: 2040 White Reflector
- SKU: 2041 Rose Gold Reflector



Spotlight Fixture -Plastic
GU10 Fitting Adjustable



Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	Φ80x125 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Plastic	Max Power	10W

- SKU: 2001 White Body
- SKU: 2002 Black Body
- SKU: 2005 White Body
- SKU: 2006 Black Body



Spotlight Fixture
GU10 Fitting



Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	Φ80x140 mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Aluminium	Max Power	35W

- SKU: 2042 Black Reflector
- SKU: 2043 White Reflector
- SKU: 2044 Rose Gold Reflector



Spotlight Fixture -Plastic
GU10 Fitting Adjustable



Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	85x85x130 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Plastic	Max Power	10W

- SKU: 2003 White Body
- SKU: 2004 Black Body
- SKU: 2007 White Body
- SKU: 2008 Black Body



Spotlight Fixture - Aluminium
GU10 Fitting Adjustable



Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ80x42 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Aluminium+PC	Max Power	35W

SKU: 2027 White Body
 SKU: 2028 Black Body



Tracklight Fixture -Aluminium
**GU10 Fitting Adjustable
 For 3-Phase Track**



Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ55x82 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Aluminium	Max Power	35W

SKU: 2017 White Body
 SKU: 2018 Black Body



Spotlight Fixture - Aluminium
GU10 Fitting



Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ60x100 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Aluminium+PC	Max Power	35W

SKU: 2029 White Body
 SKU: 2030 Black Body



Tracklight Fixture -Plastic
**GU10 Fitting Adjustable
 For Single-Phase Track**



Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ59x94x114 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Plastic	Max Power	10W

SKU: 2019 White Body
 SKU: 2020 Black Body


**Spotlight Fixture - Plastic
GU10 Fitting**


90°



GU10 Holder



IP20

Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ120x145 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Plastic	Max Power	10W

SKU: 2021 White
SKU: 2022 Black

**Spotlight Fixture - Plastic
GU10 Fitting**


90°



GU10 Holder



IP20

Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ120x145 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Plastic	Max Power	10W Each

SKU: 2025 White
SKU: 2026 Black



75x75mm



φ85mm

**Spotlight Fixture - Plastic
GU10 Fitting**


90°



GU10 Holder



IP20

Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ120x145 mm
Input Voltage	AC : 220-240V	Body Colors	White ; Black
Material	Plastic	Max Power	10W Each

SKU: 2023 Round
SKU: 2024 Square

**Spotlight Fixture - Recessed
GU10 Fitting**


GU10 Holder



IP20

Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	75x75x55mm ; φ85x50mm
Input Voltage	AC : 220-240V	Body Colors	White - Black Reflektor
Material	Aluminium+PC	Max Power	35W

SKU: 2045 Square
SKU: 2046 Round



Ceiling Fixture Trimless Recessed

GU10 Fitting
Gypsum + ALU


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ100x27mm ; 100x100x27mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Gypsum+Alu	Max Power	35W


SKU: 2060 Round
 SKU: 2061 Square

Ceiling Fixture Trimless Recessed

GU10 Fitting
Gypsum + ALU


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	120x120x60mm ; 215x118x58mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Gypsum+Alu	Max Power	35W

SKU: 2064 Square
 SKU: 2065 Rectangle



Ceiling Fixture Trimless Recessed

GU10 Fitting
Gypsum + ALU


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ130x50mm ; 120x120x60mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Gypsum+Alu	Max Power	35W

SKU: 2062 Round
 SKU: 2063 Square

Ceiling Fixture Trimless Recessed

GU10 Fitting
Gypsum + ALU


Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	120x120x60mm ; 215x118x58mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Gypsum+Alu	Max Power	35W

SKU: 2066 Round
 SKU: 2067 Square



Ceiling Fixture Trimless Recessed

GU10 Fitting
Gypsum + ALU

Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ120x65mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Gypsum+Alu	Max Power	35W



SKU: 2068 Round-Frosted
 SKU: 2069 Round



Ceiling Fixture Surface Mounted

GU10 Fitting
Gypsum + ALU

Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	70x70x70mm ; 70x70x170mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Gypsum+Alu	Max Power	35W



SKU: 2072 Square H70
 SKU: 2073 Square H170



Ceiling Fixture Surface Mounted

GU10 Fitting
Gypsum + ALU

Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ70x70 mm ; φ70x170 mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Gypsum+Alu	Max Power	35W



SKU: 2070 Round H70mm
 SKU: 2071 Round H170mm




Ceiling Fixture Surface Mounted

GU10 Fitting
Gypsum + ALU

Product code	OT1-A2	IP Rating	IP20
Socket	GU10	Dimension	φ110x140mm ; 110x110x140mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Gypsum+Alu	Max Power	35W



SKU: 2074 Round
 SKU: 2075 Square




Spotlight Fixture - Single Head
GU10 Fitting


90°



GU10 Holder



IP20

Product code	OT1-A6	IP Rating	IP20
Socket	GU10	Dimension	60x108 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium	Max Power	35W

SKU: 9072 Black
 SKU: 9076 White


Spotlight Fixture - Three Heads
GU10 Fitting


90°



GU10 Holder



IP20

Product code	OT1-A6	IP Rating	IP20
Socket	GU10x3	Dimension	540x60x180 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium	Max Power	35W Each

SKU: 9074 Black GU10x3
 SKU: 9078 White GU10x3


Spotlight Fixture - Two Heads
GU10 Fitting


90°



GU10 Holder



IP20

Product code	OT1-A6	IP Rating	IP20
Socket	GU10x2	Dimension	300x60x180mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium	Max Power	35W Each

SKU: 9073 Black GU10x2
 SKU: 9077 White GU10x2


Spotlight Fixture - Four Heads
GU10 Fitting


90°



GU10 Holder



IP20

Product code	OT1-A6	IP Rating	IP20
Socket	GU10x4	Dimension	720x60x180 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium	Max Power	35W Each

SKU: 9075 Black GU10x4
 SKU: 9079 White GU10x4


 Hanging Fixture - H300mm
GU10 Fitting



Product code	OT1-A6	IP Rating	IP20
Socket	GU10	Dimension	60x300 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium	Max Power	35W

SKU: 9050	Black - Inner range: Gold
SKU: 9051	Black - Inner range: Black
SKU: 9054	White - Inner range: Gold
SKU: 9055	White - Inner range: Black


 Hanging Fixture - H500mm
GU10 Fitting


Product code	OT1-A6	IP Rating	IP20
Socket	GU10	Dimension	60x500 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium	Max Power	35W

SKU: 9058	Black Body
SKU: 9059	White Body


 Hanging Fixture - H500mm
GU10 Fitting


Product code	OT1-A6	IP Rating	IP20
Socket	GU10	Dimension	60x500 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium	Max Power	35W

SKU: 9052	Black - Inner range: Gold
SKU: 9053	Black - Inner range: Black
SKU: 9056	White - Inner range: Gold
SKU: 9057	White - Inner range: Black


 Hanging Fixture - H200mm
GU10 Fitting


Product code	OT1-A6	IP Rating	IP20
Socket	GU10	Dimension	60x200 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium	Max Power	35W

SKU: 9060	Black Body
SKU: 9061	White Body


 Hanging Fixture - H300mm
GU10 Fitting


Product code	OT1-A6	IP Rating	IP20
Socket	GU10	Dimension	55x300 mm
Input Voltage	AC : 220-240V	Body Colors	B/W/G/CG/C
Material	Aluminium	Max Power	35W

SKU: 9062	Black Body
SKU: 9063	White Body
SKU: 9064	Gold Body
SKU: 9065	Coffee Gold Body
SKU: 9066	Chrome Body

 Hanging Fixture - H300mm
GU10 Fitting


Product code	OT1-A6	IP Rating	IP20
Socket	GU10	Dimension	55x300 mm
Input Voltage	AC : 220-240V	Body Colors	B/W/G/CG/C
Material	Aluminium	Max Power	35W

SKU: 9067	Black Body
SKU: 9068	White Body
SKU: 9069	Gold Body
SKU: 9070	Coffee Gold Body
SKU: 9071	Chrome Body



Hanging Fixture - H400mm
GU10 Fitting



Product code	OT1-A6	IP Rating	IP20
Socket	GU10	Dimension	60x400 mm
Input Voltage	AC : 220-240V	Body Colors	B/W/S/GR
Material	Aluminium	Max Power	35W

SKU: 9082	Black Body
SKU: 9083	White Body
SKU: 9080	Silver Body
SKU: 9081	Grape Red Body

Hanging Fixture - H400mm
E27 Fitting



Product code	OT1-A6	IP Rating	IP20
Socket	E27	Dimension	40x400 mm
Input Voltage	AC : 220-240V	Body Colors	B/W/CG/RG
Material	Aluminium	Max Power	35W

SKU: 9084	Black Body
SKU: 9085	White Body
SKU: 9086	Coffee Gold Body
SKU: 9087	Rose Gold Body



LED TUBES AND BATTEN LIGHTS

LED tubes are the perfect replacement for old fluorescent tubes. With variety of sizes, powers and colour temperatures they are suitable for every need – from home use to office or warehouses.

Features:

- Up to 80% power saving
- Standard sizes, fits already built lighting solutions
- Variety of colour temperatures
- Single or two side power
- Build-in starters
- Variety of covers – from nano-plastic to glass

Application:

- Indoor use – home, offices, shops
- Main lighting
- Suitable for tube fixtures



Switch




LED TUBE T5 - Plastic
Matt With Switch



3.4W
300
Lumens


Watts	3.4W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	320lm	IP Rating	IP20



SKU: 5588 6000K
SKU:5589 4000K
SKU: 5590 3000K

6.5W
600
Lumens


Watts	6.5W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	600lm	IP Rating	IP20



SKU: 5591 6000K
SKU:5592 4000K
SKU: 5593 3000K

9.6W
900
Lumens


Watts	12W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	900lm	IP Rating	IP20



SKU: 5594 6000K
SKU:5595 4000K
SKU: 5596 3000K

13W
1200
Lumens

Watts	13W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	1200lm	IP Rating	IP20



SKU: 5597 6000K
SKU:5598 4000K
SKU: 5599 3000K



T5 DOUBLE INPUT CABLE
Not Included
Length: 30cm / 50cm / 100cm




LED TUBE T5 - Plastic
Matt



3.4W
300
Lumens


Watts	3.4W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	320lm	IP Rating	IP20



SKU: 5501 6000K
SKU:5502 4000K
SKU: 5503 3000K

6.5W
600
Lumens

Watts	6.5W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	600lm	IP Rating	IP20



SKU: 5504 6000K
SKU:5505 4000K
SKU: 5506 3000K

9.6W
900
Lumens

Watts	12W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	900lm	IP Rating	IP20



SKU: 5507 6000K
SKU:5508 4000K
SKU: 5509 3000K

13W
1200
Lumens

Watts	13W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	1200lm	IP Rating	IP20



SKU: 5538 6000K
SKU:5539 4000K
SKU: 5540 3000K




With Starter

LED TUBE T8 **PF>0.9****High Lumen****Nano Plastic - One Side Power****NEW**
140
 Lumen/W

HIGH
 Lumens

270°
IP20
9W
1260
 Lumens

Product code	TU9-A3	Beam Angle	270°
Watts	9W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	1260lm	Instant Start	<0.5s



 SKU: 15541 SKU:15542
 6000K 4000K


With Starter


LED TUBE T8 **PF>0.9****Nano Plastic - One Side Power****NEW**
HIGH
 Lumens

270°
IP20
9W
900
 Lumens


Product code	TU9-A3	Beam Angle	270°
Watts	9W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	900lm	Instant Start	<0.5s


 SKU: 15511 SKU:15512 SKU: 15513
 6000K 4000K 3000K
18W
2520
 Lumens


Product code	TU18-A3	Beam Angle	270°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	2520lm	Instant Start	<0.5s


 SKU: 15544 SKU:15545
 6000K 4000K
18W
1800
 Lumens


Product code	TU18-A3	Beam Angle	270°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	1800lm	Instant Start	<0.5s


 SKU: 15514 SKU:15515 SKU: 15516
 6000K 4000K 3000K
22W
3080
 Lumens

Product code	TU22-A3	Beam Angle	270°
Watts	22W	CRI	Ra>80
Input Voltage	AC : 175-250V	IP Rating	IP20
Flux	3080lm	Instant Start	<0.5s



 SKU: 15547 SKU:15548
 6000K 4000K
22W
2400
 Lumens

Product code	TU22-A3	Beam Angle	270°
Watts	22W	CRI	Ra>80
Input Voltage	AC : 220-250V	IP Rating	IP20
Flux	2400lm	Instant Start	<0.5s


 SKU: 15517 SKU:15518 SKU: 15519
 6000K 4000K 3000K



With Starter



Rotatable

LED TUBE T8 **PF>0.9**

High Lumen

Nano Plastic - One Side Power

5
Years
Warranty

160
Lumen/W


HIGH
Lumens

270°

IP20

12W
1920
Lumens


Product code	TU12-A3	Beam Angle	270°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 175-250V	IP Rating	IP20
Flux	1920lm	Instant Start	<0.5s



SKU: 5544 6000K
SKU: 5545 4500K
SKU: 5546 2800K

16W
2560
Lumens


Product code	TU16-A3	Beam Angle	270°
Watts	16W	CRI	Ra>80
Input Voltage	AC : 175-250V	IP Rating	IP20
Flux	2560lm	Instant Start	<0.5s



SKU: 5549
2800K



With Starter



Rotatable

LED TUBE T8 **PF>0.9**

Nano Plastic - One Side Power

5
Years
Warranty


HIGH
Lumens

270°

IP20

9W
900
Lumens


Product code	TU9-A3	Beam Angle	270°
Watts	9W	CRI	Ra>80
Input Voltage	AC : 175-250V	IP Rating	IP20
Flux	900lm	Instant Start	<0.5s



SKU: 5511 6000K
SKU: 5512 4500K
SKU: 5513 2800K

18W
1800
Lumens


Product code	TU18-A3	Beam Angle	270°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 175-240V	IP Rating	IP20
Flux	1800lm	Instant Start	<0.5s



SKU: 5514 6000K
SKU: 5515 4500K
SKU: 5516 2800K

22W
2400
Lumens


Product code	TU22-A3	Beam Angle	270°
Watts	22W	CRI	Ra>80
Input Voltage	AC : 175-250V	IP Rating	IP20
Flux	2400lm	Instant Start	<0.5s




SKU: 5517 6000K
SKU: 5518 4500K
SKU: 5519 2800K

LED TUBE T8 **PF>0.9****PRO - Line****Glass - One Side Power****9W**1000
Lumens


Product code	TU9-A4	Beam Angle	270°
Watts	9W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1000lm	Instant Start	<0.5s


 SKU: 5614
 6000K
 SKU: 5615
4500K
LED TUBE T8 **PF>0.9****City Line****Glass - One Side Power****9W**900
Lumens


Product code	TU9-A2	Beam Angle	270°
Watts	9W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	900lm	Instant Start	<0.5s


 SKU: 5601
 6000K
 SKU: 5602
4500K
SKU: 5603
2800K
18W2100
Lumens


Product code	TU18-A4	Beam Angle	270°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	2100lm	Instant Start	<0.5s


 SKU: 5617
 6000K
 SKU: 5618
4500K
18W1800
Lumens


Product code	TU18-A2	Beam Angle	270°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1800lm	Instant Start	<0.5s


 SKU: 5604
 6000K
 SKU: 5605
4500K
SKU: 5606
2800K
24W2800
Lumens

Product code	TU24-A1	Beam Angle	270°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	3000lm	Instant Start	<0.5s


 SKU: 5610
 6000K
 SKU: 5611
4500K
22W2200
Lumens

Product code	TU22-A2	Beam Angle	270°
Watts	22W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	2200lm	Instant Start	<0.5s


 SKU: 5607
 6000K
 SKU: 5608
4500K
SKU: 5609
2800K



With Starter




LED TUBE T8 **PF>0.9**
Professional edition
Aluminium-One Side Power



9W
810
 Lumens

Product code	TU9-A1	Beam Angle	140°
Watts	9W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	810lm	Instant Start	<0.5s




SKU: 5611-M
 6000K

SKU: 5612-M
 2800K

18W
1440
 Lumens

Product code	TU18-A1	Beam Angle	140°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1440lm	Instant Start	<0.5s



SKU: 5624-M
 2800K




LED TUBE T8
Home edition
Glass - One Side Power

NEW



9W
720
 Lumens

Product code	TU9-A2	Beam Angle	270°
Watts	9W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	720lm	Instant Start	<0.5s




SKU: 5626
 6000K

SKU: 5627
 4000K

18W
1440
 Lumens

Product code	TU18-A2	Beam Angle	270°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1440lm	Instant Start	<0.5s




SKU: 5629
 6000K

SKU: 5630
 4000K

22W
1760
 Lumens

Product code	TU22-A2	Beam Angle	270°
Watts	22W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1760lm	Instant Start	<0.5s



SKU: 5628
 6000K

SKU: 5631
 4000K



M12 cable gland



LED FIXTURES WITH T8 TUBES

Single City Line - Glass PF>0.9**One Side Power**

180°




IP65

9W**900**

Lumens

Product code	OT1-A9	Beam Angle	180°
Watts	9W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	900lm	Instant Start	<0.5s



SKU: 6731

6000K

SKU:6732

4500K

LED FIXTURES WITH T8 TUBES

Double City Line - Glass PF>0.9**One Side Power**

180°




IP65

2*9W**1800**

Lumens

Product code	OT1-B1	Beam Angle	180°
Watts	2*9W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	1800lm	Instant Start	<0.5s



SKU: 6733

6000K

SKU:6734

4500K

18W**1800**

Lumens

Product code	OT1-A9	Beam Angle	180°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	1800lm	Instant Start	<0.5s



SKU: 6735

6000K


SKU:6736

4500K

2*18W**3600**

Lumens

Product code	OT1-B1	Beam Angle	180°
Watts	2*18W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	3600lm	Instant Start	<0.5s



SKU: 6737

6000K

SKU:6738

4500K

22W**2200**

Lumens

Product code	OT1-A9	Beam Angle	180°
Watts	22W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	2200lm	Instant Start	<0.5s



SKU: 6739

6000K

SKU:6740

4500K

2*22W**4400**

Lumens

Product code	OT1-B1	Beam Angle	180°
Watts	2*22W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	4400lm	Instant Start	<0.5s



SKU: 6741

6000K

SKU:6742

4500K




Single T8 Tube Fixture - Without Tubes

For One Side Power

SKU: 6650 For Single LED Tube 9W-60cm

SKU: 6652 For Single LED Tube 18W-120cm

SKU: 6654 For Single LED Tube 22W-150cm






Double T8 Tube Fixture - Without Tubes

For One Side Power

SKU: 6651 For Two LED Tube 9W-60cm

SKU: 6653 For Two LED Tube 18W-120cm

SKU: 6655 For Two LED Tube 22W-150cm






M12 cable gland

NEW



Linkable

40W LED
IP65 Fixture Type
Linkable



180°



IP65

40W 4000 Lumens	Product code	OT40-A1	Beam Angle	180°
	Watts	40W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	4000lm	Instant Start	<0.5s

SKU: 16701 SKU:16702
6000K 4500K

40W 4000 Lumens	Product code	OT40-A1	Beam Angle	180°
	Watts	40W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	4000lm	Instant Start	<0.5s



SKU: 16705 SKU:16706
6000K 4500K

40W 4000 Lumens	Product code	TU40-A1	Beam Angle	180°
	Watts	40W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	4000lm	Instant Start	<0.5s



Emergency

SKU: 16709 SKU:16710
6000K 4500K




M12 cable gland

NEW



Linkable

55W LED
IP65 Fixture Type
Linkable



180°



IP65

55W 6000 Lumens	Product code	OT55-A1	Beam Angle	180°
	Watts	55W	CRI	Ra>80
	Input Voltage	AC : 220-240v	IP Rating	IP65
	Flux	6000lm	Instant Start	<0.5s

SKU: 16703 SKU:16704
6000K 4500K

55W 6000 Lumens	Product code	OT55-A1	Beam Angle	180°
	Watts	55W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	6000lm	Instant Start	<0.5s



SKU: 16707 SKU:16708
6000K 4500K

55W 6000 Lumens	Product code	OT55-A1	Beam Angle	180°
	Watts	55W	CRI	Ra>80
	Input Voltage	AC :220-240V	IP Rating	IP65
	Flux	6000lm	Instant Start	<0.5s



Emergency

SKU: 16711 SKU:16712
6000K 4500K




M12 cable gland



Stainless steel clips

40W LED
IP65 Fixture Type
Stainless steel clips



40W 4000 Lumens	Product code	OT40-A1	Beam Angle	180°
	Watts	40W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	4000lm	Instant Start	<0.5s

SKU: 6701 SKU:6702
6000K 4500K

40W 4000 Lumens	Product code	OT40-A1	Beam Angle	180°
	Watts	40W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	4000lm	Instant Start	<0.5s



SKU: 6705 SKU:6706
6000K 4500K

40W 4000 Lumens	Product code	TU40-A1	Beam Angle	180°
	Watts	40W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	4000lm	Instant Start	<0.5s



SKU: 6709 SKU:6710
6000K 4500K

Emergency




M12 cable gland



Stainless steel clips

55W LED
IP65 Fixture Type
Stainless steel clips



55W 6000 Lumens	Product code	OT55-A1	Beam Angle	180°
	Watts	55W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	6000lm	Instant Start	<0.5s

SKU: 6703 SKU:6704
6000K 4500K

55W 6000 Lumens	Product code	OT55-A1	Beam Angle	180°
	Watts	55W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	6000lm	Instant Start	<0.5s



SKU: 6707 SKU:6708
6000K 4500K

55W 6000 Lumens	Product code	OT55-A1	Beam Angle	180°
	Watts	55W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	6000lm	Instant Start	<0.5s



SKU: 6711 SKU:6712
6000K 4500K

Emergency


**Single T8 Fixture
for LED One Side Power Tube**


Product code	OT1-A7	IP Rating	IP20
Socket	T8	Dimension	606x33mm;1250x33mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Metal+PC	Max Power	100W

SKU: 6745	1xT8-60cm Tube
SKU: 6746	1xT8-120cm Tube
SKU: 6749	1xT8-150cm Tube


**Double T8 Fixture
for LED One Side Power Tube**



Product code	OT1-A7	IP Rating	IP20
Socket	2xT8	Dimension	606x73mm;1250x73mm
Input Voltage	AC : 220-240V	Body Colors	White
Material	Metal+PC	Max Power	100W

SKU: 6747	2xT8-60cm Tube
SKU: 6748	2xT8-120cm Tube
SKU: 6750	2xT8-150cm Tube


**LED Batten Light PF>0.9
Stainless steel clips**


10W
1150
 Lumens


Product code	OT10-A2	Beam Angle	120°
Watts	10W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	1150lm	Instant Start	<0.5s



SKU: 6671	SKU:6672	SKU: 6673
6000K	4000K	2800K

20W
2300
 Lumens


Product code	OT20-A1	Beam Angle	120°
Watts	20W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	2300lm	Instant Start	<0.5s



SKU: 6674	SKU:6675	SKU: 6676
6000K	4000K	2800K

40W
3320
 Lumens


Product code	OT40-A4	Beam Angle	120°
Watts	40W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3320lm	Instant Start	<0.5s



SKU: 6677	SKU:6678	SKU: 6679
6000K	4000K	2800K

50W
4150
 Lumens


Product code	OT50-A1	Beam Angle	120°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	4150lm	Instant Start	<0.5s




SKU: 6680	SKU:6681
6000K	4000K

LED Batten Lights **PF>0.9****Waterproof IP65**


20W	Product code	OT20-A2	Beam Angle	120°
	Watts	20W	CRI	Ra>80
1600	Input Voltage	AC : 220-240V	IP Rating	IP65
Lumens	Flux	1600lm	Instant Start	<0.5s


 SKU: 6691 SKU:6692
 6000K 4000K

40W	Product code	OT40-A5	Beam Angle	120°
	Watts	40W	CRI	Ra>80
3200	Input Voltage	AC : 220-240V	IP Rating	IP65
Lumens	Flux	3200lm	Instant Start	<0.5s


 SKU: 6694 SKU:6695
 6000K 4000K


50W	Product code	OT50-A2	Beam Angle	120°
	Watts	50W	CRI	Ra>80
4150	Input Voltage	AC : 220-240V	IP Rating	IP65
Lumens	Flux	4150lm	Instant Start	<0.5s


 SKU: 6697 SKU:6698
 6000K 4000K



M12 cable gland

LED Light Fitting **PF>0.9****Stainless steel clips****With fast M12 cable gland**


18W	Product code	OT18-A1	Beam Angle	180°
	Watts	18W	CRI	Ra>80
1800	Input Voltage	AC : 220-240V	IP Rating	IP65
Lumens	Flux	1800lm	Instant Start	<0.5s


 SKU: 6721 SKU:6722
 6000K 4000K

36W	Product code	OT36-A1	Beam Angle	180°
	Watts	36W	CRI	Ra>80
3600	Input Voltage	AC : 175-250V	IP Rating	IP65
Lumens	Flux	3600lm	Instant Start	<0.5s


 SKU: 6723 SKU:6724
 6000K 4000K

45W	Product code	OT45-A1	Beam Angle	180°
	Watts	45W	CRI	Ra>80
4500	Input Voltage	AC : 220-240V	IP Rating	IP65
Lumens	Flux	4500lm	Instant Start	<0.5s


 SKU: 6725 SKU:6726
 6000K 4000K



Industry-wide requirement throughout the entire world now, a prerequisite for all residential and business sites, OPTONICA LED covers all major subcategories.

Features:

- Up to 80% power saving
- Self-test mode with battery state indicator
- Various directions pictograms included
- 3 hours emergency operation
- Highly reliable with instant automatic on.

Application:

- Suitable for residential, industrial and commercial projects



EMERGENCY LED EXIT SIGN

An emergency light is a battery-backed lighting device that switches on automatically when a building experiences a power outage.

All bulkhead and exit signs include 4 pictograms:



Battery

● Left Arrow



● Right Arrow



● UP Arrow



● EXIT



EMERGENCY LED EXIT SIGN

Wall / Surface Mount



Battery

Product code	WW1-A1
Watts	3W
Input Voltage	AC : 220-240V
IP Rating	IP20
Battery	3.6V 900mAh Ni-Cd battery
Emergency Duration	> 3 Hours

SKU: 7203 White Light 6000K



EMERGENCY LED EXIT SIGN

Wall / Surface Mount



Battery

Product code	WW1-A1
Watts	3W
Input Voltage	AC : 220-240V
IP Rating	IP20
Battery	3.6V 900mAh Ni-Cd battery
Emergency Duration	> 3 Hours

SKU: 7204 White Light 6000K



EMERGENCY LED EXIT SIGN

Recessed Fixed



Battery

Product code	WW1-A1
Watts	3W
Input Voltage	AC : 220-240V
IP Rating	IP20
Battery	3.6V 900mAh Ni-Cd battery
Emergency Duration	> 3 Hours

SKU: 7206 White Light 6000K



EMERGENCY LED EXIT SIGN

Recessed Hanging



Battery

Product code	WW1-A1
Watts	3W
Input Voltage	AC : 220-240V
IP Rating	IP20
Battery	3.6V 900mAh Ni-Cd battery
Emergency Duration	> 3 Hours

SKU: 7205 White Light 6000K



EMERGENCY LED EXIT SIGN

Bulkhead

Product code	WW1-A1	 Battery
Watts	4W	
Input Voltage	AC : 220-240V	
IP Rating	IP65	
Battery	3.6V 1500mAh Ni-Cd battery	
Emergency Duration	> 3 Hours	

SKU: 7201 White Light 

SKU: 7202 Recessed kit for SKU: 7201



EMERGENCY LED EXIT SIGN

Wall Mounted

Product code	WW1-A1	 Battery
Watts	3W	
Input Voltage	AC : 220-240V	
IP Rating	IP20	
Battery	3.6V 1200mAh Ni-Cd battery	
Emergency Duration	> 3 Hours	

SKU: 7207 White Light 

EMERGENCY LED TWINSPOTS 3W

Wall Mount - Self Test

Product code	WW1-A2	 280 Lumens
Watts	2x3 pcs 0.5W	
Input Voltage	AC : 220-240V	
IP Rating	IP20	
Battery	3.6V 1800mAh	
Emergency Duration	> 3 Hours	

SKU: 7208 White Light 

EMERGENCY LED TWINSPOTS 6W

Wall Mount - Self Test

Product code	WW1-A2	 450 Lumens
Watts	2x6 pcs 0.5W	
Input Voltage	AC : 220-240V	
IP Rating	IP20	
Battery	3.6V 3000mAh	
Emergency Duration	> 3 Hours	

SKU: 7209 White Light 

EMERGENCY LED LIGHT

Downlight

Product code	WW1-A3	 250 Lumens
Watts	3W	
Input Voltage	AC : 220-240V	
IP Rating	IP20	
Battery	3.6V 1800mAh	
Emergency Duration	> 3 Hours	

SKU: 7210 White Light OSRAM
Chips

EMERGENCY LED LIGHT

Downlight - Osram chip

Product code	WW1-A3	 460 Lumens
Watts	3W	
Input Voltage	AC : 220-240V	
IP Rating	IP20	
Battery	3.6V 1800mAh	
Emergency Duration	> 3 Hours	

SKU: 7211 White Light 




Allowing full flexibility of installation on every hard surface so there are no more design restraints.

Features:

- Up to 80% power saving
- Variety of colour temperatures
- Glossy or matt finishing
- Standard sizes
- Variety of powers

Application:

- Extremely wide indoor application use – home, office, retail, hospitals, restaurants, indoor parking lots, manufacturing spaces





3 Years
Warranty

100°

IP44



Color Changing knob

CCT - SURFACE LED PANELS


ROUND Build-in Driver

6W

450
Lumens

Product code DL6-A3
Watts 6W
Input Voltage AC : 165-265V
Flux 450lm

Beam Angle 100°
CRI Ra>80
IP Rating IP44 Front
Dimension ø115x32mm



SKU: 2535

CCT - Steps


6000K 4500K 3000K

12W

950
Lumens

Product code DL12-A3
Watts 12W
Input Voltage AC : 165-265V
Flux 950lm

Beam Angle 100°
CRI Ra>80
IP Rating IP44 Front
Dimension ø170x32mm



SKU: 2536

CCT - Steps


6000K 4500K 3000K

18W

1450
Lumens

Product code DL18-A3
Watts 18W
Input Voltage AC : 165-265V
Flux 1450lm

Beam Angle 100°
CRI Ra>80
IP Rating IP44 Front
Dimension ø220x32mm



SKU: 2537

CCT - Steps


6000K 4500K 3000K

24W

2565
Lumens

Product code DL24-A3
Watts 24W
Input Voltage AC : 165-265V
Flux 2565lm

Beam Angle 100°
CRI Ra>80
IP Rating IP44 Front
Dimension ø240x32mm



SKU: 2538

CCT - Steps

6000K 4500K 3000K



3 Years
Warranty

100°

IP44



Color Changing Knob

CCT - SURFACE LED PANELS


SQUARE Build-in Driver

6W

450
Lumens

Product code DL6-A3
Watts 6W
Input Voltage AC : 165-265V
Flux 450lm

Beam Angle 100°
CRI Ra>80
IP Rating IP44 Front
Dimension 122x122x35mm



SKU: 2539

CCT - Steps


6000K 4500K 3000K

12W

950
Lumens

Product code DL12-A3
Watts 12W
Input Voltage AC : 165-265V
Flux 950lm

Beam Angle 100°
CRI Ra>80
IP Rating IP44 Front
Dimension 172x172x35mm



SKU: 2540

CCT - Steps


6000K 4500K 3000K

18W

1450
Lumens

Product code DL18-A3
Watts 18W
Input Voltage AC : 165-265V
Flux 1450lm

Beam Angle 100°
CRI Ra>80
IP Rating IP44 Front
Dimension 227x227x35mm



SKU: 2541

CCT - Steps


6000K 4500K 3000K

24W

2150
Lumens

Product code DL24-A3
Watts 24W
Input Voltage AC : 165-265V
Flux 2150lm

Beam Angle 100°
CRI Ra>80
IP Rating IP44 Front
Dimension 227x227x35mm



SKU: 2542

CCT - Steps

6000K 4500K 3000K

NEW



LED BACKLIT SURFACE PANELS


ROUND - Driver-on-board

Home Edition

6W



Product code	DL6-B1	Beam Angle	120°
Watts	6W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	360lm	Material	Plastic




SKU: 2975 6000K
SKU: 2976 4500K
SKU: 2977 2700K

12W



Product code	DL12-B1	Beam Angle	120°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	840lm	Cutting Size	Plastic




SKU: 2978 6000K
SKU: 2979 4500K
SKU: 2980 2700K

18W



Product code	DL18-B1	Beam Angle	120°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	1350lm	Cutting Size	Plastic




SKU: 2981 6000K
SKU: 2982 4500K
SKU: 2983 2700K

24W



Product code	DL24-B1	Beam Angle	120°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	1920lm	Cutting Size	Plastic



SKU: 2984 6000K
SKU: 2985 4500K
SKU: 2986 2700K

NEW



LED BACKLIT SURFACE PANELS


SQUARE - Driver-on-board

Home Edition

6W



Product code	DL6-B1	Beam Angle	120°
Watts	6W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	360lm	Material	Plastic




SKU: 2987 6000K
SKU: 2988 4500K
SKU: 2989 2700K

12W



Product code	DL12-B1	Beam Angle	120°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	840lm	Material	Plastic




SKU: 2990 6000K
SKU: 2991 4500K
SKU: 2992 2700K

18W



Product code	DL18-B1	Beam Angle	120°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	1350lm	Material	Plastic




SKU: 2993 6000K
SKU: 2994 4500K
SKU: 2995 2700K

24W



Product code	DL24-B1	Beam Angle	120°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	1920lm	Material	Plastic



SKU: 2996 6000K
SKU: 2997 4500K
SKU: 2998 2700K


LED SURFACE PANELS
ROUND - HOME EDITION


120°




IP20

6W

480

Lumens


Product code	DL6-B1	Beam Angle	120°
Watts	6W	CRI	Ra>80
Input Voltage	AC : 180-260V	IP Rating	IP20
Flux	480lm	Dimension	ø117x28mm


 SKU: 2401 SKU: 2402 SKU: 2403
 6000K 4000K 2800K
12W

960

Lumens


Product code	DL12-B1	Beam Angle	120°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 180-260V	IP Rating	IP20
Flux	960lm	Dimension	ø160x28mm


 SKU: 2404 SKU: 2405 SKU: 2406
 6000K 4000K 2800K
18W

1440

Lumens


Product code	DL18-B1	Beam Angle	120°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 180-260V	IP Rating	IP20
Flux	1440lm	Dimension	ø205x28mm


 SKU: 2407 SKU: 2408 SKU: 2409
 6000K 4000K 2800K
24W

1920

Lumens

Product code	DL24-B1	Beam Angle	120°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 180-260V	IP Rating	IP20
Flux	1920lm	Dimension	ø285x28mm


 SKU: 2410 SKU: 2411 SKU: 2412
 6000K 4000K 2800K

LED SURFACE PANELS
SQUARE - HOME EDITION


120°




IP20

6W

480

Lumens


Product code	DL6-B1	Beam Angle	120°
Watts	6W	CRI	Ra>80
Input Voltage	AC : 180-260V	IP Rating	IP20
Flux	480lm	Dimension	118x118x28mm


 SKU: 2413 SKU: 2414 SKU: 2415
 6000K 4000K 2800K
12W

960

Lumens


Product code	DL12-B1	Beam Angle	120°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 180-260V	IP Rating	IP20
Flux	960lm	Dimension	160x160x28mm


 SKU: 2416 SKU: 2417 SKU: 2418
 6000K 4000K 2800K
18W

1440

Lumens


Product code	DL18-B1	Beam Angle	120°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 180-260V	IP Rating	IP20
Flux	1440lm	Dimension	208x208x28mm


 SKU: 2419 SKU: 2420 SKU: 2421
 6000K 4000K 2800K
24W

1920


Lumens

Product code	DL24-B1	Beam Angle	120°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 180-260V	IP Rating	IP20
Flux	1920lm	Dimension	288x288x28mm


 SKU: 2422 SKU: 2423 SKU: 2424
 6000K 4000K 2800K



**LED SURFACE PANELS
ROUND**


6W	Product code	DL6-A1	Beam Angle	120°
480	Watts	6W	CRI	Ra>80
Lumens	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	480lm	Dimension	ø120x38mm




SKU: 2231 SKU:2243 SKU: 2232

12W	Product code	DL12-A1	Beam Angle	120°
960	Watts	12W	CRI	Ra>80
Lumens	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	960lm	Dimension	ø172x38mm




SKU: 2244 SKU:2245 SKU: 2246

18W	Product code	DL18-A1	Beam Angle	120°
1440	Watts	18W	CRI	Ra>80
Lumens	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	1440lm	Dimension	ø225x38mm



SKU: 2235 SKU:2247 SKU: 2236


24W	Product code	DL24-A1	Beam Angle	120°
1920	Watts	24W	CRI	Ra>80
Lumens	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	1920lm	Dimension	ø300x38mm



SKU: 2248 SKU:2249 SKU: 2250



**LED SURFACE PANELS
SQUARE**


6W	Product code	DL6-A1	Beam Angle	120°
480	Watts	6W	CRI	Ra>80
Lumens	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	480lm	Dimension	120x120x38mm




SKU: 2237 SKU:2251 SKU: 2238

12W	Product code	DL12-A1	Beam Angle	120°
960	Watts	12W	CRI	Ra>80
Lumens	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	960lm	Dimension	167x167x38mm




SKU: 2252 SKU:2253 SKU: 2254

18W	Product code	DL18-A1	Beam Angle	120°
1440	Watts	18W	CRI	Ra>80
Lumens	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	1440lm	Dimension	220x220x32mm



SKU: 2241 SKU:2255 SKU: 2242

24W	Product code	DL24-A1	Beam Angle	120°
1920	Watts	24W	CRI	Ra>80
Lumens	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	1920lm	Dimension	295x295x32mm



SKU: 2256 SKU:2257 SKU: 2258



LED ceiling lights are increasingly popular and are available in all shapes and sizes, with high-quality fittings available for any type of room. Whether you have a stately home or a terraced house, you can use these lamps to good effect.


Features:

- Up to 80% power saving
- Variety of colour temperatures
- Glossy or matt finishing
- Standard sizes
- Variety of powers

Application:

- Suspended ceilings
- Indoor use – home or office
- Large spaces






LED CEILING LIGHTS

Black Round - CCT + RGB



18W
1440
Lumens


Watts	18W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	1440lm	IP Rating	IP20



SKU: 2941
RGB + CCT
6000K 4500K 3000K

24W
1920
Lumens


Watts	24W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	1920lm	IP Rating	IP20




SKU: 2942
RGB + CCT
6000K 4500K 3000K

32W
2565
Lumens

Watts	32W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	2565lm	IP Rating	IP20



SKU: 2943
RGB + CCT
6000K 4500K 3000K




LED CEILING LIGHTS

White Round - CCT + RGB



18W
1440
Lumens


Watts	18W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	1440lm	IP Rating	IP20



SKU: 2944
RGB + CCT
6000K 4500K 3000K

24W
1920
Lumens


Watts	24W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	1920lm	IP Rating	IP20



SKU: 2945
RGB + CCT
6000K 4500K 3000K

32W
2565
Lumens

Watts	32W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	2565lm	IP Rating	IP20



SKU: 2946
RGB + CCT
6000K 4500K 3000K




LED CEILING LIGHTS

Round - CCT Switch



18W
1880
Lumens


Watts	18W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	1880lm	IP Rating	IP54



SKU: 2501
CCT
6000K 4500K 3000K

24W
2565
Lumens

Watts	24W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	2565lm	IP Rating	IP54




SKU: 2502
CCT
6000K 4500K 3000K

18W
1880
Lumens



Watts	18W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	1880lm	IP Rating	IP54



SKU: 2505
CCT
6000K 4500K 3000K




LED CEILING LIGHTS

Square - CCT Switch



18W
1880
Lumens


Watts	18W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	1880lm	IP Rating	IP54



SKU: 2503
CCT
6000K 4500K 3000K

24W
2565
Lumens

Watts	24W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	2565lm	IP Rating	IP54




SKU: 2504
CCT
6000K 4500K 3000K

18W
1880
Lumens



Watts	18W	Beam Angle	120°
Input Voltage	AC : 220-240V	CRI	Ra>80
Flux	1880lm	IP Rating	IP54



SKU: 2506
CCT
6000K 4500K 3000K




LED CEILING LIGHTS

Black Body - Round



18W 1350 Lumens	Product code	PD18-A2	Beam Angle	120°
	Watts	18W	CRI	Ra>80
	Input Voltage	AC : 175-260V	IP Rating	IP20
	Flux	1350lm	Body Color	Black




SKU:2901 4500K
SKU: 2902 3000K

LED CEILING LIGHTS

White Body - Round




18W 1350 Lumens	Product code	PD18-A2	Beam Angle	120°
	Watts	18W	CRI	Ra>80
	Input Voltage	AC : 175-260V	IP Rating	IP20
	Flux	1350lm	Body Color	White




SKU:2903 4500K
SKU: 2904 3000K

30W 2250 Lumens	Product code	PD30-A2	Beam Angle	120°
	Watts	30W	CRI	Ra>80
	Input Voltage	AC : 175-260V	IP Rating	IP20
	Flux	2250lm	Body Color	Black




SKU:2905 4500K
SKU: 2906 3000K

30W 2250 Lumens	Product code	PD30-A2	Beam Angle	120°
	Watts	30W	CRI	Ra>80
	Input Voltage	AC : 175-260V	IP Rating	IP20
	Flux	2250lm	Body Color	White




SKU:2907 4500K
SKU: 2908 3000K

54W 4050 Lumens	Product code	PD54-A2	Beam Angle	120°
	Watts	54W	CRI	Ra>80
	Input Voltage	AC : 175-260V	IP Rating	IP20
	Flux	4050lm	Body Color	Black



SKU:2909 4500K
SKU: 2910 3000K

54W 4050 Lumens	Product code	PD54-A2	Beam Angle	120°
	Watts	54W	CRI	Ra>80
	Input Voltage	AC : 175-260V	IP Rating	IP20
	Flux	4050lm	Body Color	White



SKU:2911 4500K
SKU: 2912 3000K

LED CEILING LIGHTS


36W - Black

Product code DL36-A2
 Watts 36W
 Input Voltage AC : 175-260V
 Flux 2700lm
 Beam Angle 120°
 Shape Round

SKU:2913 SKU: 2914
 ■ 4500K ■ 3000K

CRI Ra>80
 IP Rating IP20
 Dimension ø500x80 mm
 Body Color Black
 Dimmable NO

2700
 Lumens 120° IP20



LED CEILING LIGHTS

36W - White

Product code DL36-A2
 Watts 36W
 Input Voltage AC : 175-260V
 Flux 2700lm
 Beam Angle 120°
 Shape Round

SKU:2915 SKU: 2916
 ■ 4500K ■ 3000K

CRI Ra>80
 IP Rating IP20
 Dimension ø500x80 mm
 Body Color White
 Dimmable NO

2700
 Lumens 120° IP20



LED CEILING LIGHTS

64W - Black

Product code DL64-A2
 Watts 64W
 Input Voltage AC : 175-260V
 Flux 4800lm
 Beam Angle 120°
 Shape Round

SKU:2917 SKU: 2918
 ■ 4500K ■ 3000K

CRI Ra>80
 IP Rating IP20
 Dimension ø800x80 mm
 Body Color Black
 Dimmable NO

4800
 Lumens 120° IP20



LED CEILING LIGHTS

64W - White

Product code DL64-A2
 Watts 64W
 Input Voltage AC : 175-260V
 Flux 4800lm
 Beam Angle 120°
 Shape Round

SKU:2919 SKU: 2920
 ■ 4500K ■ 3000K

CRI Ra>80
 IP Rating IP20
 Dimension ø800x80 mm
 Body Color White
 Dimmable NO

4800
 Lumens 120° IP20



LED CEILING LIGHTS


30W - Black

Product code DL36-A2
 Watts 36W
 Input Voltage AC : 175-260V
 Flux 2250lm
 Beam Angle 120°
 Shape Square

SKU:2921 SKU: 2922
 ■ 4500K ■ 3000K

CRI Ra>80
 IP Rating IP20
 Dimension 380x380 mm
 Body Color Black
 Dimmable NO

2250
 Lumens 120° IP20



LED CEILING LIGHTS


30W - White

Product code DL36-A2
 Watts 36W
 Input Voltage AC : 175-260V
 Flux 2250lm
 Beam Angle 120°
 Shape Square

SKU:2923 SKU: 2924
 ■ 4500K ■ 3000K

CRI Ra>80
 IP Rating IP20
 Dimension 380x380 mm
 Body Color White
 Dimmable NO

2250
 Lumens 120° IP20



LED CEILING LIGHTS


64W - Black

Product code DL64-A2
 Watts 64W
 Input Voltage AC : 175-260V
 Flux 4800lm
 Beam Angle 120°
 Shape Square

SKU:2925 SKU: 2926
 ■ 4500K ■ 3000K

CRI Ra>80
 IP Rating IP20
 Dimension 600x600 mm
 Body Color Black
 Dimmable NO

4800
 Lumens 120° IP20



LED CEILING LIGHTS


64W - White

Product code DL64-A2
 Watts 64W
 Input Voltage AC : 175-260V
 Flux 4800lm
 Beam Angle 120°
 Shape Square

SKU:2927 SKU: 2928
 ■ 4500K ■ 3000K

CRI Ra>80
 IP Rating IP20
 Dimension 600x600 mm
 Body Color White
 Dimmable NO

4800
 Lumens 120° IP20





Remote Control

LED CEILING LIGHTS

Sandy White - Round



Product code	DL72-A1	CRI	Ra>80
Watts	36x2W	IP Rating	IP20
Input Voltage	AC : 180-260V	Dimension	ø500x50 mm
Flux	5400lm	Body Color	White
Beam Angle	120°	Dimmable	NO
Shape	Round		



SKU: 2931




Remote Control

LED CEILING LIGHTS

Sandy White - Round



Product code	DL96-A1	CRI	Ra>80
Watts	48x2W	IP Rating	IP20
Input Voltage	AC : 180-260V	Dimension	ø500x50 mm
Flux	7200lm	Body Color	White
Beam Angle	120°	Dimmable	NO
Shape	Round		



SKU: 2930



Remote Control

LED CEILING LIGHTS

Sandy White - Square



Product code	DL120-A1	CRI	Ra>80
Watts	60x2W	IP Rating	IP20
Input Voltage	AC : 180-260V	Dimension	500x500x50 mm
Flux	9000lm	Body Color	White
Beam Angle	120°	Dimmable	NO
Shape	Square		



SKU: 2929

3800156629295

Ceiling plate for pendant lamps
Does not contain pendant lamps

HANGING ACCESSORIES

Black

SKU: 5181 3800156651814




HANGING ACCESSORIES

White

SKU: 5180 3800156651807



- 3
Years
Warranty
- NON-Dimmable
- EPISTAR
Chips
- 120°
- IP20



LED Ceiling Light 38W **PF>0.95**
Sandy White - Square



Product code	DL38-A1	CRI	Ra>80
Watts	38W	IP Rating	IP20
Input Voltage	AC : 175-240V	Dimension	450x450x100 mm
Flux	1900lm	Body Color	Sandy White
Beam Angle	120°	Dimmable	NO
Shape	Square		

SKU: 2297 Warm White 3000K



Remote Control included



- Dimmable
- IP20


LED Ceiling Light 60W
HOME EDITION - Allstar



Product code	DL60-A6	Remote	Yes
Watts	60W	CRI	Ra>80
Input Voltage	AC : 185-240V	IP Rating	IP20
Flux	4200lm	Dimension	Φ485x115 mm
Beam Angle	120°	Body Color	Matt White
Shape	Round	Dimmable	Yes



SKU: 2889





LED SURFACE CEILING

Bulkhead-Thermoplastic



8W



640 Lumens

Product code	DL8-A3	Beam Angle	120°
Watts	8W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	640lm	Instant Start	<0.5s

SKU:2807 SKU: 2808
4500K 2700K

13W



1050 Lumens

Product code	DL13-A1	Beam Angle	120°
Watts	13W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	1050lm	Instant Start	<0.5s

SKU:2813 SKU: 2814
4500K 2700K

8W



640 Lumens

Product code	DL8-A4	Beam Angle	120°
Watts	8W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	640lm	Instant Start	<0.5s



MW Sensor

SKU:2809 SKU: 2810
4500K 2700K

13W



1050 Lumens

Product code	DL13-A3	Beam Angle	120°
Watts	13W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	1050lm	Instant Start	<0.5s



MW Sensor

SKU:2815 SKU: 2816
4500K 2700K

8W



640 Lumens

Product code	DL8-A5	Beam Angle	120°
Watts	8W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	640lm	Instant Start	<0.5s



Emergency

SKU:2811 SKU: 2812
4500K 2700K

13W



1050 Lumens

Product code	DL13-A4	Beam Angle	120°
Watts	13W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	1050lm	Instant Start	<0.5s



Emergency

SKU:2817 SKU: 2818
4500K 2700K

LED SURFACE CEILING 8W

Bulkhead-Thermoplastic

SKU: 2801 SKU:2802 SKU: 2803
6000K 4000K 2700K

Watts	8W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	600lm	Dimension	160x90x51 mm
Beam Angle	120°	Body Color	White
Shape	Bulkhead	Dimmable	NO



Sensor




1260 Lumens



120°



IP20



LED SURFACE CEILING 18W

Thermoplastic - PIR

SKU: 2804 SKU:2805 SKU: 2806
6000K 4000K 2700K

Watts	18W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	1260lm	Dimension	ø295x70 mm
Beam Angle	120°	Body Color	White
Shape	Round	Dimmable	NO




LED CEILING LIGHTS

HOME EDITION - Matt White**12W****880**

Lumens

Product code	DL12-B1	Beam Angle	120°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	880lm	Body Color	White



 SKU: 2870 SKU:2871 SKU: 2872
 6000K 4500K 3000K

LED CEILING LIGHTS

HOME EDITION - Dotty Sparkle**12W****880**


Lumens

Product code	DL12-B1	Beam Angle	120°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	880lm	Body Color	White


 SKU: 2879 SKU:2880 SKU: 2881
 6000K 4500K 3000K
18W**1550**


Lumens

Product code	DL18-B1	Beam Angle	120°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1550lm	Body Color	White


 SKU: 2873 SKU:2874 SKU: 2875
 6000K 4500K 3000K
18W**1550**


Lumens

Product code	DL18-B1	Beam Angle	120°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1550lm	Body Color	White


 SKU:2883 SKU: 2884
 4500K 3000K
24W**1900**


Lumens

Product code	DL24-B1	Beam Angle	120°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1900lm	Body Color	White


 SKU: 2876 SKU:2877 SKU: 2878
 6000K 4500K 3000K
24W**1900**

Lumens

Product code	DL24-B1	Beam Angle	120°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	1900lm	Body Color	White


 SKU: 2887
 3000K




LED CEILING LIGHTS

CITY LINE - Matt White



12W	Product code	DL12-B1	Beam Angle	120°
880	Watts	12W	CRI	Ra>80
Lumens	Input Voltage	AC : 175-265V	IP Rating	IP20
	Flux	880lm	Body Color	White




SKU: 2840	SKU:2841	SKU: 2842
6000K	4500K	3000K

LED CEILING LIGHTS

CITY LINE - Dotty Sparkle




12W	Product code	DL12-B1	Beam Angle	120°
840	Watts	12W	CRI	Ra>80
Lumens	Input Voltage	AC : 175-265V	IP Rating	IP20
	Flux	840lm	Body Color	White




SKU: 2849	SKU:2850	SKU: 2851
6000K	4500K	3000K

18W	Product code	DL18-B1	Beam Angle	120°
1550	Watts	18W	CRI	Ra>80
Lumens	Input Voltage	AC : 175-265V	IP Rating	IP20
	Flux	1550lm	Body Color	White




SKU: 2843	SKU:2844	SKU: 2845
6000K	4500K	3000K

18W	Product code	DL18-B1	Beam Angle	120°
1260	Watts	18W	CRI	Ra>80
Lumens	Input Voltage	AC : 175-265V	IP Rating	IP20
	Flux	1260lm	Body Color	White




SKU: 2852	SKU:2853	SKU: 2854
6000K	4500K	3000K

24W	Product code	DL24-B1	Beam Angle	120°
1900	Watts	24W	CRI	Ra>80
Lumens	Input Voltage	AC : 175-265V	IP Rating	IP20
	Flux	1900lm	Body Color	White



SKU: 2846	SKU:2847	SKU: 2848
6000K	4500K	3000K

24W	Product code	DL24-B1	Beam Angle	120°
1900	Watts	24W	CRI	Ra>80
Lumens	Input Voltage	AC : 175-265V	IP Rating	IP20
	Flux	1900lm	Body Color	White



SKU: 2855	SKU:2856	SKU: 2857
6000K	4500K	3000K



Remote Control included



Color changing LED 3000 to 6000K

LED Ceiling Light 36W PF>0.9
Matt White



2500 Lumens



SKU: 2858 3800156628588

6000K 4500K 3000K

Product code	DL36-A4	Remote	No
Watts	36W	CRI	Ra>80
Input Voltage	AC : 185-265V	IP Rating	IP20
Flux	2500lm	Dimension	ø460x70 mm
Beam Angle	120°	Body Color	Matt White
Shape	Round	Dimmable	Yes



Remote Control included



Color changing LED 3000 to 6000K

LED Ceiling Light 36W PF>0.9
Matt White+Dotty Sparkle



2500 Lumens



SKU: 2860 3800156628601

6000K 4500K 3000K

Product code	DL36-A5	Remote	Yes
Watts	36W	CRI	Ra>80
Input Voltage	AC : 185-265V	IP Rating	IP20
Flux	2500lm	Dimension	430x430x70 mm
Beam Angle	120°	Body Color	Matt White
Shape	Square	Dimmable	Yes



Remote Control included



Color changing LED 3000 to 6000K

LED Ceiling Light 60W PF>0.9
Matt White



3600 Lumens



SKU: 2859 3800156628595

6000K 4500K 3000K

Product code	DL60-A4	Remote	No
Watts	60W	CRI	Ra>80
Input Voltage	AC : 185-265V	IP Rating	IP20
Flux	3600lm	Dimension	ø560x70 mm
Beam Angle	120°	Body Color	Matt White
Shape	Round	Dimmable	Yes



Remote Control included



Color changing LED 3000 to 6000K

LED Ceiling Light 60W PF>0.9
Matt White+Dotty Sparkle



3600 Lumens



SKU: 2861 3800156628618

6000K 4500K 3000K

Product code	DL60-A5	Remote	Yes
Watts	60W	CRI	Ra>80
Input Voltage	AC : 185-265V	IP Rating	IP20
Flux	3600lm	Dimension	530x530x70 mm
Beam Angle	120°	Body Color	Matt White
Shape	Square	Dimmable	Yes

LED Suspended Lighting

Round Sandy White

LED Suspended Lighting

Square Sandy White

LED Suspended Lighting

38W PF>0.95

Watts	38W	CRI	Ra>80
Input Voltage	AC : 175-240V	IP Rating	IP20
Flux	2660lm	Dimension	ø450x1200 mm
Beam Angle	120°	Body Color	Sandy White
Shape	Round	Dimmable	NO

SKU: 9036 Warm White ■ 3000K

LED Suspended Lighting

38W PF>0.95

Watts	38W	CRI	Ra>80
Input Voltage	AC : 175-240V	IP Rating	IP20
Flux	2660lm	Dimension	450x450x1200 mm
Beam Angle	120°	Body Color	Sandy White
Shape	Square	Dimmable	NO

SKU: 9038 Warm White ■ 3000K

LED Suspended Lighting

50W PF>0.95

Watts	50W	CRI	Ra>80
Input Voltage	AC : 175-240V	IP Rating	IP20
Flux	3500lm	Dimension	ø600x1200 mm
Beam Angle	120°	Body Color	Sandy White
Shape	Round	Dimmable	NO

SKU: 9037 Warm White ■ 3000K

LED Suspended Lighting

50W PF>0.95

Watts	50W	CRI	Ra>80
Input Voltage	AC : 175-240V	IP Rating	IP20
Flux	3500lm	Dimension	600x600x1200 mm
Beam Angle	120°	Body Color	Sandy White
Shape	Square	Dimmable	NO

SKU: 9039 Warm White ■ 3000K

VINTAGE PENDANTS E27



SKU: 9029 - Pearl Black



SKU: 9046 - Pearl Black



SKU: 9047 - Bronze



SKU: 9049 - Antique gold



SKU: 9028 - Rose Gold



SKU: 9048 - Rose Gold



SKU: **9027**
Product Code PD1-A2
E27 holder Max 60W
IP Rating IP20
Dimension ø90x1500mm



3D Glass Barel Pendant D200
Chrome Rhombus

SKU: **9014**
Product Code PD1-A1
E27 holder Max 40W
Material 3D Glass
IP Rating IP20
Dimension ø200x213mm
EAN: 3800156690141



3D Glass Barel Pendant D200
Chrome Squares

SKU: **9015**
Product Code PD1-A1
E27 holder Max 40W
Material 3D Glass
IP Rating IP20
Dimension ø200x213mm
EAN: 3800156690158



3D Glass Pendant D200
Chrome Square

SKU: **9004**
Product Code PD1-A1
E27 holder Max 40W
Material 3D Glass
IP Rating IP20
Dimension ø200x175mm
EAN: 3800156690042





3D Glass Pendant D200
Chrome Circles

SKU: **9019**
Product Code PD1-A1
E27 holder Max 40W
Material 3D Glass
IP Rating IP20
Dimension ø200x165mm
EAN: 3800156690196



E27 Holder



IP20



3D Glass Pendant D290
Copper Circles

SKU: **9022**
Product Code PD1-A1
E27 holder Max 40W
Material 3D Glass
IP Rating IP20
Dimension ø290x250mm
EAN: 3800156690226



E27 Holder



IP20



3D Glass Pendant D200
Chrome Seagull

SKU: **9020**
Product Code PD1-A1
E27 holder Max 40W
Material 3D Glass
IP Rating IP20
Dimension ø200x165mm
EAN: 3800156690202



E27 Holder



IP20



3D Glass Pendant D290
Chrome Seagull

SKU: **9024**
Product Code PD1-A1
E27 holder Max 40W
Material 3D Glass
IP Rating IP20
Dimension ø290x250mm
EAN: 3800156690240



E27 Holder



IP20



3D Glass Pendant D200
Copper Circles

SKU: **9021**
Product Code PD1-A1
E27 holder Max 40W
Material 3D Glass
IP Rating IP20
Dimension ø200x165mm
EAN: 3800156690219



E27 Holder



IP20



3D Glass Umbrella Pendant D400
Chrome Circles

SKU: **9018**
Product Code PD1-A1
E27 holder Max 40W
Material 3D Glass
IP Rating IP20
Dimension ø400x200mm
EAN: 3800156690189



E27 Holder



IP20



LED Flame Bulb
5W SMD E27



Product code	OT5-A1	CRI	Ra>80
Watts	5W	IP Rating	IP20
Input Voltage	AC : 220-240V	Dimension	ø47x125 mm
Flux	250lm	Socket	E27
Beam Angle	360°		

SKU: 222
■ 1300K



LED Flame Lamp Wall Mounted
5W SMD



Product code	PD5-A1	CRI	Ra>80
Watts	5W	IP Rating	IP20
Input Voltage	AC : 220-240V	Dimension	220xH285 mm
Flux	250lm	Beam Angle	360°
Beam Angle	360°	E27 holder	LED Flame Bulb Included

SKU: 9044
■ 1300K



LED Flame Lamp
5W SMD



Product code	PD5-A1	CRI	Ra>80
Watts	5W	IP Rating	IP20
Input Voltage	AC : 220-240V	Dimension	ø180xH285 mm
Flux	250lm	E27 holder	LED Flame Bulb Included
Beam Angle	360°		

SKU: 9041
■ 1300K



LED Flame Lamp Wall Mounted
5W SMD



Product code	PD5-A1	CRI	Ra>80
Watts	5W	IP Rating	IP20
Input Voltage	AC : 220-240V	Dimension	180xH260 mm
Flux	250lm	E27 holder	LED Flame Bulb Included
Beam Angle	360°		

SKU: 9045
■ 1300K



LED Flame Lamp With Battery
5W SMD



Product code	PD5-A1	CRI	Ra>80
Watts	5W	IP Rating	IP20
Input Voltage	AC : 220-240V	Dimension	ø180xH285 mm
Flux	250lm	E27 holder	LED Flame Bulb Included
Beam Angle	360°		

SKU: 9042
■ 1300K



LED Flame Lamp Hanging
5W SMD



Product code	PD5-A1	CRI	Ra>80
Watts	5W	IP Rating	IP20
Input Voltage	AC : 220-240V	Dimension	ø150xH330 mm
Flux	250lm	E27 holder	LED Flame Bulb Included
Beam Angle	360°		

SKU: 9043
■ 1300K

NEW



Portable Retro LED Lamp
2.6W Filament

110 Lumens Dimmable IP44

Watts 2.6W
Working Voltage 3.7V
Flux 8-110lm
Beam Angle 270°
CRI Ra>80
IP Rating IP44
Dimension 115x115x115 mm
Working Time 3.5-7.5 Hours

SKU: 249
CCT Steps
6000K 4500K 3000K

Battery 950mAh

NEW



Portable Retro LED Lamp
3W Filament

160 Lumens Dimmable IP44

Watts 2.6W
Working Voltage 3.7V
Flux 20-160lm
Beam Angle 270°
CRI Ra>80
IP Rating IP44
Dimension 110x110x180 mm
Working Time 2.5-7.5 Hours

SKU: 250
CCT Steps
6000K 4500K 3000K

Battery 650mAh



NEW



Rechargeable Table Lamp
2.5W Solar
USB-C Charging Cable

280 Lumens Solar Power Battery 4400mAh IP54

CCT Steps
6000K 4500K 2700K

Watts 2.5W
Working Voltage 3.7V
Flux 280lm

IP Rating IP54
Dimension Ø128x300mm
Working Time 6.5 Hours

SKU: 251 Black
SKU: 252 White
SKU: 253 Beige

NEW



Rechargeable Table Lamp
USB-C Charging Cable

280 Lumens Battery 4400mAh IP54

CCT Steps
6000K 4500K 2700K

Watts 2.5W
Working Voltage 3.7V
Flux 280lm

IP Rating IP54
Dimension Ø1104x315mm
Working Time 6.5 Hours

SKU: 254 Black
SKU: 255 White
SKU: 256 Beige



LED panels offers a broad application it different lighting solutions. With variety of standard sizes they can be placed in suspended ceilings or used as hanging lights.

Features:

- Up to 80% power saving
- Build-in or hanging installations
- Variety of colour temperatures
- Glossy or matt finishing
- Standard sizes
- Variety of powers

Application:

- Suspended ceilings
- Indoor use – home or office
- Large spaces





 LED PANEL DRIVER 36W FOR
 2701-2719
 SKU: 6043

LED PANEL PF>0.95
25W With Driver 60x60cm

Product code	DL25-A2	Beam Angle	120°
Watts	25W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	3000lm	BOX Qty	1 PCS



TP(b)RATED
 Polycarbonate Diffuser

 SKU: 2740 SKU:2741
 6000K 4500K

3
 Years
 Warranty


160 Lumens/W

10 PCS
BOX
LED BACKLIT PANEL PF>0.9
25W With Driver 60x60cm


Product code	DL25-A3	Beam Angle	120°
Watts	25W	CRI	Ra>80
Input Voltage	AC : 185-265V	IP Rating	IP20
Flux	4000lm	BOX Qty	10 PCS

 SKU: 2770 SKU:2771
 6000K 4500K

 LED DIMMABLE DRIVER 36W
 FOR 2701-2719
 SKU: 6044

LED BACKLIT PANEL PF>0.9
30W With Driver 60x60cm

Product code	DL30-A3	Beam Angle	120°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	6 PCS


TP(a)RATED
 Polycarbonate Diffuser

 SKU: 2776 SKU:2777
 6000K 4500K


6 PCS
BOX
NEW



10 PCS
BOX
LED BACKLIT PANEL PF>0.9
36W With Driver 60x60cm

Product code	DL36-A7	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	4320lm	BOX Qty	10 PCS

 SKU: 12771 SKU:12772 SKU: 12773
 6000K 4000K 2700K

NEW



10 PCS
BOX
LED BACKLIT PANEL PF>0.9
36W With Driver 120x30cm

Product code	DL36-A7	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	4320lm	BOX Qty	10 PCS

 SKU: 12774 SKU:12775 SKU: 12776
 6000K 4000K 2700K

NEW


10 PCS
BOX
LED BACKLIT PANEL PF>0.9
36W With Driver 60x60cm


Product code	DL36-A7	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	4320lm	BOX Qty	10 PCS

 SKU: 12777 SKU:12778
 6000K 4000K


LED PANEL Single Pack PF>0.9
36W With Driver 62x62cm
3600
 Lumens

 IP20



Product code	DL36-A4	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	1 PCS


 SKU: 2701 SKU:2702 SKU: 2703
 6000K 4500K 2700K

3600
 Lumens

 IP20

LED PANEL Single Pack PF>0.9
36W With Driver 62x62cm


Product code	DL36-A4	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	1 PCS


 SKU: 2704 SKU:2705 SKU: 2706
 6000K 4500K 2700K

3600
 Lumens

 IP20

LED PANEL Single Pack PF>0.9
36W With Driver 62x62cm

Product code	DL36-A4	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	1 PCS



 SKU: 2707 SKU:2708
 6000K 4500K

3600
 Lumens

 IP20

LED PANEL PF>0.9
36W With Driver 60x60cm
3600
 Lumens


 IP20

Product code	DL36-A1	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	6 PCS

 SKU: 2711 SKU:2712 SKU: 2713
 6000K 4500K 2700K

LED PANEL PF>0.9
36W With Driver 60x60cm
3600
 Lumens

 IP20


Product code	DL36-A1	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	6 PCS

 SKU: 2717 SKU:2718
 6000K 4500K

LED PANEL PF>0.95
36W With Driver 60x60cm
3500
 Lumens

 IP20

Product code	DL36-A2	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	3500lm	BOX Qty	1 PCS

TP(b)RATED
 Polycarbonate Diffuser


 SKU: 2744
 6000K

3
 Years
 Warranty



LED PANEL PF>0.9
36W With Driver 62x62cm
3600
 Lumens

 IP20

Product code	DL36-A3	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	3600lm	BOX Qty	1 PCS


 SKU: 2734 6000K
 SKU: 2736 2700K


 6 PCS
 BOX

LED PANEL PF>0.9
36W With Driver 62x62cm
3060
 Lumens

 IP20

Product code	DL36-A3	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	3060lm	BOX Qty	6 PCS


 SKU: 2737 6000K
 SKU: 2739 2700K

120
 Lumens/W

5
 Years
 Warranty

LED PANEL PF>0.9
40W With Driver 60x60cm
4800
 Lumens


 IP20

Product code	DL40-A1	Beam Angle	120°
Watts	40W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	4800lm	BOX Qty	1 PCS


 SKU: 2726 6000K
 SKU: 2727 4500K
 SKU: 2728 2700K


LED PANEL PF>0.9
45W With Driver 60x60cm



Product code	DL45-A5	Beam Angle	120°
Watts	45W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	3600lm	BOX Qty	6 PCS


 SKU: 2396
 ■ 2700K

LED PANEL PF>0.9
45W With Driver 62x62cm



Product code	DL45-A5	Beam Angle	120°
Watts	45W	CRI	Ra>95
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	3600lm	BOX Qty	6 PCS

 SKU: 2797 SKU:2798 SKU: 2799
 ■ 6000K ■ 4500K ■ 2700K

LED PANEL PF>0.9
45W With Driver 60x60cm



Product code	DL45-A5	Beam Angle	120°
Watts	45W	CRI	Ra>95
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	3600lm	BOX Qty	6 PCS

 SKU: 2399
 ■ 2700K

LED PANEL Single Pack PF>0.9
45W With Driver 62x62cm



Product code	DL45-A4	Beam Angle	120°
Watts	45W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	1 PCS

 SKU: 2791 SKU:2792 SKU: 2793
 ■ 6000K ■ 4500K ■ 2700K

LED PANEL Single Pack PF>0.9
45W With Driver 62x62cm


Product code	DL45-A5	Beam Angle	120°
Watts	45W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	3600lm	BOX Qty	1 PCS


 SKU: 2788 SKU:2789 SKU: 2790
 ■ 6000K ■ 4500K ■ 2700K

LED PANEL PF>0.9
45W With Driver 62x62cm


Product code	DL45-A4	Beam Angle	120°
Watts	45W	CRI	Ra>80
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	3600lm	BOX Qty	6 PCS

 SKU:2795 SKU: 2796
 ■ 4500K ■ 2700K



LED FRAME PANEL PF>0.9
36W With Driver 60x60cm


Product code	DL36-A4	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	2 PCS

 SKU: 2746
 ■ 6000K


 2 PCS
 BOX

LED PANEL PF>0.9
36W With Driver 60x60cm


Product code	DL36-A1	Beam Angle	120°
Watts	36W	CRI	Ra>95
Input Voltage	AC : 175-265V	IP Rating	IP20
Flux	3600lm	BOX Qty	6 PCS

 SKU: 2729 SKU:2730
 ■ 6000K ■ 4500K


 6 PCS
 BOX

LED PANEL CLOUD OPTIC
45W With Driver 60x60cm



Product code	DL45-A3	Beam Angle	120°
Watts	45W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	4 PCS

 SKU: 2780
 ■ 6000K


 4 PCS
 BOX

LED SURFACE/BACKLIT PANEL
40W With Driver 60x60cm


Product code	DL40-A3	Beam Angle	120°
Watts	40W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	10 PCS

 SKU: 2784 SKU:2785
 ■ 6000K ■ 4000K


 4 PCS
 BOX

LED BACKLIT PANEL PF>0.9
40W With Driver 60x60cm



Product code	DL40-A3	Beam Angle	120°
Watts	40W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3400lm	BOX Qty	10 PCS

 SKU: 2772 SKU:2773
 ■ 6000K ■ 4500K


 10 PCS
 BOX

LED SURFACE/BACKLIT PANEL
40W With Driver 120x30cm

Product code	DL40-A3	Beam Angle	120°
Watts	40W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	10 PCS


 SKU: 2786 SKU:2787
 ■ 6000K ■ 4500K


 4 PCS
 BOX


LED PANEL PF>0.9
36W With Driver 120x30cm
3600
 Lumens



Product code	DL36-A1	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	6 PCS

SKU: 2714	SKU: 2715	SKU: 2716
6000K	4500K	2700K


DRIVERS FOR LED PANELS
Dimmable



SKU: 6031	600mA	30-42V	25W
SKU: 6032	900mA	30-42V	36W
SKU: 6028	1000mA	30-45V	45W

Watts	25W	36W	45W
Input Voltage	AC: 180-265V	AC: 180-265V	AC: 180-265V
Output Voltage	DC: 30-42V	DC: 30-42V	DC: 30-45V
Material	Plastic	Plastic	Plastic
IP Rating	IP20	IP20	IP20
Product code	AC1-A7	AC1-A8	AC1-A6


LED SLIM PANEL Single Pack PF>0.9
36W With Driver 120x30cm
3600
 Lumens


Product code	DL36-A1	Beam Angle	120°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	3600lm	BOX Qty	1 PCS

SKU: 2731	SKU: 2732	SKU: 2733
6000K	4500K	2700K


EMERGENCY BATTERY PACK
FOR LED PANELS


Product code	AC1-A9
Battery	3.6V / 4.5Ah
Material	Plastic
Dimension	213x95x40mm
Emergency duration	3 Hours
Dimensional	213x95x45mm

SKU: 6029 Battery Pack

LED DALI DRIVER - Adjustable
FOR LED PANELS


Watts	20-40W
Input Voltage	AC: 220-240V
Output Current	550mA-1050mA
Output Voltage	25V-42V
Material	Plastic
Dimensional	106x70x45mm

Emergency duration 3 Hours


SKU: 6030 20W-40W

LED PANEL PF>0.9
45W With Driver 120x30cm
4500
 Lumens


Product code	DL45-A1	Beam Angle	120°
Watts	45W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	4500lm	BOX Qty	1 and 6 PCS

SKU: 2385	SKU: 2386	SKU: 2387
6000K	4500K	2700K

SKU: 2375	SKU: 2376	SKU: 2377
6000K	4500K	2700K






DRIVERS FOR LED PANELS


Plastic Case

SKU: 6019	900mA	36W
SKU: 6021	950mA	45W
SKU: 6022	750mA	48W

Watts	36W	45W	48W	48W
Input Voltage	AC: 175-240V	AC: 175-240V	AC: 175-240V	AC: 175-240V
Output Current	900mA	950mA	1150mA	1150mA
Material	Plastic	Plastic	Plastic	Plastic
IP Rating	IP20	IP20	IP20	IP20



Accessories for Hanging

**Stainless Steel Rope**

SKU: 5182

**Clips for LED Panels**

SKU: 5188




DRIVERS FOR LED DOWNLIGHTS

Plastic Case

SKU: 6035	3-12V	3W
SKU: 6036	15-24V	6W
SKU: 6037	20-40V	12W
SKU: 6038	40-60V	18W
SKU: 6039	60-80V	24W

Watts	3W	6W	12W	18W	24W
Input Voltage	AC: 85-265V				
Output Voltage	DC: 3-12V	DC: 15-24V	DC: 20-40V	DC: 40-60V	DC: 60-80V
Material	Plastic	Plastic	Plastic	Plastic	Plastic
IP Rating	IP20	IP20	IP20	IP20	IP20



FRAMES FOR LED PANELS

NEW SKU: 5199	Dimension	625x625mm
SKU: 5198	Dimension	600x600mm
SKU: 5197	Dimension	300x1200mm





These LED mini panel lights are suitable for recessed installation in offices, hospitals, schools. Easy and quick mounting, there is no need of maintenance, offering long lifetime up of 25 000h


Features:

- Up to 80% power saving
- Different sizes to fit old installations or new lighting projects
- Build-in

Application:

- Home or office use
- Accent lights for shops or stores






LED FRAMELESS MINI PANELS
ROUND

18W
1500
Lumens


Product code	DL18-B2	Beam Angle	180°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP54
Flux	1500lm	Cutting Size	ø108mm



SKU: 2669
6000K

24W
2010
Lumens


Product code	DL24-B2	Beam Angle	180°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP54
Flux	2010lm	Cutting Size	ø155mm




SKU: 2672 6000K
SKU: 2673 4500K
SKU: 2674 2700K

36W
3020
Lumens

Product code	DL36-B3	Beam Angle	180°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP54
Flux	3020lm	Cutting Size	ø206mm




SKU: 2675 6000K
SKU: 2676 4500K
SKU: 2677 2700K



LED FRAMELESS MINI PANELS
SQUARE

18W
1500
Lumens

Product code	DL18-B2	Beam Angle	180°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP54
Flux	1500lm	Cutting Size	108x108mm




SKU: 2681
6000K

SKU: 2683
2700K

24W
2010
Lumens

Product code	DL24-B2	Beam Angle	180°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP54
Flux	2010lm	Cutting Size	155x155mm




SKU: 2684
6000K

SKU: 2686
2700K

36W
3020
Lumens

Product code	DL36-B3	Beam Angle	180°
Watts	36W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP54
Flux	3020lm	Cutting Size	206x206mm



SKU: 2687
6000K


SKU: 2688
4500K

SKU: 2689
2700K


LED MINI PANELS
ROUND - Pro Line
TRUE COLOURS SERIES
6W**440**


Lumens

Product code	DL6-B3	Beam Angle	120°
Watts	6W	CRI	Ra>95
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	440lm	Cutting Size	ø100mm


 SKU: 2601
 ■ 6000K
12W**1000**


Lumens

Product code	DL12-B3	Beam Angle	120°
Watts	12W	CRI	Ra>95
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	1000lm	Cutting Size	ø150mm


 SKU: 2604
 ■ 6000K
18W**1500**


Lumens

Product code	DL18-B3	Beam Angle	120°
Watts	18W	CRI	Ra>95
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	1500lm	Cutting Size	ø200mm


 SKU: 2608 SKU: 2610
 ■ 6000K ■ 2700K
24W**2010**

Lumens


Product code	DL24-B3	Beam Angle	120°
Watts	24W	CRI	Ra>95
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	2010lm	Cutting Size	ø270mm


 SKU: 2613
 ■ 2700K

LED MINI PANELS
SQUARE - Pro Line
TRUE COLOURS SERIES
6W**440**


Lumens

Product code	DL6-B3	Beam Angle	120°
Watts	6W	CRI	Ra>95
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	440lm	Cutting Size	95x95mm


 SKU: 2614
 ■ 6000K
12W**1000**


Lumens

Product code	DL12-B3	Beam Angle	120°
Watts	12W	CRI	Ra>95
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	1000lm	Cutting Size	150x150mm


 SKU: 2617
 ■ 6000K
18W**1500**


Lumens

Product code	DL18-B3	Beam Angle	120°
Watts	18W	CRI	Ra>95
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	1500lm	Cutting Size	200x200mm


 SKU: 2630 SKU: 2631 SKU: 2632
 ■ 6000K ■ 4500K ■ 2700K
24W**2010**

Lumens

Product code	DL24-B3	Beam Angle	120°
Watts	24W	CRI	Ra>95
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	2010lm	Cutting Size	270x270mm


 SKU: 2642
 ■ 6000K

NEW

120°



NON-Dimmable



IP20




LED BACKLIT MINI PANELS

ROUND - Driver-on-board**Home Edition****6W****360**

Lumens

Product code	DL6-B1	Beam Angle	120°
Watts	6W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	360lm	Cutting Size	ø100mm



SKU: 2951	SKU: 2952	SKU: 2953
6000K	4500K	2700K

NEW

120°



NON-Dimmable



IP20




LED BACKLIT MINI PANELS

SQUARE - Driver-on-board**Home Edition****6W****360**

Lumens

Product code	DL6-B1	Beam Angle	120°
Watts	6W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	360lm	Cutting Size	100x100mm




SKU: 2963	SKU: 2964	SKU: 2965
6000K	4500K	2700K

12W**840**

Lumens

Product code	DL12-B1	Beam Angle	120°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	840lm	Cutting Size	ø150mm




SKU: 2954	SKU: 2955	SKU: 2956
6000K	4500K	2700K

12W**840**

Lumens

Product code	DL12-B1	Beam Angle	120°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	840lm	Cutting Size	150x150mm




SKU: 2966	SKU: 2967	SKU: 2968
6000K	4500K	2700K

18W**1350**

Lumens

Product code	DL18-B1	Beam Angle	120°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	1350lm	Cutting Size	ø200mm




SKU: 2957	SKU: 2958	SKU: 2959
6000K	4500K	2700K

18W**1350**

Lumens

Product code	DL18-B1	Beam Angle	120°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	1350lm	Cutting Size	205x205mm




SKU: 2969	SKU: 2970	SKU: 2971
6000K	4500K	2700K

24W**1920**

Lumens

Product code	DL24-B1	Beam Angle	120°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	1920lm	Cutting Size	ø270mm




SKU: 2960	SKU: 2961	SKU: 2962
6000K	4500K	2700K

24W**1920**

Lumens

Product code	DL24-B1	Beam Angle	120°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 85-265V	IP Rating	IP20
Flux	1920lm	Cutting Size	270x270mm




SKU: 2972	SKU: 2973	SKU: 2974
6000K	4500K	2700K



LED MINI PANELS


ROUND - Home Edition

3W 150 Lumens	Product code	DL3-B1	Beam Angle	120°
	Watts	3W	CRI	Ra>80
	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	150lm	Cutting Size	ø62mm




SKU: 2470	SKU: 2471	SKU: 2472
6000K	4500K	2800K

6W 360 Lumens	Product code	DL6-B1	Beam Angle	120°
	Watts	6W	CRI	Ra>80
	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	360lm	Cutting Size	ø99mm




SKU: 2473	SKU: 2474	SKU: 2475
6000K	4500K	2800K

12W 840 Lumens	Product code	DL12-B1	Beam Angle	120°
	Watts	12W	CRI	Ra>80
	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	840lm	Cutting Size	ø146mm




SKU: 2476	SKU: 2477	SKU: 2478
6000K	4500K	2800K

18W 1350 Lumens	Product code	DL18-B1	Beam Angle	120°
	Watts	18W	CRI	Ra>80
	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	1350lm	Cutting Size	ø196mm



SKU: 2479	SKU: 2480	SKU: 2481
6000K	4500K	2800K

24W 1700 Lumens	Product code	DL24-B1	Beam Angle	120°
	Watts	24W	CRI	Ra>80
	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	1700lm	Cutting Size	ø276mm




SKU: 2482	SKU: 2483	SKU: 2484
6000K	4500K	2800K



LED MINI PANELS


SQUARE - Home Edition

3W 150 Lumens	Product code	DL3-B1	Beam Angle	120°
	Watts	3W	CRI	Ra>80
	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	150lm	Cutting Size	67x67mm




SKU: 2485	SKU: 2486	SKU: 2487
6000K	4500K	2800K

6W 360 Lumens	Product code	DL6-B1	Beam Angle	120°
	Watts	6W	CRI	Ra>80
	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	360lm	Cutting Size	98x98mm




SKU: 2488	SKU: 2489	SKU: 2490
6000K	4500K	2800K

12W 840 Lumens	Product code	DL12-B1	Beam Angle	120°
	Watts	12W	CRI	Ra>80
	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	840lm	Cutting Size	148x148mm




SKU: 2491	SKU: 2492	SKU: 2493
6000K	4500K	2800K

18W 1350 Lumens	Product code	DL18-B1	Beam Angle	120°
	Watts	18W	CRI	Ra>80
	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	1350lm	Cutting Size	198x198mm



SKU: 2494	SKU: 2496	SKU: 2495
6000K	4500K	2800K

24W 1700 Lumens	Product code	DL24-B1	Beam Angle	120°
	Watts	24W	CRI	Ra>80
	Input Voltage	AC : 85-260V	IP Rating	IP20
	Flux	1700lm	Cutting Size	270x270mm



SKU: 2497	SKU: 2498	SKU: 2499
6000K	4500K	2800K



3
Years
Warranty

100°

IP44




Color Changing Knob

CCT - LED MINI PANELS
ROUND Build-in Driver
6W**450**

Lumens

Product code	DL6-A6	Beam Angle	100°
Watts	6W	CRI	Ra>80
Input Voltage	AC : 165-265V	IP Rating	IP44 Front
Flux	450lm	Cutting Size	ø105mm



SKU: 2590

CCT Steps



3
Years
Warranty

120°

IP44




Color Changing Knob

CCT - LED MINI PANELS
SQUARE Build-in Driver
6W**450**

Lumens

Product code	DL6-A6	Beam Angle	100°
Watts	6W	CRI	Ra>80
Input Voltage	AC : 165-265V	IP Rating	IP44 Front
Flux	450lm	Cutting Size	105x105mm




SKU: 2594

CCT Steps

12W**950**

Lumens

Product code	DL12-A6	Beam Angle	100°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 165-265V	IP Rating	IP44 Front
Flux	950lm	Cutting Size	ø155mm




SKU: 2591

CCT Steps

12W**950**

Lumens

Product code	DL12-A6	Beam Angle	100°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 165-265V	IP Rating	IP44 Front
Flux	950lm	Cutting Size	155x155mm




SKU: 2595

CCT Steps

18W**1880**

Lumens

Product code	DL18-A6	Beam Angle	100°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 165-265V	IP Rating	IP44 Front
Flux	1880lm	Cutting Size	ø205mm




SKU: 2592

CCT Steps

18W**1450**

Lumens

Product code	DL18-A6	Beam Angle	100°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 165-265V	IP Rating	IP44 Front
Flux	1450lm	Cutting Size	205x205mm




SKU: 2596

CCT Steps

24W**2150**

Lumens

Product code	DL24-A6	Beam Angle	100°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 165-265V	IP Rating	IP44 Front
Flux	2150lm	Cutting Size	ø225mm




SKU: 2593

CCT Steps

24W**2150**

Lumens

Product code	DL24-A6	Beam Angle	100°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 165-265V	IP Rating	IP44 Front
Flux	2150lm	Cutting Size	205x205mm



SKU: 2597

CCT Steps




LED MINI PANELS

ROUND

3W**150**

Lumens

Product code	DL3-A4	Beam Angle	120°
Watts	3W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	150lm	Cutting Size	ø80mm




SKU: 2431	SKU:2432	SKU: 2433
6000K	4500K	2700K

6W**360**

Lumens

Product code	DL6-A4	Beam Angle	120°
Watts	6W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	360lm	Cutting Size	ø110mm




SKU: 2434	SKU:2435	SKU: 2436
6000K	4500K	2700K

12W**840**

Lumens

Product code	DL12-A4	Beam Angle	120°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	840lm	Cutting Size	ø155mm




SKU: 2437	SKU:2438	SKU: 2439
6000K	4500K	2700K

18W**1350**

Lumens

Product code	DL18-A4	Beam Angle	120°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	1350lm	Cutting Size	ø205mm




SKU: 2335	SKU:2440	SKU: 2336
6000K	4500K	2700K

24W**1700**

Lumens

Product code	DL24-A4	Beam Angle	120°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	1700lm	Cutting Size	ø285mm



SKU: 2441	SKU:2442	SKU: 2443
6000K	4500K	2700K




LED MINI PANELS

SQUARE

3W**150**

Lumens

Product code	DL3-A4	Beam Angle	120°
Watts	3W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	150lm	Cutting Size	75x75mm




SKU: 2444	SKU:2445	SKU: 2446
6000K	4500K	2700K

6W**360**

Lumens

Product code	DL6-A4	Beam Angle	120°
Watts	6W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	360lm	Cutting Size	110x110mm




SKU: 2447	SKU:2448	SKU: 2449
6000K	4500K	2700K

12W**840**

Lumens

Product code	DL12-A4	Beam Angle	120°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	840lm	Cutting Size	155x155mm




SKU: 2450	SKU:2451	SKU: 2452
6000K	4500K	2700K

18W**1350**

Lumens

Product code	DL18-A4	Beam Angle	120°
Watts	18W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	1350lm	Cutting Size	205x205mm




SKU: 2348	SKU:2453	SKU: 2349
6000K	4500K	2700K

24W**1700**

Lumens

Product code	DL24-A4	Beam Angle	120°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 85-260V	IP Rating	IP20
Flux	1700lm	Cutting Size	282x282mm



SKU: 2454	SKU:2455	SKU: 2456
6000K	4500K	2700K

3
 Years
 Warranty

120°

Dimmable

IP44




Color Changing Knob



CCT - LED MINI PANELS

ROUND Build-in Driver - Dimmable**6W**
450
 Lumens

Product code	DL6-A7	Beam Angle	100°
Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP44 Front
Flux	450lm	Cutting Size	ø105mm




SKU: 2581

CCT Steps

6000K 4500K 3000K

9W
650
 Lumens

Product code	DL9-A7	Beam Angle	100°
Watts	9W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP44 Front
Flux	650lm	Cutting Size	ø105mm




SKU: 2582

CCT Steps

6000K 4500K 3000K

12W
900
 Lumens

Product code	DL16-A7	Beam Angle	100°
Watts	12W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP44 Front
Flux	900lm	Cutting Size	ø155mm




SKU: 2583

CCT Steps

6000K 4500K 3000K

20W
1600
 Lumens

Product code	DL20-A7	Beam Angle	100°
Watts	20W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP44 Front
Flux	1600lm	Cutting Size	ø205mm




SKU: 2584

CCT Steps

6000K 4500K 3000K

24W
2100
 Lumens

Product code	DL24-A7	Beam Angle	100°
Watts	24W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP44 Front
Flux	2100lm	Cutting Size	ø225mm



SKU: 2585

CCT Steps

6000K 4500K 3000K



Downlight Adapter

ROUND Build-in Driver - Dimmable

SKU: 5003

 Surface 3'D105 from 6-9W
 Compatible with SKU: 2581, 2582

SKU: 5004

 Surface 3'D105 from 12-16W
 Compatible with SKU: 2583

SKU: 5005

 Surface 7'D205 from 18-20W
 Compatible with SKU: 2584

SKU: 5006

 Surface 8'D225 from 22-24W
 Compatible with SKU: 2585


Mini Panels Dimmable Drivers



Dimmable



IP20



SKU: 6025

Dimmable Driver 220V 5-9*1W 300mA

SKU: 6026

Dimmable Driver 220V 10-18*1W 300mA

SKU: 6027

Dimmable Driver 220V 20-30*1W 300mA



Slidable spring




Color Changing Knob

LED SLIM 5 in 1 BUILD-IN/SURFACE
CCT LED 3000 to 6000K

3 Years Warranty
100° Beam Angle
IP20

18W
1600 Lumens


Product code DL18-A7
Watts 18W
Input Voltage AC : 175-265V
Flux 1600lm
Beam Angle 100°
CRI Ra>80
IP Rating IP20
Cutting Size ø65-210mm



SKU: 2586
CCT Steps
6000K 4500K 3000K

30W
3000 Lumens

Product code DL30-A7
Watts 30W
Input Voltage AC : 175-265V
Flux 3000lm
Beam Angle 100°
CRI Ra>80
IP Rating IP20
Cutting Size ø65-310mm




SKU: 2587
CCT Steps
6000K 4500K 3000K



LED CABINET LIGHT
1W Round - Black Body

Watts 1W
Input Voltage AC : 220-240V
Flux 60lm
Beam Angle 28°
CRI Ra>80
IP Rating IP20


SKU: 3296
3000K



LED CABINET LIGHT
1W Round - White Body

Watts 1W
Input Voltage AC : 220-240V
Flux 60lm
Beam Angle 28°
CRI Ra>80
IP Rating IP20

SKU: 3297
3000K



LED CABINET LIGHT
1W Square - Black Body

Watts 1W
Input Voltage AC : 220-240V
Flux 60lm
Beam Angle 28°
CRI Ra>80
IP Rating IP20

SKU: 3298
3000K



LED CABINET LIGHT
1W Square - White Body

Watts 1W
Input Voltage AC : 220-240V
Flux 60lm
Beam Angle 28°
CRI Ra>80
IP Rating IP20

SKU: 3299
3000K





LED DOWNLIGHTS




LED downlights offer a wide variety of applications, from home use as additional lights, to main or accent lighting. Applicable in homes, offices and stores.

Features:

- Up to 80% power saving
- Different sizes to fit old installations or new lighting projects
- Variety of IP ratings
- Fixed or rotatable
- Fire-rated models
- Build-in or surface installation

Application:


- Home or office use
- Accent lights for shops or stores
- Suitable for suspended ceilings




LED COB Downlight
5W Adjustable



Product code	CB5-A1	CRI	Ra>80
Watts	5W	IP Rating	IP20
Input Voltage	AC : 100-240V	Cutting Size	ø80
Flux	375lm	Body Color	White
Beam Angle	50°	Dimmable	NO

SKU: 3264 SKU:3265 SKU: 3266
 ■ 6000K ■ 4500K ■ 2700K


LED COB Downlight
5W Adjustable



Product code	CB5-A1	CRI	Ra>80
Watts	5W	IP Rating	IP20
Input Voltage	AC : 100-240V	Cutting Size	ø80
Flux	375lm	Body Color	White
Beam Angle	50°	Dimmable	NO

SKU: 3267 SKU:3268 SKU: 3269
 ■ 6000K ■ 4500K ■ 2700K


LED COB Downlight
7W Adjustable



Product code	CB7-A1	CRI	Ra>80
Watts	7W	IP Rating	IP20
Input Voltage	AC : 100-240V	Cutting Size	ø80
Flux	525lm	Body Color	White
Beam Angle	50°	Dimmable	NO

SKU: 3284 SKU:3285 SKU: 3286
 ■ 6000K ■ 4500K ■ 2700K


LED COB Downlight
7W Adjustable



Product code	CB7-A1	CRI	Ra>80
Watts	7W	IP Rating	IP20
Input Voltage	AC : 100-240V	Cutting Size	ø80
Flux	525lm	Body Color	White
Beam Angle	50°	Dimmable	NO

SKU: 3287 SKU:3288 SKU: 3289
 ■ 6000K ■ 4500K ■ 2700K


LED COB Downlight
10W Adjustable



Product code	CB10-A1	CRI	Ra>80
Watts	10W	IP Rating	IP20
Input Voltage	AC : 100-240V	Cutting Size	ø105
Flux	750lm	Body Color	White
Beam Angle	50°	Dimmable	NO

SKU: 3290 SKU:3291 SKU: 3292
 ■ 6000K ■ 4500K ■ 2700K


LED COB Downlight
10W Adjustable


Product code	CB10-A1	CRI	Ra>80
Watts	10W	IP Rating	IP20
Input Voltage	AC : 100-240V	Cutting Size	ø105
Flux	750lm	Body Color	White
Beam Angle	50°	Dimmable	NO


SKU: 3293 SKU:3294 SKU: 3295
 ■ 6000K ■ 4500K ■ 2700K




**LED COB Downlight
8W Adjustable**


Product code	CB8-A1	CRI	Ra>80
Watts	8W	IP Rating	IP20
Input Voltage	AC : 220-265V	Cutting Size	ø80
Flux	560lm	Body Color	White
Beam Angle	60°	Dimmable	NO

SKU: 3201 SKU:3206 SKU: 3202
 ■ 6000K ■ 4500K ■ 2700K


**LED COB Downlight
12W Adjustable**


Product code	CB12-A1	CRI	Ra>80
Watts	12W	IP Rating	IP20
Input Voltage	AC : 220-265V	Cutting Size	ø105
Flux	960lm	Body Color	Inox
Beam Angle	60°	Dimmable	NO

SKU: 3254
 ■ 6000K


**LED COB Downlight
8W Adjustable**


Product code	CB8-A1	CRI	Ra>80
Watts	8W	IP Rating	IP20
Input Voltage	AC : 220-265V	Cutting Size	ø80
Flux	560lm	Body Color	Inox
Beam Angle	60°	Dimmable	NO

SKU: 3203 SKU:3205 SKU: 3204
 ■ 6000K ■ 4500K ■ 2700K


**LED COB Downlight
8W Adjustable**


Product code	CB8-A1	CRI	Ra>80
Watts	8W	IP Rating	IP20
Input Voltage	AC : 220-265V	Cutting Size	ø80
Flux	560lm	Body Color	White
Beam Angle	60°	Dimmable	NO

SKU: 3207 SKU:3222 SKU: 3212
 ■ 6000K ■ 4500K ■ 2700K


**LED COB Downlight
25W Adjustable**


Product code	CB25-A1	CRI	Ra>80
Watts	25W	IP Rating	IP20
Input Voltage	AC : 220-240V	Cutting Size	ø160
Flux	2200lm	Body Color	White
Beam Angle	60°	Dimmable	NO

SKU: 3241 SKU:3242
 ■ 6000K ■ 4500K


**LED COB Downlight
8W Adjustable**


Product code	CB8-A1	CRI	Ra>80
Watts	8W	IP Rating	IP20
Input Voltage	AC : 220-265V	Cutting Size	ø80
Flux	560lm	Body Color	Inox
Beam Angle	60°	Dimmable	NO

SKU: 3223 SKU:3224 SKU: 3225
 ■ 6000K ■ 4500K ■ 2700K


**LED COB Downlight
35W Adjustable**

Product code	CB35-A1	CRI	Ra>80
Watts	35W	IP Rating	IP20
Input Voltage	AC : 220-240V	Cutting Size	ø210
Flux	3000lm	Body Color	Inox
Beam Angle	60°	Dimmable	NO


SKU: 3243
 ■ 6000K




LED COB Downlight
15W - TÜV



Product code	CB15-A2	CRI	Ra>80
Watts	15W	IP Rating	IP20
Input Voltage	AC : 220-240V	Cutting Size	ø155
Flux	1200lm	Body Color	White
Beam Angle	145°	Dimmable	NO

SKU: 3270 SKU:3271 SKU: 3272
 ■ 6000K ■ 4500K ■ 2700K


LED COB Downlight
20W - TÜV



Product code	CB20-A2	CRI	Ra>80
Watts	20W	IP Rating	IP20
Input Voltage	AC : 220-240V	Cutting Size	ø165
Flux	1600lm	Body Color	White
Beam Angle	145°	Dimmable	NO

SKU: 3273 SKU:3274 SKU: 3275
 ■ 6000K ■ 4500K ■ 2700K


LED COB Downlight
30W - TÜV



Product code	CB30-A2	CRI	Ra>80
Watts	30W	IP Rating	IP20
Input Voltage	AC : 220-240V	Cutting Size	ø195
Flux	2500lm	Body Color	White
Beam Angle	145°	Dimmable	NO

SKU: 3276 SKU:3277 SKU: 3278
 ■ 6000K ■ 4500K ■ 2700K


LED COB Downlight
40W - TÜV


Product code	CB40-A2	CRI	Ra>80
Watts	40W	IP Rating	IP20
Input Voltage	AC : 100-240V	Cutting Size	ø175
Flux	4000lm	Body Color	White
Beam Angle	60°	Dimmable	NO

SKU: 3260 SKU:3261
 ■ 6000K ■ 4500K


LED COB Downlight
60W - TÜV


Product code	CB60-A1	CRI	Ra>80
Watts	60W	IP Rating	IP20
Input Voltage	AC : 100-240V	Cutting Size	ø205
Flux	5600lm	Body Color	White
Beam Angle	60°	Dimmable	NO

SKU: 3262 SKU:3263
 ■ 6000K ■ 4500K






LED SMD FIRE-RATED PF>0.9
10W - CCT 3000K to 6000K

Product code	OT10-A1	CRI	Ra>80
Watts	10W	IP Rating	IP65
Input Voltage	AC : 200-240V	Cutting Size	ø60
Flux	750lm	Dimension	ø84x67mm
Beam Angle	40°	Dimmable	YES



CCT Knob



LED SMD FIRE-RATED PF>0.9
6W - Replaceable covers

Product code	OT6-A2	CRI	Ra>80
Watts	6W	IP Rating	IP65
Input Voltage	AC : 200-265V	Cutting Size	ø60
Flux	540lm	Dimension	ø84x67mm
Beam Angle	40°	Dimmable	YES



Magnetic replaceable covers



MAGNETIC CHROME BEZEL FOR 5044

BEZELS FOR LED FIRE-RATED DOWNLIGHT
Magnetic Bazels

SKU: 5045	CHROME BEZEL
SKU: 5046	BRUSHED BEZEL

MAGNETIC BRUSHED BEZEL FOR 5044



SKU: 5045



SKU: 5046



CCT Knob

LED SMD FIRE-RATED PF>0.9
8W - CCT 3000K to 6000K

Product code	OT8-A1	CRI	Ra>80
Watts	8W	IP Rating	IP65
Input Voltage	AC : 175-265V	Cutting Size	ø65
Flux	570-630lm	Dimension	ø80x80mm
Beam Angle	40°	Dimmable	YES



Magnetic replaceable covers



LED Strips are a flexible solution for wide variety of lighting applications, both for indoor and outdoor projects, allowing for variable shapes and abstract forms. Functioning as a core or supplementary lighting, LED strips become a common choice of lighting professionals.

Features:

- Up to 80% power saving
- Flexible and reliable
- Wide choice of colour – single colour light to RGB
- Variety of IP ratings
- Options for dimming and control

Application:

- Indoor and outdoor lighting projects
- Applicable for abstract forms and shapes
- Hidden or ambient light

LED STRIPS AND ACCESSORIES

LED Strip 12V 2835 60 LEDs
4.8W/m - Non Waterproof


Product code	ST2835-A1	LED Qty	60 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	4.8W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	300lm/m	Width	8mm

SKU: 4702 SKU:4700 SKU: 4703
 6000K 4500K 2700K


LED Strip 12V 2835 60 LEDs
4.8W/m - Non Waterproof


Product code	ST2835-A1	LED Qty	60 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	4.8W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	300lm/m	Width	8mm

SKU: 4704 SKU:4706
 RED BLUE


LED Strip 12V 2835 120 LEDs
9.6W/m - Non Waterproof


Product code	ST2835-A1	LED Qty	120 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	9.6W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	600lm/m	Width	8mm

SKU: 4710 SKU:4740 SKU: 4711
 6000K 4500K 2700K


LED Strip 12V 2835 204 LEDs
16.5W/m - Non Waterproof


Product code	ST2835-A1	LED Qty	204 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	16.5W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	1700lm/m	Width	10mm

SKU: 4761 SKU:4762 SKU: 4763
 6000K 4500K 2700K


LED Strip 12V 5050 60 LEDs
14.4W/m - Non Waterproof


Product code	ST5050-A1	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	14.4W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	1000lm/m	Width	12mm

SKU: 4313
 RGB + 6000K


LED Strip 12V 5050 60 LEDs
14.4W/m - Non Waterproof


Product code	ST5050-A1	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	14.4W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	1000lm/m	Width	12mm

SKU: 4314
 RGB + 3000K



LED Strip 12V 2835 60 LEDs
4.8W/m - Waterproof


5m-Roll



IP54



Product code	ST2835-A2	LED Qty	60 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	4.8W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP54
Flux/Meter	300lm/m	Width	8mm

 SKU: 4732 SKU:4731 SKU: 4733
 6000K 4500K 2700K

LED Strip 12V 2835 60 LEDs
4.8W/m - Waterproof


5m-Roll



IP54



Product code	ST2835-A2	LED Qty	60 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	4.8W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP54
Flux/Meter	300lm/m	Width	8mm

 SKU: 4734 SKU:4735 SKU: 4736
 RED GREEN BLUE

LED Strip 12V 2835 120 LEDs
9.6W/m - Waterproof


5m-Roll



IP54



Product code	ST2835-A2	LED Qty	120 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	9.6W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP54
Flux/Meter	600lm/m	Width	8mm

 SKU: 4720 SKU: 4721
 6000K 2700K

LED Strip 12V 5050 30 LEDs
7.2W/m - Non Waterproof


5m-Roll



IP20



Product code	ST5050-A1	LED Qty	30 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	7.2W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	500lm/m	Width	10mm

 SKU: 4801 SKU:4800 SKU: 4802
 6000K 4500K 2700K

LED Strip 12V 5050 60 LEDs
14.4W/m - Non Waterproof


5m-Roll



IP20



Product code	ST5050-A1	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	14.4W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	1000lm/m	Width	10mm

 SKU: 4807 SKU:4827 SKU: 4808
 6000K 4500K 2700K

LED Strip 12V 5050 60 LEDs
14.4W/m - Non Waterproof


5m-Roll



IP20



Product code	ST5050-A1	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	14.4W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	1000lm/m	Width	10mm

 SKU: 4823 SKU:4825
 RED BLUE



LED Strip 12V 5050 30 LEDs
7.2W/m - Waterproof


Product code	ST5050-A2	LED Qty	30 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	7.2W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP54
Flux/Meter	500lm/m	Width	10mm

SKU: 4809 SKU:4811 SKU: 4810
 6000K 4500K 2700K


LED Strip 12V 5050 60 LEDs
14.4W/m - Waterproof


Product code	ST5050-A2	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	14.4W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP54
Flux/Meter	1000lm/m	Width	10mm

SKU: 4839 SKU:4841 SKU: 4840
 6000K 4500K 2700K


LED Strip 12V 5050 60 LEDs
14.4W/m - Waterproof


Product code	ST5050-A2	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	14.4W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP54
Flux/Meter	1000lm/m	Width	10mm

SKU: 4844 SKU:4842
 RED BLUE


LED Strip 12V 5050 30 LEDs
7.2W/m


Product code	ST5050-A1	LED Qty	30 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	7.2W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20 ; IP54
Flux/Meter	500lm/m	Width	10mm

SKU: 4311 RGB IP20
 SKU: 4315 RGB IP54


LED Strip 12V 5050 60 LEDs
14.4W/m


Product code	ST5050-A1	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	14.4W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20 ; IP54
Flux/Meter	1000lm/m	Width	10mm

SKU: 4312 RGB IP20
 SKU: 4316 RGB IP54


LED Strip 24V 5050 60 LEDs
14.4W/m


Product code	ST5050-A1	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	14.4W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20 ; IP54
Flux/Meter	1000lm/m	Width	10mm

SKU: 4861 RGB 3800156648616 IP20
 SKU: 4862 RGB 3800156648623 IP54



LED Strip 12V 4040 60 LEDs
8.5W/m - Non Waterproof


Product code	ST4040-A1	LED Qty	60 SMD/m
Type LED	SMD 4040	Material	Flex PCB
Power/Meter	8.5W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	500lm/m	Width	10mm

SKU: 4921 SKU:4922 SKU: 4923
 6000K 4500K 2700K


LED Strip 24V 2835 120 LEDs
9.6W/m - Non Waterproof


Product code	ST2835-A3	LED Qty	120 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	9.6W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	1200lm/m	Width	10mm

SKU: 4856 SKU:4857 SKU: 4858
 6000K 4500K 2700K


LED Strip 12V 4014 120 LEDs
12W/m - Non Waterproof


Product code	ST4014-A1	LED Qty	120 SMD/m
Type LED	SMD 4014	Material	Flex PCB
Power/Meter	12W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	1000lm/m	Width	8mm

SKU: 4904 SKU:4905 SKU: 4906
 6000K 4500K 2700K


LED Strip 24V 5050 60 LEDs
14.4W/m - Non Waterproof


Product code	ST5050-A3	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	14.4W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	600lm/m	Width	10mm

SKU: 4851 SKU:4850 SKU: 4852
 6000K 4500K 2700K


LED Strip 12V 5630 60 LEDs
12W/m - Non Waterproof


Product code	ST5630-A1	LED Qty	60 SMD/m
Type LED	SMD 5630	Material	Flex PCB
Power/Meter	12W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	1000lm/m	Width	10mm

SKU: 4911 SKU:4913 SKU: 4912
 6000K 4500K 2700K


LED Strip 24V 5050 60 LEDs
14.4W/m - Waterproof


Product code	ST5050-A4	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	14.4W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP54
Flux/Meter	600lm/m	Width	10mm

SKU: 4853 SKU:4854 SKU: 4855
 6000K 4500K 2700K



NEW
LED Strip 24V 2835 126 LEDs
10W/m - Non Waterproof


Product code	ST2835-A3	LED Qty	126 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	10W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	1300lm/m	Width	8mm

 SKU: 4871 SKU: 4872 SKU: 4873
 6000K 4000K 3000K

LED Strip 24V 2835 196 LEDs
20W/m - Non Waterproof


Product code	ST2835-A4	LED Qty	196 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	20W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	2100lm/m	Width	12mm

 SKU: 4421 SKU: 4422 SKU: 4423
 6000K 4500K 2700K
**NEW**
LED Strip 24V 2835 182 LEDs
14W/m - Waterproof


Product code	ST2835-A3	LED Qty	182 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	14W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	1820lm/m	Width	8mm

 SKU: 4874 SKU: 4875 SKU: 4876
 6000K 4000K 3000K

LED Strip 24V 2835 196 LEDs
20W/m - Waterproof


Product code	ST2835-A5	LED Qty	196 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	20W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP65
Flux/Meter	2100lm/m	Width	12mm

 SKU: 4451 SKU: 4452 SKU: 4453
 6000K 4500K 2700K
**NEW**
LED Strip 24V 2835 238 LEDs
18W/m - Non Waterproof


Product code	ST5054-A1	LED Qty	238 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	18W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	2340lm/m	Width	12mm

 SKU: 4877 SKU: 4878 SKU: 4879
 6000K 4000K 3000K

LED Strip 24V 5054 60 LEDs
16W/m - Non Waterproof


Product code	ST5054-A1	LED Qty	60 SMD/m
Type LED	SMD 5054	Material	Flex PCB
Power/Meter	16W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	1100lm/m	Width	12mm

 SKU: 4431 SKU: 4432 SKU: 4433
 6000K 4500K 2700K


NEW

LED Strip 12V 2835 120 LEDs
9W/m - Non Waterproof
5mm Width - Slim



Product code	ST2835-A1	LED Qty	120 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	9W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	900lm/m	Width	5mm

SKU: 4907 SKU: 4908 SKU: 4909
 6000K 4500K 2700K

**NEW**

LED Strip 24V COB 624 LEDs
7+7W/m - Non Waterproof



Product code	ST624-A1	LED Qty	624 SMD/m
Type LED	COB	Material	Flex PCB
Power/Meter	7+7W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	700lm/m	Width	10mm

SKU: 4961
 CCT
 6000K 4000K 2700K



LED Strip 24V COB 320 LEDs
10W/m - Non Waterproof




Product code	ST320-A1	LED Qty	320 SMD/m
Type LED	COB	Material	Flex PCB
Power/Meter	10W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	900lm/m	Width	10mm

SKU: 4941 SKU: 4942 SKU: 4943
 6000K 4000K 3000K

**NEW**

LED Strip 24V COB 640 LEDs
8+8W/m - Non Waterproof



Product code	ST640-A1	LED Qty	640 SMD/m
Type LED	COB	Material	Flex PCB
Power/Meter	8+8W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	650lm/m	Width	10mm

SKU: 4960
 CCT
 6000K 4000K 3000K



LED Strip 24V COB 512 LEDs
12W/m - Non Waterproof



Product code	ST512-A1	LED Qty	512 SMD/m
Type LED	COB	Material	Flex PCB
Power/Meter	10W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	1100lm/m	Width	10mm

SKU: 4944 SKU: 4945 SKU: 4946
 6000K 4000K 3000K




LED Strip 24V COB 320 LEDs D Shape
20W/m - Waterproof


Product code	ST320-A2	LED Qty	320 SMD/m
Type LED	COB	Material	Flex PCB
Power/Meter	10W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP65
Flux/Meter	900lm/m	Width	10x4mm


 SKU: 6540
 FIX CLIP WITH 2 SCREWS

 SKU: 4947 SKU: 4948 SKU: 4949
 6000K 4500K 3000K

LED Strip 24V COB 640 LEDs
12W/m - Non Waterproof


Product code	ST640-A1	LED Qty	640 SMD/m
Type LED	COB	Material	Flex PCB
Power/Meter	12W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	500lm/m	Width	12x2.5mm

 SKU: 4950
 RGB+6000K

Middel connector

SKU: 6622


One end connector with wire

SKU: 6623


Two end connector

SKU: 6624


LED Strip 24V COB 320 LEDs
10W/m - Non Waterproof


Product code	ST320-A2	LED Qty	320 SMD/m
Type LED	COB	Material	Flex PC
Power/Meter	10W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	1000lm/m	Dimension	5x5000 mm

 SKU: 4931 SKU: 4932 SKU: 4933
 6000K 4500K 3000K

LED Strip 48V COB 504 LEDs
6W/m - Non Waterproof


Product code	ST320-A2	LED Qty	504 SMD/m
Type LED	COB	Material	Flex PC
Power/Meter	6W/m	Beam Angle	120°
Voltage	DC: 48V	IP Rating	IP20
Flux/Meter	630lm/m	Dimension	10x25000 mm

 SKU: 4934 SKU: 4935 SKU: 4936
 6000K 4500K 3000K

LED Strip 48V COB 504 LEDs -Milky
6W/m - Waterproof


Product code	ST504-A2	LED Qty	504 SMD/m
Type LED	COB	Material	Flex PC
Power/Meter	6W/m	Beam Angle	120°
Voltage	DC: 48V	IP Rating	IP67
Flux/Meter	500lm/m	Dimension	10x20000 mm

 SKU: 4937 SKU: 4938 SKU: 4939
 6000K 4500K 3000K

 SKU: 6539
 FIX CLIP WITH 2 SCREWS


LED Strip 24V 2835 120 LEDs
9W/m - Non Waterproof


Product code	ST2835-A3	LED Qty	120 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	9W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	1000lm/m	Width	8x2.5mm

SKU: 4865 SKU: 4866 SKU: 4867
 6000K 4500K 3000K

LED Strip 24V 2835 120 LEDs
10W/m - Non Waterproof
Runnig Water Effect


Product code	ST120-A1	LED Qty	120 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	10W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	950lm/m	Width	8.25mm

SKU: 4940
 4500K

RF Controller For Running Water Effect


Input: DC12-24V
 Output: 1 group SPI signal
 Mode: 28 kinds
 Contral IC point: 2048 point
 Support IC: WS2811, WS2812, 16703, UCS1903
 SIZE: 40x12x5mm

SKU: 6541

Amplifier


Voltage: DC5-24V
 Output: 2x4=8 group SPI singal
 Function: Multiple separate controllers by connect in parallel
 Remark: 8 pcs light can change at same step with connection in parallel

SKU: 6542



2 PIN connector for 8MM COB
 SKU: 6549



2 PIN fasten connector 8MM SMD
 SKU: 6552



3 PIN connector 10mm 3PIN SMD
 SKU: 6555



5 PIN DUAL connector 10mm 5 IN SMD RGBW
 SKU: 6558



SMD 10mm PCB single color 2 pin
 SKU: 6561



SMD 10mm PCB 3 pin (CCT, magic RGB) 15cm
 SKU: 6564



PIN connector for 8MM SMD
 SKU: 6550



2 PIN fasten DUAL connector 8MM COB
 SKU: 6553



3 PIN connector with wirep 10mm 3PIN SMD
 SKU: 6556



6 PIN connectro 12mm 6 PIN SMD
 SKU: 6559



DUAL SMD 10mm PCB single color 2 pin
 SKU: 6562



SMD 10mm PCB 4 pin (RGB)
 SKU: 6565



2 PIN fasten connector 8MM COB
 SKU: 6551



2 PIN fasten DUAL connector 8MM SMD
 SKU: 6554



5 PIN connector 10mm 5PIN SMD RGBW
 SKU: 6557



6 PIN DUAL connector 12mm 6 PIN SMD
 SKU: 6560



SMD 10mm PCB 3 pin (CCT, magic RGB)
 SKU: 6563



SMD 10mm PCB 5 pin (RGBW)
 SKU: 6566


LED Strip 24V 5054 60 LEDs
16W/m - Waterproof
3
 Years

Warranty



5m-Roll



IP65

Product code	ST5054-A2	LED Qty	60 SMD/m
Type LED	SMD 5054	Material	Flex PCB
Power/Meter	16W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP65
Flux/Meter	1100lm/m	Width	10mm

 SKU: 4461 SKU: 4462 SKU: 4463
 6000K 4500K 2700K

LED Strip 12V 2835 196 LEDs
20W/m - Non Waterproof
3
 Years

Warranty



5m-Roll



IP20

Product code	ST2835-A5	LED Qty	196 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	20W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	2100lm/m	Width	12mm

 SKU: 4424 SKU: 4425 SKU: 4426
 6000K 4500K 2700K

LED Strip 24V 5025 60 LEDs
16W/m - CCT Adjustable
Non Waterproof
3
 Years

Warranty



5m-Roll



IP20

Product code	ST5025-A1	LED Qty	60 SMD/m
Type LED	SMD 5025	Material	Flex PCB
Power/Meter	16W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP20
Flux/Meter	800lm/m	Width	10mm

 SKU: 4441
 CCT
 6000K 4000K 3000K

LED Strip 12V 2835 196 LEDs
20W/m - Waterproof
3
 Years

Warranty



5m-Roll



IP65

Product code	ST2835-A6	LED Qty	196 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	20W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP65
Flux/Meter	2100lm/m	Width	12mm

 SKU: 4454 SKU: 4455 SKU: 4456
 6000K 4500K 2800K

LED Strip 24V 5025 60 LEDs
16W/m - CCT Adjustable
Waterproof
3
 Years

Warranty



5m-Roll



IP65

Product code	ST5025-A2	LED Qty	60 SMD/m
Type LED	SMD 5025	Material	Flex PCB
Power/Meter	16W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP65
Flux/Meter	800lm/m	Width	10mm

 SKU: 4471
 CCT
 6000K 4000K 3000K

LED Strip 12V 5050 60 LEDs
16W/m - Non Waterproof


RGB



5m-Roll



IP20

Product code	ST5050-A7	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	16W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	1600lm/m	Width	12mm

SKU: 4485 RGB+White Light 3800156644854

SKU: 4486 RGB+Warm White 3800156644861


3
 Years

Warranty



LED Strip 12V 5050 60 LEDs
16W/m - Waterproof



Product code	ST5050-A8	LED Qty	60 SMD/m	3 Years Warranty
Type LED	SMD 5050	Material	Flex PCB	
Power/Meter	16W/m	Beam Angle	120°	
Voltage	DC: 12V	IP Rating	IP65	
Flux/Meter	1600lm/m	Width	12mm	

SKU: 4487 RGB+White Light 3800156644878

SKU: 4488 RGB+Warm White 3800156644885



LED Strip 24V 5050 60 LEDs
16W/m - Non Waterproof



Product code	ST5050-A5	LED Qty	60 SMD/m	3 Years Warranty
Type LED	SMD 5050	Material	Flex PCB	
Power/Meter	16W/m	Beam Angle	120°	
Voltage	DC: 24V	IP Rating	IP20	
Flux/Meter	1600lm/m	Width	10mm	

SKU: 4481 RGB+6000K

SKU: 4482 RGB+3000K



LED Strip 24V 5050 60 LEDs
16W/m Waterproof



Product code	ST5050-A6	LED Qty	60 SMD/m	3 Years Warranty
Type LED	SMD 5050	Material	Flex PCB	
Power/Meter	16W/m	Beam Angle	120°	
Voltage	DC: 24V	IP Rating	IP65	
Flux/Meter	1600lm/m	Width	10mm	

SKU: 4483 RGB+6000K

SKU: 4484 RGB+3000K




LED Strip 24V 5050 60 LEDs
9.5W/m - Non Waterproof



Product code	ST5050-A9	LED Qty	60 SMD/m	3 Years Warranty
Type LED	SMD 5050	Material	Flex PCB	
Power/Meter	9.5W/m	Beam Angle	120°	
Voltage	DC: 24V	IP Rating	IP20	
Flux/Meter	950lm/m	Width	10mm	

SKU: 4480 RGB CCT: 6000K, 4000K, 3000K

 CONNECTOR FOR STRIP 3528 SKU: 5151	 CONNECTOR FOR STRIP 5050 SKU: 5152	 CONNECTOR FOR STRIP RGB SKU: 6608
 ANGLE CONNECTOR FOR STRIP 3528 8mm SKU: 6619	 ANGLE CONNECTOR FOR STRIP 5050 10mm SKU: 6620	 ANGLE CONNECTOR FOR STRIP RGB 10mm SKU: 6621
 CONNECTOR FOR STRIP DC MALE SKU: 6610	 CONNECTOR FOR STRIP DC FEMALE SKU: 6611	 FLEXIBLE FOR STRIP 3528 DC FEMALE SKU: 6612
 FLEXIBLE FOR STRIP 5050 DC FEMALE SKU: 6613	 FLEXIBLE CONNECTOR FOR LED STRIP RGB SKU: 6614	 FLEXIBLE CONNECTOR FOR LED STRIP 3528 SKU: 6615
 FLEXIBLE CONNECTOR FOR LED STRIP 5050 SKU: 6616	 FLEXIBLE CONNECTOR FOR STRIP RGB+WH SKU: 6618	 FLEXIBLE FOR RGB LED STRIP WITH PIN SKU: 6617



SMD 2216

SMD 2110


LED Strip 24V HIGH POWER
SMD2216 ; SMD2110

1900

Lumens



240 pcs

Product code	ST2216-A1
Type LED	SMD 2216
Power/Meter	22W/m
Voltage	DC: 24V
Flux/Meter	1900lm/m

LED Qty	240 SMD/m
Material	Flex PCB
Beam Angle	120°
IP Rating	IP20
Width	10mm

3 Years
Warranty

5m-Roll



IP20

SKU: 4403 ■ 3000K

2200

Lumens



300 pcs

Product code	ST2216-A1
Type LED	SMD 2216
Power/Meter	24W/m
Voltage	DC: 24V
Flux/Meter	2200lm/m

LED Qty	300 SMD/m
Material	Flex PCB
Beam Angle	120°
IP Rating	IP20
Width	10mm

3 Years
Warranty

5m-Roll



IP20

SKU: 4404 ■ 3000K

2500

Lumens



560 pcs

Product code	ST2110-A1
Type LED	SMD 2110
Power/Meter	32W/m
Voltage	DC: 24V
Flux/Meter	2500lm/m

LED Qty	560 SMD/m
Material	Flex PCB
Beam Angle	120°
IP Rating	IP20
Width	12mm

3 Years
Warranty

5m-Roll



IP20

SKU: 4405 ■ 3000K

3400

Lumens



700 pcs

Product code	ST2110-A1
Type LED	SMD 2110
Power/Meter	38W/m
Voltage	DC: 24V
Flux/Meter	3400lm/m

LED Qty	700 SMD/m
Material	Flex PCB
Beam Angle	120°
IP Rating	IP20
Width	12mm

3 Years
Warranty

5m-Roll



IP20

SKU: 4406 ■ 3000K



RGB

3 Years

Warranty



5m-Roll



IP20


LED Digital Strip
Addressable

Product code	ST10-A1
Type LED	WS2811 10 Pixels
Power/Meter	7W/m
Voltage	DC: 12V
Flux/Meter	550lm/m
LED Qty	30 SMD/m
Material	Flex PCB
Beam Angle	120°
IP Rating	IP20
Width	10mm
EAN Code	3800156644908

SKU: 4490

SKU: 4491

SKU: 4492

Product code	ST30-A1
Type LED	WS2812b 30 Pixels
Power/Meter	8W/m
Voltage	DC: 5V
Flux/Meter	600lm/m
LED Qty	30 SMD/m
Material	Flex PCB
Beam Angle	120°
IP Rating	IP20
Width	10mm
EAN Code	3800156644915

Product code	ST60-A1
Type LED	WS2812b 30 Pixels
Power/Meter	16W/m
Voltage	DC: 5V
Flux/Meter	1200lm/m
LED Qty	60 SMD/m
Material	Flex PCB
Beam Angle	120°
IP Rating	IP20
Width	10mm
EAN Code	3800156644922

RGB



Addressable

Digital LED Strip Controller
DC5-24V SD-CARD


Voltage	5V-24V
IP Rating	IP20
Dimension	80x55x20mm
SKU: 6331	

Digital LED Strip Controller
DC5-24V


Voltage	5V-24V
IP Rating	IP20
Dimension	80x55x20mm
SKU: 6332	


**LED Strip 12V 5050 30 LEDs - SET
 Adapter + ir Controller + Remote**


Product code	ST5050-B1	LED Qty	30 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	4W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	240lm/m	Width	10mm

SKU: 4321 RGB IP20


**LED Strip 12V 5050 30 LEDs - SET
 Adapter + Bluetooth Music + Remote**


Product code	ST5050-B1	LED Qty	30 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	4W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	240lm/m	Width	10mm

SKU: 4328 RGB IP20



Music


**LED Strip 12V 5050 60 LEDs - SET
 Adapter + ir Controller + Remote**


Product code	ST5050-B1	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	8W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	480lm/m	Width	10mm

SKU: 4322 RGB IP20


**LED Strip 12V 5050 60 LEDs - SET
 Adapter + Bluetooth Music + Remote**


Product code	ST5050-B1	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	8W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	480lm/m	Width	10mm

SKU: 4329 RGB IP20



Music


**LED Strip 12V 5050 60 LEDs - SET
 Adapter + ir Controller + Remote
 Waterproof**


Product code	ST5050-B1	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	8W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP54
Flux/Meter	480lm/m	Width	10mm

SKU: 4323 RGB IP54


**LED Strip 12V 5050 60 LEDs - SET
 Adapter + Bluetooth Music + Remote
 Waterproof**


Product code	ST5050-B1	LED Qty	60 SMD/m
Type LED	SMD 5050	Material	Flex PCB
Power/Meter	8W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP54
Flux/Meter	480lm/m	Width	10mm

SKU: 4330 RGB IP54



Music


**Smart LED Strip 12V 5050+2835 - SET
 Adapter + Wifi Controller**


Product code	ST5050-B1	LED Qty	60 SMD/m
Type LED	SMD 5050+2835	Material	Flex PCB
Power/Meter	4W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	240lm/m	Width	10mm

SKU: 4324 RGB+W IP20

SKU: 4325 RGB+WW IP20


**Smart LED Strip 12V CCT 5050+2835 -SET
 Adapter + Wifi Controller**



Product code	ST5050-B1	LED Qty	90 SMD/m
Type LED	SMD 5050+2835	Material	Flex PCB
Power/Meter	6W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP54
Flux/Meter	360lm/m	Width	12mm

SKU: 4326 RGB+CCT IP20



**TV LED Strip 5V 5050+2835 60LEDs - SET
 Wifi Controller + Remote**


Product code	ST5050-B1	LED Qty	60 SMD/m
Type LED	SMD 5050+2835	Material	Flex PCB
Power/Meter	4W/m	Beam Angle	120°
Voltage	DC: 5V	IP Rating	IP20
Flux/Meter	240lm/m	Width	10mm


SKU: 4327 RGB+WW IP20


NEW


- SKU: 15115 Silver Body (L=2m)
- SKU: 15116 Black Body (L=2m)
- SKU: 15117 Iron Oxide Gray (L=2m)
- SKU: 15118 Corner Silver Body
- SKU: 15119 Corner Black Body

NEW


- SKU: 15120 Black Body (L=2m) White Cover
- SKU: 15121 White Body (L=2m) White Cover

NEW





- SKU: 15122 Black Body (L=2m) White Cover
- SKU: 15123 White Body (L=2m) White Cover

NEW



- SKU: 15113 White Body (L=2m) White Cover
- SKU: 15114 White Body (L=2m) Black Cover

NEW











- SKU: 15130 Keel Mesh for NEON 16x10mm
- SKU: 15131 Keel Mesh for NEON 16x8mm


NEWSKU: 15111 White Body- White Cover (L=2m) SKU: 15112 White Body- Black Cover (L=2m) **NEW**SKU: 15124 Black Body- White Cover (L=2m) SKU: 15125 White Body- White Cover (L=2m) SKU: 15126 Warble Body- White Cover (L=2m)

With hanging accessories


NEWSKU: 15127 Black Body- White Cover (L=2m) SKU: 15128 White Body- White Cover (L=2m) SKU: 15129 Warble Body- White Cover (L=2m)

With hanging accessories

NEWSKU: 5143 Silver Body- White Cover (L=2m) **NEW**SKU: 5144 Silver Body- White Cover (L=2m) **NEW**SKU: 5145 Silver Body- White Cover (L=2m) SKU: 5104 Black Body- White Cover (L=2m) SKU: 5105 Black Body- Black Cover (L=2m) SKU: 5106 White Body- White Cover (L=2m) SKU: 5193 Silver Body- White Cover (L=1m) SKU: 5192 Silver Body- White Cover (L=2m) SKU: 5190 Silver Body- White Cover (L=1m) SKU: 5191 Silver Body- White Cover (L=2m) SKU: 5184 White Body- White Cover (L=2m) SKU: 5185 Black Body- White Cover (L=2m) SKU: 5108 Silver Body- White Cover (L=2m) SKU: 5113 Silver Body- White Cover (L=2m) SKU: 5175 Silver Body- White Cover (L=2m)




SKU: 5107 Black Body- Black Cover (L=2m) ■■





SKU: 5002 Bendable -Silver body (L=1m) ■


SKU: 5001 Bendable -Silver body (L=2m) ■





SKU: 5109 Silver Body- White Cover (L=2m) ■□




SKU: 5111 Silver Body- White Cover (L=2m) ■□



SKU: 5183 Silver Body- White Cover (L=2m) ■□





SKU: 5112 Silver Body- White Cover (L=2m) ■□




SKU: 5101 Black Body- Black Cover (L=2m) ■□

SKU: 5102 White Body- White Cover (L=2m) □□


SKU: 5103 Silver Body- White Cover (L=2m) ■□




SKU: 5162 Silver Body- White Cover (L=2m) ■□




SKU: 5110 Silver Body- White Cover (L=2m) ■□





SKU: 5165 Silver Body- White Cover (L=2m) ■□



SKU: 5150 Silver Body- White Cover (L=2m) ■□





SKU: 5166 Silver Body- White Cover (L=2m) ■□



SKU: 5114 Black Body- Black Cover (L=2m) ■■

SKU: 5115 Silver Body- White Cover (L=2m) ■□



SKU: 5116 Black Body- White Cover (L=2m) ■□



SKU: 5117 Black Body- Black Cover (L=2m) ■■

SKU: 5118 Silver Body- White Cover (L=2m) ■□



SKU: 5119 Black Body- White Cover (L=2m) ■□



SKU: 5120 Black Body- Black Cover (L=2m) ■■

SKU: 5121 Silver Body- White Cover (L=2m) ■□



SKU: 5122 Black Body- White Cover (L=2m) ■□




SKU: 5124 Black Body- Black Cover (L=2m) ■■

SKU: 5123 Silver Body- White Cover (L=2m) ■□


SKU: 5125 Black Body- White Cover (L=2m) ■□

NEW



SKU: 5141 Silver Body- White Cover (L=2m) ■□

NEW



SKU: 5142 Silver Body- White Cover (L=2m) ■□




SKU: 5128 Silver Body- White Cover (L=2m) ■□




SKU: 5130 Silver Body- White Cover (L=2m) ■□



SKU: 5132 Silver Body- White Cover (L=2m) ■□



SKU: 5133 Silver Body- White Cover (L=2m) ■□



SKU: 5134 Silver Body- White Cover (L=2m) ■□



The new range of silicone encapsulated Neon by OPTONICA LED comprises of highly durable and flexible linear LED Solutions - suitable for both indoor and outdoor architectural applications. Designed using high-grade silicone, the neon is:

- Able to withstand wide temperature amplitudes
- Resistant to the build-up of dirt and dust, making it the first to come with a self-cleaning property
- Waterproof and impact resistant
- UV, flame and solvent resistant

LED STRIPS 220V AND FLEX NEON



LED Strip S-Type 12V 2835 60 LEDs
7.2W/m - Non Waterproof

Product code	M02835-A2	LED Qty	60 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	7.2W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	720lm/m	Width	6mm


3
Years
Warranty



5m-Roll



IP20



Free Angle Bending

SKU: 4941 SKU: 4946 SKU: 4942
 6000K 4000K 3000K



LED Strip S-Type 12V 2835 60 LEDs
7.2W/m - Waterproof

Product code	M02835-A2	LED Qty	60 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	7.2W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP65
Flux/Meter	720lm/m	Width	6mm


3
Years
Warranty



5m-Roll



IP65



Free Angle Bending

SKU: 4551 SKU: 4552
 6000K 2700K



LED Strip S-Type 12V 2835 60 LEDs
7.2W/m - Non Waterproof

Product code	M02835-A2	LED Qty	60 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	7.2W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP20
Flux/Meter	720lm/m	Width	6mm


3
Years
Warranty



5m-Roll



IP20



Free Angle Bending

SKU: 4943 SKU: 4945 SKU: 4944
 RED GREEN BLUE



LED Strip S-Type 12V 2835 60 LEDs
7.2W/m - Waterproof

Product code	M02835-A2	LED Qty	60 SMD/m
Type LED	SMD 2835	Material	Flex PCB
Power/Meter	7.2W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP65
Flux/Meter	720lm/m	Width	6mm


3
Years
Warranty



5m-Roll



IP65



Free Angle Bending

SKU: 4553 SKU: 4555 SKU: 4554
 RED GREEN BLUE



/m
120 pcs
 50m-Roll
 IP65



/m
120 pcs
 50m-Roll
 IP65



LED FLEX NEON 12V -50m Roll
2835 120 SMD/m

Product code	ST12-A2	LED Qty	120 SMD/m
Type LED	SMD 2835	Material	Flex PC
Power/Meter	6W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP65
Flux/Meter	300lm/m	Dimension	16x8 mm

SKU: 4590	6000K	
SKU: 4591	4000K	
SKU: 4592	2800K	
SKU: 4593	Blue	
SKU: 4594	Red	
SKU: 4595	Green	
SKU: 4596	Ice Blue	
SKU: 4597	Lemon	
SKU: 4598	Golden	
SKU: 4599	PURPLE	

LED FLEX NEON 220V -50m Roll
2835 120 SMD/m

Product code	ST220-A2	LED Qty	120 SMD/m
Type LED	SMD 2835	Material	Flex PC
Power/Meter	8.5W/m	Beam Angle	120°
Voltage	AC: 220V	IP Rating	IP65
Flux/Meter	300lm/m	Dimension	Single 16x10 mm RGB 25x13 mm

SKU: 4581	6000K	
SKU: 4580	4000K	
SKU: 4582	2800K	
SKU: 4584	RED	
SKU: 4585	GREEN	
SKU: 4583	BLUE	
SKU: 4587	YELLOW	
SKU: 4586	AMBER	
SKU: 4588	PINK	
SKU: 4589	RGB	

PLUG IN + CONNECTOR PIN



SKU: 6602

MOUNTING BRACKET



SKU: 6603

ALUMINIUM CLIPS



SKU: 6601

END CAP FOR



SKU: 6605

INPUT CABLE + CONNECTOR + PLUG



SKU: 6635

MIDDLE CONNECTOR



SKU: 6634

ALUMINIUM CHANNEL WITH 2 SCREWS



SKU: 6636

END CAP FOR SINGLE COLOUR



SKU: 6637

CONNECTOR PLUG



SKU: 6604



POWER CABLE+RGB CONTROLLER



SKU: 6638

ALUMINIUM CHANNEL , 5CM RGB



SKU: 6639

END CAP FOR RGB



SKU: 6640

NEW



**LED Strip 220V COB 480 LEDs
10W/m - Connect-Anyway**



50m-Roll



IP65

Product code	ST480-A1	LED Qty	480 SMD/m
Type LED	COB	Material	Flex PCB
Power/Meter	10W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP65
Flux/Meter	800lm/m	Width	9x4mm

SKU: 4957 6000K SKU:4958 4000K SKU: 4959 3000K



NEW



**LED Flex Neon - Magic RGB
9W/m - Waterproof**



5m-Roll



IP65

Product code	ST72-A1	LED Qty	72 SMD/m
Type LED	SMD 3535	Material	Flex PCB
Power/Meter	9W/m	Beam Angle	120°
Voltage	DC: 24V	IP Rating	IP65
Flux/Meter	250lm/m	Width	6x12mm

SKU: 4579 Magic RGB SKU: 6581 Fix clip for magic RGB neon



NEW



**LED FLEX NEON 24V -5m Roll
2835 140 SMD/m**



5m-Roll



IP65

Product code	ST24-A1	LED Qty	140 SMD/m
Type LED	SMD 2835	Material	Flex PC
Power/Meter	10W/m	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP65
Flux/Meter	300lm/m	Dimension	12x20 mm

SKU: 4571 6000K SKU:4572 4000K SKU: 4573 3000K

SKU: 6591 Fix clip for Neon



Magic RGB Bluetooth RF 2.4G Remote Controller

Input Voltage	DC5V-24V
Output	SPI Signal
Buttons	24 Keys
IP Rating	IP20



IP20

SKU: 6582



CCT RF Controller

Input Voltage	DC12-24V
Output	2Channels
Output Current	10A (each channel)
Output Power	12V-240W ; 24V-480W



IP20

SKU: 6583



LED Strips 220V -50m Roll
2835 120 SMD/m

/m
120 pcs

IP65



Product code	ST220-A3	LED Qty	120 SMD/m
Type LED	SMD 2835	Material	Flex PC
Power/Meter	9W/m	Beam Angle	120°
Voltage	AC: 220V	IP Rating	IP65
Flux/Meter	900lm/m	Dimension	10x4.3 mm

SKU: 4951 SKU: 4952 SKU: 4953
 6000K 4500K 3000K

50m-Roll



/m
120 pcs

50m-Roll

IP65



LED Strips 220V -50m Roll
5730 120 SMD/m

Product code	ST220-A1	LED Qty	120 SMD/m
Type LED	SMD 5730	Material	Flex PC
Power/Meter	10W/m	Beam Angle	120°
Voltage	AC: 220V	IP Rating	IP65
Flux/Meter	500lm/m	Dimension	13x5 mm

SKU: 4611 SKU: 4613 SKU: 4612
 6000K 4000K 2800K

LED Strips COB 220V -50m Roll
COB Waterproof

/m
288 pcs

IP65



Product code	ST228-A1	LED Qty	288 SMD/m
Type LED	COB	Material	Flex PC
Power/Meter	10W/m	Beam Angle	120°
Voltage	AC: 220V	IP Rating	IP65
Flux/Meter	700lm/m	Dimension	12x5 mm

SKU: 4954 SKU: 4955 SKU: 4956
 6000K 4500K 3000K

50m-Roll



2835/5730 INPUT CABLE + CONNECTOR
SKU: 6631



2835/5730 MIDDLE CONNECTOR
SKU: 6633



2835/5730 FIXING
SKU: 6632



END CAP FOR 220V
SKU: 6637




INPUT CABLE + CONNECTOR
SKU: 6546



FIX CLIP
SKU: 6547



END CAP FOR COB
SKU: 6548




LENS LED Module 1.6W - 220V
3x2835 SMD - Waterproof

100
Lumens

IP67

Product code	M0220-A1	LED Qty	3 pcs
Type LED	SMD 2835	Material	PC
Power/Module	1.2W	Beam Angle	160°
Voltage	AC: 220-265V	IP Rating	IP67
Flux/Watt	84lm/W	Dimension	88x22x11mm

SKU: 4564 White Light 6500K

3
Years
Warranty

LED Module 2.4W
4x2835 SMD - Waterproof

85
Lumens

IP65

Product code	M02835-A1	LED Qty	4 pcs
Type LED	SMD 2835	Material	PC
Power/Module	2.4W	Beam Angle	160°
Voltage	DC: 12V	IP Rating	IP65
Flux/Watt	35lm/W	Dimension	43x38x6.5mm

SKU: 4561 White Light 6500K 3800156645615

SKU: 4562 Warm White 3000K 3800156645622

3
Years
Warranty

LENS LED Module 0.72W
3x2835 SMD - Waterproof

80
Lumens

IP65

Product code	M02835-A1	LED Qty	3 pcs
Type LED	SMD 2835	Material	PC
Power/Module	0.72W	Beam Angle	160°
Voltage	DC: 12V	IP Rating	IP65
Flux/Watt	110lm/W	Dimension	58x12mm

 SKU: 4512 White Light 10000K
 SKU: 4511 White Light 6500K
 SKU: 4513 Warm White 3000K
 SKU: 4514 RED
 SKU: 4516 GREEN
 SKU: 4515 BLUE

3
Years
Warranty

LENS LED Module 0.72W
3x5050 SMD - Waterproof

85
Lumens

IP65

Product code	M05050-A1	LED Qty	3 pcs
Type LED	SMD 5050	Material	PC
Power/Module	0.72W	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP65
Flux/Watt	118lm/W	Dimension	70x16x8mm

SKU: 4563 RGB

3
Years
Warranty

LENS LED Module 1.5W
3x2835 SMD - Waterproof

120
Lumens

IP65

Product code	M02835-A1	LED Qty	3 pcs
Type LED	SMD 2835	Material	PC
Power/Module	1.5W	Beam Angle	160°
Voltage	DC: 12V	IP Rating	IP65
Flux/Watt	80lm/W	Dimension	75x15mm

 SKU: 4522 White Light 10000K
 SKU: 4521 White Light 6500K
 SKU: 4523 Warm White 3000K
 SKU: 4524 RED
 SKU: 4526 GREEN
 SKU: 4525 BLUE

3
Years
Warranty

LED Module 0.36W
3x3014 SMD - Waterproof

30
Lumens

IP65

Product code	M03014-A1	LED Qty	3 pcs
Type LED	SMD 3014	Material	PC
Power/Module	0.36W	Beam Angle	120°
Voltage	DC: 12V	IP Rating	IP65
Flux/Watt	85lm/W	Dimension	18x8x2.9mm

 SKU: 4531 White Light 6500K
 SKU: 4532 Warm White 3000K
 SKU: 4533 RED
 SKU: 4535 GREEN
 SKU: 4534 BLUE

3
Years
Warranty



LED POWER SUPPLIES



Our portfolio covers best-performing all world-wide LVD power standards including narrow-body for installation ease in tricky spaces. Cost-efficient on your utility bills and your maintenance budget.

Features:

- 5V, 12V and 24V units come in a choice of sizes and shapes
- Specialized dimmable products for panels and downlights
- Waterproof options available with various degree of ingress-protection ratings
- Extended life cycle through forced heat dissipation, making them utmost reliable

Application:

- The natural choice for each LED strip design and installation
- A vital part of any lighting application



NEW
DIN RAIL Power Supply
12V Output
Metal

 SKU: 6275 75W - 12V
 SKU: 6277 120W - 12V
 SKU: 6279 240W - 12V

Watts	75W	120W	240W
Input Voltage	100-240Vac	100-240Vac	100-240Vac
Output Voltage	DC: 12V	DC: 12V	DC: 12V
Current	6.25A	10A	20A
Dimension	32x125.2x102mm	40x125.2x113.5mm	63x125.2x113.5mm

NEW
Ultra Slim DIN RAIL Power Supply
12V Output
Plastic

 SKU: 6265 60W - 12V
 SKU: 6267 100W - 12V

Watts	60W	100W
Input Voltage	85-264Vac	85-264Vac
Output Voltage	DC: 12V	DC: 12V
Current	5A	8.33A
Dimension	52.5x90x54.5mm	70x90x54.5mm

DIN RAIL Power Supply
24V Output
Metal

 SKU: 6276 75W - 24V
 SKU: 6278 120W - 24V
 SKU: 6280 240W - 24V

Watts	75W	120W	240W
Input Voltage	100-240Vac	100-240Vac	100-240Vac
Output Voltage	DC: 24V	DC: 24V	DC: 24V
Current	3.125A	5A	10A
Dimension	32x125.2x102mm	40x125.2x113.5mm	63x125.2x113.5mm

Ultra Slim DIN RAIL Power Supply
24V Output
Plastic

 SKU: 6266 60W - 24V
 SKU: 6268 100W - 24V

Watts	60W	100W
Input Voltage	85-264Vac	85-264Vac
Output Voltage	DC: 24V	DC: 24V
Current	2.5A	4.16A
Dimension	52.5x90x54.5mm	70x90x54.5mm



Dimmable



TRIAC Dimmable Power Supplies
Metal 12V Output




3 Years
Warranty

DC:12V

IP20

SKU: 6271 75W - 12V
SKU: 6272 100W - 12V
SKU: 6273 150W - 12V

Watts	75W	100W	150W
Input Voltage	220-240V	220-240V	220-240V
Output Voltage	DC: 12V	DC: 12V	DC: 12V
Current	6.25A	8.33A	12.5A
Material	Metal	Metal	Metal
IP Rating	IP20	IP20	IP20
Dimension	190x50x31mm	206x67x37mm	206x67x37mm



TRIAC Dimmable Power Supplies
Metal 24V Output




3 Years
Warranty

DC:24V

IP20

SKU: 6281 75W - 24V
SKU: 6282 100W - 24V
SKU: 6283 150W - 24V

Watts	75W	100W	150W
Input Voltage	220-240V	220-240V	220-240V
Output Voltage	DC: 24V	DC: 24V	DC: 24V
Current	3.1A	4.17A	6.25A
Material	Metal	Metal	Metal
IP Rating	IP20	IP20	IP20
Dimension	119x52x32mm	206x67x37mm	206x67x37mm



NEW



SKU: 6299 Wire Cable

LED SUPER SLIM Power Supplies
Plastic 12V Output

DC:12V

IP20

SKU: 6291 24W - 12V
SKU: 6292 36W - 12V
SKU: 6293 60W - 12V
SKU: 6294 100W - 12V

Watts	24W	36W	60W	100W
Input Voltage	175-265V	175-265V	175-265V	175-265V
Output Voltage	DC: 12V	DC: 12V	DC: 12V	DC: 12V
Current	2A	3A	5A	8.3A
Dimension	117x55x18.5mm	137x55x18.5mm	169x59x20mm	198x59x20mm



Power Supplies for Track Light
Metal 48V Output

DC:48V

IP20

SKU: 6284 120W - 48V
SKU: 6285 250W - 48V

Watts	120W	250W
Input Voltage	220V	220V
Output Voltage	DC: 48V	DC: 48V
Current	2.5A	5.2A
Dimension	190x90x30mm	220x120x30mm





Strip Power Supplies Premium
Plastic 12V Output
3
 Years
 Warranty

 DC:12V

 IP20

 SKU: 6201 36W - 12V
 SKU: 6202 60W - 12V
 SKU: 6203 72W - 12V

Watts	36W	60W	72W
Input Voltage	100-240V	100-240V	100-240V
Output Voltage	DC: 12V	DC: 12V	DC: 12V
Current	3A	5A	6A
Material	Plastic	Plastic	Plastic
IP Rating	IP20	IP20	IP20
Dimension	119x52x32mm	119x52x32mm	119x52x32mm






Strip Power Supplies Premium
SLIM - Metal 12V Output
3
 Years
 Warranty

 DC:12V

 IP20

 SKU: 6211 60W - 12V
 SKU: 6212 100W - 12V
 SKU: 6213 150W - 12V
 SKU: 6214 200W - 12V

Watts	60W	100W	150W	200W
Input Voltage	100-240V	100-240V	176-265V	176-265V
Output Voltage	DC: 12V	DC: 12V	DC: 12V	DC: 12V
Current	5A	8.4A	12.5A	16.7A
Material	Metal	Metal	Metal	Metal
IP Rating	IP20	IP20	IP20	IP20
Dimension	130x50x31mm	190x50x31mm	200x62x31mm	208x82x32mm





Strip Power Supplies Premium
Plastic 24V Output
3
 Years
 Warranty

 DC:24V

 IP20

 SKU: 6206 36W - 24V
 SKU: 6207 60W - 24V
 SKU: 6208 72W - 24V

Watts	36W	60W	72W
Input Voltage	100-240V	100-240V	100-240V
Output Voltage	DC: 24V	DC: 24V	DC: 24V
Current	1.5A	2.5A	3A
Material	Plastic	Plastic	Plastic
IP Rating	IP20	IP20	IP20
Dimension	119x52x32mm	119x52x32mm	119x52x32mm






Strip Power Supplies Premium
SLIM - Metal 24V Output
3
 Years
 Warranty

 DC:24V

 IP20

 SKU: 6221 60W - 24V
 SKU: 6222 100W - 24V
 SKU: 6223 150W - 24V
 SKU: 6224 200W - 24V

Watts	60W	100W	150W	200W
Input Voltage	100-240V	100-240V	176-265V	176-265V
Output Voltage	DC: 24V	DC: 24V	DC: 24V	DC: 24V
Current	2.5A	4.2A	6.25A	8.35A
Material	Metal	Metal	Metal	Metal
IP Rating	IP20	IP20	IP20	IP20
Dimension	130x50x31mm	190x50x31mm	200x60x31mm	208x82x32mm





Strip Power Supplies Premium
Plastic Case 12V Output




3 Years
Warranty

DC:12V

IP20

SKU: 6231 24W - 12V
SKU: 6232 36W - 12V
SKU: 6233 60W - 12V

Watts	24W	36W	60W
Input Voltage	100-240V	100-240V	100-240V
Output Voltage	DC: 12V	DC: 12V	DC: 12V
Current	2A	3A	5A
Material	Plastic	Plastic	Plastic
IP Rating	IP20	IP20	IP20
Dimension	120x42x28mm	140x48x30mm	155x53x30mm



Strip Power Supplies Premium
Waterproof 12V Output





3 Years
Warranty

DC:12V

IP67

SKU: 6251 60W - 12V
SKU: 6252 100W - 12V
SKU: 6253 150W - 12V
SKU: 6254 200W - 12V

Watts	60W	100W	150W	200W
Input Voltage	100-240V	100-240V	176-265V	176-265V
Output Voltage	DC: 12V	DC: 12V	DC: 12V	DC: 12V
Current	5A	8.4A	12.5A	16.7A
Material	Metal	Metal	Metal	Metal
IP Rating	IP67	IP67	IP67	IP67
Dimension	158x52x32mm	220x52x32mm	233x65x32mm	244x80x32mm



Strip Power Supplies Premium
Plastic Case 24V Output




3 Years
Warranty

DC:24V

IP20

SKU: 6241 24W - 24V
SKU: 6242 36W - 24V
SKU: 6243 60W - 24V

Watts	24W	36W	60W
Input Voltage	100-240V	100-240V	100-240V
Output Voltage	DC: 24V	DC: 24V	DC: 24V
Current	1A	1.5A	2.5A
Material	Plastic	Plastic	Plastic
IP Rating	IP20	IP20	IP20
Dimension	120x42x28mm	140x48x30mm	155x53x30mm



Strip Power Supplies Premium
Waterproof 24V Output





3 Years
Warranty

DC:24V

IP67

SKU: 6261 60W - 24V
SKU: 6262 100W - 24V
SKU: 6263 150W - 24V
SKU: 6264 200W - 24V

Watts	60W	100W	150W	200W
Input Voltage	100-240V	100-240V	176-265V	176-265V
Output Voltage	DC: 24V	DC: 24V	DC: 24V	DC: 24V
Current	2.5A	4.2A	6.25A	8.35A
Material	Metal	Metal	Metal	Metal
IP Rating	IP67	IP67	IP67	IP67
Dimension	158x52x32mm	220x52x32mm	230x65x32mm	244x80x32mm





 Strip Power Supplies
Plastic 12V Output



SKU: 6120	18W - 12V
SKU: 6101	24W - 12V
SKU: 6102	36W - 12V
SKU: 6103	60W - 12V
SKU: 6119	80W - 12V

18W


Product Code	AC18-A1	Current	1,5A
Watts	18W	Material	Plastic
Input Voltage	220-240V	IP Rating	IP20
Output Voltage	DC: 12V	Dimension	85x50x34mm

**24W**


Product Code	AC24-A1	Current	2A
Watts	24W	Material	Plastic
Input Voltage	220-240V	IP Rating	IP20
Output Voltage	DC: 12V	Dimension	90x50x31mm

**36W**


Product Code	AC36-A1	Current	3A
Watts	36W	Material	Plastic
Input Voltage	220-240V	IP Rating	IP20
Output Voltage	DC: 12V	Dimension	124x58x32mm

**60W**

Product Code	AC60-A1	Current	5A
Watts	60W	Material	Plastic
Input Voltage	220-240V	IP Rating	IP20
Output Voltage	DC: 12V	Dimension	124x58x32mm

**80W**

Product Code	AC80-A1	Current	6.5A
Watts	80W	Material	Plastic
Input Voltage	220-240V	IP Rating	IP20
Output Voltage	DC: 12V	Dimension	136x64x40mm




Strip Power Supplies

Waterproof Metal 12V Output


SKU: 6110	30W - 12V
SKU: 6111	60W - 12V
NEW SKU: 6113	100W - 12V
SKU: 6112	150W - 12V

30W


Product Code	AC30-A7	Current	2.5A
Watts	30W	Material	Aluminium
Input Voltage	220V	IP Rating	IP67
Output Voltage	DC: 12V	Dimension	221x30x34mm

**60W**


Product Code	AC60-A7	Current	5A
Watts	60W	Material	Aluminium
Input Voltage	220V	IP Rating	IP67
Output Voltage	DC: 12V	Dimension	174x67x43mm

**100W**

Product Code	AC100-A7	Current	8.3A
Watts	100W	Material	Aluminium
Input Voltage	220V	IP Rating	IP67
Output Voltage	DC: 12V	Dimension	195x45x35mm

**150W**

Product Code	AC150-A7	Current	12.5A
Watts	150W	Material	Aluminium
Input Voltage	220V	IP Rating	IP67
Output Voltage	DC: 12V	Dimension	235x50x85mm






Strip Power Supplies
Metal 12V Output



- SKU: 6104 24W - 12V
- SKU: 6121 36W - 12V
- SKU: 6105 60W - 12V
- SKU: 6109 100W - 12V
- SKU: 6106 120W - 12V

Watts	24W	36W	60W	100W	120W
Input Voltage	220V	220V	220V	220V	220V
Output Voltage	DC: 12V	DC: 12V	DC: 12V	DC: 12V	DC: 12V
Current	2A	3A	5A	8.3A	10A
Material	Metal	Metal	Metal	Metal	Metal
IP Rating	IP20	IP20	IP20	IP20	IP20
Dimension	85x57x34mm	85x57x34mm	115x80x50mm	165x105x50mm	165x105x65mm



Strip Power Supplies
Metal 12V Output



- SKU: 6114 150W - 12V
- SKU: 6117 250W - 12V
- SKU: 6108 360W - 12V
- SKU: 6124 500W - 12V

Watts	150W	250W	360W	500W
Input Voltage	220V	220V	220V	220V
Output Voltage	DC: 12V	DC: 12V	DC: 12V	DC: 12V
Current	12.5A	20A	30A	41.5A
Material	Metal	Metal	Metal	Metal
IP Rating	IP20	IP20	IP20	IP20
Dimension	205x100x50mm	200x115x55mm	220x115x55mm	220x115x55mm




Strip Power Supplies
Metal 24V Output



- SKU: 6154 60W - 24V
- SKU: 6151 100W - 24V
- SKU: 6155 150W - 24V
- SKU: 6152 250W - 24V
- SKU: 6153 360W - 24V


60W

Product Code	AC60-A4	Current	2.5A
Watts	60W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 24V	Dimension	165x100x45mm




100W

Product Code	AC100-A4	Current	4.2A
Watts	100W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 24V	Dimension	210x100x45mm




150W

Product Code	AC150-A4	Current	6.25A
Watts	150W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 24V	Dimension	205x105x50mm




250W

Product Code	AC250-A4	Current	10.5A
Watts	250W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 24V	Dimension	200x110x50mm



360W

Product Code	AC360-A4	Current	15A
Watts	360W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 24V	Dimension	220x115x55mm





Strip Power Supplies

SLIM - Metal 12V Output

Slim Line



DC12V




IP20


SKU: 6131	60W - 12V
SKU: 6132	100W - 12V
SKU: 6133	150W - 12V
SKU: 6134	250W - 12V
SKU: 6135	360W - 12V

60W


Product Code	AC60-A3	Current	5A
Watts	60W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 12V	Dimension	170x45x38mm

**100W**

Product Code	AC100-A3	Current	8.5A
Watts	100W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 12V	Dimension	190x48x38mm

**150W**


Product Code	AC150-A3	Current	12.5A
Watts	150W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 12V	Dimension	207x63x49mm

**250W**

Product Code	AC250-A3	Current	20A
Watts	250W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 12V	Dimension	230x75x45mm




With FAN

**360W**

Product Code	AC360-A3	Current	30A
Watts	360W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 12V	Dimension	230x75x45mm



With FAN



Strip Power Supplies

SLIM - Metal 24V Output

Slim Line



DC:24V




IP20


SKU: 6161	60W - 24V
SKU: 6162	100W - 24V
SKU: 6163	150W - 24V
SKU: 6164	250W - 24V
SKU: 6165	360W - 24V

60W


Product Code	AC60-A4	Current	2.5A
Watts	60W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 24V	Dimension	170x45x40mm

**100W**

Product Code	AC100-A4	Current	4.2A
Watts	100W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 24V	Dimension	195x40x40mm

**150W**


Product Code	AC150-A4	Current	6.25A
Watts	150W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 24V	Dimension	205x65x45mm

**250W**

Product Code	AC250-A4	Current	10.5A
Watts	250W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 24V	Dimension	230x75x45mm




With FAN


**360W**

Product Code	AC360-A4	Current	15A
Watts	360W	Material	Metal
Input Voltage	220V	IP Rating	IP20
Output Voltage	DC: 24V	Dimension	230x75x45mm



With FAN





LED strips with all its power and might cannot be fully deployed without the appropriate diverse controllers. Touch sensors, Wi-Fi, smart home or any other popular type are available to diversify modern design and layout.

Features:

- Discreet and contemporary patterns.
- Small giants, an absolute must for any sophisticated lighting architecture
- Plug and play concept

Application:

- Probably the most widely used category with infinite applications

LED CONTROLLERS


**Dimmer LED Strip
With Remote Control 8A**

SKU:	6302
Product Code	AC2-A2
Power	96W-192W
Voltage	12V / 24V
IP Rating	IP20
Dimension	80x55x30mm


**WiFi Controller
RGB / Single Color 3x4A**

SKU:	6310	6311
Product Code	AC2-A2	AC2-A2
Power	90W-288W	90W-288W
Voltage	7.5V-24V	7.5V-24V
Strip Type	RGB	Single Color
Dimension	80x55x30mm	80x55x30mm


**Remote Control LED Strip
RGB - 4 Buttons 3x4A**

SKU:	6304
Product Code	AC2-A2
Power	144W-288W
Voltage	12V / 24V
IP Rating	IP20
Dimension	105x65x20mm


**Amplifier for LED Strip
RGB - Iron Shell 3x8A**

SKU:	6326
Product Code	AC2-A2
Power	288W-576W
Voltage	12V-24V
IP Rating	IP20
Dimension	80x70x30mm


**Remote Control LED Strip
RGB - 16 Buttons 3x2A**

SKU:	6303
Product Code	AC2-A2
Power	72W
Voltage	12V
IP Rating	IP20
Dimension	50x35x20mm


**Amplifier for LED Strip
RGB+White 4x6A**

SKU:	6328
Product Code	AC2-A2
Power	288W-576W
Voltage	12V-24V
IP Rating	IP20
Dimension	65x55x20mm


**Remote Control LED Strip
RGB - 44 Buttons**

SKU:	6306	6307
Product Code	AC2-A2	AC2-A2
Power	72W	144W
Voltage	12V	12V
IP Rating	IP20	IP20
Dimension	50x35x20mm	50x35x20mm


**Amplifier for LED Strip
RGB 3x4A**

SKU:	6305
Product Code	AC2-A2
Power	144W-288W
Voltage	12V-24V
IP Rating	IP20
Dimension	80x55x20mm




**Remote Control LED Strip
RGB Touch White/Black 3x6A**

 DC:12V/24V
 IP20

SKU:	6314	6315
Product Code	AC2-A2	AC2-A2
Power	216W-432W	216W-432W
Voltage	12V / 24V	12V / 24V
Body Color	White	Black
Dimension	95x50x30mm	95x50x30mm


**Sensor Dimmer
Wall Mounted 10A**

IP20

SKU:	6318
Product Code	AC2-A2
Power	120W-240W
Voltage	12V / 24V
Body Color	Black
Dimension	85x85x40mm


**Remote Control LED Strip
RGBW Touch 4x6A**

 DC:12V/24V
 IP20

SKU:	6329
Product Code	AC2-A2
Power	288W-576W
Voltage	12V / 24V
IP Rating	IP20
Dimension	80x45x15mm


**Sensor Dimmer
Wall Mounted 10A**

IP20

SKU:	6320
Product Code	AC2-A2
Power	120W-240W
Voltage	12V / 24V
Body Color	White
Dimension	85x85x40mm


**Music LED Controller
With Remote Control 3x4A**

 DC:12V/24V
 IP20

SKU:	6312
Product Code	AC2-A2
Power	144W-288W
Voltage	12V-24V
IP Rating	IP20
Dimension	170x85x23mm


**Sensor Dimmer
Wall Mounted RGB 3x4A**

IP20

SKU:	6317
Product Code	AC2-A2
Power	144W-288W
Voltage	12V-24V
IP Rating	IP20
Dimension	85x85x40mm


**DMX512 Decoder
3x4A**

 DC:12V/24V
 IP20

SKU:	6308
Product Code	AC2-A2
Power	144W-288W
Voltage	12V-24V
IP Rating	IP20
Dimension	160x60x42mm


**Sensor Dimmer
Wall Mounted RGB 3x4A**

IP20

SKU:	6319
Product Code	AC2-A2
Power	144W-288W
Voltage	12V-24V
IP Rating	IP20
Dimension	85x85x40mm


**LED Remote Control Set
Single Color RF 2.4G 3CH 3x4A V3**
**LED Remote**

Output signal	RF 2.4GHz
Working voltage	3VDC(CR2032)
Standby time	12 months
Remote distance	30m
Dimension	107x58.5x9mm

LED Receiver

Input voltage	12/24VDC
Output power	144W/288W
Output current	3CH,4A/CH
IP Rating	IP20
Dimension	97x33x18mm

SKU: 6348 *Professional series*
**LED Single Color Remote Control
Touch - 1 Zone RF 2.4GHZ**

- * Match with OPTONICA Professional LED Controllers.
- * Ultra sensitive color adjustment touch slide.
- * Each remote can match one or more receivers.
- * Operate with LED indicator light.
- * Magnet on the back which can be easily stuck on any metal surfaces
- * CR2032 battery powered.

SKU: 6359 *Professional series*

IP20



Dimmable



Battery


**LED Remote Control Set
RGB - RF 2.4G 3CH 3x4A V3**
**LED Remote**

Output signal	RF 2.4GHz
Working voltage	3VDC(CR2032)
Standby time	12 months
Remote distance	30m
Dimension	107x58.5x9mm

LED Receiver

Input voltage	12/24VDC
Output power	144W/288W
Output current	3CH,4A/CH
IP Rating	IP20
Dimension	97x33x18mm

SKU: 6349 *Professional series*
**LED RGB Remote Control
Touch - 1 Zone RF 2.4GHZ**

- * Match with OPTONICA Professional LED Controllers.
- * Ultra sensitive color adjustment touch slide.
- * Each remote can match one or more receivers.
- * Operate with LED indicator light.
- * Magnet on the back which can be easily stuck on any metal surfaces
- * CR2032 battery powered.

SKU: 6360 *Professional series*

IP20



Dimmable



Battery


**RGB+CCT LED Strip Controller Kit
5 channels constant voltage/Step-less dimming**


IP20

- 5 Channels constant voltage output for RGB+ CCT light
- Ultra sensitive color adjustment touch wheel
- Smooth dimming and switch without any flickering
- Built in 10 dynamic mode, include jump or gradual change style
- Independent dimming function of each R, G, B channel to achieve millions of colors
- Auto-transmitting function: Controller automatically transmit signal to another controller with 30m control distance
- Synchronize on multiple number of controllers
- Light on/off fade time 3s selectable

SKU: 6387 *Professional series*
**LED RGB + CCT Remote Control
Touch - 4 Zone RF 2.4GHZ**

- * Match with OPTONICA Professional LED Controllers.
- * Ultra sensitive color adjustment touch wheel.
- * Each remote can match one or more receivers.
- * Operate with LED indicator light.
- * AAx2 battery powered.
- * Dimension 122x53x17.5mm

SKU: 6368 *Professional series*

IP20



Dimmable



Battery


**Bluetooth & RF 2CH LED Controller
2 Channels/Push-Dim/Wireless control**


IP20

- Remote control or connected with external push switch to achieve on/off and dimming function
- Ultra sensitive brightness adjustment touch slide
- Smooth dimming and switch without any flickering
- Auto-transmitting function: Controller automatically transmit signal to another controller with 30m control distance
- Synchronize on multiple number of controllers
- Light on/off fade time 3s selectable
- Magnet on the back which can be easily stuck on back holder or any metal surfaces

SKU: 6386 *Professional series*
**LED CCT Remote Control
Touch - 4 Zone RF 2.4GHZ**

- * Match with OPTONICA Professional LED Controllers.
- * Ultra sensitive color adjustment touch wheel.
- * Each remote can match one or more receivers.
- * Operate with LED indicator light.
- * AAx2 battery powered.
- * Dimension 122x53x17.5mm

SKU: 6350 *Professional series*

IP20



Dimmable



Battery


Wall Mounted Touch Panel
4 Zone/Color wheel/AC input/DMX 512 signal


Input Voltage	12-36VDC	Output Current	2CH,5A/CH
Input Current	10.5A	Output Power	2x(60-180)W
Output Voltage	2X(12-36)VDC	Output Type	Constant Voltage

- Used for control single color or color temperature LED strip.
- Tuya APP cloud control, support on/off, color temperature and brightness adjust, delay turn on/off light,
- Each controller can also work as Bluetooth-RF converter, then use Tuya APP to control one or more RF LED controller or RF LED dimming driver synchronously.

 SKU: 6376 Professional series

Wall Mounted Touch Panel
4 Zone/Color wheel/AC input/DMX 512 signal


Input Voltage	12-24VDC	Output Power	2x(60-180)W
Input Current	10.5A	Output Type	Constant Voltage
Output Voltage	2X(12-36)VDC		

- Used for control single color or color temperature LED strip.
- Tuya APP cloud control, support on/off, color temperature and brightness adjust, delay turn on/off light,
- Each controller can also work as Bluetooth-RF converter, then use Tuya APP to control one or more RF LED controller or RF LED dimming driver synchronously.

 SKU: 6377 Professional series

LED Remote Control
Single Color Touch - 2.4GHZ


- Touch panel 4 zone 1 color RF remote.
- Each zone can remote control multiple receivers, LED controller, dimming driver or smart lamp.
- Ultra sensitive high strength glass touch panel with touch color slide in the middle.
- Smooth and accurate adjustment by touching the slide.
- Touch keys with chord tones and LED indicator.
- Free installation, no wiring, removable.
- AAA x 2 battery powered.


 SKU: 6375 Professional series

LED Remote Control
RGB/RGBW Touch - 2.4GHZ


- Touch panel 4 zone 1 color RF remote.
- Each zone can remote control multiple receivers, LED controller, dimming driver or smart lamp.
- Ultra sensitive high strength glass touch panel with touch color slide in the middle.
- Smooth and accurate adjustment by touching the slide.
- Touch keys with chord tones and LED indicator.
- Free installation, no wiring, removable.
- AAA x 2 battery powered.


 SKU: 6374 Professional series

Ultra thin Touch Wheel RF Remote Controller
4 zone RGB+CCT/Touch color wheel


- Apply to RGB+CCT LED controller.
- Ultra sensitive color a adjustment touch wheel.
- Each remote can match one or more receiver.
- CR2032 battery powered.
- Operate with LED indicator light.

 SKU: 6381 Professional series

Desk Mount RF Remote Controller
Rotary dimming/CR2032 battery


Output signal	RF(2.4GHz)	Standby current	<10μA
Working voltage	3VDC(CR2032)	Standby time	1 year
Working current	<5mA	Remote distance	30m

- Apply to RGB LED controller.
- Rotate knob to change RGB color, color temperature or brightness, support long press or twice click operation.
- Each remote can match one or more receiver.
- CR2032 battery powered.
- Desk mount, removeable anywhere easily.

 SKU: 6379 Professional series

RF Signal Repeater
AC or DC input /Wall junction box mounting


Input Voltage	12-36VDC ; 100-240VAC
Input/Output	RF 2.4GHz
RF Control Distance	30m

- Apply for wireless signal extension, greatly ensures RF communication stability and wide controlling area.
- Powered by AC100-240V or DC12-24V.
- Compatibility with RF 2.4G remote control.
- Easy to be placed in standard wall junction box.

 SKU: 6382 Professional series

WiFi & RF AC Triac Dimmer
Voice control/RF dimming/Push Dim


Input Voltage	AC100-240V	Output Current	MAX 1.5A
Output Voltage	AC100-240V	Output Power	150-360W

- WiFi + RF + Push AC phase-cut dimmer, 1 channel output.
- Voice control, support amazon ECHO and TmallGenie smart speaker.
- 256 levels 0-100% dimming smoothly without any flash.
- Compatibility with RF 2.4G single zone or multiple zone dimming remote control.
- Easy to be placed in standard wall junction box behind a push switch.
- Over-heat / Over-load protection, recover automatically.

 SKU: 6388 Professional series


Bluetooth & RF 2CH LED Controller
2 Channels/Push-Dim/Wireless control


Input Voltage	12-36VDC	Output Current	2CH,5A/CH
Input Current	10.5A	Output Power	2x(60-180)W
Output Voltage	2X(12-36)VDC	Output Type	Constant Voltage

- Used for control single color or color temperature LED strip.
- Tuya APP cloud control, support on/off, color temperature and brightness adjust, delay turn on/off light.
- Each controller can also work as Bluetooth-RF converter, then use Tuya APP to control one or more RF LED controller or RF LED dimming driver synchronously.

SKU: 6384 *Professional series*
WiFi & RF 5 in1 LED Controller
Tuya APP cloud control/Voice control/5 Channels


Input Voltage	12-24VDC	Output Current	5CH,3A/CH
Input Current	15.5A	Output Power	5x(36-72)W
Output Voltage	5X(12-24)VDC	Output Type	Constant Voltage

- 5 in 1 function, used for control RGB, RGBW, RGB+CCT, color temperature or single color LED strip.
- Voice control, support amazon ECHO and TmallGenie smart speaker.
- Match with RF 2.4G remote control optional.
- Light on/off fade time 3s selectable.

SKU: 6383 *Professional series*
Constant Voltage LED Waterproof Controller
4 Channels/Wireless remote control/Synchronize


Input Voltage	12-36VDC	Output Current	4CH,5A/CH
Input Current	20.5A	Output Power	4x(60-180)W
Output Voltage	4X(12-36)VDC	Output Type	Constant Voltage

- When using with RGB/RGBW light, built in 10 dynamic mode, include jump or gradual change style.
- Auto-transmitting function: Controller automatically transmit signal to another controller with 30m control distance.
- Synchronize on multiple number of controllers.
- Fade in and out effect selectable.

SKU: 6380 *Professional series*
Constant Voltage Waterproof Power Repeater
4 Channel/PWM signal input


Input Voltage	12-36VDC	Output Current	4CH,5A/CH
Input Current	20.5A	Output Power	4x(60-180)W
Output Voltage	4X(12-36)VDC	Output Type	Constant Voltage

- Waterproof 12-36V constant voltage power repeater with IP67 rating, suitable for outdoor and damp environment.
- 4 channel, 5A per channel.
- To receive PWM signal control.
- Power repeater in series or in parallel to expand output unlimitedly.
- Apply to single color, dual color, RGB or RGBW constant voltage LED strip or module.

SKU: 6395 *Professional series*
6 Channel DMX Sliding Fader Console
6 Sliding Faders / Real DMX Value LED Screen


Ideal Cost Efficient 6 Channel Mini DMX Fader Console

- Easy Usage
- Suitable for permanent installations by using available brackets
- Ideal for Sample Testing and Trouble-Shooting on-site or workshops
- Powered by 3 x AAA Batteries or external 5-12V Power-Supply
- 3 Digit LED Screen 0-100% or DMX000-DMX255 (Settings by internal DIP-Switch)
- 6 Channel Mode or 5 Channel & Master Mode (Settings by internal DIP-Switch)

SKU: 6392 *Professional series*
Constant Voltage DMX512 & RDM Decoder
Linear or logarithmic dimming/Numeric display


Comply with the DMX512 standard protocols.

- Digital numeric display, set DMX decode start address by buttons.
- RDM function can realize intercommunication between DMX decoder address can be set by DMX master console.
- 1/2/4 DMX channel output selectable.
- 16bit (65536 levels) /8bit (256 levels) grey level selectable.
- Stand-alone RGB/RGBW mode and 4 channel dimmer mode selectable, which be controlled by buttons with built-in programs, instead of DMX signal.

SKU: 6390 *Professional series*
4 Ways DMX Signal Splitter
DMX512-A compatible


- One DMX512 signal input, repeat four DMX512 signal output, each allowing for 32 DMX devices to be connected.
- Dedicated to amplify, distribute and insulate the signal that comes from the lighting system equipment when it is connected to the bus of DMX512(or RS-485).
- Input isolated from outputs to 500VAC, 1000VDC.
- Outputs are isolated from each other to 500VAC, 1000VDC.
- Input and outputs are ture RS-485 rated, and no microprocessors are used for maximum reliability.

SKU: 6391 *Professional series*
Constant Voltage Power Repeater
5 Channel/PWM signal input/Constant voltage


- 12-24V constant voltage power repeater.
- 5 channel, 5A per channel.
- To receive PWM signal control.
- Power repeater in series or in parallel to expand output unlimitedly.
- Apply to RGB+CCT constant voltage LED strip or module.

SKU: 6396 *Professional series*


Constant Voltage Power Repeater
1 Channel/PWM signal input


IP20

Input Voltage	12-24VDC	Output Current	15A
Input Current	15.5A	Output Power	180-360W
Output Voltage	12-36VDC	Output Type	Constant Voltage

- 12-24V constant voltage power repeater.
- one channel, 15A.
- To receive PWM signal control.
- Power repeater in series or in parallel to expand output unlimitedly.
- Apply to single color constant voltage LED strip or module.

SKU: 6393 Professional series
12-60V Constant Voltage Power Repeater
4 Channel/12-60V/PWM signal input


IP20

Input Voltage	12-60VDC	Output Current	4CH,5A/CH
Input Current	20A	Output Power	4x(60-300)W
Output Voltage	4X(12-60)VDC	Output Type	Constant Voltage

- 12-60V constant voltage power repeater.
- 3/4 channel, 5A max. per channel.
- To receive PWM signal control.
- Power repeater in series or in parallel to expand output unlimitedly.
- Apply to single color, dual color, RGB or RGBW constant voltage LED strip or module.

SKU: 6394 Professional series
Dimming High Voltage LED Strip Controller
3 Channels/Step-less dimming/Wireless control


IP20

Input Voltage	110-240VAC	Output Current	3CH,1A/CH
Input Current	3.2A	Output Power	3x(110-240)W
Output Voltage	3X(110-240)VDC		

- 3 channel high voltage LED strip RF 2.4G controller
- Match with RF 2.4G single zone or multiple zone single color, dual color and RGB/RGBW remote control.
- One RF controller accept up to 10 remote control.
- When using with RGB light, built in 10 dynamic mode, include jump or gradual change style.

SKU: 6397 Professional series
PIR Sensor Stair Light Controller
PIR sensor/Daylight Sensor/Max 32 step


IP20

Input Voltage	5-24VDC	Output Current	32CH,1A/CH
Output Voltage	32 x (5-24)VDC	Output Power	32 x (5-24)W
Output Type	Constant Voltage+SPI(TTL)		

- Multiple function PIR sensor stair light controller with daylight sensor.
- 32 channels constant voltage output drive low voltage LED strip, Max. 1A
- Built-in multiple color mode, speed and brightness 1-8 grade adjustable.
- Push switch can also be as induction signal input.
- With fast self-testing function.
- Any damaged LED channel in 32 channels can be set disable.

SKU: 6385 Professional series
RGB LED Mini Controller without remote
3 channel constant voltage/Max 4.5A output


IP20

Input Voltage	12-24VDC	Output Current	3CH,1.5A/CH
Output Voltage	12-24VDC	Output Type	Constant Voltage

- 3 channel constant voltage RGB LED mini controller.
- 3 key operation with on/off, mode and color adjustment.
- 1.5A per channel, output connect with 5 meters RGB LED strip.
- 256 levels 0-100% dimming smoothly without any flash.
- Built in 10 dynamic mode, include jump or gradual change style.

SKU: 6378 Professional series
DMX512 /0-10V to Triac Dimmer
RDM/Stand-alone function/Numeric display/


IP20

Input Voltage	100-240VAC	Output Current	1CH,6A/CH
Output Voltage	100-240VAC	Output Power	600-1440)W

- AC phase-cut mosfet dimmer with DMX512 function, one channel output.
- Comply with the DMX512 standard protocols.
- Digital numeric display, set DMX decode start address by buttons.
- Reverse-phase dimming or forward-phase dimming selectable.
- Minimum brightness set from 1% to 40%.
- Stand-alone dynamic mode and dimmer mode selectable, which be controlled by buttons with built-in programs, instead of DMX signal.

SKU: 6389 Professional series
3CH High voltage DMX512 Decoder
RDM/Stand-alone function/Numeric display/


IP20

Input Voltage	100-240VAC	Output Current	3CH,1.5A/CH
Output Voltage	100-240VAC	Output Power	3x(165-360)W

- Comply with the DMX512 standard protocols.
- Digital numeric display, set DMX decode start address by buttons.
- RDM function can realize intercommunication between DMX master and decoder
- 1/3 DMX channel output selectable.
- PWM frequency 1000/2000/4000/8000Hz selectable.
- Logarithmic or linear dimming curve selectable.
- Match with RF 2.4G single zone or multiple zone RGB remote control optional.

SKU: 6330 Professional series
NEW




Wall mounted holder for 6345

SKU: 6347



LED RGB/RGBW Remote Control

4 Zone RF 2.4GHZ*Professional series*

- * Match with OPTONICA Professional LED Controllers.
- * Ultra sensitive color adjustment touch wheel.
- * Each remote can match one or more receivers.
- * Operate with LED indicator light.
- * AAAx2 battery powered.
- * Dimension 122x53x17.5mm

SKU: 6345



IP20



Dimmable



Battery



Remote Holder for all remotes

SKU: 6334



LED RGB/RGBW Remote Control

4 Zone RF 2.4GHZ*Professional series*

- * Match with OPTONICA Professional LED Controllers.
- * Ultra sensitive color adjustment touch wheel.
- * Each remote can match one or more receivers.
- * Slim and light
- * CR2032 battery powered.
- * Dimension 107x58.5x9mm

SKU: 6335



IP20



Dimmable



Battery



Wall mounted holder for 6341

SKU: 6346



LED Remote Control

4 Zone Single Color RF 2.4GHZ*Professional series*

- * Match with OPTONICA Professional LED Controllers.
- * Each remote can match one or more receivers.
- * Slim and light
- * IP20
- * CR2032 battery powered.
- * Dimension 135x40x11mm

SKU: 6341



IP20



Dimmable



Battery



Wall mounted holder for 6340

SKU: 6346



LED Remote Control

1 Zone CCT RF 2.4GHZ*Professional series*

- * Match with OPTONICA Professional LED Controllers.
- * Each remote can match one or more receivers.
- * Slim and light.
- * IP20
- * CR2032 battery powered.
- * Dimension 107x58.5x9mm

SKU: 6340



IP20



Dimmable



Battery

LED Controller

3 Channel x 4A*Professional series*

IP20



SKU:	6353	Output Voltage	3X(12-24)VDC
Product Code	AC2-A3	Output Current	3CH,4A/CH
Input Voltage	12-24VDC	Output Power	144/288W
Input Current	12.5A	Output Type	Constant Voltage
Input Signal	RF2.4Ghz	Dimension	96x33x17 mm

- * Match with OPTONICA Professional Series Remote Controls.
- * One RF controller accept up to 10 remote control.
- * Build in 10 dynamic mode, include jump or gradual change style.
- * Auto-transmitting function: Controller automatically transmit signal of another controller with 30m control distance.
- *Synchronize on multiple number of controllers.

LED Controller

4 Channel x 5A*Professional series*

IP20



SKU:	6342	Output Voltage	4x(12-36)VDC
Product Code	AC2-A3	Output Current	4CH,5A/CH
Input Voltage	12-36VDC	Output Power	4x(60-180)W
Input Current	20.5A	Output Type	Constant Voltage
Input Signal	RF2.4Ghz+Push	Dimension	175x45x27 mm

- * Match with OPTONICA Professional Series Remote Controls.
- * One RF controller accept up to 10 remote control.
- * Build in 10 dynamic mode, include jump or gradual change style.
- * Auto-transmitting function: Controller automatically transmit signal of another controller with 30m control distance.
- *Synchronize on multiple number of controllers.
- *Connect with external push switch to achieve on/off and dimming function.

LED Controller

4 Channel x 300mA Constant Current*Professional series*

IP20



SKU:	6343	Output Voltage	4x(12-48)VDC
Product Code	AC2-A3	Output Current	4CH,300mA/CH
Input Voltage	12-48VDC	Output Power	4x(3.6-14.4)W
Input Current	1.5A	Output Type	Constant Current
Input Signal	RF2.4Ghz+Push	Dimension	175x45x27 mm

- * Match with OPTONICA Professional Series Remote Controls.
- * One RF controller accept up to 10 remote control.
- * Build in 10 dynamic mode, include jump or gradual change style.
- * Auto-transmitting function: Controller automatically transmit signal of another controller with 30m control distance.
- *Synchronize on multiple number of controllers.
- *Connect with external push switch to achieve on/off and dimming function.


**Smart Wifi-BLE Music Controller
IR 44 Keys RGB**

Input Voltage DC12-24V
 Output 3 Channels
 Output Current 2A (each channel)
 Output Power 12V-72W ; 24V-144W
 Dimension 70x30x15 mm

* Support remote/ local control through 2G / 3G /4G / Wi-Fi networks.

SKU: 6336



IP20



Dimmable



Battery


**Smart Wifi-BLE Controller
IR 24 Keys RGCCT**

Input Voltage DC12-24V
 Output 5 Channels
 Output Current 1A (each channel)
 Output Power 12V-60W ; 24V-120W
 Dimension 70x30x15 mm

* Support remote/ local control through 2G / 3G /4G / Wi-Fi networks.

SKU: 6337



IP20



Dimmable



Battery


**Smart Wifi-BLE Controller
IR 14 Keys CCT**

Input Voltage DC12-24V
 Output 2 Channels
 Output Current 2A (each channel)
 Output Power 12V-48W ; 24V-96W
 Dimension 70x30x15 mm

* Support remote/ local control through 2G / 3G /4G / Wi-Fi networks.

SKU: 6338



IP20



Dimmable



Battery


**LED Controller
IR 40 Keys RGBW**

Input Voltage DC12-24V
 Output 4 Channels
 Output Current 2A (each channel)
 Output Power 12V-96W ; 24V-192W
 Dimension 70x30x15 mm

* Support remote/ local control through 2G / 3G /4G / Wi-Fi networks.

SKU: 6339



IP20



Dimmable



Battery


**LED Controller
1 Channel x 8A**

Professional series

SKU: 6321
 Product Code AC2-A3
 Input Voltage 12-24VDC
 Input Current 8A
 Output Voltage 1X(12-24)VDC
 Output Current 8A/CH
 Output Power 96/384W
 Output Type Constant Voltage
 Dimension 97x33x18 mm

* Match with OPTONICA Professional Series Remote Controls.
 * Fade-in Fade-out LED dimmer with smooth fading effect for soft start and stop
 * The fading speed can be set via knob potentiometer, 1S, 3S, 5S, 10S, 20S selectable.
 * Connect with self-resetting metal button or push switch to achieve on/off and 0-100% dimming function.
 * Push input can accept either positive or negative trigger.



IP20


**LED Controller
1 Channel x 8A**

Professional series

SKU: 6322
 Product Code AC2-A3
 Input Voltage 5-36VDC
 Input Current 8.5A
 Output Voltage 1X(5-36)VDC
 Output Current 1CH,8A
 Output Power 40W/96W/192W/288W
 Output Type Constant Voltage
 Dimension 97x33x18 mm

* 4096 levels 0-100% dimming smoothly without any fash.
 * One RF controller accept up to 10 remote control.
 * Match with RF 2.4G single zone or multiple zone dimming remote control.
 * Auto-transmitting function: Controller automatically transmit signal to another controller with 30m control distance.
 * Synchronize on multiple number of controllers.



IP20


**LED Controller
1 Channel x 8A**

Professional series

SKU: 6352
 Input Voltage 5-25VDC
 Input Current 8A
 Input Signal Tuya App + RF 2.4Ghz
 Output Signal SPI(TTL)x2
 Dimension 120x43x27 mm

* Multi-pixel RGB/RGBW LED strip controller with SPI signal output, Tuya APP cloud control.
 * Voice control, support for Amazon ECHO, Google, Tmall Genie and Xiaodu smart speakers.
 * Compatible with 45 kinds of RGB or RGBW LED strips.
 * Rich dynamic effects: 44 default and 10+ custom dynamic scenarios, 16 variations.
 * Match with RF 2.4G RGB remote control.



IP20

DMX512 & RDM Decoder
4 Channel x 5A

Professional series



IP20



SKU:	6364	Output Voltage	12-24VDC
Product Code	AC2-A3	Output Current	4CH,5A/CH
Input Voltage	12-24VDC	Output Power	4x(60-120)W
Input Current	20.5A	Output Type	Constant Voltage
IP Rating	IP20	Dimension	170x50x24 mm

- * Match with OPTONICA Professional Series Remote Controls.
- * Comply with the DMX512 standard protocols.
- * Digital numeric display, set DMX address by buttons.
- * RDM function can realize intercommunication between DMX master and decoder.
- * 1/2/4 DMX channel output selectable.
- * Stand-alone RGB/RGBW mode and 4 channel dimmer mode selectable.

LED Controller
5 Channel x 5A

Professional series



IP20



SKU:	6366	Output Voltage	5x(12-24)VDC
Product Code	AC2-A3	Output Current	5CH,5A/CH
Input Voltage	12-24VDC	Output Power	5x(60-120)W
Input Current	25.5A	Output Type	Constant Voltage
IP Rating	IP20	Dimension	175x45x27 mm

- * Match with OPTONICA Professional Series Remote Controls.
- * One RF controller accept up to 10 remote control.
- * Build in 10 dynamic mode, include jump or gradual change style.
- * Auto-transmitting function: Controller automatically transmit signal of another controller with 30m control distance.
- * Synchronize on multiple number of controllers.
- * Connect with external push switch to achieve on/off and dimming function.

LED Dimmer
1 Channel 12A

Professional series



IP20



SKU:	6367	Output Voltage	12-36VDC
Product Code	AC2-A3	Output Current	1CH,12A
Input Voltage	12-36VDC	Output Power	144-432W
Input Current	12.5A	Output Type	Constant Voltage
Input Signal	0/1-10V+Push	Dimension	175x45x27 mm

- * Match with OPTONICA Professional Series Remote Controls.
- * 1 channel 0/1-10V LED dimming driver with push-dim function.
- * 1 channel 0/1-10V input, 1 channel PWM constant voltage output.
- * 0~100% dimming range via logarithmic characteristic can be very comfortable for human eyes.

LED Dimmer
4 Channel x 5A

Professional series



IP20



SKU:	6369	Output Voltage	12-36VDC
Product Code	AC2-A3	Output Current	4CH,5A/CH
Input Voltage	12-36VDC	Output Power	4x(60-180)W
Input Current	20.5A	Output Type	Constant Voltage
Input Signal	0/1-10V+Push	Dimension	175x45x27 mm

- * Match with OPTONICA Professional Series Remote Controls.
- * 4 channel 0/1-10V LED dimming driver with push-dim function.
- * 4 channel 0/1-10V input, 4 channel PWM constant voltage output.
- * 0~100% dimming range via logarithmic characteristic can be very comfortable for human eyes.

DALI LED Dimmer
1 Channel 15A

Professional series



IP20



SKU:	6371	Output Voltage	12-24VDC
Product Code	AC2-A3	Output Current	1CH,15A
Input Voltage	12-24VDC	Output Power	180W/360W
Input Current	15A	Output Type	Constant Voltage
Input Signal	DALI+Push	Dimension	175x45x27 mm

- * Match with OPTONICA Professional Series Remote Controls.
- * Constant voltage DALI LED dimmer with 1 channel, 15A output.
- * DALI address will be automatically assigned by DALI master, 1 DALI address.
- * PWM digital dimming, standard DALI logarithmic dimming curve.
- * Connect with external push switch to achieve on/off and dimming function.

DALI LED Dimmer
4 Channel x 5A

Professional series



IP20



SKU:	6372	Output Voltage	12-24VDC
Product Code	AC2-A3	Output Current	4CH,5A/CH
Input Voltage	12-24VDC	Output Power	4x(60-120)W
Input Current	20.5A	Output Type	Constant Voltage
Input Signal	DALI	Dimension	175x45x27 mm

- * Match with OPTONICA Professional Series Remote Controls.
- * 4 channel constant voltage DALI LED Dimmer, 5A per channel.
- * 4 DALI address, 4 channel work separately.
- * DALI address will be automatically assigned by DALI master.
- * PWM digital dimming, standard DALI logarithmic dimming curve.

AC Triac DALI Dimmer

Professional series



IP20



SKU:	16302	Output Voltage	AC100-240V
Product Code	AC2-A3	Output Current	Max 1.5A
Input Voltage	AC100-240V	Output Power	150-360W
Dimming level	256 levels	Dimension	190x48x25 mm

- * AC phase-cut DALI dimmer, one DALI address, one channel output.
- * DALI address can be manually assigned and shown in digital display or automatically assigned by DALI master.
- * Reverse-phase dimming or forward-phase dimming selectable.
- * To dim and switch single color dimmable LED lamps, traditional incandescent and halogen lights.

LED Controller

Professional series



SKU:	6355	Output Voltage	4x(12-24)VDC
Product Code	AC2-A3	Output Current	4CH,5A/CH
Input Voltage	12-24VDC	Output Power	4x(60-120)W
Input Current	20.5A	Output Type	Constant Voltage
IP Rating	IP20	Dimension	110x64x45mm



IP20

- * Match with OPTONICA Professional Series Remote Controls.
- * Digital numeric display and easy key operation.
- * Can set as 1 channel dimmer, 4 channel, dual color, RGB or RGBW controller.
- * Logarithmic or linear dimming curve selectable.
- * Synchronize on multiple number of controllers.

AC TRIAC Dimmer

Professional series



SKU:	6365	Output Voltage	100-240VAC
Product Code	AC2-A3	Output Current	1CH,2A/CH
Input Voltage	100-240VAC	Output Power	200-480W
Input Signal	RF2.4GHz+Push	Dimming level	100 levels
IP Rating	IP20	Dimension	110x64x45 mm



IP20

- * Match with OPTONICA Professional Series Remote Controls.
- * RF+ Push AC phase-cut dimmer, 1channel output.
- * Digital numeric display, set brightness by buttons.
- * 0-100% dimming smoothly without any flash.
- * Reverse-phase dimming or forward-phase dimming selectable.
- * Minimum brightness set from 1% to 40%

Power Repeater

Professional series



SKU:	6370	Output Voltage	4x(12-24)VDC
Product Code	AC2-A3	Output Current	4CH,5A/CH
Input Voltage	12-24VDC	Output Power	4x(60-120)W
Input Current	20.5A	Output Type	Constant Voltage
IP Rating	IP20	Dimension	110x64x45 mm



IP20

- * Match with OPTONICA Professional Series Remote Controls.
- * To receive PWM signal control.
- * Power repeater in series or in parallel to expand output unlimitedly.
- * Apply to single color,dual color,RGB or RGBW constant voltage LED strip or module.
- * 3KV Optoelectronic isolation.

AC Triac RF Dimmer

RF 2.4GHz + Push

Professional series



SKU:	6363	Output Voltage	100-240VAC
Product Code	AC2-A3	Output Current	MAX 1A
Input Voltage	100-240VAC	Output Power	100-240W
Input Signal	RF2.4GHz+Push	Dimming level	256 levels
IP Rating	IP20	Dimension	56x56x26 mm



IP20

- * Match with OPTONICA Professional Series Remote Controls.
- * RF+ Push AC phase-cut dimmer, 1channel output.
- * 0-100% dimming smoothly without any flash.
- * Connect with external push switch to achieve ON/OFF and dimming function.
- * Easy to be inserted into standard 86x86mm wall box

LED Controller

3 Channel x 10A

Professional series



SKU:	6356	Output Voltage	3x(12-36)VDC
Product Code	AC2-A3	Output Current	3CH,10A/CH
Input Voltage	12-36VDC	Output Power	3x(120-360)W
Input Current	30.5A	Output Type	Constant Current
Input Signal	RF2.4GHz	Dimension	105x75x25 mm



IP20

- * Match with OPTONICA Professional Series Remote Controls.
- * One RF controller accept up to 10 remote control.
- * Build in 10 dynamic mode, include jump or gradual change style.
- * Auto-transmitting function: Controller automatically transmit signal of another controller with 30m control distance.
- * Synchronize on multiple number of controllers.

WiFi - Relay 2.4GHz

WiFi to RF Converter

Professional series



SKU:	6354	Output Control	RGB,RGBW,CT
Product Code	AC2-A3	Working Temp.	-20°C~50°C
Input Voltage	5-24VDC	Platform	iOS, Android
Wifi standard	802.11 b/g/n	Dimension	ø72x25 mm



IP20





LED 0-10V DIMMER

4 Zones - Touch glass panel

Professional series



SKU:	6398	Output Signal	0-10V (20mA)
Input Voltage	100-240V	Output Current	20mA/CH
IP Rating	IP20	Dimension	86x86x33 mm

- *Touch panel 0-10V dimmer, output 4 channel 0-10V signal
- * Output connect with 0/1-10V dimmable driver.
- * Ultra sensitive high strength glass touch panel with touch slide in the middle.
- * Compatibility with RF 2.4G dimming remote control.
- *Touch keys with LED indicator.



LED 0-10V DIMMER

1 Channel - Rotary glass panel

Professional series



SKU:	6399	Output Signal	0-10V (50mA)
Input Voltage	100-240V	Output Current	1.5A
IP Rating	IP20	Dimension	86x86x48 mm

- * Rotary glass panel 1-10V dimmer, 1 channel output.
- * Output connect with 0/1-10V dimmable driver.
- * Output 1 channel 1-10V signal, connect with 1-10V dimmable driver.
- * High voltage AC input, High voltage AC relay output.
- *Compatibility with RF 2.4G single zone or multiple zone dimming remote control.



LED AC TRIAC DIMMER

1 Channel - Rotary glass panel

Professional series



SKU:	6351	Output Power	150-360W
I/O Voltage	100-240V	Output Current	Max 1.5A
IP Rating	IP20	Dimension	86x86x48 mm

- * Rotary glass panel AC phase-cut dimmer, 1 channel output.
- * To dim and switch single color dimmable LED lamps, traditional incandescent and halogen lights.
- * 256 levels 0-100% dimming smoothly without any flash.
- * Leading edge dimming or trailing edge dimming set by dip switch.
- * Over-heat / Over-load protection, recover automatically.



LED Single Color Controller

4A*3CH

Professional series



SKU:	6357	Output Voltage	3x(12-24)VDC
Product Code	AC2-A3	Output Current	3CH,4A/CH
Input Voltage	12-24VDC	Output Power	144-288W
Input Current	12.5A	Output Type	Constant Voltage
IP Rating	IP20	Dimension	86x86x53 mm



LED RGB Controller

4A*3CH

Professional series



SKU:	6358	Output Voltage	3x(12-24)VDC
Product Code	AC2-A3	Output Current	3CH,4A/CH
Input Voltage	12-24VDC	Output Power	144-288W
Input Current	12.5A	Output Type	Constant Voltage
IP Rating	IP20	Dimension	86x86x53 mm



LED DMX Controller

4 Zones control DMX512+RF 2.4G

Professional series



SKU:	6361	Control Mode	4 Zone Control
Product Code	AC2-A3	Light Type	Single Color
Input Voltage	85-265V	Remote Distance	30m
Output Signal	DMX512+RF	Working Temp.	-20°C/+50°C
IP Rating	IP20	Dimension	86x86x36 mm



LED RGBW DMX Controller

4 Zones control DMX512+RF 2.4G

Professional series



SKU:	6362	Control Mode	4 Zone Control
Product Code	AC2-A3	Light Type	RGBW
Input Voltage	85-265V	Remote Distance	30m
Output Signal	DMX512+RF	Working Temp.	-20°C/+50°C
IP Rating	IP20	Dimension	86x86x36 mm



Highly specialized luminaires with concentrated light distribution angle intended for retail or other spot required presentation area. These adjustable fixtures can be combined with variously lengthen three phased tracks along with connectors to suit every design, including rapid solutions for trade fair halls and shopping malls.

Features:

- Three colour temperatures offered to match the needs of most commercial shelf products
- Upto 80% cost-saving use
- Quick and easy fool proof on and off installation

Application:

- Indoor use
- Any show-room, art gallery, dining rooms companions.
- Popular choice for both residential and commercial projects.



**LED Linear Suspended Light
40W Slim Linkable**


5 Years

Warranty




Linkable

Product code LN40-A3
 Watts 40W
 Input Voltage AC : 200-240V
 Flux 4000lm
 Beam Angle 120°

CRI Ra>80
 IP Rating IP20
 Dimension 1185x60x70 mm
 Body Color BLACK
 Dimmable NO

SKU: 5470 6000K
 SKU: 5380 4000K


**LED Linear L-Shape Connector
10W Slim Linkable**


5 Years

Warranty

Product code LN10-A3
 Watts 10W
 Input Voltage AC : 200-240V
 Flux 1000lm
 Beam Angle 120°

CRI Ra>80
 IP Rating IP20
 Dimension 176x176x70 mm
 Body Shape L-Shape
 Dimmable NO

White Light 6000K

SKU: 5060 Black Body
 SKU: 5061 Silver Body
 SKU: 5062 White Body

Neutral White 4000K

SKU: 5027 Black Body
 SKU: 5028 Silver Body
 SKU: 5029 White Body

**LED Linear Suspended Light
40W Slim Linkable**


5 Years

Warranty




Linkable

Product code LN40-A3
 Watts 40W
 Input Voltage AC : 200-240V
 Flux 4000lm
 Beam Angle 120°

CRI Ra>80
 IP Rating IP20
 Dimension 1185x60x70 mm
 Body Color SILVER
 Dimmable NO

SKU: 5471 6000K
 SKU: 5381 4000K


**LED Linear T-Shape Connector
15W Slim Linkable**


5 Years

Warranty

Product code LN15-A3
 Watts 15W
 Input Voltage AC : 200-240V
 Flux 1500lm
 Beam Angle 120°

CRI Ra>80
 IP Rating IP20
 Dimension 300x176x70 mm
 Body Shape T-Shape
 Dimmable NO

White Light 6000K

SKU: 5063 Black Body
 SKU: 5064 Silver Body
 SKU: 5065 White Body

Neutral White 4000K

SKU: 5030 Black Body
 SKU: 5036 Silver Body
 SKU: 5037 White Body

**LED Linear Suspended Light
40W Slim Linkable**


5 Years

Warranty




Linkable

Product code LN40-A3
 Watts 40W
 Input Voltage AC : 200-240V
 Flux 4000lm
 Beam Angle 120°

CRI Ra>80
 IP Rating IP20
 Dimension 1185x60x70 mm
 Body Color WHITE
 Dimmable NO

SKU: 5472 6000K
 SKU: 5382 4000K


**LED Linear X-Shape Connector
20W Slim Linkable**


5 Years

Warranty

Product code LN20-A3
 Watts 20W
 Input Voltage AC : 200-240V
 Flux 2000lm
 Beam Angle 120°

CRI Ra>80
 IP Rating IP20
 Dimension 300x300x70 mm
 Body Shape X-Shape
 Dimmable NO

White Light 6000K

SKU: 5066 Black Body
 SKU: 5067 Silver Body
 SKU: 5068 White Body

Neutral White 4000K

SKU: 5038 Black Body
 SKU: 5039 Silver Body
 SKU: 5040 White Body


LED Linear Suspended Light
50W UP-DOWN



Product code	LN50-A3	CRI	Ra>80
Watts	50W	IP Rating	IP20
Input Voltage	AC : 200-240V	Dimension	1185x28x68 mm
Flux	5000lm	Body Color	BLACK
Beam Angle	120°	Dimmable	NO



SKU: 5383
4000K




LED Linear Suspended Light
50W Linkable



Product code	LN50-A4	CRI	Ra>80
Watts	50W	IP Rating	IP20
Input Voltage	AC : 200-240V	Dimension	1200x35x67 mm
Flux	4500lm	Body Color	BLACK
Beam Angle	60°	Dimmable	NO



SKU: 5386
4000K




LED Linear Suspended Light
50W UP-DOWN



Product code	LN50-A3	CRI	Ra>80
Watts	50W	IP Rating	IP20
Input Voltage	AC : 200-240V	Dimension	1185x28x68 mm
Flux	5000lm	Body Color	SILVER
Beam Angle	120°	Dimmable	NO



SKU: 5384
4000K




LED Linear Suspended Light
50W Linkabe



Product code	LN50-A4	CRI	Ra>80
Watts	50W	IP Rating	IP20
Input Voltage	AC : 200-240V	Dimension	1200x35x67 mm
Flux	4500lm	Body Color	SILVER
Beam Angle	60°	Dimmable	NO



SKU: 5387
4000K




LED Linear Suspended Light
50W UP-DOWN



Product code	LN50-A3	CRI	Ra>80
Watts	50W	IP Rating	IP20
Input Voltage	AC : 200-240V	Dimension	1185x28x68 mm
Flux	5000lm	Body Color	WHITE
Beam Angle	120°	Dimmable	NO



SKU: 5385
4000K




LED Linear Suspended Light
50W Linkable



Product code	LN50-A4	CRI	Ra>80
Watts	50W	IP Rating	IP20
Input Voltage	AC : 200-240V	Dimension	1200x35x67 mm
Flux	4500lm	Body Color	WHITE
Beam Angle	60°	Dimmable	NO



SKU: 5388
4000K






NEW

LED Linear Suspended Light
40W NON-Linkable



Product code	LN50-A4	CRI	Ra>80
Watts	40W	IP Rating	IP20
Input Voltage	AC : 200-240V	Dimension	1200x57x60 mm
Flux	4400lm	Body Color	BLACK
Beam Angle	120°	Dimmable	NO

SKU: 5478
■ 4000K



3 Years
Warranty




NEW

LED Linear Suspended Light
40W NON-Linkable



Product code	LN50-A4	CRI	Ra>80
Watts	40W	IP Rating	IP20
Input Voltage	AC : 200-240V	Dimension	1200x57x60 mm
Flux	4400lm	Body Color	BLACK
Beam Angle	120°	Dimmable	NO

SKU: 5479
■ 4000K



3 Years
Warranty

Linkable Connector for Linear Lights
For SKU: 5380-5382/5027-5040



SKU: 65315

Suspension Kit for Linear Lights



SKU: 65316



LED COB Track Light


25W For 3 Phase 4 Line Tracks

3 Years
Warranty

2750
Lumens

Product code	FL25-A1	CRI	Ra>80
Watts	25W	IP Rating	IP20
Input Voltage	AC : 220-240V	Dimension	ø80x145x160mm
Flux	2750lm	Body Color	WHITE
Beam Angle	24°		

SKU: 5321 SKU: 5322 SKU: 5323
■ 5000K ■ 4000K ■ 3000K



LED COB Track Light


25W For 3 Phase 4 Line Tracks

3 Years
Warranty

2750
Lumens

Product code	FL25-A1	CRI	Ra>80
Watts	25W	IP Rating	IP20
Input Voltage	AC : 220-240V	Dimension	ø80x145x160mm
Flux	2750lm	Body Color	BLACK
Beam Angle	24°		

SKU: 5327 SKU: 5328 SKU: 5329
■ 5000K ■ 4000K ■ 3000K



LED COB Track Light


35W For 3 Phase 4 Line Tracks

3 Years
Warranty

3850
Lumens

Product code	WL35-A1	CRI	Ra>80
Watts	35W	IP Rating	IP20
Input Voltage	AC : 220-240V	Dimension	ø90x160x160mm
Flux	3850lm	Body Color	WHITE
Beam Angle	24°		

SKU: 5324 SKU: 5325 SKU: 5326
■ 5000K ■ 4000K ■ 3000K



LED COB Track Light


35W For 3 Phase 4 Line Tracks

3 Years
Warranty

3850
Lumens

Product code	WL35-A1	CRI	Ra>80
Watts	35W	IP Rating	IP20
Input Voltage	AC : 220-240V	Dimension	ø90x160x160mm
Flux	3850lm	Body Color	BLACK
Beam Angle	24°		

SKU: 5330 SKU: 5331 SKU: 5332
■ 5000K ■ 4000K ■ 3000K



NEW




LED COB Track Light
12W 1 Phase Track System



Watts 12W
Input Voltage AC : 220-240V
Flux 1200lm
Beam Angle 24°

CRI Ra>80
IP Rating IP20
Dimension ø50x130mm
Body Color BLACK

SKU: 15101 4000K
SKU: 15102 2700K



NEW




LED COB Track Light
12W 1 Phase Track System



Watts 12W
Input Voltage AC : 220-240V
Flux 1200lm
Beam Angle 24°

CRI Ra>80
IP Rating IP20
Dimension ø50x130mm
Body Color WHITE

SKU: 15103 4000K
SKU: 15104 2700K



NEW




LED Track Light CCT
20-25-30W Adjustable
For 4 Line Track System



Watts 20-25-30W
Input Voltage AC : 220-240V
Flux 2700lm
Beam Angle 24°-90°

CRI Ra>90
IP Rating IP20
Dimension ø72x210x170mm
Body Color BLACK

SKU: 15105 CCT
6000K 4000K 3000K



NEW




LED Track Light CCT
20-25-30W Adjustable
For 4 Line Track System



Watts 20-25-30W
Input Voltage AC : 220-240V
Flux 2700lm
Beam Angle 24°-90°

CRI Ra>90
IP Rating IP20
Dimension ø72x210x170mm
Body Color WHITE


SKU: 15106 CCT
6000K 4000K 3000K



Extremely Flexible
Free Flowing



LED Flexible Track (Colour Bridge)
SERIES



LED Flexible Track (Colour Bridge) DIY SET V1

SKU: 15401



2000 Lumens
LED Linear Light 40W



390 Lumens
LED Spot Light 7W - 2Pcs



Flexible Track (Black)-5m



Fixed Parts (Black)-5Pcs



MW
Meanwell Driver -75W

LED Flexible Track (Colour Bridge) DIY SET V2

SKU: 15402



390 Lumens
LED Spot Light 7W - 3Pcs



Flexible Track (Black)-5m



Fixed Parts (Black)-6Pcs



MW
Meanwell Driver -50W


LED Wall washer for Tracks

30W For 3 Phase 4 Line Tracks



Product code	LN30-A3	CRI	Ra>80
Watts	30W	IP Rating	IP20
Input Voltage	AC : 200-240V	Dimension	610x40x90 mm
Flux	2700lm	Body Color	BLACK
Beam Angle	24°	Dimmable	NO

SKU: 5389
4000K



5 Years
Warranty




LED Wall washer for Tracks

40W For 3 Phase 4 Line Tracks



Product code	LN40-A4	CRI	Ra>80
Watts	40W	IP Rating	IP20
Input Voltage	AC : 200-240V	Dimension	905x40x90 mm
Flux	3600lm	Body Color	BLACK
Beam Angle	24°	Dimmable	NO

SKU: 5390
4000K



5 Years
Warranty



ACCESSORIES FOR 3-PHASE TRACK LIGHTS



TRACK SYSTEM 3PHASES - 1M WHITE
SKU: 5007



TRACK SYSTEM 3PHASES - 1M BLACK
SKU: 5009



TRACK SYSTEM 3PHASES - 2M WHITE
SKU: 5008



TRACK SYSTEM 3PHASES - 2M BLACK
SKU: 5010



STRAIGHT CONNECTOR WHITE
SKU: 5013



MINI STRAIGHT CONNECTOR WHITE
SKU: 5011



T-CONNECTOR WHITE
SKU: 5017



END CAP WHITE
SKU: 5023



STRAIGHT CONNECTOR BLACK
SKU: 5014



MINI STRAIGHT CONNECTOR BLACK
SKU: 5012



T-CONNECTOR BLACK
SKU: 5018



END CAP BLACK
SKU: 5024

ACCESSORIES FOR TRACK LIGHTS



TRACK SYSTEM - 1M WHITE
SKU: 5153



TRACK SYSTEM - 1M BLACK
SKU: 5154



TRACK SYSTEM - 2M WHITE
SKU: 5155



TRACK SYSTEM - 2M BLACK
SKU: 5156



CONNECTOP ANGLE - WHITE
SKU: 5157



CONNECTOP LINE - BLACK
SKU: 5159



CONNECTOP ANGLE - WHITE
SKU: 5158



CONNECTOP ANGLE - BLACK
SKU: 5160



L-FEEDER WHITE
SKU: 5019



L-CONNECTOR WHITE
SKU: 5015



X-CONNECTOR WHITE
SKU: 5021



FLEXIBLE CONNECTOR WHITE
SKU: 5025



L-FEEDER BLACK
SKU: 5020



L-CONNECTOR BLACK
SKU: 5016



X-CONNECTOR BLACK
SKU: 5022



FLEXIBLE CONNECTOR BLACK
SKU: 5026

MAGNETIC TRACK SERIES


Magnetic force connects profile and modules both mechanical and electrical.



Magnetic



IP20



TRACK SYSTEM 3 PHASES R35

- SKU: 5350 BLACK BODY - 1m
- SKU: 5351 BLACK BODY - 1.5m
- SKU: 5352 BLACK BODY - 2m



ANGLE CONNECTOR
SKU: 5358



END CAP
SKU: 5353



Magnetic



TRACK SYSTEM 3 PHASES R35 Build-in

- SKU: 5360 BLACK BODY - 1m
- SKU: 5361 BLACK BODY - 1.5m
- SKU: 5362 BLACK BODY - 2m



ANGLE CONNECTOR
SKU: 5363



END CAP
SKU: 5411



Magnetic



TRACK SYSTEM 3 PHASES R35B-Build-in

- SKU: 5420 BLACK BODY - 1m
- SKU: 5421 BLACK BODY - 1.5m
- SKU: 5422 BLACK BODY - 2m



ANGLE CONNECTOR
SKU: 5423



END CAP
SKU: 5411



Magnetic



TRACK SYSTEM 3 PHASES S20

- SKU: 5364 BLACK BODY - 1m
- SKU: 5365 BLACK BODY - 1.5m
- SKU: 5366 BLACK BODY - 2m



ANGLE CONNECTOR
SKU: 5412



END CAP
SKU: 5413



Magnetic



TRACK SYSTEM 3 PHASES R20 Build-In

- SKU: 5367 BLACK BODY - 1m
- SKU: 5368 BLACK BODY - 1.5m
- SKU: 5369 BLACK BODY - 2m



ANGLE CONNECTOR
SKU: 5414



END CAP
SKU: 5415



Magnetic



TRACK SYSTEM 3 PHASES R20B-Build-in

- SKU: 5450 BLACK BODY - 1m
- SKU: 5451 BLACK BODY - 1.5m
- SKU: 5452 BLACK BODY - 2m



ANGLE CONNECTOR
SKU: 5453



END CAP
SKU: 5415



Magnetic


LED Magnetic Track Light
12W ; 20W

Product code	LN12-A4 ; LN20-A4	CRI	Ra>80
Power	12W ; 20W	IP Rating	IP20
Beam Angle	120°	Dimension 12W	300x34x50mm
Voltage	DC:48V	Dimension 20W	600x34x50mm

M35

TRACK



Magnetic



IP20

SKU: 5340 12W 30cm 3000K

SKU: 5391 12W 30cm 4000K

SKU: 5341 20W 60cm 3000K

SKU: 5392 20W 60cm 4000K


LED Magnetic Track Light
10W ; 20W

Product code	LN10-A4 ; LN20-A4	CRI	Ra>80
Power	10W ; 20W	IP Rating	IP20
Beam Angle	24°	Dimension 10W	135x34x95mm
Voltage	DC:48V	Dimension 20W	270x34x95mm



45°

M35

TRACK



Magnetic



IP20

SKU: 5347 10W 13.5cm 3000K

SKU: 5398 10W 13.5cm 4000K

SKU: 5348 20W 27cm 3000K

SKU: 5399 20W 27cm 4000K


LED Magnetic Track Light
10W ; 20W

Product code	LN10-A4 ; LN20-A4	CRI	Ra>80
Power	10W ; 20W	IP Rating	IP20
Beam Angle	24°	Dimension 10W	135x34x50mm
Voltage	DC:48V	Dimension 18W	270x34x50mm

M35

TRACK



Magnetic



IP20

SKU: 5342 10W 13.5cm 3000K

SKU: 5393 10W 13.5cm 4000K

SKU: 5343 20W 27cm 3000K

SKU: 5394 20W 27cm 4000K


LED Magnetic Track Light
7W Focusing Spot Light

Product code	LN7-A4	Beam Angle	15-60°
Watts	7W	CRI	Ra>90
Input Voltage	48V	IP Rating	IP20
Flux	560lm	Dimension	Φ60x200mm

M35

TRACK



Magnetic



IP20

SKU: 5349 Warm White 3000K

SKU: 5400 Neutral White 4000K

LED Magnetic Track Light
7W



Product code LN7-A4
Watts 7W
Input Voltage 48V
Flux 560lm
Beam Angle 15°

SKU: 5395 SKU: 5344
4000K 3000K

CRI Ra>90
IP Rating IP20
Dimension ϕ 55x105mm
Body Color Black



Power Supplies for Track Light
BUILT-IN 48V Output



SKU: 5424 100W - 48V
SKU: 5425 200W - 48V
SKU: 5426 100W - 48V
SKU: 5427 200W - 48V
SKU: 5428 280W - 48V

Watts	100W	200W	100W	200W	280W
Input Voltage	220V	220V	220V	220V	220V
Output Voltage	DC: 48V	DC: 48V	DC: 48V	DC: 48V	DC: 48V
Current	2.1A	4.2A	2.1A	4.2A	5.85A
Material	PC	PC	PC	PC	PC
IP Rating	IP20	IP20	IP20	IP20	IP20
Dimension	190x90x30mm	220x120x30mm	220x120x30mm	220x120x30mm	220x120x30mm

Magnetic Track Light	M20	M20	M35	M35	M35
	TRACK	TRACK	TRACK	TRACK	TRACK

LED Magnetic Track Light
12W



Product code LN12-A4
Watts 12W
Input Voltage 48V
Flux 960lm
Beam Angle 15°

SKU: 5396 SKU: 5345
4000K 3000K

CRI Ra>90
IP Rating IP20
Dimension ϕ 65x130mm
Body Color Black




LED Magnetic Track Light
20W



Product code LN20-A4
Watts 20W
Input Voltage 48V
Flux 1600lm
Beam Angle 15°

SKU: 5397 SKU: 5346
4000K 3000K

CRI Ra>90
IP Rating IP20
Dimension ϕ 65x130mm
Body Color Black



800
Lumens



1440
Lumens



LED Magnetic Track Light - M20
10W ; 18W

M20
TRACK
Magnetic
IP20

Product code	LN10-A4 ; LN18-A4	CRI	Ra>80
Power	10W ;18W	IP Rating	IP20
Beam Angle	120°	Dimension 10W	300x22x25mm
Voltage	DC:48V	Dimension 18W	600x22x25mm

SKU: 5417	10W 30cm	3000K
SKU: 5416	10W 30cm	4000K
SKU: 5419	18W 60cm	3000K
SKU: 5418	18W 60cm	4000K

480
Lumens



960
Lumens



LED Magnetic Track Light - M20
6W ; 12W

M20
TRACK
Magnetic
IP20

Product code	LN6-A4 ; LN12-A4	CRI	Ra>80
Power	6W ;12W	IP Rating	IP20
Beam Angle	24°	Dimension 10W	112x22x45mm
Voltage	DC:48V	Dimension 18W	220x22x45mm

SKU: 5312	6W	3000K
SKU: 5311	6W	4000K
SKU: 5314	12W	3000K
SKU: 5313	12W	4000K

LED Magnetic Track Light
12W

M20
TRACK
Magnetic
IP20



Watts	12W	CRI	Ra>90
Input Voltage	DC48V	IP Rating	IP20
Flux	960lm	Dimension	Φ65x130mm
Beam Angle	15°	Body Color	Black

SKU: 5316	Warm White	3000K
SKU: 5315	Neutral White	4000K

LED Magnetic Track Light
10W

M20
TRACK
Magnetic
IP20



Watts	10W	CRI	Ra>90
Input Voltage	DC48V	IP Rating	IP20
Flux	800lm	Dimension	Φ70x100mm
Beam Angle	15-24°	Body Color	Black

SKU: 5379	Warm White	3000K
SKU: 5378	Neutral White	4000K



Straight Joint

SKU: 5356



Joining Cable

SKU: 5357




Input Cable

SKU: 5355



Hanging Accessories

SKU: 5354



LED Magnetic Track Light 9W

720
Lumens

M20
TRACK

45°

Magnetic

IP20

Product code LN9-A4
Power 9W
Beam Angle 24°
Voltage DC:48V

CRI Ra>80
IP Rating IP20
Dimension 137x34x95mm

SKU: 5318 Warm White 3000K
SKU: 5317 Neutral White 4000K



LED Magnetic Track Light 5W

560
Lumens

M20
TRACK

Magnetic

IP20

Product code LN5-A4
Power 5W
Beam Angle 15-60°
Voltage DC:48V

CRI Ra>80
IP Rating IP20
Dimension $\phi 60 \times 200$ mm

SKU: 5320 Warm White 3000K
SKU: 5319 Neutral White 4000K



LED Magnetic Track Light 6W

480
Lumens

Magnetic

IP20

Product code LN6-A5
Watts 6W
Input Voltage DC48V
Flux 480lm
Beam Angle 90°

CRI Ra>80
IP Rating IP20
Dimension $\phi 130$ mm
Body Color Black

SKU: 5335 Neutral White 4000K
SKU: 5334 Warm White 3000K

M20
M35
TRACK



LED Magnetic Track Light 10W

800
Lumens

Magnetic

IP20

Product code LN10-A5
Watts 10W
Input Voltage DC48V
Flux 800lm
Beam Angle 90°

CRI Ra>80
IP Rating IP20
Dimension $\phi 85$ mm
Body Color Black

SKU: 5337 Neutral White 4000K
SKU: 5336 Warm White 3000K

M20
M35
TRACK



LED Magnetic Track Light 5W

400
Lumens

Magnetic

IP20

Product code LN5-A5
Watts 5W
Input Voltage DC48V
Flux 400lm
Beam Angle 50°

CRI Ra>80
IP Rating IP20
Dimension 88x75mm
Body Color Black

SKU: 5339 Neutral White 4000K
SKU: 5338 Warm White 3000K

M20
M35
TRACK



TRACK SYSTEM Three-Phase

WHITE

Length: 1.0m ; 1.5m ; 2.0m

S35

- SKU: 5241 WHITE BODY - 1m
- SKU: 5242 WHITE BODY - 1.5m
- SKU: 5243 WHITE BODY - 2m

R35 Build-in


- SKU: 5250 WHITE BODY - 1m
- SKU: 5251 WHITE BODY - 1.5m
- SKU: 5252 WHITE BODY - 2m

R35B Build-in

- SKU: 5255 WHITE BODY - 1m
- SKU: 5256 WHITE BODY - 1.5m
- SKU: 5257 WHITE BODY - 2m



END CAP - R35
SKU: 5260



END CAP - R35
SKU: 5244

Accessories:



INPUT CABLE
SKU: 5246



STRAIGHT JOINT
SKU: 5247




JOINING CABLE
SKU: 5248



COVER PLATE
SKU: 5254



S35 SURFACE CORNER
SKU: 5249



R35 SURFACE CORNER
SKU: 5253



R35-B SURFACE CORNER
SKU: 5258



R35-A Concave Angle
SKU: 5259



SLIM POWER SUPPLY 48V
100W 2.08A



Watts	100W	Current	2.08A
Input Voltage	220V	Material	Metal
Output Voltage	DC: 48V	IP Rating	IP20

SKU: 5216 WHITE BODY



SLIM POWER SUPPLY 48V
200W 4.16A



Watts	200W	Current	4.16A
Input Voltage	220V	Material	Metal
Output Voltage	DC: 48V	IP Rating	IP20

SKU: 5217 WHITE BODY



**LED Magnetic Track Light
12W**


Watts 12W
 Input Voltage DC48V
 Flux 960lm
 Beam Angle 120°

SKU: 5265 SKU: 5261
 ■ 4000K ■ 3000K

CRI Ra>90
 IP Rating IP20
 Dimension 300x34x50.5mm
 Body Color White


**LED Magnetic Track Light
12W**


Watts 12W
 Input Voltage DC48V
 Flux 960lm
 Beam Angle 90°

SKU: 5271 SKU: 5263
 ■ 4000K ■ 3000K

CRI Ra>90
 IP Rating IP20
 Dimension Φ65x130
 Body Color White


**LED Magnetic Track Light
20W**


Watts 20W
 Input Voltage DC48V
 Flux 1600lm
 Beam Angle 120°

SKU: 5266 SKU: 5262
 ■ 4000K ■ 3000K

CRI Ra>90
 IP Rating IP20
 Dimension 600x34x50.5mm
 Body Color White


**LED Magnetic Track Light
10W**


Watts 10W
 Input Voltage DC48V
 Flux 800lm
 Beam Angle 90°

SKU: 5268 SKU: 5267
 ■ 4000K ■ 3000K

CRI Ra>90
 IP Rating IP20
 Dimension 134x34x50.5mm
 Body Color White


**LED Magnetic Track Light
20W**


Watts 20W
 Input Voltage DC48V
 Flux 1600lm
 Beam Angle 120°

SKU: 5270 SKU: 5269
 ■ 4000K ■ 3000K

CRI Ra>90
 IP Rating IP20
 Dimension 270x34x50.5mm
 Body Color White


**LED Magnetic Track Light
10W**


Watts 10W
 Input Voltage DC48V
 Flux 800lm
 Beam Angle 24°

SKU: 5273
 ■ 3000K

CRI Ra>90
 IP Rating IP20
 Dimension 137x34x95
 Body Color White





TRACK SYSTEM Three-Phase

BLACK

Length: 1.0m ; 1.5m ; 2.0m

S15

- SKU: 5207 BLACK BODY - 1m
- SKU: 5208 BLACK BODY - 1.5m
- SKU: 5209 BLACK BODY - 2m

R15 Build-in

- SKU: 5203 BLACK BODY - 1m
- SKU: 5204 BLACK BODY - 1.5m
- SKU: 5205 BLACK BODY - 2m

R15B Build-in

- SKU: 5201 BLACK BODY - 1m
- SKU: 5202 BLACK BODY - 1.5m
- SKU: 5203 BLACK BODY - 2m



ACCESSORIES:



POWER CONNECTOR
SKU: 5211



STRAIGHT CONNECTOR
SKU: 5212



ADJUSTABLE CONNECTOR
SKU: 5213

SLIM POWER SUPPLY 48V - BLACK



SKU: 5214
80W 1.66A



SKU: 5215
150W 3.12A

Watts	80W	Current	1.66A
Input Voltage	220V	Material	Metal
Output Voltage	DC: 48V	IP Rating	IP20

Watts	150W	Current	3.12A
Input Voltage	220V	Material	Metal
Output Voltage	DC: 48V	IP Rating	IP20



LED Magnetic Track Light
6W ; 10W

M15
TRACK



Watts	6W ; 10W	CRI	Ra>90
Input Voltage	DC48V	IP Rating	IP20
Flux	480 ; 800lm	Dimension	φ35x70 mm
Beam Angle	90°	Body Color	Black

480 Lumens **6W** SKU: 5221 4000K SKU: 5222 3000K

800 Lumens **10W** SKU: 5223 4000K SKU: 5224 3000K



LED Magnetic Track Light
10W ; 20W

M15
TRACK



Watts	10W ; 20W	CRI	Ra>90
Input Voltage	DC48V	IP Rating	IP20
Flux	650 ; 1300lm	Dimension 10W	300x15x18mm
Beam Angle	120°	Dimension 20W	600x15x18mm

650 Lumens **10W** SKU: 5225 4000K SKU: 5226 3000K

1300 Lumens **20W** SKU: 5227 4000K SKU: 5228 3000K



LED Magnetic Track Light
12W

M15
TRACK



Watts	12W	CRI	Ra>90
Input Voltage	DC48V	IP Rating	IP20
Flux	780lm	Dimension	232x15x18mm
Beam Angle	24°	Body Color	Black

780 Lumens **12W** SKU: 5229 4000K SKU: 5230 3000K



MINI MAGNETIC TRACK SYSTEM

BLACK - 30mm


Length: 1.0m ; 1.5m ; 2.0m

MM30

- SKU: 5480 BLACK BODY - 1m
- SKU: 5481 BLACK BODY - 1.5m
- SKU: 5482 BLACK BODY - 2m



ACCESSORIES:



SKU: 5483

SKU: 5484

SKU: 5485

SKU: 5486

SKU: 5487



SLIM POWER SUPPLY 48V




SKU: 5488 100W 2.08A

Watts	100W	Current	2.08A
Input Voltage	220V	Material	Aluminium
Output Voltage	DC: 48V	IP Rating	IP20

SKU: 5489 200W 2.08A

Watts	200W	Current	4.16A
Input Voltage	220V	Material	Aluminium
Output Voltage	DC: 48V	IP Rating	IP20





**LED Mini Magnetic Track Light
6W**



Watts	6W	CRI	Ra>90
Input Voltage	DC48V	IP Rating	IP20
Flux	720lm	Dimension	φ54x63x98mm
Beam Angle	32°	Body Color	Black

SKU: 5494 SKU: 5495
■ 4000K ■ 3000K



MM30
TRACK



**LED Mini Magnetic Track Light
12W**



Watts	12W	CRI	Ra>90
Input Voltage	DC48V	IP Rating	IP20
Flux	400lm	Dimension	300x32x11mm
Beam Angle	110°	Body Color	Black

SKU: 5490 SKU: 5491
■ 4000K ■ 3000K



MM30
TRACK



**LED Mini Magnetic Track Light
5W**



Watts	5W	CRI	Ra>90
Input Voltage	DC48V	IP Rating	IP20
Flux	425lm	Dimension	48x35x60mm
Beam Angle	38°	Body Color	Black

SKU: 5496 SKU: 5497
■ 4000K ■ 3000K



MM30
TRACK



**LED Mini Magnetic Track Light
10W**



Watts	10W	CRI	Ra>90
Input Voltage	DC48V	IP Rating	IP20
Flux	520lm	Dimension	240x32x11mm
Beam Angle	25°	Body Color	Black

SKU: 5492 SKU: 5493
■ 4000K ■ 3000K



MM30
TRACK



**LED Mini Magnetic Track Light
4W**



Watts	4W	CRI	Ra>90
Input Voltage	DC48V	IP Rating	IP20
Flux	240lm	Dimension	48x35x60mm
Beam Angle	80°	Body Color	Black

SKU: 5498 SKU: 5499
■ 4000K ■ 3000K



MM30
TRACK





LED Floodlights are commonly used for outdoor lighting large areas. Applicable for villas and country houses, LED floodlights are number one choice for gardens and large open spaces.


Features:

- Up to 80% power saving
- High power and IP65 rating
- Large beam angles for single product lighting
- Wall or pylon mountable
- Tough and reliable
- Options with solar panels

Application:

- Outdoor lighting
- Large area coverage
- Houses or warehouse usage

LED FLOODLIGHTS



LED FLOODLIGHTS



LED CCT SOLAR FLOODLIGHT
Solar Panel Power:5V/10W

1000 Lumens 120° IP65

EQ.Watts	10W	Beam Angle	120°
Battery	3.2V / 10Ah	CRI	Ra>80
Flux	1000lm	IP Rating	IP65

SKU: 5473
CCT
6000K 4500K 3000K



LED SMD SOLAR FLOODLIGHT
Solar Panel Power:6V/8W

500 Lumens 120° IP65

EQ.Watts	16W	Beam Angle	120°
Battery	3.2V / 5Ah	CRI	Ra>80
Flux	500lm	IP Rating	IP65

SKU: 5430
6000K




LED CCT SOLAR FLOODLIGHT
Solar Panel Power:5V/20W

1800 Lumens 120° IP65

EQ.Watts	10W	Beam Angle	120°
Battery	3.2V / 20Ah	CRI	Ra>80
Flux	1800lm	IP Rating	IP65

SKU: 5474
CCT
6000K 4500K 3000K



LED SMD SOLAR FLOODLIGHT
Solar Panel Power:6V/16W

1200 Lumens 120° IP65

EQ.Watts	16W	Beam Angle	120°
Battery	3.2V / 10Ah	CRI	Ra>80
Flux	1200lm	IP Rating	IP65

SKU: 5431
6000K



LED CCT SOLAR FLOODLIGHT
Solar Panel Power:5V/30W

2700 Lumens 120° IP65

EQ.Watts	30W	Beam Angle	120°
Battery	3.2V / 30Ah	CRI	Ra>80
Flux	2700lm	IP Rating	IP65

SKU: 5475
CCT
6000K 4500K 3000K



LED SMD SOLAR FLOODLIGHT
Solar Panel Power:6V/20W

1600 Lumens 120° IP65

EQ.Watts	20W	Beam Angle	120°
Battery	3.2V / 15Ah	CRI	Ra>80
Flux	1600lm	IP Rating	IP65

SKU: 5432
6000K



LED SMD SOLAR FLOODLIGHT
Solar Panel Power:6V/30W

3000 Lumens 120° IP65

EQ.Watts	30W	Beam Angle	120°
Battery	3.2V / 30Ah	CRI	Ra>80
Flux	3000lm	IP Rating	IP65

SKU: 5468
6000K



LED SMD SOLAR FLOODLIGHT
Solar Panel Power:6V/25W

2200 Lumens 120° IP65

EQ.Watts	25W	Beam Angle	120°
Battery	3.2V / 20Ah	CRI	Ra>80
Flux	2200lm	IP Rating	IP65

SKU: 5433
6000K





LED SOLAR POWER FLOOD LIGHT **PF>0.9**
with Solar Panel and Remote



6W EQ.Watts	800 Lumens	Solar Panel Flux	6W/5V 800lm	IP Rating	IP65	Body Color	Black	3.2V 6Ah	SKU: 5291	6000K
10W EQ.Watts	1200 Lumens	Solar Panel Flux	10W/5V 1200lm	IP Rating	IP65	Body Color	Black	3.2V 10Ah	SKU: 5292	6000K
15W EQ.Watts	2000 Lumens	Solar Panel Flux	15W/5V 2000lm	IP Rating	IP65	Body Color	Black	3.2V 15Ah	SKU: 5293	6000K
20W EQ.Watts	2600 Lumens	Solar Panel Flux	20W/5V 2600lm	IP Rating	IP65	Body Color	Black	3.2V 20Ah	SKU: 5294	6000K
25W EQ.Watts	3200 Lumens	Solar Panel Flux	25W/5V 3200lm	IP Rating	IP65	Body Color	Black	3.2V 25Ah	SKU: 5295	6000K
30W EQ.Watts	3800 Lumens	Solar Panel Flux	30W/5V 3800lm	IP Rating	IP65	Body Color	Black	3.2V 30Ah	SKU: 5296	6000K
40W EQ.Watts	4800 Lumens	Solar Panel Flux	40W/5V 4800lm	IP Rating	IP65	Body Color	Black	3.2V 40Ah	SKU: 5297	6000K
NEW 40W EQ.Watts	6000 Lumens	Solar Panel Flux	40W/5V 6000lm	IP Rating	IP65	Body Color	Black	3.2V 40Ah	SKU: 5298	6000K

NEW **SANAN** CHIP ANTI GLARE



LED SMD FLOODLIGHT
Milky-Lens



20W 1600 Lumens	Product code	FL20-B1	Beam Angle	120°	 SKU:5991 4000K
	Watts	20W	CRI	Ra>80	
	Input Voltage	AC : 180-265V	IP Rating	IP65	
	Flux	1600lm	Body Color	Black	
30W 2400 Lumens	Product code	FL30-B1	Beam Angle	120°	 SKU:5992 4000K
	Watts	30W	CRI	Ra>80	
	Product code	AC : 180-265V	IP Rating	IP65	
	Flux	2400lm	Body Color	Black	
50W 4000 Lumens	Product code	FL50-B1	Beam Angle	120°	 SKU:5993 4000K
	Watts	50W	CRI	Ra>80	
	Input Voltage	AC : 180-265V	IP Rating	IP65	
	Flux	4000lm	Body Color	Black	



LED SMD FLOODLIGHT PF>0.9
With Solar Panels and Remote Control




LED SMD FLOODLIGHT PF>0.9
With Solar Panels and Remote Control



800
Lumens


Product code	FL25-A6	Beam Angle	120°
EQ.Watts	12W	CRI	Ra>80
Battery	3.2V / 5.5Ah	IP Rating	IP65
Flux	800lm	Body Color	Black



SKU: 5460
6000K

400
Lumens


Product code	FL6-B5	Beam Angle	90°
EQ.Watts	6W	CRI	Ra>80
Battery	3.2V / 5Ah	IP Rating	IP65
Flux	400lm	Body Color	Grey



SKU: 5455
6000K

1300
Lumens


Product code	FL40-A6	Beam Angle	120°
EQ.Watts	40W	CRI	Ra>80
Battery	3.2V / 11Ah	IP Rating	IP65
Flux	1300lm	Body Color	Black



SKU: 5461
6000K

500
Lumens


Product code	FL8-B5	Beam Angle	90°
EQ.Watts	8W	CRI	Ra>80
Battery	3.2V / 6Ah	IP Rating	IP65
Flux	500lm	Body Color	Grey



SKU: 5456
6000K

1800
Lumens


Product code	FL60-B2	Beam Angle	120°
EQ.Watts	20W	CRI	Ra>80
Battery	6.4V / 11Ah	IP Rating	IP65
Flux	1800lm	Body Color	Black



SKU: 5462
6000K

1200
Lumens


Product code	FL15-B5	Beam Angle	90°
EQ.Watts	15W	CRI	Ra>80
Battery	3.2V / 10Ah	IP Rating	IP65
Flux	1200lm	Body Color	Grey



SKU: 5457
6000K

2500
Lumens


Product code	FL100-B2	Beam Angle	120°
EQ.Watts	35W	CRI	Ra>80
Battery	6.4V / 16.5Ah	IP Rating	IP65
Flux	2500lm	Body Color	Black



SKU: 5463
6000K

1800
Lumens


Product code	FL20-B5	Beam Angle	90°
EQ.Watts	20W	CRI	Ra>80
Battery	3.2V / 20Ah	IP Rating	IP65
Flux	1800lm	Body Color	Grey



SKU: 5458
6000K

2400
Lumens

Product code	FL30-B5	Beam Angle	90°
EQ.Watts	30W	CRI	Ra>80
Battery	3.2V / 25Ah	IP Rating	IP65
Flux	2400lm	Body Color	Grey



SKU: 5459
6000K

NEW

120°

90
Lumens/W

IP65




LED SMD FLOODLIGHT


White Body - 15cm Cable

10W900
Lumens


Product code	FL10-B3	Beam Angle	120°
Watts	10W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	900lm	Body Color	White


 SKU:15801 SKU:15802 SKU:15803
 6000K 4000K 3000K
20W1800
Lumens


Product code	FL20-B3	Beam Angle	120°
Watts	20W	CRI	Ra>80
Product code	AC : 180-265V	IP Rating	IP65
Flux	1800lm	Body Color	White


 SKU:15804 SKU:15805 SKU:15806
 6000K 4000K 3000K
30W2700
Lumens


Product code	FL30-B3	Beam Angle	120°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	2700lm	Body Color	White


 SKU:15807 SKU:15808 SKU:15809
 6000K 4000K 3000K
50W4500
Lumens

Product code	FL50-B3	Beam Angle	120°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	4500lm	Body Color	White


 SKU:15810 SKU:15811 SKU:15812
 6000K 4000K 3000K
100W9000
Lumens

Product code	FL100-B3	Beam Angle	120°
Watts	100W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	9000lm	Body Color	White


 SKU:15813 SKU:15814 SKU:15815
 6000K 4000K 3000K
NEW

120°

90
Lumens/W

IP65




LED SMD FLOODLIGHT


Black Body - 15cm Cable

10W900
Lumens


Product code	FL10-B3	Beam Angle	120°
Watts	10W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	900lm	Body Color	Black


 SKU:15816 SKU:15817 SKU:15818
 6000K 4000K 3000K
20W1800
Lumens


Product code	FL20-B3	Beam Angle	120°
Watts	20W	CRI	Ra>80
Product code	AC : 180-265V	IP Rating	IP65
Flux	1800lm	Body Color	Black


 SKU:15819 SKU:15820 SKU:15821
 6000K 4000K 3000K
30W2700
Lumens


Product code	FL30-B3	Beam Angle	120°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	2700lm	Body Color	Black


 SKU:15822 SKU:15823 SKU:15824
 6000K 4000K 3000K
50W4500
Lumens

Product code	FL50-B3	Beam Angle	120°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	4500lm	Body Color	Black


 SKU:15825 SKU:15826 SKU:15827
 6000K 4000K 3000K
100W9000
Lumens

Product code	FL100-B3	Beam Angle	120°
Watts	100W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	9000lm	Body Color	Black


 SKU:15828 SKU:15829 SKU:15830
 6000K 4000K 3000K

NEW

Sensor



120°

90
Lumens/W

IP65



LED SMD FLOODLIGHT


Sensor - White Body -15cm Cable

10W

900

Lumens


Product code	FL10-B3	Beam Angle	120°
Watts	10W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	900lm	Body Color	White


 SKU:15837 SKU:15838 SKU:15839
 ■ 6000K ■ 4000K ■ 3000K
20W

1800

Lumens


Product code	FL20-B3	Beam Angle	120°
Watts	20W	CRI	Ra>80
Product code	AC : 180-265V	IP Rating	IP65
Flux	1800lm	Body Color	White


 SKU:15840 SKU:15841 SKU:15842
 ■ 6000K ■ 4000K ■ 3000K
30W

2700

Lumens


Product code	FL30-B3	Beam Angle	120°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	2700lm	Body Color	White


 SKU:15843 SKU:15844 SKU:15845
 ■ 6000K ■ 4000K ■ 3000K
50W

4500

Lumens

Product code	FL50-B3	Beam Angle	120°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	4500lm	Body Color	White


 SKU:15846 SKU:15847
 ■ 6000K ■ 4000K
NEW

Sensor



120°

90
Lumens/W

IP65



LED SMD FLOODLIGHT


Sensor - Black Body -15cm Cable

10W

900

Lumens


Product code	FL10-B3	Beam Angle	120°
Watts	10W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	900lm	Body Color	Black


 SKU:15848 SKU:15849 SKU:15850
 ■ 6000K ■ 4000K ■ 3000K
20W

1800

Lumens


Product code	FL20-B3	Beam Angle	120°
Watts	20W	CRI	Ra>80
Product code	AC : 180-265V	IP Rating	IP65
Flux	1800lm	Body Color	Black


 SKU:15851 SKU:15852 SKU:15853
 ■ 6000K ■ 4000K ■ 3000K
30W

2700

Lumens


Product code	FL30-B3	Beam Angle	120°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	2700lm	Body Color	Black


 SKU:15854 SKU:15855 SKU:15856
 ■ 6000K ■ 4000K ■ 3000K
50W

4500

Lumens

Product code	FL50-B3	Beam Angle	120°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	4500lm	Body Color	Black


 SKU:15857 SKU:15858
 ■ 6000K ■ 4000K

NEW
5
 Years
 Warranty

90°

 100
 Lumens/W

IP65


**PREMIUM LINE**

LED SMD FLOODLIGHT

White Body**10W**

 1000
 Lumens


Product code	FL10-A5	Beam Angle	90°
Watts	10W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	1000lm	Body Color	White


 SKU:15859 SKU:15860 SKU:15861

20W

 2000
 Lumens


Product code	FL20-A5	Beam Angle	90°
Watts	20W	CRI	Ra>80
Product code	AC : 180-265V	IP Rating	IP65
Flux	2000lm	Body Color	White


 SKU:15862 SKU:15863 SKU:15864

30W

 3000
 Lumens


Product code	FL30-A5	Beam Angle	90°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	3000lm	Body Color	White


 SKU:15865 SKU:15866 SKU:15867

50W

 5000
 Lumens


Product code	FL50-A5	Beam Angle	90°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	5000lm	Body Color	White


 SKU:15868 SKU:15869 SKU:15870

100W

 10000
 Lumens

Product code	FL100-A5	Beam Angle	90°
Watts	100W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	10000lm	Body Color	White


 SKU:15871 SKU:15872 SKU:15873

NEW
5
 Years
 Warranty

90°

 100
 Lumens/W

IP65


**PREMIUM LINE**

LED SMD FLOODLIGHT

Black Body**10W**

 1000
 Lumens


Product code	FL10-A5	Beam Angle	90°
Watts	10W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	1000lm	Body Color	Black


 SKU:15874 SKU:15875 SKU:15876

20W

 2000
 Lumens


Product code	FL20-A5	Beam Angle	90°
Watts	20W	CRI	Ra>80
Product code	AC : 180-265V	IP Rating	IP65
Flux	2000lm	Body Color	Black


 SKU:15877 SKU:15878 SKU:15879

30W

 3000
 Lumens


Product code	FL30-A5	Beam Angle	90°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	3000lm	Body Color	Black


 SKU:15880 SKU:15881 SKU:15882

50W

 5000
 Lumens


Product code	FL50-A5	Beam Angle	90°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	5000lm	Body Color	Black


 SKU:15883 SKU:15884 SKU:15885

100W

 10000
 Lumens

Product code	FL100-A5	Beam Angle	90°
Watts	100W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	10000lm	Body Color	Black


 SKU:15886 SKU:15887 SKU:15888



5
Years
Warranty

90°

HIGH
Lumens

IP65


NEW



PREMIUM LINE


LED SMD FLOODLIGHT **HIGH POWER**
Black Body

150W	Product code	FL150-A5	Beam Angle	90°
15000 Lumens	Watts	150W	CRI	Ra>80
	Input Voltage	AC : 180-265V	IP Rating	IP65
	Flux	15000lm	Body Color	Black




SKU:15889 6000K
SKU:15890 4000K

200W	Product code	FL200-A5	Beam Angle	90°
28000 Lumens	Watts	200W	CRI	Ra>80
	Product code	AC : 180-265V	IP Rating	IP65
	Flux	28000lm	Body Color	Black




SKU:15891 6000K
SKU:15892 4000K

300W	Product code	FL300-A5	Beam Angle	90°
42000 Lumens	Watts	300W	CRI	Ra>80
	Input Voltage	AC : 180-265V	IP Rating	IP65
	Flux	42000lm	Body Color	Black




SKU:15893 6000K
SKU:15894 4000K

400W	Product code	FL400-A5	Beam Angle	90°
56000 Lumens	Watts	400W	CRI	Ra>80
	Input Voltage	AC : 180-265V	IP Rating	IP65
	Flux	56000lm	Body Color	Black



SKU:15895 6000K
SKU:15896 4000K

500W	Product code	FL100-A5	Beam Angle	90°
70000 Lumens	Watts	500W	CRI	Ra>80
	Input Voltage	AC : 180-265V	IP Rating	IP65
	Flux	10000lm	Body Color	Black



SKU:15897 6000K
SKU:15898 4000K

NEW

120°


90
Lumens/W

IP65




LED SMD FLOODLIGHT **HIGH POWER**
Black Body

150W	Product code	FL150-A5	Beam Angle	120°
13500 Lumens	Watts	150W	CRI	Ra>80
	Input Voltage	AC : 180-265V	IP Rating	IP65
	Flux	13500lm	Body Color	Black




SKU:15831 6000K
SKU:15832 4000K

200W	Product code	FL200-A5	Beam Angle	120°
18000 Lumens	Watts	200W	CRI	Ra>80
	Product code	AC : 180-265V	IP Rating	IP65
	Flux	18000lm	Body Color	Black



SKU:15833 6000K
SKU:15834 4000K

300W	Product code	FL300-A5	Beam Angle	120°
27000 Lumens	Watts	300W	CRI	Ra>80
	Input Voltage	AC : 180-265V	IP Rating	IP65
	Flux	27000lm	Body Color	Black




SKU:15835 6000K
SKU:15836 4000K



LED SMD FLOODLIGHT


White Body

10W 900 Lumens	Product code	FL10-B3	Beam Angle	90°
	Watts	10W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	900lm	Body Color	White




SKU: 5701 6000K SKU: 5702 4500K SKU: 5703 2700K

20W 1800 Lumens	Product code	FL20-B3	Beam Angle	90°
	Watts	20W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	1800lm	Body Color	White




SKU: 5704 6000K SKU: 5705 4500K SKU: 5706 2700K

30W 2700 Lumens	Product code	FL30-B3	Beam Angle	90°
	Watts	30W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	2700lm	Body Color	White




SKU: 5707 6000K SKU: 5708 4500K SKU: 5709 2700K

50W 4500 Lumens	Product code	FL50-B3	Beam Angle	90°
	Watts	50W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	4500lm	Body Color	White



SKU: 5710 6000K SKU: 5711 4500K SKU: 5712 2700K

100W 9000 Lumens	Product code	FL100-B3	Beam Angle	90°
	Watts	100W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	9000lm	Body Color	White




SKU: 5713 6000K SKU: 5714 4500K SKU: 5715 2700K



LED SMD FLOODLIGHT


Black Body

10W 900 Lumens	Product code	FL10-B3	Beam Angle	90°
	Watts	10W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	900lm	Body Color	Black




SKU: 5721 6000K SKU: 5722 4500K SKU: 5723 2700K

20W 1800 Lumens	Product code	FL20-B3	Beam Angle	90°
	Watts	20W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	1800lm	Body Color	Black




SKU: 5724 6000K SKU: 5725 4500K SKU: 5726 2700K

30W 2700 Lumens	Product code	FL30-B3	Beam Angle	90°
	Watts	30W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	2700lm	Body Color	Black




SKU: 5727 6000K SKU: 5728 4500K SKU: 5729 2700K

50W 4500 Lumens	Product code	FL50-B3	Beam Angle	90°
	Watts	50W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	4500lm	Body Color	Black



SKU: 5730 6000K SKU: 5731 4500K SKU: 5732 2700K

100W 9000 Lumens	Product code	FL100-B3	Beam Angle	90°
	Watts	100W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	9000lm	Body Color	Black




SKU: 5733 6000K SKU: 5734 4500K SKU: 5735 2700K



LED SMD FLOODLIGHT


White Body - PIR Sensor

10W 900 Lumens	Product code	FL10-B3	Beam Angle	90°
	Watts	10W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	900lm	Body Color	White




SKU: 5760 SKU: 5761 SKU: 5762

20W 1800 Lumens	Product code	FL20-B3	Beam Angle	90°
	Watts	20W	CRI	Ra>80
	Product code	AC : 220-240V	IP Rating	IP65
	Flux	1800lm	Body Color	White




SKU: 5763 SKU: 5764 SKU: 5765

30W 2700 Lumens	Product code	FL30-B3	Beam Angle	90°
	Watts	30W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	2700lm	Body Color	White



SKU: 5766 SKU: 5767 SKU: 5768

50W 4500 Lumens	Product code	FL50-B3	Beam Angle	90°
	Watts	50W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	4500lm	Body Color	White




SKU: 5769 SKU: 5770



LED SMD FLOODLIGHT


Black Body - PIR Sensor

10W 900 Lumens	Product code	FL10-B3	Beam Angle	90°
	Watts	10W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	900lm	Body Color	Black




SKU: 5771 SKU: 5772 SKU: 5773

20W 1800 Lumens	Product code	FL20-B3	Beam Angle	90°
	Watts	20W	CRI	Ra>80
	Product code	AC : 220-240V	IP Rating	IP65
	Flux	1800lm	Body Color	Black




SKU: 5774 SKU: 5775 SKU: 5776

30W 2700 Lumens	Product code	FL30-B3	Beam Angle	90°
	Watts	30W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	2700lm	Body Color	Black



SKU: 5777 SKU: 5778 SKU: 5779

50W 4500 Lumens	Product code	FL50-B3	Beam Angle	90°
	Watts	50W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	4500lm	Body Color	Black



SKU: 5780 SKU: 5781




LED SMD FLOODLIGHT PF>0.9

High Power - Grey Body



150W 15000 Lumens	Product code	FL150-B4	Beam Angle	90°
	Watts	150W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	15000lm	Body Color	Grey



SKU: 5743 6000K
SKU: 5744 4500K



Floodlight Spike

Body Color	Black
Material	Aluminium

SKU: 6682 160x35cm
SKU: 6683 265x55cm



Billboard Stand

Body Color	Black
Material	Iron

SKU: 6684 150x500cm
SKU: 6685 200x800cm

NEW



LED SMD FLOODLIGHT


Black Body
***Optional Sensor**

CCT SWITCH




SKU: 5985
PIR Sensor
NOT INCLUDED

20W 1800 Lumens	Product code	FL20-C1	Beam Angle	120°
	Watts	10W	CRI	Ra>80
	Input Voltage	AC : 180-265V	IP Rating	IP65
	Flux	1800lm	Body Color	Black




SKU: 5981
CCT
6000K 4000K 3000K

30W 2700 Lumens	Product code	FL30-C1	Beam Angle	120°
	Watts	30W	CRI	Ra>80
	Input Voltage	AC : 180-265V	IP Rating	IP65
	Flux	2700lm	Body Color	Black




SKU: 5982
CCT
6000K 4000K 3000K

50W 4500 Lumens	Product code	FL50-C1	Beam Angle	120°
	Watts	50W	CRI	Ra>80
	Input Voltage	AC : 180-265V	IP Rating	IP65
	Flux	4500lm	Body Color	Black



SKU: 5983
CCT
6000K 4000K 3000K

100W 9000 Lumens	Product code	FL100-C1	Beam Angle	120°
	Watts	100W	CRI	Ra>80
	Input Voltage	AC : 180-265V	IP Rating	IP65
	Flux	9000lm	Body Color	Black



SKU: 5984
CCT
6000K 4000K 3000K

*SKU:5985 PIR SENSOR NOT INCLUDED

5 Years
Warranty


HIGH
Lumens

IP65



Power Cable Length-0.70m


LED SMD FLOODLIGHT PF>0.9
Premium Line - White Body


10W 850 Lumens	Product code	FL10-A5	Beam Angle	150°
	Watts	10W	CRI	Ra>80
	Input Voltage	AC : 175-265V	IP Rating	IP65
	Flux	850lm	Body Color	White


 SKU: 5865 SKU: 5866


30W 2550 Lumens	Product code	FL30-A5	Beam Angle	150°
	Watts	30W	CRI	Ra>80
	Input Voltage	AC : 175-265V	IP Rating	IP65
	Flux	2550lm	Body Color	White


 SKU: 5871 SKU: 5873

50W 4250 Lumens	Product code	FL50-A5	Beam Angle	150°
	Watts	50W	CRI	Ra>80
	Input Voltage	AC : 175-265V	IP Rating	IP65
	Flux	4250lm	Body Color	White


 SKU: 5876

100W 8500 Lumens	Product code	FL100-A5	Beam Angle	150°
	Watts	100W	CRI	Ra>80
	Input Voltage	AC : 175-265V	IP Rating	IP65
	Flux	8500lm	Body Color	White


 SKU: 5879

5 Years
Warranty


HIGH
Lumens

IP65



Power Cable Length-0.70m


LED SMD FLOODLIGHT PF>0.9
Premium Line - Black Body


10W 850 Lumens	Product code	FL10-A5	Beam Angle	150°
	Watts	10W	CRI	Ra>80
	Input Voltage	AC : 175-265V	IP Rating	IP65
	Flux	850lm	Body Color	Black


 SKU: 5880


20W 1700 Lumens	Product code	FL20-A5	Beam Angle	150°
	Watts	20W	CRI	Ra>80
	Input Voltage	AC : 175-265V	IP Rating	IP65
	Flux	1700lm	Body Color	Black


 SKU: 5883

30W 2550 Lumens	Product code	FL30-A5	Beam Angle	150°
	Watts	30W	CRI	Ra>80
	Input Voltage	AC : 175-265V	IP Rating	IP65
	Flux	2550lm	Body Color	Black


 SKU: 5886 SKU: 5888


100W 8500 Lumens	Product code	FL100-A5	Beam Angle	150°
	Watts	100W	CRI	Ra>80
	Input Voltage	AC : 175-265V	IP Rating	IP65
	Flux	8500lm	Body Color	Black


 SKU: 5893




LED SMD FLOODLIGHT
CITY LINE - White Body

10W 800 Lumens	Product code	FL10-B1	Beam Angle	120°
	Watts	10W	CRI	Ra>80
	Input Voltage	AC : 220-265V	IP Rating	IP65
	Flux	800lm	Body Color	White




SKU: 5900 6000K
SKU: 5901 4500K

20W 1600 Lumens	Product code	FL20-B1	Beam Angle	120°
	Watts	20W	CRI	Ra>80
	Input Voltage	AC : 220-265V	IP Rating	IP65
	Flux	1600lm	Body Color	White




SKU: 5903 6000K
SKU: 5905 2800K

30W 2400 Lumens	Product code	FL30-B1	Beam Angle	120°
	Watts	30W	CRI	Ra>80
	Input Voltage	AC : 220-265V	IP Rating	IP65
	Flux	2400lm	Body Color	White




SKU: 5907 4500K
SKU: 5908 2800K

50W 4000 Lumens	Product code	FL50-B1	Beam Angle	120°
	Watts	50W	CRI	Ra>80
	Input Voltage	AC : 220-265V	IP Rating	IP65
	Flux	4000lm	Body Color	White



SKU: 5911 2800K

100W 8000 Lumens	Product code	FL100-B1	Beam Angle	120°
	Watts	100W	CRI	Ra>80
	Input Voltage	AC : 220-265V	IP Rating	IP65
	Flux	8000lm	Body Color	White




SKU: 5914 2800K




LED SMD FLOODLIGHT
CITY LINE - Black Body

10W 800 Lumens	Product code	FL10-B1	Beam Angle	120°
	Watts	10W	CRI	Ra>80
	Input Voltage	AC : 220-265V	IP Rating	IP65
	Flux	800lm	Body Color	Black




SKU: 5915 6000K
SKU: 5916 4500K

20W 1600 Lumens	Product code	FL20-B1	Beam Angle	120°
	Watts	20W	CRI	Ra>80
	Input Voltage	AC : 220-265V	IP Rating	IP65
	Flux	1600lm	Body Color	Black




SKU: 5918 6000K
SKU: 5919 4500K
SKU: 5920 2800K

30W 2400 Lumens	Product code	FL30-B1	Beam Angle	120°
	Watts	30W	CRI	Ra>80
	Input Voltage	AC : 220-265V	IP Rating	IP65
	Flux	2400lm	Body Color	Black




SKU: 5921 6000K
SKU: 5922 4500K
SKU: 5923 2800K

50W 4000 Lumens	Product code	FL50-B1	Beam Angle	120°
	Watts	50W	CRI	Ra>80
	Input Voltage	AC : 220-265V	IP Rating	IP65
	Flux	4000lm	Body Color	Black



SKU: 5925 4500K


100W 8000 Lumens	Product code	FL100-B1	Beam Angle	120°
	Watts	100W	CRI	Ra>80
	Input Voltage	AC : 220-265V	IP Rating	IP65
	Flux	8000lm	Body Color	Black



SKU: 5927 6000K
SKU: 5928 4500K



LED SMD FLOODLIGHT
CITY LINE- White Body
With PIR Sensor
10W
800
 Lumens

Product code	FL10-B2	Beam Angle	120°
Watts	10W	CRI	Ra>80
Input Voltage	AC : 220-265V	IP Rating	IP65
Flux	800lm	Body Color	White


 SKU: 5930 6000K
 SKU: 5931 4500K
 SKU: 5932 2800K


20W
1600
 Lumens

Product code	FL20-B2	Beam Angle	120°
Watts	20W	CRI	Ra>80
Input Voltage	AC : 220-265V	IP Rating	IP65
Flux	1600lm	Body Color	White


 SKU: 5934 4500K
 SKU: 5935 2800K


30W
2400
 Lumens

Product code	FL30-B2	Beam Angle	120°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 220-265V	IP Rating	IP65
Flux	2400lm	Body Color	White


 SKU: 5937 4500K
 SKU: 5938 2800K

50W
4000
 Lumens


Product code	FL50-B2	Beam Angle	120°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 220-265V	IP Rating	IP65
Flux	4000lm	Body Color	White



SKU: 5939 6000K



LED SMD FLOODLIGHT
CITY LINE - Black Body
With PIR Sensor
10W
800
 Lumens

Product code	FL10-B2	Beam Angle	120°
Watts	10W	CRI	Ra>80
Input Voltage	AC : 220-265V	IP Rating	IP65
Flux	800lm	Body Color	Black


 SKU: 5942 4500K
 SKU: 5943 2800K


20W
1600
 Lumens

Product code	FL20-B2	Beam Angle	120°
Watts	20W	CRI	Ra>80
Input Voltage	AC : 220-265V	IP Rating	IP65
Flux	1600lm	Body Color	Black


 SKU: 5945 4500K
 SKU: 5946 2800K


30W
2400
 Lumens

Product code	FL30-B2	Beam Angle	120°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 220-265V	IP Rating	IP65
Flux	2400lm	Body Color	Black


 SKU: 5948 4500K
 SKU: 5949 2800K

50W
4000
 Lumens

Product code	FL50-B2	Beam Angle	120°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 220-265V	IP Rating	IP65
Flux	4000lm	Body Color	Black




SKU: 5950 6000K




LED SMD FLOODLIGHT PF>0.9
CCT LIGHT - Black Body




50W 5000 Lumens	Product code Watts Input Voltage Flux	FL50-A7 50W AC : 200-277V 5 000lm	Beam Angle CRI IP Rating Body Color	120° Ra>80 IP66 Black
---------------------------	--	--	--	--------------------------------




100W 10000 Lumens	Product code Watts Input Voltage Flux	FL100-A7 100W AC : 200-277V 10000lm	Beam Angle CRI IP Rating Body Color	120° Ra>80 IP66 Black
-----------------------------	--	--	--	--------------------------------



150W 15000 Lumens	Product code Watts Input Voltage Flux	FL150-A7 150W AC : 200-277V 15000lm	Beam Angle CRI IP Rating Body Color	120° Ra>80 IP66 Black
-----------------------------	--	--	--	--------------------------------




200W 20000 Lumens	Product code Watts Input Voltage Flux	FL200-A7 200W AC : 200-277V 20000lm	Beam Angle CRI IP Rating Body Color	120° Ra>80 IP66 Black
-----------------------------	--	--	--	--------------------------------




LED SMD FLOODLIGHT
CITY LINE - Black Body
With PIR Sensor




10W 800 Lumens	Product code Watts Input Voltage Flux	FL10-B2 10W AC : 220-265V 800lm	Beam Angle CRI IP Rating Body Color	120° Ra>80 IP65 Black
--------------------------	--	--	--	--------------------------------




20W 1600 Lumens	Product code Watts Input Voltage Flux	FL20-B2 20W AC : 220-265V 1600lm	Beam Angle CRI IP Rating Body Color	120° Ra>80 IP65 Black
---------------------------	--	---	--	--------------------------------



30W 2400 Lumens	Product code Watts Input Voltage Flux	FL30-B2 30W AC : 220-265V 2400lm	Beam Angle CRI IP Rating Body Color	120° Ra>80 IP65 Black
---------------------------	--	---	--	--------------------------------



50W 4000 Lumens	Product code Watts Input Voltage Flux	FL50-B2 50W AC : 220-265V 4000lm	Beam Angle CRI IP Rating Body Color	120° Ra>80 IP65 Black
---------------------------	--	---	--	--------------------------------





LED SMD FLOODLIGHT
On Stand - Foldable




20W



1600
Lumens

Product code	FL20-A8	Beam Angle	120°
Watts	20W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP65
Flux	1600lm	Body Color	Yellow




SKU: 5403
6000K

30W



2400
Lumens

Product code	FL30-A8	Beam Angle	120°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP65
Flux	2400lm	Body Color	Yellow




SKU: 5404
6000K

50W



4000
Lumens

Product code	FL50-A8	Beam Angle	120°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP65
Flux	4000lm	Body Color	Yellow



SKU: 5405
6000K



PORTABLE LED SMD FLOODLIGHT
Rechargeable + Battery



Input Voltage	AC : 200-240V	Body Color	Yellow+Black
Beam Angle	120°	CRI	Ra>80
IP Rating	IP44	Dimension 10W	123x133x218mm
		Dimension 20W	156x163x250mm

10W



600
Lumens



3.7V 2200mAh

SKU: 5401
6000K

20W



1200
Lumens



3.7V 4400mAh

SKU: 5402
6000K



Solar Power



1850
Lumens



120°



IP65

Flux	1850lm	Beam Angle	120°
Battery	3.7V 8Ah	CRI	Ra>80
Body Color	Yellow	Dimension	215x175x55mm



LED SMD PORTABLE FLOODLIGHT
Solar Panel Power: 6V/2.3W

- SOS Emergency Light
- Power Bank Function
- USB Ports



3.7V 8Ah

SKU: 5464
CCT
6000K 4500K 3000K



LED SMD FLOODLIGHT

Black Body -Green Light

90°




IP65

10W**800**

Lumens

Product code	FL10-B3	Beam Angle	90°
Watts	10W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	800lm	Body Color	Black


 SKU: 5751
 Green


LED RGB SMD FLOODLIGHT

Black Body + Remote Control

RGB



120°




IP65

10W**800**


Lumens

Product code	FL10-B4	Beam Angle	120°
Watts	10W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP65
Flux	800lm	Body Color	Black


 SKU: 5754
 RGB
20W**1600**


Lumens

Product code	FL20-B3	Beam Angle	90°
Watts	20W	CRI	Ra>70
Product code	AC : 220-240V	IP Rating	IP65
Flux	1600lm	Body Color	Black


 SKU: 5752
 Green
30W**2400**


Lumens

Product code	FL30-B4	Beam Angle	120°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP65
Flux	2400lm	Body Color	Black


 SKU: 5755
 RGB
30W**2400**


Lumens

Product code	FL30-B3	Beam Angle	90°
Watts	30W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	2400lm	Body Color	Black


 SKU: 5753
 Green
50W**4000**

Lumens

Product code	FL50-B4	Beam Angle	120°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP65
Flux	4000lm	Body Color	Black



 SKU: 5756
 RGB



LED SMD FLOODLIGHT
High Power - Black Body




150W 13500 Lumens	Product code	FL150-B3	Beam Angle	90°
	Watts	150W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	13500lm	Body Color	Black



SKU: 5736 SKU: 5737
■ 6000K ■ 4500K

200W 18000 Lumens	Product code	FL200-B3	Beam Angle	90°
	Watts	200W	CRI	Ra>80
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	18000lm	Body Color	Black




SKU: 5738 SKU: 5739
■ 6000K ■ 4500K



LED SMD5730 FLOODLIGHT **PF>0.9**
Dual Voltage With Terminal Block



100W 9000 Lumens	Product code	FL100-A9	Beam Angle	120°
	Watts	100W	CRI	Ra>80
	Input Voltage	AC : 85-265V	IP Rating	IP65
	Flux	9000lm	Body Color	Black



SKU: 5277
■ 6000K




**TRIPOD FOR FLOODLIGHTS
With Cross Bar**

Product code OT1-B9
 Body Color Yellow , Black
 Material Iron
 Maximum size 157x64x64cm
 Height Adjustment: 64-157cm
 Sections: 3 Pcs

SKU: 6686 BLACK BODY ■
 SKU: 6687 YELLOW BODY ■

**Terminal Block
Waterproof Box**

Rated Voltage 250V
 Material Flame Retardant PP
 Wire Range 0.5-1.5mm²
 Wire Range-T 0.5-2.5mm²
 Rated Current 16A


**Terminal Blocks Professional
Metal-Waterproof Box**

Rated Voltage 450V
 Material Cast Aluminium
 Body Size 80x75x60mm
 Rated Current 24A


**Lever Connectors
Easy Clip**

Rated voltage 450V
 Rated current 32A
 Wire range 18-12AWG 0.08--2.5mm²
 Ambient temperature -40°C~+105°C
 Strip length 12-13mm

SKU: 6501
 SKU: 6502
 SKU: 6503
 SKU: 6504
 SKU: 6505

Rated voltage 450V
 Rated current 32A
 Housing material: thermoplastic, 94V-0
 Flame-retardant
 Temperature: 110 degrees Celsius
 Wire range: #24 to #12 AWG solid wires

SKU: 6506
 SKU: 6507
 SKU: 6508

**Terminal Blocks Professional
Polycarbonate-Waterproof Box**

Rated Voltage 250V
 Rated Current 16A
 Material Polycarbonate
 Body Size 120x35x50 mm

Rated Voltage 450V
 Rated Current 24A
 Material Polycarbonate
 Body Size 120x35x70 mm



SKU: 6647 2-Connectors



SKU: 6648 3-Connectors

**Terminal Block Splitter
Waterproof Box**

Rated Voltage 250V
 Material Polypropylene 94 V2
 Wire Range 0.5-2.5mm²
 Rated Current 16A


**Terminal Block Splitter
Waterproof Box**

Rated Voltage 450V
 Material Polypropylene 94 V2
 Wire Range 0.5-4mm²
 Rated Current 24A


**Terminal Block Splitter
Waterproof Box**

Rated Voltage 450V
 Material Polypropylene 94 V2
 Wire Range 0.5-4mm²
 Rated Current 24A


**Terminal Block Splitter
Waterproof Box**

Rated Voltage 450V
 Material Polypropylene 94 V2
 Wire Range 0.5-4mm²
 Rated Current 24A





LED STREET AND INDUSTRIAL LIGHTS



LED industrial lights are series of highly efficient, reliable and easy to install products for production sites, warehouses or specialised areas. With different types – low or high bays, bulbs or linear lighting fixtures. These products will meet all industry standards and cover any lighting needs.

Features:

- Up to 80% power saving
- Variety of shapes and types
- Long lifetime and reliability
- Different types of mounting options
- Comply with industrial standards

Application:

- Production sites and warehouses
- Industrial places and factories
- Special lighting requirements





NEW



LED STREET LIGHT
Solar Power + Battery
Remote+ PIR SENSOR



<p>1200 Lumens</p>	Product code	SL8-A2	Beam Angle	120°	<p>231mm 413x47mm</p>	<p>SKU: 9145 6000K</p>
	Watts	8W	CRI	Ra>70		
	Battery	5V 8AH	IP Rating	IP65		
	Flux	1200lm	Body Color	Black		
<p>1800 Lumens</p>	Product code	SL12-A2	Beam Angle	120°	<p>231mm 511x47mm</p>	<p>SKU: 9146 6000K</p>
	Watts	12W	CRI	Ra>70		
	Battery	5V 12AH	IP Rating	IP65		
	Flux	1200lm	Body Color	Black		
<p>2700 Lumens</p>	Product code	SL20-A2	Beam Angle	120°	<p>251mm 722x47mm</p>	<p>SKU: 9147 6000K</p>
	Watts	20W	CRI	Ra>70		
	Battery	5V 18AH	IP Rating	IP65		
	Flux	2700lm	Body Color	Black		



LED SOLAR INDUSTRIAL LIGHTS

Remote Control



30W

4300
Lumens

Power Solar	5V/30W	CRI	Ra>80
Beam Angle	60°	IP Rating	IP66
Flux	4300lm	Body Color	Black

Battery
3.2V 30Ah

SKU: 9141
6000K

40W

5200
Lumens

Power Solar	5V/40W	CRI	Ra>80
Beam Angle	60°	IP Rating	IP66
Flux	5200lm	Body Color	Black

Battery
3.2V 35Ah

SKU: 9142
6000K

50W

6300
Lumens

Power Solar	5V/50W	CRI	Ra>80
Beam Angle	60°	IP Rating	IP66
Flux	6300lm	Body Color	Black

Battery
3.2V 45Ah

SKU: 9143
6000K




LED STREET LIGHT

Solar Power + Battery



500
Lumens


Product code	SL8-B6	Beam Angle	120°
Watts	8W	CRI	Ra>70
Battery	3.2V 5AH	IP Rating	IP65
Flux	500lm	Body Color	Black



SKU: 9126
6000K

1200
Lumens


Product code	SL10-B6	Beam Angle	120°
Watts	10W	CRI	Ra>70
Battery	3.2V 10AH	IP Rating	IP65
Flux	1200lm	Body Color	Black



SKU: 9127
6000K

1800
Lumens


Product code	SL15-B6	Beam Angle	120°
Watts	15W	CRI	Ra>70
Battery	3.2V 15AH	IP Rating	IP65
Flux	1800lm	Body Color	Black



SKU: 9128
6000K

2400
Lumens

Product code	SL18-B6	Beam Angle	120°
Watts	18W	CRI	Ra>70
Battery	3.2V 20AH	IP Rating	IP65
Flux	2400lm	Body Color	Black



SKU: 9129
6000K



LED STREET LIGHT
8W Solar Power + Battery

Watts	8W	CRI	Ra>70
Battery	3.2V / 16.5Ah	IP Rating	IP65
Flux	950lm	Dimension	490x240x65mm
Beam Angle	120°	Body Color	Black

- * Intelligent Light Control
- * Time Switch

SKU: 9135
■ 6000K



Wireless Remote Control



950
Lumens



Battery



>1500 Cycles



Solar Power



IP65



LED STREET LIGHT
35W Solar Power + Battery

Watts	35W	CRI	Ra>70
Battery	6.4V / 16.5Ah	IP Rating	IP65
Flux	2600lm	Dimension	490x240x65mm
Beam Angle	120°	Body Color	Black

- * Intelligent Light Control
- * Time Switch

SKU: 9137
■ 6000K



Wireless Remote Control



2600
Lumens



Battery



>1500 Cycles



Solar Power



IP65



LED STREET LIGHT
12W Solar Power + Battery

Watts	12W	CRI	Ra>70
Battery	3.2V / 22Ah	IP Rating	IP65
Flux	1200lm	Dimension	650x250x65mm
Beam Angle	120°	Body Color	Black

- * Intelligent Light Control
- * Time Switch

SKU: 9136
■ 6000K



Wireless Remote Control



1200
Lumens



Battery



>1500 Cycles



Solar Power



IP65



LED STREET LIGHT
40W Solar Power + Battery

Watts	40W	CRI	Ra>70
Battery	6.4V / 22h	IP Rating	IP65
Flux	3000lm	Dimension	490x240x65mm
Beam Angle	120°	Body Color	Black

- * Intelligent Light Control
- * Time Switch

SKU: 9138
■ 6000K



Wireless Remote Control



3000
Lumens



Battery



>1500 Cycles



Solar Power



IP65

NEW



PREMIUM LINE

LED STREET LIGHT **PF>0.9**
High Lumens



5 Years
Warranty

30cm Cable


150
Lumens/W

75x130°

IP65

100W
15000
Lumens


Product code	SL100-A9	Beam Angle	75x130°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	15000lm	Body Color	Gray



SKU:9227 6000K
SKU:9225 4000K

150W
22500
Lumens


Product code	SL150-A9	Beam Angle	75x130°
Watts	100W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	22500lm	Body Color	Gray



SKU:9228 6000K
SKU:9226 4000K

200W
30000
Lumens

Product code	SL200-A9	Beam Angle	75x130°
Watts	200W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	30000lm	Body Color	Gray



SKU:9229 6000K

NEW



PREMIUM LINE

LED STREET LIGHT **PF>0.9**
High Lumens



5 Years
Warranty

30cm Cable


HIGH
Lumens

75x130°

IP65

30W
3600
Lumens


Product code	SL30-A9	Beam Angle	75x130°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	3600lm	Body Color	Gray



SKU:9250 6000K
SKU:9251 4000K
SKU:9252 3000K

50W
6000
Lumens


Product code	SL50-A9	Beam Angle	75x130°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	6000lm	Body Color	Gray



SKU:9241 6000K
SKU:9242 4000K
SKU:9243 3000K

100W
12000
Lumens


Product code	SL100-A9	Beam Angle	75x130°
Watts	100W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	12000lm	Body Color	Gray



SKU:9244 6000K
SKU:9245 4000K
SKU:9246 3000K

200W
24000
Lumens

Product code	SL200-A9	Beam Angle	75x130°
Watts	200W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	24000lm	Body Color	Gray



SKU:9247 6000K
SKU:9248 4000K
SKU:9249 3000K

NEW




LED STREET LIGHT **PF>0.9**
Slim Line

SANAN
CHIP



30W
3000
Lumens

Product code	SL30-A9	Beam Angle	75x130°
Watts	30W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	3000lm	Body Color	Black



SKU:9231
6000K

SKU:9232
4000K

NEW




LED STREET LIGHT **PF>0.9**
Slim Line - Sensor Day/Night

SANAN
CHIP



30W
3000
Lumens


Product code	SL30-A9	Beam Angle	75x130°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	3000lm	Body Color	Black



SKU:9237
4000K

50W
5000
Lumens

Product code	SL50-A9	Beam Angle	75x130°
Watts	50W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	5000lm	Body Color	Black




SKU:9233
6000K

SKU:9234
4000K

50W
5000
Lumens


Product code	SL50-A9	Beam Angle	75x130°
Watts	100W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	5000lm	Body Color	Black



SKU:9238
4000K

100W
10000
Lumens

Product code	SL100-A9	Beam Angle	75x130°
Watts	100W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	10000lm	Body Color	Black




SKU:9235
6000K

SKU:9236
4000K

100W
10000
Lumens

Product code	SL100-A9	Beam Angle	75x130°
Watts	200W	CRI	Ra>80
Input Voltage	AC : 180-265V	IP Rating	IP65
Flux	10000lm	Body Color	Black



SKU:9239
4000K




Adjusting angle

LED STREET LIGHT PF>0.9
High Lumens




50W 5000 Lumens	Product code Watts Input Voltage Flux	SL50-A9 50W AC : 220-240V 5000lm	Beam Angle CRI IP Rating Body Color	75x135° Ra>70 IP65 Gray
---------------------------	--	---	--	----------------------------------




SKU: 9221
6000K

100W 10000 Lumens	Product code Watts Input Voltage Flux	SL100-A9 100W AC : 220-240V 10000lm	Beam Angle CRI IP Rating Body Color	75x135° Ra>70 IP65 Gray
-----------------------------	--	--	--	----------------------------------




SKU: 9222
6000K

150W 15000 Lumens	Product code Watts Input Voltage Flux	SL150-A9 150W AC : 220-240V 15000lm	Beam Angle CRI IP Rating Body Color	75x135° Ra>70 IP65 Gray
-----------------------------	--	--	--	----------------------------------



SKU: 9223
6000K

200W 20000 Lumens	Product code Watts Input Voltage Flux	SL200-A9 200W AC : 220-240V 20000lm	Beam Angle CRI IP Rating Body Color	75x135° Ra>70 IP65 Gray
-----------------------------	--	--	--	----------------------------------




SKU: 9224
6000K

LED STREET LIGHT PF>0.9
High Lumens




20W 2000 Lumens	Product code Watts Input Voltage Flux	SL20-A9 20W AC : 220-240V 2000lm	Beam Angle CRI IP Rating Body Color	75x135° Ra>70 IP65 Gray
---------------------------	--	---	--	----------------------------------




SKU: 9216 6000K
SKU: 9217 4500K
SKU: 9218 2700K

30W 3000 Lumens	Product code Watts Input Voltage Flux	SL30-A9 30W AC : 220-240V 3000lm	Beam Angle CRI IP Rating Body Color	75x135° Ra>70 IP65 Gray
---------------------------	--	---	--	----------------------------------




SKU: 9201 6000K
SKU: 9202 4500K
SKU: 9203 2700K

150W 15000 Lumens	Product code Watts Input Voltage Flux	SL150-A9 150W AC : 220-240V 15000lm	Beam Angle CRI IP Rating Body Color	75x135° Ra>70 IP65 Gray
-----------------------------	--	--	--	----------------------------------



SKU: 9210 6000K
SKU: 9212 2700K

200W 20000 Lumens	Product code Watts Input Voltage Flux	SL200-A9 200W AC : 220-240V 20000lm	Beam Angle CRI IP Rating Body Color	75x135° Ra>70 IP65 Gray
-----------------------------	--	--	--	----------------------------------



SKU: 9213 6000K



PREMIUM LINE

LED STREET LIGHT **PF>0.95**
High Lumens-Moso Driver



5 Years
Warranty

150
Lumens/W

HIGH
Lumens


120°

IP65

120W

18000
Lumens

Product code	SL120-A7	Beam Angle	120°
Watts	120W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	18000lm	Protection	Class 1



SKU: 9180
5700K



LED STREET LIGHT **PF>0.95**
High Lumens-Moso Driver



5 Years
Warranty

140
Lumens/W

HIGH
Lumens

IP66

80W

11200
Lumens

Product code	SL80-A8	Beam Angle	120°
Watts	80W	CRI	Ra>70
Input Voltage	AC : 100-240V	IP Rating	IP66
Flux	11200lm	Protection	Class 1

SKU: 9196
5700K

100W

14000
Lumens

Product code	SL50-A8	Beam Angle	120°
Watts	100W	CRI	Ra>70
Input Voltage	AC : 100-240V	IP Rating	IP66
Flux	14000lm	Protection	Class 1

SKU: 9197
5700K

150W

21000
Lumens

Product code	SL150-A8	Beam Angle	120°
Watts	150W	CRI	Ra>70
Input Voltage	AC : 100-240V	IP Rating	IP66
Flux	21000lm	Protection	Class 1

SKU: 9198
5700K

180W

25200
Lumens

Product code	SL180-A8	Beam Angle	120°
Watts	180W	CRI	Ra>70
Input Voltage	AC : 100-240V	IP Rating	IP66
Flux	25200lm	Protection	Class 1

SKU: 9199
5700K



Adjusting angle



LED STREET LIGHT PF>0.9
2 pcs BOX



2 PCS
BOX



5 Years
Warranty



HIGH
Lumens



120°




IP65

50W



7500
Lumens

Product code	SL50-A2	Beam Angle	120°
Watts	50W	CRI	Ra>70
Input Voltage	AC : 100-240V	IP Rating	IP65
Flux	7500lm	Protection	Class 1



SKU: 9157
■ 5700K



LED STREET LIGHT PF>0.9
2 pcs BOX



HIGH
Lumens



120°




IP65

20W



2000
Lumens

Product code	SL20-A1	Beam Angle	120°
Watts	20W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	2000lm	Protection	Class 2




SKU: 9171
■ 6000K

50W



5000
Lumens

Product code	SL50-A1	Beam Angle	120°
Watts	50W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	5000lm	Protection	Class 2




SKU: 9172
■ 6000K

80W



8000
Lumens

Product code	SL80-A1	Beam Angle	120°
Watts	80W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	8000lm	Protection	Class 2



SKU: 9173
■ 6000K






LED STREET LIGHT **PF>0.9**
Bridgelux 3030 Chips

5 Years Warranty
 HIGH Lumens
 120° Beam Angle
 IP65 Protection

150W
 14250 Lumens


Product code	SL150-A3	Beam Angle	120°
Watts	150W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	14250lm	Protection	Class 1



SKU: 9181
 5700K

200W
 19000 Lumens

Product code	SL200-A3	Beam Angle	120°
Watts	200W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	19000lm	Protection	Class 1



SKU: 9182
 5700K

Adapter Matt Grey Φ60mm to Φ40mm

SKU: 9118



Adapter Φ60mm to Φ60 mm Adjustable Angle 90°

SKU: 9119




LED INDUSTRIAL LIGHTS **PF>0.9**
Stadium Floodlight

5 Years Warranty
 HIGH Lumens
 90° Beam Angle
 IP65 Protection

100W
 10000 Lumens


Product code	SL100-A5	Beam Angle	90°
Watts	100W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	10000lm	Protection	Class 1



SKU: 9175
 5700K

150W
 16500 Lumens


Product code	SL150-A5	Beam Angle	90°
Watts	150W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	16500lm	Protection	Class 1



SKU: 9176
 5700K

240W
 26400 Lumens


Product code	SL240-A5	Beam Angle	90°
Watts	240W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	26400lm	Protection	Class 1



SKU: 9177
 5700K

480W
 68000 Lumens

Product code	SL480-A5	Beam Angle	90°
Watts	480W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	68000lm	Protection	Class 1



SKU: 9178
 5700K



NEW



PREMIUM LINE

LED INDUSTRIAL LIGHTS **PF>0.9**


UFO High Bay



100W

15000
Lumens

Watts	100W	Beam Angle	90°
Input Voltage	AC :180-265V	IP Rating	IP65
Flux	15000lm	Body Color	Black




SKU: 8227
6000K SKU: 8248
6000K

150W

30000
Lumens

Watts	150W	Beam Angle	90°
Input Voltage	AC :180-265V	IP Rating	IP65
Flux	30000lm	Body Color	Black




SKU: 8228
6000K SKU: 8249
6000K

200W

45000
Lumens

Watts	200W	Beam Angle	90°
Input Voltage	AC :180-265V	IP Rating	IP65
Flux	45000lm	Body Color	Black



SKU: 8229
6000K SKU: 8250
6000K



NEW



LED INDUSTRIAL LIGHTS **PF>0.9**


UFO High Bay



50W

5000
Lumens

Watts	50W	Beam Angle	120°
Input Voltage	AC :180-265V	IP Rating	IP65
Flux	5000lm	Body Color	Black




SKU: 8239
6000K SKU: 8240
4000K

100W

10000
Lumens

Watts	100W	Beam Angle	120°
Input Voltage	AC :180-265V	IP Rating	IP65
Flux	10000lm	Body Color	Black




SKU: 8241
6000K SKU: 8242
4000K

150W

15000
Lumens

Watts	150W	Beam Angle	120°
Input Voltage	AC :180-265V	IP Rating	IP65
Flux	15000lm	Body Color	Black




SKU: 8243
6000K SKU: 8244
4000K

200W

20000
Lumens

Watts	200W	Beam Angle	120°
Input Voltage	AC :180-265V	IP Rating	IP65
Flux	20000lm	Body Color	Black




SKU: 8245
6000K SKU: 8246
4000K

300W

30000
Lumens

Watts	300W	Beam Angle	120°
Input Voltage	AC :180-265V	IP Rating	IP65
Flux	30000lm	Body Color	Black



SKU: 8247
6000K




LED INDUSTRIAL LIGHTS **PF>0.9**
SLIM LINE



50W

5000
Lumens

Watts	50W	Beam Angle	90°
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	5000lm	Body Color	Grey




SKU: 8231 SKU: 8232
6000K 4500K

100W

10000
Lumens

Watts	100W	Beam Angle	90°
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	10000lm	Body Color	Grey




SKU: 8233 SKU: 8234
6000K 4500K

150W

15000
Lumens

Watts	150W	Beam Angle	90°
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	15000lm	Body Color	Grey




SKU: 8235 SKU: 8236
6000K 4500K

200W

20000
Lumens

Watts	200W	Beam Angle	90°
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	20000lm	Body Color	Grey



SKU: 8237 SKU: 8238
6000K 4500K


LED INDUSTRIAL LIGHTS **PF>0.9**
High Lumens



100W

10000
Lumens

Product code	HB100-B1	Beam Angle	90°
Watts	100W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	10000lm	Body Color	Black




SKU: 8221 White Light 6000K
SKU: 8222 Neutral Light 4500K

150W

15000
Lumens

Product code	HB150-B1	Beam Angle	90°
Watts	150W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	15000lm	Body Color	Black




SKU: 8223 White Light 6000K
SKU: 8224 Neutral Light 4500K

200W

20000
Lumens

Product code	HB200-B1	Beam Angle	90°
Watts	200W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	20000lm	Body Color	Black



SKU: 8225 White Light 6000K
SKU: 8226 Neutral Light 4500K




LED INDUSTRIAL LIGHT HIGH LUMEN
HIGH BAY PF>0.9



100W
18000
Lumens


Product code	HB110-A1	Beam Angle	90°
Watts	100W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	18000lm	Protection	Class 1



SKU: 8190
■ 5700K

150W
27000
Lumens


Product code	HB150-A3	Beam Angle	90°
Watts	150W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	27000lm	Protection	Class 1



SKU: 8191
■ 5700K

200W
36000
Lumens

Product code	HB210-A1	Beam Angle	90°
Watts	200W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	36000lm	Protection	Class 1



SKU: 8192
■ 5700K




LED INDUSTRIAL LIGHT
HIGH BAY UFO PF>0.9



100W
11000
Lumens


Product code	HB100-A5	Beam Angle	90°
Watts	100W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	11000lm	Protection	Class 1



SKU: 8140
■ 5700K

200W
22000
Lumens

Product code	HB200-A5	Beam Angle	90°
Watts	200W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	22000lm	Protection	Class 1




SKU: 8126
■ 5700K


LED INDUSTRIAL LIGHT
HIGH BAY - UFO - 90°
50W

5000
 Lumens


Product code	HB50-A8	Beam Angle	90°
Watts	50W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	5000lm	Protection	Class 1


 SKU: 8201 SKU: 8202
 6000K 4500K

LED INDUSTRIAL LIGHT
HIGH BAY - UFO - 120°
50W


5000
 Lumens

Product code	HB50-A8	Beam Angle	120°
Watts	50W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	5000lm	Protection	Class 1


 SKU: 8211 SKU: 8212
 6000K 4500K
100W


10000
 Lumens

Product code	HB100-A8	Beam Angle	90°
Watts	100W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	10000lm	Protection	Class 1


 SKU: 8203 SKU: 8204
 6000K 4500K
100W


10000
 Lumens

Product code	HB100-A8	Beam Angle	120°
Watts	100W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	10000lm	Protection	Class 1


 SKU: 8213 SKU: 8214
 6000K 4500K
150W


15000
 Lumens

Product code	HB150-A8	Beam Angle	90°
Watts	150W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	15000lm	Protection	Class 1


 SKU: 8205 SKU: 8206
 6000K 4500K
150W


15000
 Lumens

Product code	HB150-A8	Beam Angle	120°
Watts	150W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	15000lm	Protection	Class 1


 SKU: 8215 SKU: 8216
 6000K 4500K
200W


20000
 Lumens

Product code	HB200-A8	Beam Angle	90°
Watts	200W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	20000lm	Protection	Class 1


 SKU: 8207 SKU: 8208
 6000K 4500K
200W

20000
 Lumens

Product code	HB200-A8	Beam Angle	120°
Watts	200W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	20000lm	Protection	Class 1


 SKU: 8217 SKU: 8218
 6000K 4500K




LED INDUSTRIAL LIGHT
HIGH BAY - UFO 2 - 90°



LED INDUSTRIAL LIGHT
HIGH BAY - UFO 2 - 120°




100W 8500 Lumens	Product code	HB100-A6	Beam Angle	90°
	Watts	100W	CRI	Ra>70
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	8500lm	Protection	Class 1




SKU: 8168 SKU: 8169
 6000K 4500K

100W 8500 Lumens	Product code	HB100-A6	Beam Angle	120°
	Watts	100W	CRI	Ra>70
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	8500lm	Protection	Class 1




SKU: 8177
 4500K

150W 12750 Lumens	Product code	HB150-A6	Beam Angle	90°
	Watts	150W	CRI	Ra>70
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	12750lm	Protection	Class 1




SKU: 8170 SKU: 8171
 6000K 4500K

150W 12750 Lumens	Product code	HB150-A6	Beam Angle	120°
	Watts	150W	CRI	Ra>70
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	12750lm	Protection	Class 1



SKU: 8178 SKU: 8179
 6000K 4500K

200W 17000 Lumens	Product code	HB200-A6	Beam Angle	90°
	Watts	200W	CRI	Ra>70
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	17000lm	Protection	Class 1



SKU: 8172
 6000K




LED INDUSTRIAL LIGHT

Linear High Bay



50W
5000
Lumens


Product code	HB50-A2	Beam Angle	120*60°
Watts	50W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP44
Flux	5000lm	Body Color	Class 1



SKU: 8151
6000K 4500K

100W
10000
Lumens


Product code	HB100-A2	Beam Angle	120*60°
Watts	50W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP44
Flux	10000lm	Body Color	Black



SKU: 8153 8154
6000K 4500K

150W
15000
Lumens


Product code	HB150-A2	Beam Angle	120*60°
Watts	50W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP44
Flux	15000lm	Body Color	Black



SKU: 8155 8156
6000K 4500K

200W
20000
Lumens

Product code	HB200-A2	Beam Angle	120*60°
Watts	50W	CRI	Ra>70
Input Voltage	AC : 220-240V	IP Rating	IP44
Flux	20000lm	Body Color	Black



SKU: 8157 8158
6000K 4500K




LED INDUSTRIAL Bulb **PF>0.9**
40W E27



Product code	HB40-A1	Socket	E27
Watts	40W	CRI	Ra>80
Input Voltage	AC : 180-264V	IP Rating	IP20
Flux	4100lm	Dimension	ø90x212 mm
Beam Angle	270°	Dimmable	NO

SKU: 225 226
6000K 4500K





LED INDUSTRIAL Bulb **PF>0.9**
50W E40



Product code	HB50-A3	Socket	E40
Watts	50W	CRI	Ra>70
Input Voltage	AC : 110-264V	IP Rating	IP20
Flux	5000lm	Dimension	ø75x235 mm
Beam Angle	270°	Dimmable	NO


SKU: 221
6000K






LED Wall Washers
30°

9W 700 Lumens	Product code	WW9-A1	Beam Angle	30°
	Watts	9W	CRI	Ra>70
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	700lm	Body Color	Black




SKU: 7134 6000K
SKU: 7131 2700K

18W 1400 Lumens	Product code	WW18-A1	Beam Angle	30°
	Watts	18W	CRI	Ra>70
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	1400lm	Protection	Black



SKU: 7135 6000K
SKU: 7132 2700K

36W 2800 Lumens	Product code	WW36-A1	Beam Angle	30°
	Watts	36W	CRI	Ra>70
	Input Voltage	AC : 220-240V	IP Rating	IP65
	Flux	2800lm	Protection	Black



SKU: 7136 6000K
SKU: 7133 2700K

NEW



LED Mirror/Wall Light
14W



Watts	14W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP20
Flux	910lm	Dimension	595 mm
Beam Angle	120°	Body Color	White
Material	Aluminium	Dimmable	NO

SKU: 7551 4000K
SKU: 7552 3000K



NEW



LED Mirror/Wall Light
14W




Watts	14W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP20
Flux	910lm	Dimension	595 mm
Beam Angle	120°	Body Color	Black
Material	Aluminium	Dimmable	NO

SKU: 7553 4000K
SKU: 7554 3000K





LED WALL AND STEP LIGHTS




You can even make your outdoor areas radiate in the worst of weather conditions: Our exterior use wall lights are robust, energy-efficient and powerful. You can choose between different designs and set stylish accents.

Features:

- Up to 80% power saving
- Home, garden or park use
- Different forms, shapes and colours
- Discrete, spot or main lighting
- Easy installation and long lifecycle
- With or without bulbs

Application:

- Wall or pylon mountable
- Lanes, alleys or pathways
- Gardens and parks




 LED Wall Light - Black
2 Lens 4W


Watts	4W
Input Voltage	AC : 200-240V
Flux	340lm
Beam Angle	48°
Material	Aluminium

CRI	Ra>80
IP Rating	IP65
Dimension	106x80x38 mm
Body Color	Black
Dimmable	NO

 SKU: 7407
 3000K

 LED Wall Light - Black
2 Lens 4W


Watts	4W
Input Voltage	AC : 200-240V
Flux	340lm
Beam Angle	48°
Material	Aluminium

CRI	Ra>80
IP Rating	IP65
Dimension	106x80x38 mm
Body Color	White
Dimmable	NO

 SKU: 7408
 3000K

 LED Wall Light - Black
3 Lens 6W


Watts	6W
Input Voltage	AC : 200-240V
Flux	510lm
Beam Angle	48°
Material	Aluminium

CRI	Ra>80
IP Rating	IP65
Dimension	158x80x40 mm
Body Color	Black
Dimmable	NO

 SKU: 7409
 3000K

 LED Wall Light - Black
3 Lens 6W


Watts	6W
Input Voltage	AC : 200-240V
Flux	510lm
Beam Angle	48°
Material	Aluminium

CRI	Ra>80
IP Rating	IP65
Dimension	158x80x40 mm
Body Color	White
Dimmable	NO

 SKU: 7410
 3000K

 LED Wall Light - Black
2 Lens 8W


Watts	8W
Input Voltage	AC : 200-240V
Flux	680lm
Beam Angle	48°
Material	Aluminium

CRI	Ra>80
IP Rating	IP65
Dimension	210x80x48 mm
Body Color	Black
Dimmable	NO

 SKU: 7411
 3000K

 LED Wall Light - Black
2 Lens 8W


Watts	8W
Input Voltage	AC : 200-240V
Flux	680lm
Beam Angle	48°
Material	Aluminium

CRI	Ra>80
IP Rating	IP65
Dimension	210x80x48 mm
Body Color	White
Dimmable	NO

 SKU: 7412
 3000K

LED Wall Light
12W


Watts	12W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP20
Flux	600lm	Dimension	315x90x30mm
Beam Angle	160°	Body Color	WHITE
Material	Aluminium	Dimmable	NO

 SKU: 2095

LED Wall Light
12W


Watts	12W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP65
Flux	1200lm	Dimension	ø160x60mm
Beam Angle	90°	Body Color	White
Material	Plastic	Dimmable	NO

 SKU: 2089

LED Wall Light
12W


Watts	12W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP20
Flux	600lm	Dimension	315x90x30mm
Beam Angle	160°	Body Color	BLACK
Material	Aluminium	Dimmable	NO

 SKU: 2096

LED Wall Light
12W


Watts	12W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP65
Flux	1200lm	Dimension	ø160x60mm
Beam Angle	90°	Body Color	BLACK
Material	Plastic	Dimmable	NO

 SKU: 2090

LED Solar Wall Light
1W


Watts	1W	CRI	Ra>80
Voltage	5.5V	IP Rating	IP44
Flux	60lm	Dimension	ø85x238mm
Beam Angle	80°	Body Color	White
Battery	3.7V/18Ah	Dimmable	NO

 SKU: 2085 SKU: 2086


LED Wall Light - Aluminium
12W


Watts	12W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP65
Flux	670lm	Dimension	ø150x46mm
Beam Angle	90°	Body Color	WHITE
Material	Aluminium	Dimmable	NO

 SKU: 2091

LED Solar Wall Light
1W


Watts	1W	CRI	Ra>80
Voltage	5.5V	IP Rating	IP44
Flux	60lm	Dimension	ø85x238mm
Beam Angle	80°	Body Color	Black
Battery	3.7V/18Ah	Dimmable	NO

 SKU: 2087 SKU: 2088


LED Wall Light - Aluminium
12W


Watts	12W	CRI	Ra>80
Input Voltage	AC : 200-240V	IP Rating	IP65
Flux	670lm	Dimension	ø150x46mm
Beam Angle	90°	Body Color	BLACK
Material	Aluminium	Dimmable	NO

 SKU: 2092


LED Wall / Ceiling Light

15W

Watts	15W
Input Voltage	AC : 220-240V
Flux	80lm
Beam Angle	120°
Shape	Round


SKU: 7529 SKU: 7528
 ■ 4200K ■ 3000K

CRI	Ra>80
IP Rating	IP65
Dimension	ø169x100 mm
Body Color	BLACK
Dimmable	NO

750
Lumens

120°


IP65



750
Lumens

120°

IP65



LED Wall / Ceiling Light

15W

Watts	15W
Input Voltage	AC : 220-240V
Flux	80lm
Beam Angle	120°
Shape	Square

SKU: 7531 SKU: 7530
 ■ 4200K ■ 3000K

CRI	Ra>80
IP Rating	IP65
Dimension	160x160x100 mm
Body Color	BLACK
Dimmable	NO

LED Wall / Ceiling Light

15W

Watts	15W
Input Voltage	AC : 220-240V
Flux	1000lm
Beam Angle	145°
Shape	Round


SKU: 7533 SKU: 7532
 ■ 4200K ■ 3000K

CRI	Ra>80
IP Rating	IP65
Dimension	ø169x100 mm
Body Color	BLACK
Dimmable	NO

1000
Lumens

145°

IP65



LED Wall / Ceiling Light

15W

Watts	15W
Input Voltage	AC : 220-240V
Flux	1000lm
Beam Angle	145°
Shape	Square


SKU: 7535 SKU: 7534
 ■ 4200K ■ 3000K

CRI	Ra>80
IP Rating	IP65
Dimension	160x160x100 mm
Body Color	BLACK
Dimmable	NO

1000
Lumens

145°

IP65



LED Solar Wall Light

16W

Watts	16W
Input Voltage	220-240V
Flux	1120lm
Beam Angle	90°
Material	Aluminium
CRI	Ra>80
IP Rating	IP20
Dimension	800x60x100mm
Dimmable	NO

SKU: 2093 SKU: 2094
 ■ 4200K ■ 3000K

1120
Lumens

90°

IP20



LED Wall Light

9W

Product code	WL9-A1
Watts	12W
Input Voltage	AC : 200-240V
Flux	780lm
Beam Angle	6°
Shape	Single Head
CRI	Ra>80
IP Rating	IP54
Dimension	230x110x76
Body Color	BLACK
Dimmable	NO

SKU: 7404 SKU: 7403
 ■ 4000K ■ 3000K

780
Lumens

6°

IP54



LED BULKHEAD WALL LIGHT

12W

Product code	WL12-A3
Watts	12W
Input Voltage	AC : 220-240V
Flux	780lm
Beam Angle	120°
Shape	Rectangle
CRI	Ra>80
IP Rating	IP65
Dimension	230x110x76mm
Body Color	GREY
Dimmable	NO

SKU: 7527 SKU: 7526
 ■ 4200K ■ 3000K

780
Lumens

120°


IP65




LED Wall Light
6W


Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	660lm	Dimension	110x54x97
Beam Angle	120°	Body Color	WHITE
Shape	Single Head	Dimmable	NO

Rotatable 355°


 SKU: 7478 SKU: 7475
 4000K 3000K

LED Wall Light
2x6W


Watts	12W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	1320lm	Dimension	221x54x97mm
Beam Angle	120°	Body Color	WHITE
Shape	Double Head	Dimmable	NO


Rotatable 355°


 SKU: 7484 SKU: 7481
 4000K 3000K

LED Wall Light
6W


Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	660lm	Dimension	110x54x97
Beam Angle	120°	Body Color	BLACK
Shape	Single Head	Dimmable	NO

Rotatable 355°


 SKU: 7479 SKU: 7476
 4000K 3000K

LED Wall Light
2x6W


Watts	12W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	1320lm	Dimension	221x54x97mm
Beam Angle	120°	Body Color	BLACK
Shape	Double Head	Dimmable	NO


Rotatable 355°


 SKU: 7485 SKU: 7482
 4000K 3000K

LED Wall Light
6W


Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	660lm	Dimension	110x54x97
Beam Angle	120°	Body Color	GREY
Shape	Single Head	Dimmable	NO

Rotatable 355°


 SKU: 7480 SKU: 7477
 4000K 3000K

LED Wall Light
2x6W


Watts	12W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	1320lm	Dimension	221x54x97mm
Beam Angle	120°	Body Color	GREY
Shape	Double Head	Dimmable	NO

Rotatable 355°


 SKU: 7486 SKU: 7483
 4000K 3000K




LED Wall Light
6W



Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	660lm	Dimension	90x90x200mm
Beam Angle	Up 15°-Down 90°	Body Color	WHITE
Shape	Triangle	Dimmable	NO

SKU: 7472 SKU: 7469
■ 4200K ■ 3000K




LED Wall Light
6W



Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	660lm	Dimension	140x115x100mm
Beam Angle	0°- 90°	Body Color	WHITE
Shape	Round	Dimmable	NO

SKU: 7466 SKU: 7463
■ 4000K ■ 3000K




LED Wall Light
6W



Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	660lm	Dimension	90x90x200mm
Beam Angle	Up 15°-Down 90°	Body Color	BLACK
Shape	Triangle	Dimmable	NO

SKU: 7473 SKU: 7470
■ 4200K ■ 3000K




LED Wall Light
6W



Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	660lm	Dimension	140x115x100mm
Beam Angle	0°- 90°	Body Color	BLACK
Shape	Round	Dimmable	NO

SKU: 7467 SKU: 7464
■ 4000K ■ 3000K




LED Wall Light
6W



Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	660lm	Dimension	90x90x200mm
Beam Angle	Up 15°-Down 90°	Body Color	GREY
Shape	Triangle	Dimmable	NO

SKU: 7474 SKU: 7471
■ 4200K ■ 3000K




LED Wall Light
6W




Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	660lm	Dimension	140x115x100mm
Beam Angle	0°- 90°	Body Color	GREY
Shape	Roun	Dimmable	NO

SKU: 7468 SKU: 7465
■ 4000K ■ 3000K





LED Wall Light
6W



WHITE
SKU: 7454 SKU: 7451
4000K 3000K


BLACK
SKU: 7455 SKU: 7452
4000K 3000K

GREY
SKU: 7456 SKU: 7453
4000K 3000K

Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	660lm	Dimension	100x100 mm
Beam Angle	0°-90°	Body Colors	White ; Black ; Grey
Shape	Square	Dimmable	NO



LED Wall Light
12W




WHITE
SKU: 7460 SKU: 7457
4000K 3000K


BLACK
SKU: 7461 SKU: 7458
4000K 3000K

GREY
SKU: 7462 SKU: 7459
4000K 3000K

Watts	12W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	1320lm	Dimension	100x100 mm
Beam Angle	0°-90°	Body Colors	White ; Black ; Grey
Shape	Square	Dimmable	NO



LED Wall Light
4W-4 Beam




WHITE
SKU: 7490 SKU: 7487
4000K 3000K


BLACK
SKU: 7491 SKU: 7488
4000K 3000K

GREY
SKU: 7492 SKU: 7489
4000K 3000K

Watts	4W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	440lm	Dimension	ø110x93 mm
Beam Angle	90°	Body Colors	White ; Black ; Grey
Shape	Round	Dimmable	NO



LED Wall Light
6W-2 Beam



WHITE
SKU: 7496 SKU: 7493
4000K 3000K

BLACK
SKU: 7497 SKU: 7494
4000K 3000K

GREY
SKU: 7498 SKU: 7495
4000K 3000K


Watts	6W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP54
Flux	660lm	Dimension	ø110x93 mm
Beam Angle	90°	Body Colors	White ; Black ; Grey
Shape	Round	Dimmable	NO


LED STEP LIGHT
2W Round

Watts 2W
 Input Voltage AC : 220-240V
 Flux 80lm
 Beam Angle 55°
 Shape Round

CRI Ra>80
 IP Rating IP65
 Dimension ϕ 150x27 mm
 Body Color BLACK
 Dimmable NO


SKU: 7504 SKU: 7503
■ 4200K ■ 3000K


LED STEP LIGHT
2W Square

Watts 2W
 Input Voltage AC : 220-240V
 Flux 80lm
 Beam Angle 55°
 Shape Square

CRI Ra>80
 IP Rating IP65
 Dimension 124x124x27mm
 Body Color BLACK
 Dimmable NO


SKU: 7510 SKU: 7509
■ 4200K ■ 3000K


LED STEP LIGHT
2W Round

Watts 2W
 Input Voltage AC : 220-240V
 Flux 80lm
 Beam Angle 55°
 Shape Round

CRI Ra>80
 IP Rating IP65
 Dimension ϕ 150x27 mm
 Body Color WHITE
 Dimmable NO


SKU: 7506 SKU: 7505
■ 4200K ■ 3000K


LED STEP LIGHT
2W Square

Watts 2W
 Input Voltage AC : 220-240V
 Flux 80lm
 Beam Angle 55°
 Shape Square

CRI Ra>80
 IP Rating IP65
 Dimension 124x124x27mm
 Body Color WHITE
 Dimmable NO



SKU: 7512 SKU: 7511
■ 4200K ■ 3000K


LED STEP LIGHT
2W Round

Watts 2W
 Input Voltage AC : 220-240V
 Flux 80lm
 Beam Angle 55°
 Shape Round

CRI Ra>80
 IP Rating IP65
 Dimension ϕ 150x27 mm
 Body Color GREY
 Dimmable NO


SKU: 7508 SKU: 7507
■ 4200K ■ 3000K


LED STEP LIGHT
2W Square

Watts 2W
 Input Voltage AC : 220-240V
 Flux 80lm
 Beam Angle 55°
 Shape Square

CRI Ra>80
 IP Rating IP65
 Dimension 124x124x27mm
 Body Color GREY
 Dimmable NO

SKU: 7514 SKU: 7513
■ 4200K ■ 3000K




LED STEP LIGHT

3W Rectangular

Watts	3W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	100lm	Dimension	280x280x28 mm
Beam Angle	65°	Body Color	BLACK
Shape	Rectangular	Dimmable	NO

SKU: 7516 SKU: 7515
 ■ 4200K ■ 3000K




LED STEP LIGHT

3W Round

Watts	3W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	90lm	Dimension	ø80x51 mm
Beam Angle	34°	Body Color	WHITE
Shape	Round	Dimmable	NO

SKU: 7523 SKU: 7522
 ■ 4200K ■ 3000K




LED STEP LIGHT

3W Rectangular

Watts	3W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	100lm	Dimension	280x280x28 mm
Beam Angle	65°	Body Color	WHITE
Shape	Rectangular	Dimmable	NO

SKU: 7518 SKU: 7517
 ■ 4200K ■ 3000K




LED STEP LIGHT

3W Square

Watts	3W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	90lm	Dimension	80x80x51 mm
Beam Angle	34°	Body Color	WHITE
Shape	Square	Dimmable	NO

SKU: 7525 SKU: 7524
 ■ 4200K ■ 3000K




LED STEP LIGHT

3W Rectangular

Watts	3W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	100lm	Dimension	280x280x28 mm
Beam Angle	65°	Body Color	GREY
Shape	Rectangular	Dimmable	NO

SKU: 7520 SKU: 7519
 ■ 4200K ■ 3000K




LED STEP LIGHT

3W Square

Watts	3W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP65
Flux	195lm	Dimension	84x27 mm
Beam Angle	58°	Body Color	WHITE
Shape	Square	Dimmable	NO

SKU: 7521
 ■ 4200K




LED CABINET LIGHT
Slim Fit 1.5W
100
 Lumens

 IP20

Voltage	DC:5V	CRI	Ra>80
Flux	100lm	IP Rating	IP20
Beam Angle	120°	Body Color	Black
Battery	3.7V 0.9Ah	Dimension	240x40x10mm

 SKU: 240
 3000K


Battery Sensor


LED CABINET LIGHT
Slim Fit 1.5W
100
 Lumens

 IP20

Voltage	DC:5V	CRI	Ra>80
Flux	100lm	IP Rating	IP20
Beam Angle	120°	Body Color	Silver
Battery	3.7V 0.9Ah	Dimension	240x40x10mm

 SKU: 241
 3000K


Battery Sensor


LED CABINET LIGHT
Slim Fit 3.5W
230
 Lumens

 IP20

Voltage	DC:5V	CRI	Ra>80
Flux	100lm	IP Rating	IP20
Beam Angle	120°	Body Color	Black
Battery	3.7V 2.2Ah	Dimension	600x40x10mm

 SKU: 242
 3000K


Battery Sensor



LED CABINET LIGHT
Slim Fit 3.5W
230
 Lumens

 IP20

Voltage	DC:5V	CRI	Ra>80
Flux	100lm	IP Rating	IP20
Beam Angle	120°	Body Color	Silver
Battery	3.7V 2.2Ah	Dimension	600x40x10mm

 SKU: 243
 3000K


Battery Sensor


LED CABINET LIGHT
Slim Fit 1.5W
140
 Lumens

 IP20

Voltage	DC:5V	CRI	Ra>80
Flux	140lm	IP Rating	IP20
Beam Angle	120°	Body Color	Silver
Battery	3.7V 1.1Ah	Dimension	240x40x10mm

 SKU: 230
 4500K

 SKU: 231
 3000K


Battery Sensor


LED CABINET LIGHT
Slim Fit 2.5W
200
 Lumens

 IP20

Voltage	DC:5V	CRI	Ra>80
Flux	200lm	IP Rating	IP20
Beam Angle	180°	Body Color	Silver
Battery	3.7V 2Ah	Dimension	240x40x10mm

 SKU: 230
 CCT
 6000K 4500K 3000K


Battery Sensor


LED CABINET LIGHT
Magnetic Control 0.5W
40
 Lumens

 IP20

Voltage	DC:1.5V	CRI	Ra>80
Flux	40lm	IP Rating	IP20
Beam Angle	120°	Body Color	Silver
Battery	2*AAA	Dimension	64x43x15mm

 SKU: 233
 4500K

 SKU: 234
 3000K


2*AAA Battery


LED CABINET LIGHT
Hanging/Stand 0.5W
40
 Lumens

 IP20


Voltage	DC:1.5V	CRI	Ra>80
Flux	40lm	IP Rating	IP20
Beam Angle	120°	Body Color	Silver
Battery	3*AAA	Dimension	φ80x23mm

 SKU: 235
 4500K

 SKU: 236
 3000K


3*AAA Battery

Sensor



Step outside with our great range of outdoor lighting solutions. Whether you're looking to light up your garden with exterior use wall lights or increase your home's safety with security lights.

Features:

- Up to 80% power saving
- garden or park use
- Different forms, shapes and colours
- Discrete, spot or main lighting
- With or without bulbs

Application:

- Wall or pylon mountable
- Lanes, alleys or pathways
- Gardens and parks



LED OUTDOOR LIGHT

LED OUTDOOR LIGHT

LED SOLAR WALL LIGHT

Solar Panel Power: 5.5V 1.8W

500
Lumens

IP54


Voltage	5.5V	CRI	Ra>80
Flux	500lm	IP Rating	IP54
Beam Angle	60°	Body Color	Black
Battery	3.2V 2Ah	Dimension	160x130x28mm

 SKU: 7541
 6000K


LED WALL LAMP 7W

Aluminium Body

490
Lumens

IP54


Power	7W	CRI	Ra>80
Voltage	AC: 220-240V	IP Rating	IP54
Flux	490lm	Body Color	Black
Beam Angle	60°	Dimension	160x130x28mm

 SKU: 9343
 2700K

LED SOLAR WALL LIGHT

Solar Panel Power: 5.5V 5W

1000
Lumens

IP54


Voltage	5.5V	CRI	Ra>80
Flux	1000lm	IP Rating	IP54
Beam Angle	60°	Body Color	Black
Battery	3.2V 4Ah	Dimension	350x140x28mm

 SKU: 7542
 6000K


LED SOLAR WALL LIGHT

9W

400
Lumens

IP44


Voltage	5V	CRI	Ra>80
Flux	400lm	IP Rating	IP54
Beam Angle	110°	Body Color	Dark Grey
Battery	3.7V 2Ah	Dimension	160x130x190mm

 SKU: 9345
 3000K


LED SOLAR WALL LIGHT

Solar Panel Power: 5V 12.5W

1200
Lumens

IP54


Voltage	5V	CRI	Ra>80
Flux	1200lm	IP Rating	IP54
Beam Angle	60°	Body Color	Black
Battery	3.2V 6Ah	Dimension	350x266x28mm

 SKU: 7543
 6000K


LED SOLAR WALL LIGHT

9W

400
Lumens

IP54


Voltage	5V	CRI	Ra>80
Flux	400lm	IP Rating	IP44
Beam Angle	110°	Body Color	Dark Grey
Battery	3.7V 2Ah	Dimension	180x120x127mm

 SKU: 9347
 3000K




SKU: 7422 Stainless Steel



SKU: 7423 Stainless Steel

Wall Lamp Fitting
E27 Holder

Product code	WL1-A1	IP Rating	IP44
Socket	E27	Dimension	303x100x91 mm
Input Voltage	AC : 220-240V	Body Colors	Stainless Steel
Material	Aluminium	Max Power	16W



E27 Holder



IP44

Wall Lamp Fitting
E27 Holder

Product code	WL1-A1	IP Rating	IP44
Socket	E27	Dimension	245x180x93 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium+Glass	Max Power	60W



E27 Holder



IP44

SKU: 7401 Black Body

SKU: 7402 White Body


LED Wall Light Fitting
GU10 Socket

Product code	WL2-A3
Socket	GU10
Input Voltage	AC : 220-240V
Material	Aluminium

IP Rating	IP44
Dimension	100x66x92 mm
Body Colors	Black ; White ; Silver
Max Power	35W



GU10 Holder



IP44

SKU: 7443 Black Body

SKU: 7444 White Body

SKU: 7445 Silver Body


Wall Lamp Fitting
E27 Holder

Product code	WL1-A1	IP Rating	IP44
Socket	E27	Dimension	245x180x93 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium+Glass	Max Power	60W



E27 Holder



IP44

SKU: 7401 Black Body

SKU: 7402 White Body


LED Wall Light Fitting
Two GU10 Sockets

Product code	WL2-A4
Socket	2xGU10
Input Voltage	AC : 220-240V
Material	Aluminium

IP Rating	IP44
Dimension	92x68x150 mm
Body Colors	Black ; White ; Silver
Max Power	2x35W



GU10 Holder



IP44

SKU: 7446 Black Body

SKU: 7447 White Body

SKU: 7448 Silver Body


LED Wall Light Fitting
GU10 Socket


Product code	WL2-A1	IP Rating	IP54
Socket	GU10	Dimension	92x68x80 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White ; Silver ; Polished
Material	Aluminium	Max Power	35W

SKU: 7431	Black Body
SKU: 7432	White Body
SKU: 7433	Silver Body
SKU: 7449	Polished


LED Wall Light Fitting
GU10 Socket


Product code	WL2-A1	IP Rating	IP54
Socket	GU10	Dimension	100x66x92 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White ; Grey
Material	Aluminium	Max Power	35W

SKU: 7434	Black Body
SKU: 7435	White Body
SKU: 7436	Grey Body


LED Wall Light Fitting
Two GU10 Sockets


Product code	WL2-A2	IP Rating	IP54
Socket	2xGU10	Dimension	92x68x150 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White ; Silver ; Polished
Material	Aluminium	Max Power	2x35W

SKU: 7437	Black Body
SKU: 7438	White Body
SKU: 7439	Silver Body
SKU: 7450	Polished


LED Wall Light Fitting
Two GU10 Sockets


Product code	WL2-A2	IP Rating	IP54
Socket	2xGU10	Dimension	92x68x150 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White ; Grey
Material	Aluminium	Max Power	2x35W

SKU: 7440	Black Body
SKU: 7441	White Body
SKU: 7442	Grey Body



LED SOLAR POWER GARDEN LIGHT




LED SOLAR GARDEN LIGHT
Solar Panel Power: 5.5V 0.6W



Voltage	5.5V	CRI	Ra>80
Flux	8lm	IP Rating	IP65
Beam Angle	120°	Body Color	Black
Battery	3.7V 2Ah	Dimension	165x165x31.5mm

Wall Mounted or Pin Mounted



LED SOLAR GARDEN LIGHT
Solar Panel Power: 5.5V 0.6W



Voltage	5.5V	CRI	Ra>80
Flux	8lm	IP Rating	IP65
Beam Angle	120°	Body Color	Black
Battery	3.7V 2Ah	Dimension	165x165x31.5mm

Wall Mounted or Pin Mounted



LED Light Fixture
GU10 Socket



Product code	WL2-A2	IP Rating	IP65
Socket	1xGU10	Dimension	92x68x150 mm
Input Voltage	AC : 220-240V	Body Colors	Black
Material	PC	Max Power	35W

SKU: 2084 GU10-Black



LED SOLAR LAMP
1.5W Lawn Light



Watts	1.5W	CRI	Ra>80
Voltage	6V	IP Rating	IP65
Flux	60lm	Material	Aluminium
Beam Angle	110°	Body Color	Black
Battery	1.2V/1500mAh	Dimension	168x75.5x340 mm

- SKU: 9321 6000K
- SKU: 9322 3000K
- SKU: 9323 Blue Light
- SKU: 9324 Green Light

CHARGING TIME~(7-8) Hours
DETECTION RANGE~8±2m



LED SOLAR LAMP
0.75W Wall Light



Product code	WL2-A6	CRI	Ra>80
Watts	0.75W	IP Rating	IP54
Voltage	5.5V	Material	ABS+PC
Flux	110lm	Body Color	Black
Beam Angle	110°	Dimension	124x95x48mm
Battery	1200mAh		

SKU: 7405 White Light 6000K

CHARGING TIME~(7-8) Hours
DETECTION RANGE~8±2m



LED SOLAR LAMP
1.5W Wall Light



Product code	WL5-A6	CRI	Ra>80
Watts	1.5W	IP Rating	IP54
Voltage	7.4V	Material	ABS+PC
Flux	150lm	Body Color	Black
Beam Angle	110°	Dimension	196x115x45mm
Battery	1200mAh		

SKU: 7406 6000K

CHARGING TIME~(7-8) Hours
DETECTION RANGE~8±2m



LED SOLAR GARDEN LIGHT
Solar Panel Power: 5.5V 1W

60 Lumens IP54

Voltage	5.5V	CRI	Ra>80
Flux	60lm	IP Rating	IP54
Beam Angle	270°	Body Color	Black
Battery	3.7V 1.2Ah	Dimension	180x116x740mm

Table Way or Pin Mounted

SKU: 9349
CCT
6000K 4000K 3000K

Battery Solar Power



LED SOLAR GARDEN LIGHT
Solar Panel Power: 5.5V 1W

60 Lumens IP54

Voltage	5.5V	CRI	Ra>80
Flux	60lm	IP Rating	IP54
Beam Angle	270°	Body Color	Black
Battery	3.7V 1.2Ah	Dimension	230x116x150mm

Table Way or Wall Mounted

SKU: 9350
CCT
6000K 4000K 3000K

Battery Solar Power



LED SOLAR GARDEN LIGHT
Solar Panel Power: 5V 1.8W

70 Lumens IP54

Voltage	5.5V	CRI	Ra>80
Flux	70lm	IP Rating	IP54
Beam Angle	270°	Body Color	Black
Battery	3.7V 1.2Ah	Dimension	160x160x213mm

Remote Control

SKU: 9351
CCT
6000K 4000K 3000K

Battery Solar Power



LED SOLAR WALL LIGHT
0.5W

40 Lumens IP44

Voltage	3.7V	CRI	Ra>80
Flux	40lm	IP Rating	IP44
Beam Angle	120°	Body Color	Black
Battery	3.7V 1.2Ah	Dimension	105x70x40mm

SKU: 9352
3000K

Battery Solar Power



LED SOLAR LIGHT SPIKE
2W

160 Lumens IP65

Voltage	3.7V	CRI	Ra>80
Flux	160lm	IP Rating	IP65
Beam Angle	120°	Body Color	Black
Battery	3.7V 1.8Ah	Dimension	102x169x313mm

Light Brigness Control

SKU: 9353
3000K

Battery Solar Power



LED SOLAR LIGHT SPIKE
1W

80 Lumens IP65

Voltage	3.7V	CRI	Ra>80
Flux	80lm	IP Rating	IP65
Beam Angle	120°	Body Color	Black
Battery	3.7V 1.2Ah	Dimension	φ130x395mm

Light Brigness Control

SKU: 9354
3000K

Battery Solar Power



2 PCS
Box

LED SOLAR LIGHT SPIKE
Solar Panel Power: 5V 1W

90 Lumens IP65

Voltage	3.2V	CRI	Ra>80
Flux	90lm	IP Rating	IP65
Beam Angle	60°	Body Color	Black
Battery	3.2V 1.2Ah	Dimension	φ126x51.8mm

SKU: 9357
6000K



LED LAWN LIGHT 7W
Aluminium Body

490 Lumens IP54

Power	7W	CRI	Ra>80
Voltage	AC: 220-240V	IP Rating	IP54
Flux	490lm	Body Color	Dark Grey
Beam Angle	150°	Dimension	φ123x800mm

SKU: 9344
3000K



2 PCS
Box

LED SOLAR LIGHT SPIKE
Solar Panel Power: 5V 1W

90 Lumens IP65

Voltage	3.2V	CRI	Ra>80
Flux	90lm	IP Rating	IP65
Beam Angle	60°	Body Color	Black
Battery	3.2V 1.2Ah	Dimension	φ126x51.8mm

SKU: 9358
4000K



LED SOLAR LAMP
9W

400 Lumens IP44

Voltage	3.7V	CRI	Ra>80
Flux	400lm	IP Rating	IP44
Beam Angle	110°	Body Color	Dark Grey
Battery	3.7V 2Ah	Dimension	150x195x762mm

SKU: 9346
3000K



2 PCS
Box

LED SOLAR LIGHT SPIKE
Solar Panel Power: 5V 1W

90 Lumens IP65

Voltage	3.2V	CRI	Ra>80
Flux	90lm	IP Rating	IP65
Beam Angle	60°	Body Color	Black
Battery	3.2V 1.2Ah	Dimension	φ126x51.8mm

SKU: 9359
RGB



LED SOLAR LAMP
9W

400 Lumens IP44

Voltage	3.7V	CRI	Ra>80
Flux	400lm	IP Rating	IP44
Beam Angle	110°	Body Color	Dark Grey
Battery	3.7V 2Ah	Dimension	150x195x762mm

SKU: 9346
3000K




LED SOLAR LAMP
2W Wall Light


Watts	2W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	200lm	Material	Aluminium
Beam Angle	110°	Body Color	SS Brushed
Battery	3.7V/1200mAh	Dimension	142x125x188mm

 SKU: 9331
 3000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m

LED SOLAR LAMP
4.4W Wall Light


Watts	4.4W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	600lm	Material	Aluminium
Beam Angle	110°	Body Color	SS Brushed
Battery	3.7V/2600mAh	Dimension	173x160x155mm

 SKU: 9334
 3000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m

LED SOLAR LAMP
2W Lawn Spike


Watts	2W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	200lm	Material	Aluminium
Beam Angle	110°	Body Color	SS Brushed
Battery	3.7V/1200mAh	Dimension	125x125x500mm

 SKU: 9332
 3000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m

LED SOLAR LAMP
4.4W Lawn Spike


Watts	4.4W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	600lm	Material	Aluminium
Beam Angle	110°	Body Color	SS Brushed
Battery	3.7V/2600mAh	Dimension	160x160x500mm

 SKU: 9335
 3000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m

LED SOLAR LAMP
2W Lawn Light


Watts	2W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	200lm	Material	Aluminium
Beam Angle	110°	Body Color	SS Brushed
Battery	3.7V/1200mAh	Dimension	125x125x800mm

 SKU: 9333
 3000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m

LED SOLAR LAMP
4.4W Lawn Light


Watts	4.4W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	600lm	Material	Aluminium
Beam Angle	110°	Body Color	SS Brushed
Battery	3.7V/2600mAh	Dimension	142x125x188mm

 SKU: 9336
 3000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m

LED SOLAR LAMP
4.4W Wall Light


Watts	4.4W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	600lm	Material	Aluminium
Beam Angle	110°	Body Color	SS Brushed
Battery	3.7V/2600mAh	Dimension	162x150x155mm

 SKU: 9337
 3000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m

LED SOLAR LAMP
6W Wall Light


Watts	6W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	600lm	Material	Aluminium
Beam Angle	110°	Body Color	Black
Battery	3.7V/2200mAh	Dimension	173x160x155mm

 SKU: 9340
 6000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m

LED SOLAR LAMP
4.4W Lawn Spike


Watts	4.4W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	600lm	Material	Aluminium
Beam Angle	110°	Body Color	SS Brushed
Battery	3.7V/2600mAh	Dimension	150x150x500mm

 SKU: 9338
 3000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m

LED SOLAR LAMP
6W Lawn Light 50cm


Watts	6W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	600lm	Material	Aluminium
Beam Angle	110°	Body Color	Black
Battery	3.7V/2200mAh	Dimension	150x150x500mm

 SKU: 9341
 6000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m

LED SOLAR LAMP
4.4W Lawn Light


Watts	4.4W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	600lm	Material	Aluminium
Beam Angle	110°	Body Color	SS Brushed
Battery	3.7V/2600mAh	Dimension	150x150x800mm

 SKU: 9339
 3000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m

LED SOLAR LAMP
6W Lawn Light 90cm


Watts	6W	CRI	Ra>80
Voltage	3.7V	IP Rating	IP44
Flux	600lm	Material	Aluminium
Beam Angle	110°	Body Color	Black
Battery	3.7V/2200mAh	Dimension	150x150x900mm

 SKU: 9341
 6000K

 CHARGING TIME~(7-8) Hours
 DETECTION RANGE~8±2m


Wall Lamp Up
E27 Holder


Product code	GD1-A1	IP Rating	IP44
Socket	E27	Dimension	215x170x220 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium+PC	Max Power	60W

SKU: 9301 Black Body
 SKU: 9302 White Body


Stand Lamp
E27 Holder


Product code	GD1-A2	IP Rating	IP44
Socket	E27	Dimension	170x170x290 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium+PC	Max Power	60W

SKU: 9305 Black Body
 SKU: 9306 White Body


Wall Lamp Down
E27 Holder


Product code	GD1-A1	IP Rating	IP44
Socket	E27	Dimension	215x170x220 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium+PC	Max Power	60W

SKU: 9303 Black Body
 SKU: 9304 White Body


Ceiling Lamp
E27 Holder


Product code	GD1-A3	IP Rating	IP44
Socket	E27	Dimension	170x170x740 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium+PC	Max Power	60W

SKU: 9307 Black Body
 SKU: 9308 White Body



Lawn Lamp 60cm
E27 Holder

Product code	GD1-A1	IP Rating	IP44
Socket	E27	Dimension	170x170x600 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium+PC	Max Power	60W



E27 Holder



IP44

SKU: 9309 Black Body

SKU: 9310 White Body



Lawn Lamp 90cm
E27 Holder

Product code	GD1-A1	IP Rating	IP44
Socket	E27	Dimension	170x170x900 mm
Input Voltage	AC : 220-240V	Body Colors	Black ; White
Material	Aluminium+PC	Max Power	60W



E27 Holder



IP44

SKU: 9311 Black Body

SKU: 9312 White Body



Lawn Lamp
E27 Holder

Product code	GD1-A7	IP Rating	IP54
Socket	E27	Dimension	76x76x800/1000 mm
Input Voltage	AC : 220-240V	Body Colors	Grey
Material	Aluminium+PC	Max Power	16W



E27 Holder



IP54

SKU: 9315 Grey Body 80cm

SKU: 9316 Grey Body 100cm



1W



7W



1W



1.3W

Powerful LED Pond Wall Lights
LED Light 1.3W ; 7W



Product code	UN1-A5	IP Rating	IP68
Power	1.3W ; 7W	Dimension	60 x 60 x 78 mm
Voltage	DC:24V		

- SKU: 590 1W ■ 3000K
- SKU: 856 7W ■ 4200K

Decorative Mini LED Pond Wall Lights
LED Light 1-1.3W



Product code	UN1-A6	IP Rating	IP68
Power	1W -1.3W	Dimension	35 x 28 mm
Voltage	DC:24V		

- SKU: 591 ■ RGB
- SKU: 594 ■ 6000K
- SKU: 595 ■ 3000K



Mini Wall & Floor Lights
LED Light 1.2W

Product code	UN1-A5	IP Rating	IP68
Power	1.2W	Dimension	38 x 30 mm
Voltage	DC:24V		

- SKU: 586 ■ 6000K
- SKU: 587 ■ 3000K
- SKU: 588 ■ Blue
- SKU: 589 ■ RGB



1W



1.3W

Powerful LED Pond Wall Light
LED Light 1W-1.3W

Product code	UN1-A9	IP Rating	IP68
Power	1W-1.3W	Dimension	32 x 44 mm
Voltage	DC:24V		



- SKU: 565 ■ RGB
- SKU: 566 ■ Blue
- SKU: 567 ■ Green
- SKU: 568 ■ Amber



1 Side Beam



2 Side Beam

Mini Directional Ground Lights

LED Light 1.3W

Product code	UN1-A8	IP Rating	IP68
Power	1.3W	Dimension	44 x 43 mm
Voltage	DC:24V		



- SKU: 596 ■ 6000K 1 Side Beam
- SKU: 597 ■ 3000K 1 Side Beam
- SKU: 598 ■ 6000K 2 Side Beam
- SKU: 599 ■ 3000K 2 Side Beam



1W



1.3W

LED Mini Floor Lights

LED Light 1-1.3W

Product code	UN1-A3	IP Rating	IP68
Power	1W -1.3W	Dimension	23 x 40 mm
Voltage	DC:24V		



- SKU: 580 1W ■ 6000K
- SKU: 581 1W ■ 3000K
- SKU: 582 1W ■ Blue
- SKU: 583 1.3W ■ 6000K
- SKU: 584 1.3W ■ 3000K
- SKU: 585 1.3W ■ Blue



LED Spike Lights
LED Light 1.3W

Product code	UN1-A5	IP Rating	IP68
Power	1.3W	Dimension	38 x 30 mm
Voltage	DC:24V		



- SKU: 866 ■ 6000K
- SKU: 867 ■ 4000K
- SKU: 868 ■ 3000K



Sleeve for LED Underground Lights

- SKU: 873 Size - 22*55MM
- SKU: 872 Size - 55*150MM
- SKU: 874 Size - 35*150MM



Mini Ground Lights
HALF-SHADING 1.3W

Product code	UN1-A6	IP Rating	IP68
Power	1.3W	Dimension	60 x 45 mm
Voltage	DC:24V		

- SKU: 592 ■ 6000K
- SKU: 593 ■ 3000K



Mini Recessed Wall Lights
LED Light 1W

Product code	UN1-A6	IP Rating	IP44
Power	1W	Dimension	64 x 43 mm
Voltage	DC:24V		

- SKU: 863 ■ 6000K
- SKU: 864 ■ 4000K
- SKU: 865 ■ 3000K
- SKU: 879 ■ Blue



LED Pool Light
12W PAR56

 1200 Lumens
 90°
 IP68

Product code PL12-A1
 Watts 12W
 Input Voltage AC/DC :12V
 Flux 1200lm
 Beam Angle 90°
 Socket PAR56

CRI Ra>80
 IP Rating IP68
 Dimension ø178x114 mm
 Body Glass
 Dimmable NO

SKU: 571 6000K

SKU: 572 2700K

Chips

LED Pool Light
12W PAR56

 RGB
 1200 Lumens
 90°
 IP68

Product code PL12-A1
 Watts 12W
 Input Voltage AC/DC :12V
 Flux 1200lm
 Beam Angle 90°
 Socket PAR56

CRI Ra>80
 IP Rating IP68
 Dimension ø178x114 mm
 Body Glass
 Dimmable NO

SKU: 573

Chips


With Remote


LED Outdoor Light
1W Spotlight


 80 Lumens
 ø58mm
 18°
 IP65

Watts 1W
 Input Voltage AC : 220-245V
 Flux 80lm
 Beam Angle 18°

CRI Ra>80
 IP Rating IP65
 Dimension ø65x78mm
 Body Color Stainless steel

SKU: 507 6000K

SKU: 517 2800K


LED Outdoor Light
3W Spotlight


 240 Lumens
 ø90mm
 18°
 IP65

Watts 3W
 Input Voltage AC : 220-245V
 Flux 240lm
 Beam Angle 18°

CRI Ra>80
 IP Rating IP65
 Dimension ø100x82mm
 Body Color Stainless steel

SKU: 501 6000K

SKU: 502 2800K


LED Outdoor Light
5W Spotlight


 400 Lumens
 ø132mm
 18°
 IP65

Watts 5W
 Input Voltage AC : 220-245V
 Flux 400lm
 Beam Angle 18°

CRI Ra>80
 IP Rating IP65
 Dimension ø140x93 mm
 Body Color Stainless steel

SKU: 515 6000K

SKU: 516 2800K


LED Outdoor Light
7W Spotlight


 560 Lumens
 ø132mm
 18°
 IP65

Watts 7W
 Input Voltage AC : 220-245V
 Flux 560lm
 Beam Angle 18°

CRI Ra>80
 IP Rating IP65
 Dimension ø150x93 mm
 Body Color Stainless steel

SKU: 550 6000K

SKU: 551 2800K





Outdoor Solar String Lights- Milky
G50 Bulbs 20 pcs -10 Meters

SKU: 9092
2700K

128 Lumens

Solar Power IP65

Battery
3.7V 0.5Ah

Outdoor Solar String Lights- Clear
G50 Bulbs 20 pcs -10 Meters

SKU: 9093
2700K

128 Lumens

Solar Power IP65

Battery
3.7V 0.5Ah

Outdoor Solar String Lights- Milky
G50 Bulbs 20 pcs - 7 Meters
- 8 Modes

SKU: 9094
2700K

200 Lumens

Solar Power IP65

Battery
3.7V 0.5Ah

Outdoor Solar String Lights- Clear
G50 Bulbs 20 pcs - 7 Meters
- 8 Modes

SKU: 9095
2700K

200 Lumens

Solar Power IP65

Battery
3.7V 0.5Ah


**Outdoor String Lights
E27 Holders**

- * 6 or 14.4 Meters Long String
- * 10 or 15 Pcs E27 Sockets
- * Up to 5A
- * Suspended Sockets
- * IP65
- * Black Color

SKU: 5054 10pcs E27 - 6m
SKU: 5051 15pcs E27 - 14.4m



E27 Holder



IP65



Linkable up to 2 Strings

**Outdoor String Lights
Colourful Bulbs**

- * 8 or 13 Meters Long String
- * 10 or 20 Bulbs included
- * 0.5 Watts Per Bulb
- * IP65
- * Black Color

SKU: 5056 10pcs Bulbs - 8m - 3W Colourful Bulbs
SKU: 5092 20pcs Bulbs - 13m - 6W Colourful Bulbs



IP65


**Outdoor String Lights
E27 Holders**

- * 6 or 14.4 Meters Long String
- * 10 or 15 Pcs E27 Sockets
- * Up to 5A
- * Fixed Sockets
- * IP65
- * White Color

SKU: 5055 10pcs E27 - 6m
SKU: 5053 15pcs E27 - 14.4m



E27 Holder



IP65



Linkable up to 2 Strings

**Outdoor String Lights
Colourful Bulbs**

- * 8 or 13 Meters Long String
- * 10 or 20 Bulbs included
- * 0.5 Watts Per Bulb
- * IP65
- * White Color

SKU: 5090 10pcs Bulbs - 8m - 3W Colourful Bulbs
SKU: 5095 20pcs Bulbs - 13m - 6W Colourful Bulbs



IP65


**Outdoor String Lights
E27 Holders**

- * 14.4 Meters Long String
- * 15 Pcs E27 Sockets
- * Up to 5A
- * Fixed Sockets
- * IP65
- * Black Color

SKU: 5052 15pcs E27 - 14.4m



E27 Holder



IP65



Linkable up to 2 Strings

**Outdoor String Lights
With Bulbs**

- * 8 or 13 Meters Long String
- * 10 or 20 Bulbs included
- * 0.5 Watts Per Bulb
- * IP65
- * Black Color

SKU: 5057 10pcs Bulbs - 8m - 3W ■ 6000K
SKU: 5058 10pcs Bulbs - 8m - 3W ■ 2700K
SKU: 5093 20pcs Bulbs - 13m - 6W ■ 6000K
SKU: 5094 20pcs Bulbs - 13m - 6W ■ 2700K



IP65


**Outdoor String Lights
10m - 1.5m Power cable**
 Include Adapter: DC24V

Watts	1.4W	CRI	Ra>80
Input Voltage	AC : 220-245V	IP Rating	IP44
Flux	50lm	Dimension	10m
Beam Angle	270°	Body Color	Transparent

SKU: 9091 ■ 2700K



IP44



Linkable up to 2 Strings


**Outdoor String Lights
With Bulbs**

- * 8 or 13 Meters Long String
- * 10 or 20 Bulbs included
- * 0.5 Watts Per Bulb
- * IP65
- * White Color

SKU: 5091 10pcs Bulbs - 8m - 3W ■ 2700K
SKU: 5096 20pcs Bulbs - 13m - 6W ■ 2700K



IP65



A universe of possibilities when combining the existing lighting solutions with various detecting devices to further enable energy saving and efficiency.

Features:

- Up to 80% power saving
- Home, office, garden or park use
- Different forms, shapes and colours
- Easy installation and long lifecycle

Application:

- Wall or pylon mountable

LED MOTION SENSORS



Microwave Sensor Remote Control

Input Voltage	AC:120-277V	Body Color	White
Detection	360°	Class	II
Range	4-15m Max	Max Power	1000W LED
Frequency	50-60 Hz	LUX	<5 Lux-200 Lux
Working Temp.	-20°C/+40°C	Material	Plastic+ALU
IP Rating	IP65	Dimension	66x81mm




SKU: 7324 White Body



PIR Motion Sensor

Product code	SE1-A1	Body Color	White
Input Voltage	AC:110-240V	Class	II
Beam Angle	180°	Time	10sec-7min
Range	12m Max	Max Power	300W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP44	Dimension	∅65x86.5mm



SKU: 7301 White Body
SKU: 7302 Black Body



Smoke Alarm 85dB (3m)

Low Battery Alert: 7-15Days

Input Voltage	DC: 9V	Body Color	White
Alarm Sound	85dB (3m)	Class	II
Working Temp.	-20°C/+40°C	Material	Plastic+ALU
IP Rating	IP20	Dimension	66x81mm




***Battery not included**

SKU: 7325 White Body





PIR Motion Sensor

Product code	SE1-A3	Body Color	Black
Input Voltage	AC:110-240V	Class	II
Beam Angle	180°	Time	10sec-7min
Range	12m Max	Max Power	200W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP54	Dimension	∅77x70mm



SKU: 7306 White Body
SKU: 7307 Black Body



PIR Motion Sensor

Product code	SE1-A2	Body Color	White
Input Voltage	AC:110-240V	Class	II
Beam Angle	360°	Time	10sec-7min
Range	16m Max	Max Power	300W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP20	Dimension	∅88x55.5mm





SKU: 7305 White Body

PIR Motion Sensor

Product code	SE1-A2	Body Color	White
Input Voltage	AC:110-240V	Class	II
Beam Angle	360°	Time	10sec-7min
Range	8m Max	Max Power	1000W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP20	Dimension	∅108x25mm



SKU: 7310 White Body



PIR Motion Sensor

Product code	SE1-A2	Body Color	White
Input Voltage	AC:220-240V	Class	II
Beam Angle	360°	Time	10sec-7min
Range	6m Max	Max Power	300W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP20	Dimension	∅76x58mm





SKU: 7317 White Body
SKU: 7320 Black Body
SKU: 7321 Gray Body

PIR Motion Sensor

Product code	SE1-A2	Body Color	White
Input Voltage	AC:110-240V	Class	II
Beam Angle	360°	Time	10sec-7min
Range	6m Max	Max Power	1000W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP20	Dimension	∅65x86.5mm



SKU: 7311 White Body



PIR Motion Sensor

Functions: D2D: DUSK TO DAWN

Product code	SE1-A2	Body Color	Black
Input Voltage	AC:220-240V	Class	II
Beam Angle	180°	Time	10sec-10min
Range	16m Max	Max Power	400W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP54		





SKU: 7318 Black Body

PIR Motion Sensor

Product code	SE1-A2	Body Color	White
Input Voltage	AC:220-240V	Class	II
Beam Angle	160°	Time	10sec-7min
Range	9m Max	Max Power	400W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP20		



SKU: 7322 White Body



PIR Motion Sensor

Product code	SE1-A2	Body Color	White
Input Voltage	AC:220-240V	Class	II
Beam Angle	120°	Time	10sec-7min
Range	10m Max	Max Power	300W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP44		



SKU: 7319 White Body

PIR Motion Sensor

Product code	SE1-A2	Body Color	White
Input Voltage	AC:220-240V	Class	II
Beam Angle	360°	Time	5sec-10min
Range	20m Max	Max Power	1000W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP20	Dimension	ø65x86.5mm



SKU: 7323 White Body



ON/OFF via moving hand



Dimming + Driver
5.8 Ghz

Short Distance IR

Product code	SE1-A2	Body Color	White
Input Voltage	AC:110-240V	Class	II
Beam Angle	180°	Time	10sec-7min
Range	5cm Max	Max Power	200W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic
IP Rating	IP20	Dimension	75x18mm




SKU: 7304 White Body

Microwave Sensor

Product code	SE1-A5	Body Color	White
Input Voltage	AC:110-240V	Class	II
Beam Angle	180°/ 300°	Time	10sec-30min
Range	25-100%	Max Power	300W LED
Frequency	50-60 Hz	Ambient Light	5,10,20,30,50,100,200lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP20	Dimension	75x47mm



SKU: 7315 White Body



Dimming + Driver
5.8 Ghz

PIR Motion Sensor

Product code	SE1-A4	Body Color	White
Input Voltage	AC:110-240V	Class	II
Beam Angle	120°	Time	10sec-7min
Range	2-10m Max	Max Power	100W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP65	Dimension	57x35mm




SKU: 7309 White Body

Microwave Sensor

Product code	SE1-A5	Body Color	White
Input Voltage	AC:110-240V	Class	II
Beam Angle	180°	Time	10sec-7min
Range	3-10m Max	Max Power	300W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP20	Dimension	56x42mm



SKU: 7316 White Body




PIR Motion Sensor

Product code	SE1-A2	Body Color	White
Input Voltage	AC:110-240V	Class	II
Beam Angle	360°	Time	10sec-7min
Range	8m Max	Max Power	300W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP20	Dimension	∅80x62mm



SKU: 7312 White Body



PIR Motion Sensor

Product code	SE1-A1	Body Color	White
Input Voltage	AC:110-240V	Class	II
Beam Angle	300°	Time	10sec-7min
Range	16m Max	Max Power	300W LED
Frequency	50-60 Hz	Ambient Light	<10Lux-2000Lux
Working Temp.	-30°C/+50°C	Material	Plastic+ALU
IP Rating	IP44	Dimension	165x117mm



SKU: 7313 White Body



Light Control Sensor

Product code	SE1-A1	Body Color	White+Blue
Input Voltage	AC:110-240V	Class	II
Power	6A Max	Ambient Light	<10Lux ON; >40Lux OFF
Frequency	50-60 Hz	Material	Plastic+ALU
Working Temp.	-30°C/+50°C	Dimension	46x44x35mm
IP Rating	IP44		



SKU: 7314 White Body



LED DISPLAYS AND STAGE EFFECTS



LED Displays have large variety of applications – for commercial use, information boards and other decorative purposes, with wide customization options.

Features:

- High power and flexible applications
- For commercial and public use
- Different options for resolutions
- Indoor and outdoor use
- Easy to install and maintain
- Low energy consumption

Application:

- Stadiums and concerts
- Indoor music halls
- Commercial outdoor use





LED Displays

Module Indoor

SKU: 608 P2Size
 SKU: 66364 P2.604Size
 SKU: 631 P3 Size
 SKU: 601 P4 Size
 SKU: 629 P4 Size
 SKU: 602 P5 Size




	P2	NEW P2.604	P3	P4	P4	P5
Pixel pitch	2 mm	2.604 mm	3 mm	4 mm	4 mm	5 mm
Module size	256x128 mm	250x250 mm	192x192 mm	256x128 mm	256x256 mm	320x160 mm
Module pixels	128x64 pixel	96x96 pixel	64x64 pixel	64x32 pixel	64x64 pixel	64x32 pixel
Brightness	2000cd/m ²	1100cd/m ²	1100cd/m ²	1100cd/m ²	2000cd/m ²	2000cd/m ²
Refresh rate	1920 Hz	3840 Hz	1920 Hz	1920 Hz	3840 Hz	1920 Hz
Drive mode	1/32 Scan	1/32 Scan	1/32 Scan	1/16 Scan	1/16 Scan	1/16 Scan
Module Power	16.5W	16.5W	16.5W	16.5W	33W	17W
Working Temp.	-20°C/+50°C	-20°C/+65°C	-20°C/+50°C	-20°C/+50°C	-20°C/+65°C	-20°C/+50°C
Pixel Composition	SMD 3in1 RGB					
Life Span	50 000 h	100 000 h	50 000 h	50 000 h	50 000 h	50 000 h

LED Display Cabinet
Fix INDOOR Ver 2.0

SKU: 610 P3 Size
 SKU: 611 P4 Size
 SKU: 612 P5 Size



	P3	P4	P5
Pixel pitch	3 mm	4 mm	5 mm
Display size	960x960mm	768x768mm	960x960mm
Module size	192x192mm	256x128mm	320x192mm
Brightness	2000cd/m ²	2000cd/m ²	2000cd/m ²
Pixel Density	111 111dots/ m ²	62 500dots/ m ²	40 000dots/ m ²
Drive mode	1/32 Scan	1/16 Scan	1/16 Scan
Refresh rate	1920 Hz	1920 Hz	1920 Hz
Working Temp.	-20°C/+50°C	-20°C/+50°C	-20°C/+50°C
MAX Power	750W	750W	750W
Life Span	50 000 h	50 000 h	50 000 h




LED Displays

Module Outdoor

SKU: 609 P3 Size
 SKU: 66022 P3 Size
 SKU: 603 P4 Size
 SKU: 604 P5 Size
 SKU: 606 P6 Size
 SKU: 605 P8 Size



	P3	NEW P3	P4	P5	P6	P8
Pixel pitch	3 mm	3 mm	4 mm	5 mm	6 mm	8 mm
Module size	192x192 mm	192x192 mm	256x128 mm	320x160 mm	196x196 mm	256x128 mm
Module pixels	64x64pixel	64x64pixel	64x32pixel	64x32 pixel	32x32 pixel	32x16 pixel
Brightness	6500cd/m ²	6500cd/m ²	5500cd/m ²	5500cd/m ²	5500cd/m ²	5500cd/m ²
Refresh rate	1920 Hz					
Drive mode	1/16 Scan	1/4 Scan				
Module Power	35W	35W	35W	39W	26W	27W
Working Temp.	-20°C/+50°C	-20°C/+50°C	-20°C/+50°C	-20°C/+50°C	-20°C/+50°C	-20°C/+50°C
Pixel Composition	SMD 3in1 RGB					
Life Span	50 000 h					

LED Display Cabinet
Fix INDOOR Ver 2.0

SKU: 638 P3 Size
 SKU: 639 P4 Size
 SKU: 640 P5 Size




	P3	P4	P5
Pixel pitch	3 mm	4 mm	5 mm
Display size	960x960mm	768x768mm	960x960mm
Module size	192x192mm	256x128mm	320x192mm
Brightness	2000cd/m ²	2000cd/m ²	2000cd/m ²
Pixel Density	111 111dots/ m ²	62 500dots/ m ²	40 000dots/ m ²
Drive mode	1/32 Scan	1/16 Scan	1/16 Scan
Refresh rate	1920 Hz	1920 Hz	1920 Hz
Working Temp.	-20°C/+50°C	-20°C/+50°C	-20°C/+50°C
MAX Power	750W	750W	750W
Life Span	50 000 h	50 000 h	50 000 h


LED Displays
Module Indoor

 SKU: 635 P2.5 Size
 SKU: 636 P3.07 Size


	P2.5	P3.07
Pixel pitch	2.5 mm	3.07 mm
Module size	320x160 mm	320x160 mm
Module pixels	192x192 pixel	192x192 pixel
Brightness	650cd/m ²	600cd/m ²
Refresh rate	3840 Hz	3840 Hz
Drive mode	1/32 Scan	1/32 Scan
Module Power	140W	127W
Working Temp.	-20°C/+50°C	-20°C/+50°C
Pixel Composition	SMD 3in1 RGB	SMD 3in1 RGB
Life Span	100 000 h	100 000 h


LED Transparent Displays
Module Indoor

SKU: 66020 P3.91 Size



	P3.91
Pixel pitch	Horizontal 3.91mm Vertical 7.82mm
Module size	1000x1000 mm
Drive mode	1/16 Scan
Brightness	2500cd/m ²
Refresh rate	960 Hz
Pixel Density	32768 dot/m ²
Module Power	400W/m ²
Working Temp.	-20°C/+50°C
Pixel Composition	SMD 3in1 RGB
Life Span	50 000 h


LED Display Front Service
Module Indoor

 SKU: 66019 P1.875 Size
 SKU: 66018 P2.5 Size


	P1.875	P2.5
Pixel pitch	1.875 mm	2.5 mm
Module size	480x480 mm	480x480 mm
Module pixels	240x240 pixel	240x240 pixel
Brightness	500-800cd/m ²	500-800cd/m ²
Refresh rate	3840 Hz	3840 Hz
Pixel Density	284 444dots/m ²	160 000dots/m ²
Module Power	500W/m ²	20W
Working Temp.	-20°C/+50°C	-20°C/+50°C
Pixel Composition	SMD 3in1 RGB	SMD 3in1 RGB
Life Span	50 000 h	50 000 h


LED Displays Rental
Module Indoor

SKU: 101 P2.6 Size



	P2.6
Pixel pitch	2.6 mm
Module size	500x500 mm
Module pixels	192x192 pixel
Brightness	2000cd/m ²
Refresh rate	3840 Hz
Drive mode	1/32 Scan
Module Power	650W Max
Working Temp.	-20°C/+50°C
Pixel Composition	SMD 3in1 RGB
Life Span	100 000 h



LED Display Cabinet
Fix OUTDOOR

- SKU: 617 P4 Size
- SKU: 618 P5 Size
- SKU: 619 P8 Size
- SKU: 607 P10 Size



	P4	P5	P8	P10
Pixel pitch	5 mm	5 mm	8 mm	10 mm
Display size	768x768mm	960x960mm	768x768mm	960x960mm
Module size	256x128mm	160x160mm	256x128mm	160x160mm
Brightness	5500cd/m ²	5500cd/m ²	5500cd/m ²	7500cd/m ²
Pixel Density	62 500dots/ m ²	40 000dots/ m ²	15 625dots/ m ²	40 000dots/ m ²
Drive mode	1/8 Scan	1/8 Scan	1/8 Scan	1/8 Scan
Refresh rate	1920 Hz	1920 Hz	1920 Hz	1920 Hz
Working Temp.	-20°C/+50°C	-20°C/+50°C	-20°C/+50°C	-20°C/+50°C
MAX Power	800W	800W	800W	800W
Life Span	50 000 h	50 000 h	50 000 h	50 000 h




LED Displays
Rental INDOOR

- SKU: 620 P2.5 Size
- SKU: 614 P5 Size



	P2.5	P5
Pixel pitch	2.5 mm	5 mm
Display size	640x640mm	960x960mm
Module size	160x160mm	320x160mm
Brightness	2000cd/m ²	2000cd/m ²
Pixel Density	160 000dots/ m ²	40 000dots/ m ²
Drive mode	1/16 Scan	1/16 Scan
Port Type	HUB75	HUB75
Working Temp.	-20°C/+50°C	-20°C/+50°C
MAX Power	600W	750W
Life Span	50 000 h	50 000 h



	P2.91	P3.91	P5
Pixel pitch	2.91 mm	3.91 mm	5 mm
Display size	500x1000mm	500x1000mm	960x960mm
Module size	250x250mm	250x250mm	320x160mm
Brightness	5000cd/m ²	65000cd/m ²	7500cd/m ²
Pixel Density	32 768dots/ m ²	65 532dots/ m ²	40 000dots/ m ²
Drive mode	1/21 Scan	1/16 Scan	1/8 Scan
Port Type	HUB75	HUB75	HUB75
Working Temp.	-20°C/+65°C	-20°C/+50°C	-20°C/+50°C
MAX Power	800W	800W	750W
Life Span	100 000 h	50 000 h	50 000 h

LED Displays
Rental OUTDOOR

- SKU: 66209 P2.91 Size
- SKU: 615 P3.91 Size
- SKU: 616 P5 Size





LED Display Poster

Outdoor

SKU: 66027 P3 Size

SKU: 66025 P3.84 Size



DC 5V



150°



IP65

	P3	P3.84
Pixel pitch	3 mm	3.84 mm
Display size	600x1200mm	600x1200mm
Module size	200x200mm	200x200mm
Brightness	>6000cd/m ²	>6000cd/m ²
Pixel Density	102400dots/ m ²	67600dots/ m ²
Drive mode	1/16S	1/13S
Refresh rate	4000 Hz	4000 Hz
Working Temp.	-20°C/+70°C	-20°C/+70°C
MAX Power	950W /m ²	820W /m ²
Life Span	100 000 h	50 000 h



LED Displays Rental INDOOR

SKU: 102 P2.9 Size

SKU: 628 P3.91 Size



DC 5V



150°



IP20

	P2.9	P3.91
Pixel pitch	2.9 mm	3.91 mm
Display size	500x500mm	500x500mm
Module size	168x168mm	128x128mm
Brightness	5000cd/m ²	5000cd/m ²
Pixel Density	28224dots/ m ²	62 500dots/ m ²
Drive mode	1/21 Scan	1/21 Scan
Refresh rate	3840 Hz	3840 Hz
Working Temp.	-20°C/+50°C	-20°C/+50°C
MAX Power	650W	650W
Life Span	100 000 h	100 000 h



LED Display Poster

Outdoor Double-sided

SKU: 66028 P3 Size

SKU: 66026 P3.84 Size



DC 5V



150°



IP65

	P3	P3.84
Pixel pitch	3 mm	3.84 mm
Display size	600x1200mm	600x1200mm
Module size	200x200mm	200x200mm
Brightness	>6000cd/m ²	>6000cd/m ²
Pixel Density	102400dots/ m ²	67600dots/ m ²
Drive mode	1/16S	1/13S
Refresh rate	4000 Hz	4000 Hz
Working Temp.	-20°C/+70°C	-20°C/+70°C
MAX Power	950W /m ²	820W /m ²
Life Span	100 000 h	50 000 h



LED Displays FIX OUTDOOR V2

SKU: 624 P4 Size

SKU: 623 P8 Size



DC 5V



150°



IP20

	P4	P8
Pixel pitch	2.9 mm	3.91 mm
Display size	960x960mm	960x960mm
Module size	321x160mm	320x1620mm
Brightness	6500cd/m ²	6500cd/m ²
Pixel Density	62 500dots/ m ²	62 500dots/ m ²
Drive mode	1/16 Scan	1/16 Scan
Refresh rate	3840 Hz	1920 Hz
Working Temp.	-20°C/+50°C	-30°C/+65°C
MAX Power	600W	600W
Life Span	100 000 h	100 000 h


LED Display Cabinet
Fix OUTDOOR

SKU: 148 P3.91 Size
 SKU: 634 P5 Size
 SKU: 626 P6.67 Size



IP65


LED Displays
INDOOR Poster Display

SKU: 621 P3 Size



DC 5V



150°



IP20

	P3.91	P5	P6.67
Pixel pitch	3.91 mm	5 mm	6.67 mm
Display size	1000x1000mm	960x960mm	960x960mm
Module size	256x256pixels	320x320pixels	144x144pixels
Brightness	6500cd/m ²	6500cd/m ²	6500cd/m ²
Pixel Density	65 536dots/ m ²	36 864dots/ m ²	20 736dots/ m ²
Drive mode	1/8 Scan	1/8 Scan	1/8 Scan
Refresh rate	3840 Hz	3840 Hz	1920 Hz
Working Temp.	-30°C/+80°C	-30°C/+65°C	-30°C/+65°C
MAX Power	600W	600W	600W
Life Span	100 000 h	100 000 h	100 000 h

	P3
Pixel pitch	3 mm
Module size	192x192 mm
Module pixels	64x64 pixel
Brightness	2000cd/m ²
Pixel Density	111 111dots/ m ²
Drive mode	1/32 Scan
Port Type	HUB75
Working Temp.	-20°C/+50°C
Pixel Composition	SMD 3in1 RGB
Life Span	100 000 h


LED Display Cabinet P3.91
Fix OUTDOOR

SKU: 66173 P3.91 Size



IP65



Pixel pitch	3.91 mm
Display size	1000x500mm
Module size	256x128pixels
Brightness	6500cd/m ²
Drive mode	1/8 Scan
Refresh rate	1920 Hz
Working Temp.	-30°C/+80°C
MAX Power	600W
Life Span	100 000 h


LED DISPLAYS
43 inch IR touch

CPU: Bay Trail-D Celeron Quad-core J1900 2.0GHZ
 Chipset: Intel Bay trail SOC
 GPU Integrate: Intel HD Graphics
 Display output : VGA, built-in VGA pin, HDMI, HDMI pin, LVDS
 Memory: DDR3 2GB
 Hard drive: 32G Hard drive

SKU: 671 43inch



IP20



LED Displays Flexible

Module Indoor

SKU: 66367 P1.86 Size

SKU: 66368 P2 Size

SKU: 66206 P2.5Size

SKU: 66207 P3 Size



IP20

	P1.86	P2	P2.5	P3
Pixel pitch	1.86 mm	2 mm	2.5 mm	3 mm
Module size	320x160 mm	320x160 mm	320x160 mm	320x160 mm
Module pixels	172x86 pixel	160x80 pixel	128x64 pixel	128x64 pixel
Brightness	600cd/m ²	600cd/m ²	700-750cd/m ²	700-750cd/m ²
Refresh rate	3840 Hz	3840 Hz	1920-3840 Hz	1920-3840 Hz
Drive mode	1/43 Scan	1/40 Scan	1/32 Scan	1/32 Scan
Module Power	21W	21W	20W	21W
Working Temp.	-20°C/+65°C	-20°C/+65°C	-20°C/+65°C	-20°C/+65°C
Pixel Composition	SMD 3in1 RGB	SMD 3in1 RGB	SMD 3in1 RGB	SMD 3in1 RGB
Life Span	100 000 h	100 000 h	100 000 h	100 000 h



LED Display Banner P3.91

Fix OUTDOOR

SKU: 66420



IP65

Pixel pitch	3.91 mm
Display size	500x1500mm
Transparency	53%
Brightness	4500cd/m ²
Pixel Density	98 304dots/ m ²
Refresh rate	3840-5120 Hz



LED Display Cabinet

Fix INDOOR

SKU: 66208



IP20

Pixel pitch	1.86 mm
Display size	640x480mm
Module size	320x160pixels
Brightness	500-800cd/m ²
Drive mode	1/64 Scan
Refresh rate	3840 Hz
Working Temp.	-20°C/+50°C
Life Span	100 000 h



LED Display Transparent P2.6


Fix OUTDOOR

SKU: 66421



IP65

Pixel pitch	2.6 mm
Display size	1000x1500mm
Transparency	65%
Brightness	1200nits
Resolution	256x192
Refresh rate	5120 Hz


**LED Displays
Module Indoor**

SKU: 66366 P1.86 Size
 SKU: 66302 P2 Size
 SKU: 66021 P2.5 Size



IP20

	P1.86	P2	P2.5
Pixel pitch	1.86 mm	2 mm	2.5 mm
Module size	320x160 mm	320x160 mm	320x160 mm
Module pixels	172x86 pixel	160x80 pixel	128x64 pixel
Brightness	600cd/m ²	600cd/m ²	1200cd/m ²
Refresh rate	3840 Hz	3840 Hz	3840 Hz
Drive mode	1/43 Scan	1/40 Scan	1/32 Scan
Module Power	24W	24W	20W
Working Temp.	-20°C/+65°C	-20°C/+65°C	-20°C/+50°C
Pixel Composition	SMD 3in1 RGB	SMD 3in1 RGB	SMD 3in1 RGB
Life Span	100 000 h	100 000 h	100 000 h


**LED Displays 45°
Module Indoor**

SKU: 66202 P2 Size
 SKU: 66201 P2.5 Size
 SKU: 66203 P4 Size



IP20

	P2	P2.5	P4
Pixel pitch	2 mm	2.5 mm	4 mm
Module size	320x160 mm	320x160 mm	256x256 mm
Module pixels	160x80 pixels	128x64 pixels	64x64 pixels
Brightness	800cd/m ²	1000cd/m ²	1000cd/m ²
Refresh rate	3840 Hz	3840 Hz	3840 Hz
Drive mode	1/32 Scan	1/32 Scan	1/32 Scan
Module Power	20W	20W	20W
Working Temp.	-20°C/+65°C	-20°C/+65°C	-20°C/+65°C
Pixel Composition	SMD 3in1 RGB	SMD 3in1 RGB	SMD 3in1 RGB
Life Span	100 000 h	100 000 h	100 000 h

LED Display Accessories
Splitter


DIS-300 is specialized for multi-screens and super large led screens. The card possesses two input ports and eight output ports, enabling that one split to eight and two split to four. Functions change automatically. Each RJ45 port can be independently adjusted, and support read back parameters from scan board.

Description:

- 1 in 8 out or 2 in 4 out, automatic switching.
- Each RJ45 port can be independently adjusted.
- No need to install the drivers



SKU: 952




IP20


**LED Displays
Module Outdoor**


SKU: 66023 P2.5 Size
 SKU: 66496 P8 Size



IP65



	P2.5	P8
Pixel pitch	2.5 mm	8 mm
Module size	320x160 mm	320x160 mm
Module pixels	128x64 pixel	40x20 pixel
Brightness	6500cd/m ²	4500cd/m ²
Refresh rate	1920 Hz	3840 Hz
Drive mode	1/16 Scan	1/5 Scan
Module Power	35W	27W
Working Temp.	-30°C/+65°C	-30°C/+65°C
Pixel Composition	SMD 3in1 RGB	SMD 3in1 RGB
Life Span	100 000 h	100 000 h


**RECEIVING CARDS
FOR LED DISPLAYS**


DC 5V



IP20

SKU No.	950	654	655	113
Resolution	256 x 226	256 x 226	512x256	512 x 384
RGB Data Output	16 Groups	24 Groups	32 Groups	24 Groups
Interface	8 x HUB75	12 x HUB75	16 x HUB75	32 x HUB75


MX40 PRO LED Screen Controller

SKU: 66488

Inputs: 3x HDMI 2.0, 1x DP 1.2, 1x 12G-SDI
 Outputs: 20x LED-Out (RJ45), 3x HDMI 2.0
 Loop, 1x 12G-SDI Loop, 4x OPT-Out (10G)
 Voltage: AC 100-240V, 50/60HZ
 Consumption: 70 watts
 Dimensions: 482.6 x 467.0. x 94.2mm
 (WxDxH)
 Weight: 7.5kg


**SENDING CARD
FOR LED DISPLAYS**


DC 5V



IP20

SKU No.	650	651
Input Resolutin	1280x1024,1024x1200,1600x848	1920x1200,2048x1152,2560x96
Capacity	1.3 million pixels	2.3 million pixels
Supply Voltage	5V	5V
Control Method	USB Interface	USB Interface
Video Interface	DVI	HDMI/DVI
Audio Interface	3.5mm	HDMI/3.5mm
Video Format	RGB	RGB ,YCrCb4:2:2,YCrCb4:4:4
Output Interface	2 Ethernet ports	4 Ethernet ports
Bit Depth	8bit	8/10/12bit

**Multifunctional CARD
FOR LED DISPLAYS**

SKU: 972



DC 5V



IP20

MFN300
 Ethernet connection: 2x Gigabit Ethernet
 connection
 RS232: Sub-D 9-pin connector
 Audio: 3.5mm
 Supply voltage: DC 5V
 Operating temperature: -20 ~ 75°C
 Dimensions: 144 x 92 x 20mm
 Weight: 0.165 kg



TB40 CONTROLLER

Multimedia Players

Wi-Fi media player used in the construction of LED screens with 2 Ethernet ports with a capacity of up to 1,300,000 pixels each with a maximum width of 4096 pixels and a maximum height of 4096 pixels.

TB40 enables intelligent control of the LED screen with an application for tablets and smartphones.

- 4 core 1.8 GHz processor
- 1 GB of RAM
- 16 GB of internal storage (4 GB available)
- Dual Wi-Fi modes

SKU: 152



IP20



TB6 CONTROLLER

Multimedia Players

- Loading capacity up to 1,300,000 pixels, with the maximum width of 4096 pixels and maximum height of 1920 pixels
- Wired Gigabit Ethernet
- Stereo audio output
- HDMI Loop
- HDMI input and auto full-screen display
- 2 USB ports allowing for USB playback
- Onboard light sensor connector allowing for automatic and scheduled brightness adjustment
- Synchronization mechanism for multi-screen playing
- Powerful processing capability
- Comprehensive control plans
- Synchronous and asynchronous dual-mode
- Dual-Wi-Fi mode
- Redundant backup

SKU: 661



IP20



TB40 CONTROLLER

Multimedia Players

Wi-Fi media player used in the construction of LED screens with 2 Ethernet ports with a capacity of up to 1,300,000 pixels each with a maximum width of 4096 pixels and a maximum height of 4096 pixels.

TB40 enables intelligent control of the LED screen with an application for tablets and smartphones.

- 4 core 1.8 GHz processor
- 1 GB of RAM
- 16 GB of internal storage (4 GB available)
- Dual Wi-Fi modes

SKU: 153



IP20



TB8 CONTROLLER

Multimedia Player

- 4 Ethernet ports, loading capacity of each port up to 2,300,000 pixels, with the maximum width of 4096 pixels and maximum height of 1920 pixels
- Wired Gigabit Ethernet
- Stereo audio output
- HDMI Loop
- HDMI input and auto full-screen display
- 2 USB ports allowing for USB playback
- Onboard light sensor connector allowing for automatic and scheduled brightness adjustment synchronization mechanism for multi-screen playing
- Powerful processing capability
- Comprehensive control plans
- Synchronous and asynchronous dual-mode
- Dual-Wi-Fi mode

SKU: 946



IP20





Sending Box

LED Display Controller

The Optonica Sender card control box is a sending card inside of an enclosure with a built in power supply. You can order the stand alone card if you do not need the enclosure.

Product Type:	Controller
Capacity:	1.3 million pixels
Supply Voltage:	AC-100-240V-50/60HZ
Control Method:	USB Interface
Video Interface:	DVI
Audio Interface:	3.5mm
Viedo Format:	RGB
Output Interface :	2 Ethernet ports
Bit Depth Of Video Resource:	8bit
Light Sensor Interface:	1
USB Cable:	1.5M



SKU: 948



IP20



Sending Box Synchronous LED Display Controller MCTRL700

The MCTRL700 is a video controller for LED screens developed by NovaStar. It supports 1x DVI input, 1x HDMI input, 1x audio input and 6 Ethernet outputs, with a loading capacity of 1920x1200@60Hz. The MCTRL700 is suitable for rental and fixed installations, such as concerts, live shows, monitoring centers, events, sports halls, etc.

Product specification: Product Type Controller
 Inputs: 1xSL-DVI (IN-OUT) 1xHDMI 1.3 (IN-OUT) 1xAUDIO
 Outputs: 6x RJ45, 1x HDMI 1.3, 1x SL-DVI
 Capacity: 650,000 pixels
 Dimensions (w/h/d): 482.6 x 44.4 x 268.50mm
 Weight: 2.6 kg

SKU: 114



IP20

Video Processor for LED screens

LED Display Controller

VX600



High-quality and precise video processor used in LED screen installations

Тип: Video Controller

SKU: 150 VX600

Inputs: 2x HDMI 1.3, 1x DVI, 1x 3G-SDI (max. 1920x1080@60Hz)
 Outputs: 6x LED-Out (RJ45) 1x HDMI 1.3 Out, 2x OPT-Out (10G)
 Capacity: 3.9 million pixels

VX1000



SKU: 151 VX1000

Inputs: 2x HDMI 1.4, 1x DVI, 1x 3G-SDI Max. width: 4092 pixels (4092x1136@60Hz)
 Outputs: 10x LED-Out (RJ45) 1x HDMI 1.3 Out, 2x OPT-Out (10G)
 Capacity: 6.5 million pixels with a maximum width of 10,240 pixels and a maximum height of 8192 pixels

Dimensions (w/h/d): 483.6 x 351.2 x 50.1mm
 Weight: 4 kg



IP20



Sending Box Synchronous LED Display Controller

supports extra-large resolution. With HDMI/DVI video input and four Ethernet port outputs, a single unit is able to load 2560x960. Multiple units can be cascaded for uniform control.

Product specification: Product Type Controller
 Input Resolution: 1920x1200,2048x1152,2560x960
 Capacity: 2.3 million pixels
 Supply Voltage: AC-100-240V-50/60HZ
 Control Method: USB Interface
 Video Interface: HDMI / DVI
 Audio Interface: HDMI/3.5mm
 Viedo Format: RGB,YCrCb4:2:2,YCrCb4:4:4
 Output Interface: 4 Ethernet ports
 Bit Depth Of Video Resource: 8/10/12bit
 Light Sensor Interface: 1



SKU: 947



IP20



MCTRL660 PRO LED Screen Controller

SKU: 66491

Inputs: 1x 3G-SDI 1x HDMI 1.4a 1x SL-DVI
 Outputs: 6x LED-Out (RJ45) 2x 10G (OOPT Out (OPT Out 1 for Ethernet Ports 1-8; OPT Out 2 Backup)
 Voltage: AC 100-240V, 50/60HZ
 Consumption: 20 watts
 Dimensions: 482.6 x 356. x 50.1 mm (WxDxH)
 Weight: 4.6 kg



MCTRL R5 LED Screen Controller

SKU: 66401

Inputs: 1x 6G-SDI 1x HDMI 1.4 1x Dual-Link DVI
 Outputs: 8x LED-Out (RJ45) 2x 10G (OOPT Out (OPT Out 1 for Ethernet Ports 1-8; OPT Out 2 Backup)
 Voltage: AC 100-240V, 50/60HZ
 Consumption: 25 watts
 Dimensions: 482.6 x 334.6 x 52mm (WxDxH)
 Weight: 4.3kg



Processor for LED screens TU15 Pro

SKU: 66404

Inputs: 2x HDMI 1.3 3x USB 2.0 for multimedia playback
 Outputs: 4x LED-Out (RJ45) 2x audio output (1x SPDIF, 1x 3.5mm)
 Operating system: Android 11
 Bluetooth: 5.1
 Memory: 4GB RAM 32GB internal memory
 Voltage: DC 12V 3A
 Consumption: 21W
 Dimensions: 211.7 x 185.0 x 50.6mm
 Weight: 1.12kg



TB30 Wi-Fi media player for LED screens

SKU: 66402

2 Gigabit Ethernet ports capacity of up to 650,000 pixels (1x Main, 1xBackup) (Maximum width/height: 4096 pixels)
 WLAN (stand-alone or as an access point)
 Stereo audio output
 Процессор: Quad-Core ARM A55 1.8Ghz
 1GB memory
 16GB internal memory
 2 connections for sensors (e.g. NovaStar NS060 light sensor) configurable via LAN/WLAN with ViPlex Express & NovaLCT
 Synchronised playback between multiple devices possible (synchronisation via NTP or GPS(4G module required))
 Supports the NovaStar 4G module (not included)
 Voltage: AC-100-240V, 50/60HZ
 Dimensions: 274.3mm×139.0mm×40.0mm (WxDxH)



Processor for LED screens TU20 Pro

SKU: 66405

Inputs: 2x HDMI 1.3 3x USB 2.0 for multimedia playback
 Outputs: 6x LED-Out (RJ45) 2x audio output (1x SPDIF, 1x 3.5mm) 1x HDMI (1080p)
 Operating system: Android 11
 Bluetooth: 5.1
 Memory: 4GB RAM 32GB internal memory
 Voltage: DC 12V 3A
 Consumption: 21W
 Dimensions: 211.7 x 185.0 x 50.6mm
 Weight: 1.12kg



TB50 Wi-Fi media player for LED screens

SKU: 66403

2 Gigabit Ethernet ports capacity of up to 650,000 pixels
 WLAN (stand-alone or as an access point)
 1x HDMI 1.4 output (Max.: 1080p@60Hz, can be used as loop-out)
 1x HDMI 1.4 input
 Stereo audio output
 Processor: Quad-Core ARM A55 1.8Ghz
 1GB memory
 16GB internal memory
 2 connections for sensors (eg NovaStar NS060 light sensor) configurable via LAN/WLAN with ViPlex Express & NovaLCT
 Synchronised playback between multiple devices possible
 Voltage: AC-100-240V, 50/60HZ
 Dimensions: 274.3mm×139.0mm×40.0mm (WxDxH)



Video processor for LED screens VX400

SKU: 66214

Type: Video Controller
 Inputs: 1x HDMI 1.3 (IN & LOOP), 1x HDMI 1.3, 1x DVI (IN & LOOP), 1x 3G-SDI (IN & LOOP), 1x optical fiber port (OPT1)
 Outputs: 4x Gigabit Ethernet ports, 2x Fiber outputs, 1x HDMI 1.3
 Capacity: 2.6 million pixels
 Dimensions (w/h/d): 482.6 x 43.6 x 301.2mm
 Weight: 4 kg



IP20



DMX384 Moving Light Control

SKU: 696

DMX384 moving light control DMX512 controller for controlling spectacular stage lighting.

Channels: 384
 DMX input/output: 3 pin male/female XLR
 Power supply: DC 9V 1000mA
 Dimensions: 520mm×183mm×73mm
 Weight: 2.6 kg



IP20



Video processor for LED screens J6

SKU: 66217

1x DP 1.1 (3840×2160@30Hz) or HDMI 1.4 (3840×2160@30Hz)
 2x 3G-SDI (1920×1080@60Hz) and Loop
 1x HDMI 1.3 (1920×1080@60Hz)
 4x DVI (1920×1080@60Hz) or HDMI 1.3 (1920×1080@60Hz)
 Outputs:
 8x DVI (4 groups with 2 outputs per group)
 2x Dual-Link DVI (1x Main and 1x Backup each)
 1x HDMI for preview monitor
 Further Features , Genlock Input&Loop
 Control via USB or Ethernet
 Supply voltage: AC-100-240V-50/60HZ
 Consumption: 50W
 Dimensions: 482.6 x 373.5 x 96mm (with rackmount)



IP20



Wireless DMX512 Controller

SKU: 662

Input voltage: 9-12V DC 300mA min
 Communication distance: 700m (visible distance)
 Operating frequency: 2.4G ISM, 126 frequency band
 Maximum transmission power: 20dBm
 Receive sensitivity: -94dBm
 DMX signal output: 3/5 pin XLR
 Dimensions: 75 x 147 x 43mm
 Weight: 360g



IP20



Video processor for LED screens H5

SKU: 66494

Max. Number of input cards: 10
 Max. Number of input channels: 40
 Max. Number of output cards: 3
 Max. Loading Capacity: 39,000,000 Pixels
 Max. Number of layers: 48
 Supply voltage: AC 100 - 240V, 50/60 Hz
 Consumption: 400Watt
 Dimensions: 482.6 × 532.8 × 228.2mm (W×D×H)
 Weight: 25 kg



IP20



DMX Power Splitter

3 pin XLR IN/OUT
 Power: 15W
 Output: 4 or 8 DMX
 Size: 430x50x180mm
 Net weight: 2.35kg

SKU: 694 Output: 4 DMX

SKU: 695 Output: 8 DMX



IP20



H_1X HDMI 2.0+1X DP 1.2 INPUT CARD screens TCC70G

SKU: 66489

1x HDMI 2.0: -Backwards compatible with HDMI 1.4 & HDMI 1.3
 Max. Resolution: 4096×2160@60Hz or 8192×1080@60Hz HDCP 2.2 compatible
 Custom EDID's: Max. Width: 4092 pixels (4092×2261@60Hz), Max. Height: 4095 Pixel (2188×4095@60Hz)
 1x DP 1.2: Backwards compatible with DP 1.1
 Max. Resolution: 4096×2160@60Hz or 8192×1080@60Hz
 HDCP 2.2 compatible
 Custom EDID's: Max width: 8192 pixels (8192×1146@60Hz), Max. Height: 4095 Pixel (2188×4095@60Hz)



Wi-Fi media player for LED screens LCB4K

SKU: 66492

Hardware
 -Processor: Quad-core ARM A55 @ 1.8 GHz.
 -Video Decoding: H.264/H.265 4K@60Hz.
 -Memory: 2 GB RAM.
 -Storage: 32 GB internal storage.
 Dimensions (W/H/D): 274.3 mm × 139.0 mm × 40.0 mm
 Weight: 1.1 kg



H_20x RJ45 sending card

SKU: 66490

20x RJ45 Gigabit Ethernet outputs:
 At 8Bit color depth:
 650,000 pixels per port
 At 10-bit color depth:
 320,000 pixels per port
 Hot backup capable



Controller for LED screens U5TB30

SKU: 66503

Voltage: 100-240V~, 3.0-1.5A, 50/60Hz
 Consumption: 240 W
 Dimensions: 740 × 651.4 × 431.6 mm (L × W × H)
 Weight: 24kg
 87 programmable LCD buttons
 4 encoders
 8 Fader
 T-Bar
 PixelFlow software integrated
 Timecode capable (LTC input & output)
 KVM function
 Simultaneous control of multiple switchers and media servers
 PTZ Control
 Folding screen
 21.5" Main touchscreen, 8" Smart touchscreen



Wireless DMX controller CARD screens TCC70G

SKU: 66447



MCTRL4K LED Screen Controller

SKU: 66213

Type: Video Controller
 Inputs: 1x DP 1.2, 1x HDMI 2.0, 2x Dual-Link DV
 Outputs: 16x LED output (RJ45),
 4x OPT Out (2x Main, 2x Backup)
 Capacity: 8.8 million pixels
 Dimensions (w/h/d): 482.6 x 372 x 89mm
 Weight: 4.6 kg


18*10W Flat aluminium RGBW LED PAR Light

Voltage: AC90-260V 50/60Hz
 Power: 180W
 Light source: 18*10W RGBW led par light
 LED life: 50,000 hours.
 Lens degree: 15° 25°, 45° (optional)
 DMX channel: 4/8CH
 Control Mode: Auto, Sound, DMX512, Master-slave
 Strobe: 0 ~ 20 times / sec.

SKU: 683



RGB+W



IP20


7*10w Mini RGBW LED PAR Light

Voltage: AC100~240V 50~60Hz
 Power consumption: 70W
 Light source: 7*10W RGBW 4in1 LED
 Beam angle: 15° 25° 40° optional
 DMX channels: 7 CHS
 Function: DMX AutoSound Master-slave, strobe, dimmer
 Housing Material: plastic
 Working Environment: -20~40
 Packing size: 22.5*10*22.5Cm (1pc/CTN)

SKU: 691



RGB+W



IP20


18*10W Flat aluminium RGB LED PAR Light

Voltage: AC90-260V 50/60Hz
 Power: 180W
 Light source: 18x 10W 4 in 1 LED
 LED life: 50,000 hours.
 Lens degree: 15° 25°, 45° (optional)
 DMX channel: 4/8CH
 Control Mode: Auto, Sound, DMX512, Master-slave
 Strobe: 0 ~ 20 times / sec.

SKU: 943



RGB



IP20


7*10w Remote Mini RGB+WW LED PAR Light

Voltage: AC100~240V 50~60Hz
 Power consumption 70W
 Light source: 7*10W RGB+WW 4in1 LED
 Beam angle: 25° optional
 DMX channels: 4/6CH
 Function: DMX, Remote, Auto, Sound, Master-slave, Strobe, Dimmer
 Housing Material: Plastic
 Protection power: IEC power in and out Working Environment: -20~40
 Packing size: 22.5*10*22.5Cm (1pc/CTN)

SKU: 692



RGB+WW



IP20


LED Slim Flat PAR Can 18x18W RGBWA+UV 6 in 1

Voltage: AC90-245V, 50-60HZ
 Power: 180W
 Light source: 18x 18W RGBWA+UV 6 in 1 LED
 LED life: 50,000 hours.
 Lens degree: 15° 25°, 45° (optional)
 DMX channel: 10/6CH
 Control Mode: Auto, Sound, DMX512, Master-slave
 Function effect: dimmer /Strobe /Eotic /Gradual change
 Strobe: 0 ~ 20 times / sec.

Size: 265x80x280 mm
 Net weight 3kg

SKU: 177



RGBWA+UV



IP20


36*3W LED PAR Light

Voltage: AC100-260V 50Hz/60Hz
 Consumption: 50W/120W
 Lamp: 3W*36* LED lamp R12G12B12
 Channel: 7CH
 Mode of control: DMX512, automatic, voice active.
 Function: Can make magic, color mixed, charming effect
 Packing size: 290*290*410mm

SKU: 690



RGB



IP20

Laser RGB5000



Voltage: AC90-240V, 50/60HZ
 Consumption: 120W
 Scanner: 25kkps
 Laser power:
 1x1000mW Red 638nm,
 1x1000mW Green 520nm,
 1X3000mW Blue 450nm
 Colors: RGB full color
 Control signal: DMX-512
 Control mode: music, auto, master-slave and DMX-512, ILDA control
 DMX channel: 10/34ch
 Size: 270x200x160 mm
 Weight: 5.5 kg

SKU: 166



IP20



3pcs *60W warm white + 36 *3W RGB

Input voltage: 100-240Vac/50-60Hz
 Product power: 250W
 Light source: 3pcs *60W warm white + 36 *3W RGB
 Channel: 14CH/22CH
 Control mode: DMX512, master/slave,
 self-propelled, voice control
 Dimming method: 0-100% ultra-smooth dimming
 Strobe: 25 times/sec

SKU: 128



RGB



IP20

Laser RGB3000



Voltage: AC90-240V, 50/60HZ
 Consumption: 120W
 Scanner: 25kkps
 Laser power:
 1x500mW Red 638nm,
 1x800mW Green 520nm,
 1X1700mW Blue 450nm
 Colors: RGB full color
 Control signal: DMX-512
 Control mode: music, auto, master-slave and DMX-512, ILDA control
 DMX channel: 10/34ch
 Size: 270x200x160 mm
 Weight: 5.5 kg

SKU: 165



IP20



WATERPFOOR RGBW 4in1 Flat Par 18

Voltage: AC100-240V
 Frequency: 50Hz-60Hz
 Consumption: 180W
 Lamp: 18pcs10W RGBW 4in1 LED
 Channel: 8/4CH
 IP rate: IP65
 Mode of control: DMX512, Auto, Sound, Master-slave.
 Function: Can make magic, color mixed, charming effect
 Net weight: 3.7KG

SKU: 129



RGB+W



IP20

Laser RGB1000



Voltage: AC90-240V, 50/60HZ
 Consumption: 120W
 Scanner: 20kkps
 Laser power:
 1x170mW Red 638nm,
 1x100mW Green 520nm,
 1X700mW Blue 445nm,
 Colors: RGB full color
 Control signal: DMX-512
 Control mode: music, auto, master-slave and DMX-512, ILDA control
 DMX channel: 10/34ch
 Size: 270x200x160 mm
 Weight: 5.5 kg

SKU: 164



IP20



7x100W Waterproof White Halogen Lamps

Work voltage: 220V/50-60Hz
 Light source: 7x100W Halogen lamps (philips)
 Power consumption: 700 W
 Color temperature: 1650K-6500k
 Control mode: Auto-run , Master-Slave , DMX control
 DMX channel: 1CH/6CH /7CH
 DMX connector: 3+5 pin XLR connector (selected)
 Display: Color LCD display
 Installation Tripod stand /Hang on /Base
 Reflector bowl color: Silver
 Size: 456*520*130 mm
 Weight: 7.65KG

SKU: 967



IP65



Battery

7x12W Waterproof RGB 6IN1 LED PAR Light Battery - Wireless

Waterproof 7x12W RGB 6IN1 Battery Wireless Led Par
 Light source: 7pcs 15w LED 4in1 mixing color
 Beam Angle: 25°
 Dimmer: 0-100% dimmer
 Strobe rate:0-24HZ
 Working Environment: -20-40
 DMX Channels: 2 DMX modes, 4channels mode & 8 channels mode
 Control Mode: DMX512,Master-slave,Sound,Auto,Wireless,remote.
 Battery type: Lithium Ion
 Battery Charge Time: 3hours(full power)
 Battery Life: 3.5(all on) hours,14 (single Color) hours
 Battery Power: 24V, 5Ah
 Wireless effective distance: 400meters

SKU: 940



RGB



IP54



Waterproof 44x10w RGBW 4in1 Led wall light

Power Supply: AC 90-240V/50-60Hz
 Power consumption: 450W
 Light source: 44pcsx10W RGBW Led
 Beam Angel: 25-35°
 Dimmer: 0-100% dimmer
 IP rate: IP67,outdoor
 Control Mode: RDM, DMX512 Control, Sweden Import wireless DMX

SKU: 66127



RGB+W



IP67



Battery

7x8W Waterproof RGB 6IN1 LED PAR Light Battery - Wireless

Light source: 7pcs 8w LED 4in1 mixing color
 Beam Angle: 25°
 Dimmer: 0-100% dimmer
 Strobe rate:0-24HZ
 Working Environment: -20-40
 DMX Channels: 2 DMX modes, 4channels mode & 8 channels mode
 Control Mode: DMX512,Master-slave,Sound,Auto,Wireless,remote.
 Battery type: Lithium Ion
 Battery Charge Time: 3hours(full power)
 Battery Life: 3.5(all on) hours,14 (single Color) hours
 Battery Power: 24V, 5Ah
 Wireless effective distance: 400meters

SKU: 941



RGB



IP54



Battery

9*10W Wifi control Waterproof RGBA+UV 6 in 1

Power Supply: AC 100-240V/50-60Hz
 Power consumption: 90W
 Light source: 9pcs LED RGBWA+UV 6in1 mixing color
 Beam Angel: 15°
 Dimmer: 0-100% dimmer
 Strobe rate:0-24HZ
 Working Environment: -20-40
 DMX Channels: 2 DMX modes, 6channels mode & 10 channels mode
 Control Mode: DMX512,Master-slave,Sound,Auto,Wireless,remote, wifi
 Battery type: Lithium Ion
 Battery Charge Time: 6 hours
 Battery Life: (all on) 4 hours, (single Color) 24hours
 Battery Power: 12V, 25Ah

SKU: 932



RGB+UV



IP54



Battery

24X3W RGB 3IN1 LED Wall Washer Battery - Wireless

Power Supply: AC 100-240V/50-60Hz
 Power consumption:80W
 Light source: 24pcs*3w LED RGB 3in1 mixing color
 Beam Angle: 10/20/25 degree
 Dimmer: 0-100% dimmer
 Strobe rate:0-24HZ
 Control Mode: DMX512,Master-slave,Sound,Auto, remote
 Build-in more than 9 build-in programs
 Generate endless effects with built-in, automated programs
 Product size: 1030x62x58mm

SKU: 936



RGB+W



IP20

Pixel control 18*10w RGBW 4in1 LED Wallwasher



Voltage: AC90V-245V/50-60Hz
 Power: 200W Light source
 Pixel control: 18*10w RGBW 4in1 LED wash
 Beam angle: 15° or 40° Rate :use indoor only
 Leds: 18pcs 10W RGBW 4IN1 LEDS
 Life time: >100 thousand hours
 Color: RGBW Wcolor can be mixed to more than 16.7million kinds of color
 Function effect: dimmer, strobe, eotic, gradual change

SKU: 993



Compact Pinspot LED 40W RGBW 4in1 Par with manual zoom

Power Supply: AC 100-240V/50-60Hz
 Power consumption: 40W
 Light source: 40 W RGBW 4in1 LED
 Beam Angle: 40°
 Zoom range: 4~60° manual zoom
 Dimmer: 0-100% dimmer
 Strobe rate: 0-20HZ
 Working Environment: -20-40
 IP rate: IP20,indoor
 DMX Channels: 6ch
 Control Mode: DMX512,Master-slave,Sound,Auto, Remote
 Net weight: 2kg

SKU: 990



5 Head Matrix Blinder



Voltage: AC100-240V 50/60Hz
 Power: 60W
 Light source: 5PCS 10W CREE RGB 3in1 LED
 Function: Color mix, automatic color change, built-in program and strobe effect with adjustable speed, dimmer, master/slave
 Light size: 620*130*160mm
 Weight: 4kg

SKU: 992



1000W LED Strobe RGB

Voltage: AC110-240V, 50/60HZ
 Consumption: 1000W
 Light source: 800pcs 1.2w SMD RGB LEDs
 Channel: 1CH /3CH/6CH
 IP rate: IP20
 Display Panel: LED Blue Display
 Housing material: Black Aluminum shell
 Mode of control: DMX512,Master-slave,Sound,Auto
 Dimension: 510*220*305mm
 Weight: 5.7kgs

SKU: 995



LED COB Blinder 2X100 W



LED: 2pcs*100W COB LED
 Light Color: Single color WW(100W)
 LED light time: over 50000 hours
 Voltage: AC 100V-240V 50-60Hz
 Power consumption: 260W
 Beam angle: 30 degree
 Dimmer: 0-100% linear adjustable
 Strobe: Variable speed (1-30Hz)
 Refresh rate: 11700Hz , 100% flicker free for film and TV camera
 Color effect feature: with individual control effect
 Power input: powercorn connector
 Housing material: Metal
 Control mode: DMX512,Master/Slave,Auto,Sound alone,Sound active
 DMX Channel: 2/5 CH

SKU: 994



Battery Mini 4 *10W RGBWA+UV 6in1 LED PAR

Power Supply: AC 100-240V/50-60Hz
 Power consumption: 40W
 Light source: 4pcs 10W LED RGBWA+UV 6in1 mixing color
 Beam Angle: 15°
 Dimmer: 0-100% dimmer
 Strobe rate: 0-24HZ
 Working Environment: -20-40
 IP rate: IP20,indoor
 DMX Channels: 6CH ,10CH
 Control Mode: DMX512, Master-slave,Sound,Auto, Remote

SKU: 988



NEW PRODUCT



LED PAR 712E

SKU: 66442

Life Span: 50000H
 Light Source: 7x12W 4-IN-1 LEDs (RGBW) 60x0.2W 3-IN-1 LEDs (RGB)
 Optics: 25°Beam angle (other angles optional) 35°Field angle
 Color System: RGBW for main light, CTO, 2800K-5600K c
 Strobe Effect: 0-25Hz LED shutter/strobe effect with variable speed
 Dimming System: 0-100% Smooth linear LED dimming
 Control System: 7/8/10/18/184 DMX-512
 Display System: 1.44" TFT LCD display
 Product Dimensions: 101(D)/258(W)/264.5(H)mm
 Net Weight: 2.2kg

NEW PRODUCT



12W RGB scanner laser bar

SKU: 66107

Configuration W2000(R500 + G400 + B1.2W) x 6pcs
 Rated Voltage: AC100~240V 50/60Hz;
 Power consumption: ≤200W
 Laser color: RGB full color
 Beam diameter: φ15mm
 Motor: 7pcs 42 high torque stepper motor
 Modulation: analog
 Rotation: Y axis 240° rotation, each head 140° rotation
 Channel: 14/35/42CH
 Control mode: sound/ automatic/DMX512/ master-slave
 Control technology: RDM data bidirectional transmission
 DMX512 upgrade
 Operating requirement: dry, less dust, 0~35

NEW PRODUCT



LED PAR P3245

SKU: 66443

Life Span: 50000H
 Light Source: 324*0.5W 5730 LEDs (WW+CW)
 9 Individual control rings
 Optics: 120°Field angle
 Color System: Warm white cold white, CTO, 2800K-5600K
 Strobe Effect: 0-25Hz LED shutter/strobe effect with variable speed
 Dimming System: 0-100% Smooth linear LED dimming
 Control System: 3/4/5/8/9 DMX-512, master-slave, sound or auto, IR Remote control, RDM
 Display System: 1.44" TFT LCD display
 Product Dimensions: 101(D)*258(W)*264.5(H)mm
 Weight: 2.03kg

NEW PRODUCT



12W RGB Laser Bar Hot Wheels

SKU: 66109

Configuration: W2000C(R635-500mW/G525-400mW/B450-1.2W) x6pcs
 Rated voltage: AC100~240V 50/60Hz 140W@AC220V
 LED strobe source: 0.2W RGB x90pcs
 Control mode: Sound/ Automatic/Master-slave/DMX512(25CH/55CH)
 Control interface: 3 pin DMX512IN/OUT
 Effect: 16 kinds of Auto dynamic effect, built-in rich color macro function control
 Laser effect: Beam
 LED effect: Strobe
 X axis: infinite rotation
 Single axis stroke: 0-140° scanning range
 Scanning system: precision stepping motor
 Electronic control technology: RDM data bidirectional transmission
 DMX512 upgrade
 Cooling system: low noise air cooling
 Working environment: indoor
 Operating requirement: dry, less dust, 0~35

NEW PRODUCT



LED PAR IP3245

SKU: 66444

Light Source: 324*0.5W 5730 LEDs (WW+CW)
 9 Individual control rings
 Optics: 120°Field angle
 Color System: Warm white cold white, CTO, 2800K-5600K
 Strobe Effect: 0-25Hz LED shutter/strobe effect with variable speed
 Dimming System: 0-100% Smooth linear LED dimming
 Control System: 3/4/5/8/9 DMX-512, master-slave, sound or auto, IR Remote control, RDM
 Display System: 1.44" TFT LCD display
 Product Dimensions: 101(D)*258(W)*264.5(H)mm
 Weight: 2.03kg

NEW PRODUCT



2W RGB Beam laser

SKU: 66110

Configuration W2000C(R500+G400+B1200)
 Operation voltage: AC100~240V 50/60HZ
 Power consumption: ≤35W
 Control model: auto/master-slave/Dmx512
 Control interface: 3 pin Dmx512
 Color: RGB
 Effect: one beam RGB effect
 Channel: 7CH
 Application: disco, clubs, KTV, pub, bar, family party
 Working temperature: 0-35

NEW PRODUCT



12W RGB Laser Bar

SKU: 66106

Configuration W2000(R500 + G400 + B1.2W) x 6pcs
 Rated Voltage: AC100~240V 50/60Hz;
 Power consumption: ≤200W
 Laser color: RGB full color
 Beam diameter: φ15mm
 Motor: 7pcs 42 high torque stepper motor
 Modulation: analog
 Rotation: Y axis 240° rotation, each head 140° rotation
 Channel: 14/35/42CH
 Control mode: sound/ automatic/DMX512/ master-slave
 Control technology: RDM data bidirectional transmission
 DMX512 upgrade
 Operating requirement: dry, less dust, 0~35

NEW PRODUCT



960 Strobe

SKU: 66416

Voltage: AC100 ~ 240V 50 / 60Hz
 Power: 38V / 280W
 Lamp beads: 864 5050 three color LED lamp beads + 96 white LEDs
 Control mode: DMX512, self-propelled, master-slave, voice control, with RDM function.
 DMX channels: Ch11, ch39, ch39
 Dimming: 32bit 0 ~ 100% linear dimming
 Features: 8 + 8 section horse running + dyeing + Flash
 Operating temperature: - 30 ~ 50
 Stroboscopic frequency: 1 ~ 30Hz
 Appearance: metal, black
 Connection mode: DMX512 input / output / power input / output.
 IP class: IP20
 Packing Size: 510x300x135 MM
 Product Weight: 3.6 kg

NEW PRODUCT



7x15w 4in1 LED Bar

SKU: 66226

Voltage: AC100~240V 50/60HZ
 Power: 180W
 Lamp beads: 7pcs 4 in 1 lamp beads
 Control mode: DMX512, self-propelled, master-slave, voice control, with RDM function
 Channel: CH18, CH42
 Dimming: 32bit 0~100% linear dimming
 Features: XY moving head + beam + burst flash + XY induction
 Operating temperature: -30 degrees ~ 50 degrees
 Strobe frequency: 1~30HZ
 Appearance: Metal, black
 Connection: DMX512 input and output / Power input and output.
 IP Rating: IP20
 Dimensions: Height: 23.5cm Length: 58 cm Width: 18 cm
 Weight: 5.9 kg

NEW PRODUCT



960 Moving Strobe

SKU: 66417

Voltage: AC100~240V 50 / 60HZ
 Power: 350W
 Light beads: 960 RGB + W, 12 + 12 segments
 Control mode: DMX512, self-going, master, slave, voice control, with RDM function.
 Channel: CH 8, CH 20, CH52
 Dimming: 16 bit 0~100% linear dimming
 Features: flash + dyeing + effect + shake the head
 Operating temperature: -30 degrees ~50 degrees
 Strobe frequency: 1~30HZ
 Appearance: Metal, black and Silver
 Connection mode: DMX512 IO / power IO.
 IP level: IP20
 Size: 280x85x260 mm
 Product Weight: 6.5 kg

NEW PRODUCT



10x30W RGBW LED Bar

SKU: 66103

Power: 350w
 LED Source: 10pcs 30w RGBW LED Chips
 Zoom: 7-50degrees
 Tilt: 210degrees
 Control: DMX512, AUTO, MUSIC, PIXEL MAPPING
 Cooling: fan, temperature control, overheating protect
 Dimmer: 0-100% electronic
 Shutter: Max 10Hz electronically
 Connector: XLR 3 pin in and out Power con in and out

NEW PRODUCT



480PCS LED 5050 RGB+240PCS White LED Strip Strobe Light

SKU: 66351

Power supply AC90240V 50Hz/60Hz
 Rated power 200W
 Light source 480x0.2w 5050 RGB+240x1W white
 Strobe frequency 1-30Hz
 Control channel 4CH/11CH/140CH DMX-512 signal channel
 Dimming 0~100% linear dimming
 Features: 60 segments horse racing, 40 segments of RGB color light+20 segments of white light, dyeing, flash
 Control mode: DMX-512, auto, master-slave, voice control, with RDM function
 Size: 103x10x15 cm
 Weight: 3.4 kg

4x10W Wifi Control RGB 6IN1 Charging F Case



Power Supply: AC 100-240V/50-60Hz
 Power consumption: 40W
 Light source: 4pcs LED RGBWA+UV 6in1 mixing color
 Beam Angle: 15°
 Dimmer: 0-100% dimmer
 Strobe rate:0-24HZ
 DMX Channels: 2 DMX modes, 6channels mode & 10 channels mode
 Control Mode: DMX512,Master-slave,Sound,Auto,Wireless,Wifi, Remote
 Battery type: Lithium Ion
 Battery Charge Time: 3 hours(full power)
 Battery Life: (all on) 6hours, (single Color) 36hours
 Battery Power: 12V, 10Ah
 Wireless effective distance: 400meters
 Product size: 140*140*200mm



Battery



RGB+WA



IP20

SKU: 935



Beam Moving Head Double Prism

Voltage: 100-240V 50/60Hz
 Power: 230W
 Channel: 16ch
 Light source: 230W Lamp
 Gobo wheel: 17 metal gobos+white
 Color wheel: 14 colors+white
 8/16prism/24prism optional ,prism rotation
 Lens : 6-layer optic glass lens
 Motor : 2-phase step motors
 Features: moving more smoothly and no shake
 The channel list is same with Clay Paky
 Display : Roller Button screen
 Size: 410x460x510mm



IP20

SKU: 685

9X10W RGB 6IN1 LED PAR Light Charging F Case - Wireless Transmitter



Power consumption: 90W
 Light source: 9pcs LED RGBWA+UV 6in1 mixing color
 Beam Angle: 15°
 Dimmer: 0-100% dimmer
 Strobe rate:0-24HZ
 DMX Channels: 2 DMX modes, 6channels mode & 10 channels mode
 Control Mode: DMX512,Master-slave,Sound,Auto,Wireless.
 Battery type: Lithium Ion
 Battery Charge Time: 6 hours
 Battery Life: (all on) 4 hours, (single Color) 24hours
 Battery Power: 12V, 25Ah
 Wireless effective distance: 400meters



Battery



RGB+WA



IP20

SKU: 937



Compact Mini Beam 7R Moving Head Light

Voltage: 100-240V 50/60Hz
 Power: 250W
 Channel:16ch
 Light source: 230W Lamp
 Gobo wheel: 14 metal gobos+white
 Color wheel:13 colors+white
 8facet prism ,prism rotation
 Lens : 6-layer optic glass lens
 Motor : 2-phase step motors
 Features: moving more smoothly and no shake
 The channel list is same with Clay Paky
 Size: 310x220x440mm



IP20

SKU: 686

6X10 RGB 6in1 Battery LED PAR Light



Power consumption: 60W
 Light source:6pcs LED RGBWA+UV 6in1 mixing color
 Beam Angel: 30°
 Dimmer: 0-100% dimmer
 Strobe rate:0-24HZ
 DMX Channels: 2 DMX modes, 6channels mode & 10 channels mode
 Control Mode: DMX512,Master-slave,Sound,Auto,Wireless.
 Battery type: Lithium Ion
 Battery Charge Time: 4 hours
 Battery Life: (all on) 3.5hours, (single LED) 21hours
 Battery Power: 12V, 15Ah
 Wireless effective distance: 400meters



Battery



RGB+WA



IP20

SKU: 938



Beam Moving Head 330 15R

Power Supply: AC110v-240V 50/60hz
 Power:350w
 Light source: 15R 330w lamp
 Ballast:electronic ballast
 Lens: 6-Layer option glass lens
 Beam angle parallel beam angel :0-3.8°
 Channel:16ch
 Color temperature:8000K
 Prism: prism 1: Floral prism rotation, prism 2: 8 Prism rotation
 Gobo: 13 gobos+blank double rotation rainbow effect
 Colors 13 color+blank,single rotation rainbow effect
 Focus: option focus
 Mode of control: DMX512/Master-slave/Stand-alone /Auto mode
 Pan: 540degree (16bit) Electric correction
 Tilt:270degree (16bit) Electric correction



IP20

SKU: 687



60W LED Spot Moving Head +12x0.2W RGB

Input Voltage: AC100V-240V,50-60HZ
 Total power: 100W
 Light source: 1x60W white lamp bead, 12 RGB 0.2W lamp bead
 Pattern: 7 patterns + white light
 Color: 7 colors + white light
 Channel: 10/12CH
 Control mode: Voice control, master - slave, self - walk, DMX
 Level: X axis: 540° Y axis: 270°

SKU: 66122



280W Beam Spot Wash 3in1 135pcs 0.5W RGB LED

Voltage: 220V AC, 50Hz
 Power: 380 w
 Bulb size: 300W high power white light
 LED color panel: basic color 9 + white light
 Fixed pattern: 10 patterns + white light, pattern flow from slow to fast
 Rotating pattern plate: 7 patterns + white light,
 Prism: 6 prism +6 row mirror + atomizing mirror
 Focus: Electronic focus, 6 degrees to 24 degrees linear zoom
 Rotation Angle: horizontal direction 540°, vertical direction 270°
 Control mode: DMX512, 18 channels
 Operating mode: Single-machine mode, controller mode,
 Size: 275*245*411mm

SKU: 66230



37x15w RGBW 4in1 Moving Head

Input Voltage: AC100V-240V,50-60HZ , rated power 600W
 Light source: 37 15W high brightness quad-bead, light source life: 50000 hours on average
 Zoom Angle: 5-60°
 Stroboscopic flashing: 1-25 times/second
 Control signal: DMX512, master/slave, voice control or self - program
 Control channel: 20/60 two DMX channel modes
 Applicable environment: indoor
 Color: red, green, blue and white in one
 Level: 540 degrees +16bit fine tuning;
 Vertical: 270 degrees +16bit fine tuning
 Product size: 386 mm*423 mm*263 mm

SKU: 66126



400W BSW 3in1 moving head with CMY and CTO

Input Voltage: AC100V-240V,50-60HZ Power Consumption: 430W
 Color temperature: 8000K
 Light source specification: SSL350W Lumen illuminance: 4 meters 80,000 lm
 Focusing system: linear adjustment from 4 meters to 50 meters
 Atomization system: 1 independent atomization effect, soft and natural light spot
 High-speed strobe: 0-30 times/sec. Adjustable speed strobe effect.
 Color: 12 colors + white light. Color half-color function
 Color system: independent CMY+CTO color mixing system
 Fixed patterns: 12 fixed patterns + white light
 Prism system: standard single 6-row prism and 8 + 8 prism, each prism can be independently forward and reverse
 Product size: 380*270*650 mm

SKU: 66125



37x15w RGBW 4in1 Moving Head

Input Voltage: AC100V-240V,50-60HZ , rated power 600W
 Light source: 37 15W high brightness quad-bead, light source life: 50000 hours on average
 Zoom Angle: 5-60°
 Stroboscopic flashing: 1-25 times/second
 Control signal: DMX512, master/slave, voice control or self - program
 Control channel: 20/60 two DMX channel modes
 Applicable environment: indoor
 Color: red, green, blue and white in one
 Level: 540 degrees +16bit fine tuning;
 Vertical: 270 degrees +16bit fine tuning
 Product size: 386 mm*423 mm*263 mm

SKU: 66123



5x60w Pixel Beam Wash Strobe Bar Led Moving Head

Input Voltage: AC100V-240V,50-60HZ Power Consumption: 500W
 Light Source: Front: Original Osram 5x 60W RGBW 4in1 LED;
 Back: 42x 3W White LED + 84x 0.3W RGB 3in1 LED
 LED Control Feature: Front: 5pcs RGBW LED each Pixel control; Back: 14 sections pixel control, each section 9pcs led.
 Control mode: DMX512,Sound, Master/Slave, Auto run&Sound active
 Channel: 24CH/29CH/105CH - Zoom: 3.8° - 50°
 Pan/Tilt movement: 360 degree infinite rotating
 Power connector: Powercon in/out
 DMX connector: 3-pin XLR in/out
 Effect: Beam , Wash , Strobe Multiple Effect, Pan Tilt infinite rotating

SKU: 66124






WATERPROOF RGBW 4in1 Flat Par 18

SKU: 66400

Voltage: AC100-240V
 Frequency: 50Hz-60Hz
 Consumption: 180W
 Lamp: 18pcs10W RGBW 4in1 LED
 Channel: 8/4CH
 IP rate: IP65
 Mode of control: DMX512, Auto, Sound, Master-slave.
 Function: Can make magic, color mixed, charming effect
 Net weight: 3.7KG




19x15W LED PAR ZOOM 135pcs 0.5W RGB LED

SKU: 66104

Power consumption: 300W
 Voltage: AC 100V-240V,50-60Hz
 Light source: 19pcs 15w 4-IN-1 LEDs (R, G, B, W)
 Zoom range: 15-60degree
 Operation mode: DMX512, master-slave, Sound, Auto
 Channels: 5 modes: mode1: 32CHs; mode2: 16CHs;
 mode3: 10CHs; mode4: 5CHs; mode5: 32CHs
 Dimmer: 0-100% smoothly dimmer
 Strobe: 20t/s strobe effect with variable speed
 Protection level: IP20




LED Battery Butterfly light

SKU: 66371

Voltage: 110V-240V/50-60Hz
 Power: 25W
 Light Source: 2x12W RGBW Leds
 Channel: 9ch
 Control mode: DMX512, Wireless DMX, Remote,
 Sound, Master-slave, Auto
 Size: 300.4x231.7x279.5 mm
 Weight: 3.22kg
 Battery charge time: 3hours
 Battery using time: About 7-8 hours
 Battery capacity: 5000mAH




9x40W LED Beam light with 135pcs 0.5W RGB LED

SKU: 66120

Power Supply: 90v-240v/50-60Hz
 Power consumption: 40W
 Light source: 9pcs led
 Effect: Light beam and wash
 Dimmer: 0-100% dimmer
 Channel: 4/10/36/46CH
 Control Mode: DMX512




40x10w 4in1 LED Wash light

SKU: 66102

Power supply 100-240V 50/60Hz
 Power: 480W
 LAMP SOURCE: 40x10W RGBW LEDs,
 Feature: small size, high power, super brightness, colour mixture
 Beam Angle: 40°
 Tilt: 210°, 16 bit
 IP rate: IP65
 Dimmer: 0-100% linear electronic dimmer, no flicker or jitter occurs
 Strobe: Adjustable speed stop/strobe effect,
 Size: 450*131*310mm
 Protocol: DMX-512
 DMX channels: 4/8CH
 Connections: 3-pin XLR DMX input/output
 Display: Easy-to-use 4-button control panel with LCD display
 Operating modes: DMX512, master/slave, auto, sound




Waterproof blinder 4x100W LED COB 135pcs 0.5W RGB LED

SKU: 66305

Input Voltage: AC100-240V 50-60Hz
 Power: 415W
 LED: 4pcs 100w warm white COB LED
 Beam angle: 50degrees
 Field angle: 80degrees
 Strobe: 1-30Hz
 Dimming
 DMX channel: 4/8ch
 IP Rating: IP65
 Cooling: Waterproof fan+ die-casting aluminum
 Net weight: 6KG



120w Moving Head

Working voltage: AC95V-245V/50Hz
 Product power: 120W
 Pattern parameters: 10 patterns, 8 colors 4. Lamp bead parameters: 1 100W white light bead
 Control mode: international general DMX512, 10 channels
 Working mode: DMX512, master/slave, self-propelled, voice control
 Dimming mode: 0~100% ultra-smooth dimming
 Strobe: 20 times/second
 Opening size: 22cm deep 8cm

SKU: 977



IP20



Mini Beam 100W

Power: 150W
 Light source: 1pc 100W LED White color
 Working lifetime: About 50000 hours
 Working temperature: -20-40
 Control mode: DMX 512, Auto, Master-slave, sound
 Power Socket: Powercon In/Out
 DMX socket: 3pin DMX In/Out
 Prism: 8 prisms
 Color wheel: 7colors+white
 Gobo wheel: 7gobos+white
 Size: 330x280x260mm

SKU: 973



IP20



120W Three Prism Wash Gobo 2in1 Moving Head

Working voltage: AC95V-245V/50Hz
 Total product power: 140W
 Pattern parameters: 8 patterns, 8 colors 4. Lamp parameters: 1 80W white lamp, 6 5050 8W RGBW lamp beads
 Control mode: international general DMX512, 15 channels
 Working mode: DMX512, master/slave, self-propelled, voice control
 Dimming mode: 0~100% ultra-smooth dimming
 Strobe: 20 times/second
 Opening size: 22cm deep 8cm

SKU: 974



RGB+W



IP20



4 LED Wash Moving Head

Working voltage: AC95V-245V/50Hz
 Power sumption: 100W
 Control mode: DMX512, auto, sound, master-slave
 Channel: 15/10CH
 Dimmer: 0-100% super dimmer
 Strobe: 25 times per second

SKU: 976



IP20



100W Small Steel Cannon Moving Head

Working voltage: AC95V-245V/50Hz
 Product power: 100W
 Pattern parameters: 10 patterns, 8 colors 4. Lamp bead parameters: 1 80W white light bead
 Control mode: international general DMX512, 10 channels
 Working mode: DMX512, master/slave, self-propelled, voice control
 Dimming mode: 0~100% ultra-smooth dimming
 Strobe: 20 times/second
 Opening size: 22cm deep 8cm

SKU: 975



IP20



Mini Beam 100W

Power: 150W
 Light source: 1pc 100W LED White color
 Working lifetime: About 50000 hours
 Working temperature: -20-40
 Control mode: DMX 512, Auto, Master-slave, sound
 Power Socket: Powercon In/Out
 DMX socket: 3pin DMX In/Out
 Prism: 8 prisms
 Color wheel: 7colors+white
 Gobo wheel: 7gobos+white
 Size: 330x280x260mm

SKU: 977



IP20



Fully embedded magic ball 3in1

Working voltage: AC95V-245V/50Hz
 Product power: 40W (magic ball 15W, strobe 20W, 30mW red and green laser)
 Lamp bead parameters: 1 15W Osram 4 in 1 lamp bead, 2 10W strobe, 30mW red and green laser
 Control method: international general DMX512, 13 channels
 Working mode: DMX512, master/slave, self-propelled, voice control
 Dimming method: 0~100% super smooth dimming
 Strobe: 20 times/second
 Hole size: 20cm deep 18cm

SKU: 66374



IP20



Fully embedded COB surface light

Working voltage: AC110-240V/50Hz
 Product power: 100W
 Lamp bead parameters: 100W dual color temperature lamp bead
 Control method: international general DMX512, 4 channels
 Working mode: DMX512, master/slave, self-propelled, voice control
 Dimming method: 0~100% super smooth dimming
 Strobe: 25 times/second
 Hole size: 20cm deep 18cm

SKU: 66377



IP20



Fully embedded 24 dyeing

Working voltage: AC110-240V/50Hz
 Product power: 80W
 Lamp parameters: 6 x RGBW monochrome 3W
 Control method: international general DMX512, 6 channels
 Working mode: DMX512, master/slave, self-propelled, voice control
 Dimming method: 0~100% super smooth dimming
 Strobe: 25 times/second
 Hole size: 20cm deep 18cm

SKU: 66376



IP20



Six Bee Eye Laser

Working voltage: AC220V/50Hz
 Product power: 80W
 Lamp parameters: 6*10W four-in-one and 1*50mW green laser
 Control method: international general DMX512, 9 channels
 Working mode: DMX512, master/slave, self-propelled, voice control
 Dimming method: 0~100% super smooth dimming
 Strobe: 20 times/second
 Hole size: 20cm deep 18cm

SKU: 66375



IP20



Fully Embedded Butterfly Laser

Laser: 500MW green light/150MW red light
 Lamp bead: LED 4 in 1 RGBW 2x10W Voltage: AC110/240V 50-60Hz
 Power: 50W Strobe LED: 20W white light
 Control: DMX512, voice control, master-slave, self-propelled
 Function: dot matrix effect, music dynamic opening size: 20cm deep 18cm"

SKU: 66373



IP20



Full color animation Laser

500MW power: green 80mw, red 350mw blue 150mw)
 1000MW Power: Green 100mw, Red 300mw, Blue 600mw Playback system: DMX512, voice control, automatic,
 Control system: high-speed galvanometer; scanning angle $\pm 20^\circ$
 Program effect: show beam effect in three-dimensional space, enhance space
 Control interface: DMX512 (12 control channels)
 Power supply: AC 110/220V 50/60HZ
 Hole size: 20cm deep 18cm

SKU: 66372



IP20

60W RGBW LED 5050 SMD 3in1 MINI Moving Head



Input Voltage: AC100V-240V,50-60HZ
 Power Consumption: 60W
 Light Source: 60W RGBW LED with 5050 SMD 3in1 MINI moving
 Control mode: DMX512,Sound, Master/Slave, Auto run&Sound active
 Channel: 16/21 CH
 Beam Angle: 8°
 Product Size:160/150/230cm



SKU: 965

Remote control LED 30W spot moving head



Voltage: AC100-240V, 50/60HZ 60W
 Light Source: 1pc*30W White Lamp Bead
 Laser: Green 80mW
 Control Channel: 9/11CH
 Control Mode: Auto,DMX512,Master-slave,Sound
 Pan/Tilt": 540 degrees / 270 degrees



SKU: 123

6x10W Bee Eyes Shaking Head + Laser



Voltage: AC100-240V 50/60 HZ
 Total power: 120W
 Light source 1: 6 Cree+ 10W four-in-one (RGBW) lamp beads
 Light source 2: 1 515nm green laser
 Channel: 15CH
 Control mode: DMX512, master-slave, self-propelled, voice control
 X-axis: 540°
 Y-axis: 180°



SKU: 966

260 9R Beam Moving Head



Voltage: AC90-260V 50/60hz Power: 450W
 Source: YODN MSD 260W 9R,
 Average Lamp Life: 2000H Lumen Output: 10400LM
 Color Wheel: 14 color + white, halftone effect adjustment
 Gobo Wheel: 11 patterns + white
 Prisms: 8prism + Honeycomb prism (2 prisms can be superimposed to 40, can be two-way independent rotation)
 Pan: 540°(16bit accuracy) Tilt: 270°(16bit accuracy)
 Motors: 14 super mute motors, XY three-phase motor
 Frost/Atomization: independent frost effect, spot soft and natural
 Channel: 16/20CHs
 Size: 320*220*580mm (LWH)
 Net Weight: 14.8kg



SKU: 124

MINI 7x12W LED RGBW Moving Head



Input Voltage: AC100-240V/50-60Hz
 Power consumption: 95W
 Light Source: 7pcs 12W LEDs RGBW
 DMX channel: 10CH/15CH
 Control mode: DMX512,auto-run,sound-control,master-slave
 Movement: Pan:540°Tilt:190°
 Display: LED Display
 Housing: LCP+Aluminium Alloy
 Weight: 4.5kg
 Dimension: 160*150*300 mm



SKU: 964

150W LED Beam Spot Wash 3in1 Moving Head



Voltage: AC100-240V,50/60Hz Power: 280W
 Led source: 150W White LED
 Led Life Time: 50000 Hours
 Channel: 18 DMX channel
 Pan: 540 degree + fine ; Tilt: 270 degree + fine
 Zoom range: 8-17°
 Strobe: 1-25 Hz with pulse effect
 Color Wheel: 9 colors + open, with rainbow effect
 Static Gobo Wheel: 10 gobos
 Rotation gobo wheel: 6 gobos+open
 Prism: 3 facet prism with bi-direction rotating
 Frost: With frost effect
 Display: LCD display, can adjust 180 degree to fit
 Product size: 275*200*475mm
 Net Weight: 9kg



SKU: 125



250W LED BSW Moving Head Light

Input Voltage: AC90-260V 50/60Hz
 Power Consumption: 350W
 Light Source: 250W High Output White LED
 Control Signal: DMX 512, master-slave and sound activated or auto operation
 Control Channel: 16/18 DMX Channels USITT DMX-512
 Prism: 8-facet Prism, bi-directional rotatable at variable speeds
 Dimensions: 320*220*480mm
 Weight: 13.50kg

SKU: 981

LED



Light

IP20



60W LED Spot Moving Head Light

Voltage: 100-240V 50/60Hz
 Power consumption: 80 W
 Color: 8 colors
 Gobo: 8 gobos
 Channel: 9/11ch
 Light source: 1PCS 60W high power White LED
 Control: DMX, Sound, Master-slave, Auto
 Size: 198*144*272 mm
 Net weight: 3.2 kg

SKU: 689

LED



Light

IP20



80W LED Zoom Beam Moving Head

Input voltage: 110-260 V, 50/60 Hz Power: 150W
 Light source: 80W LED
 Working lifetime: About 50000 hours
 Control mode: DMX 512, Auto, Master-slave, Sound
 Channel: 16ch /20ch
 2DMX Modes: STD (16ch)/EXT (20ch)
 Prism: 8 linear prism rotating ,16 linear prism rotating
 Color Wheel: 13 colors+white
 Gobo Wheel: 11 gobos+white,gobo-flow effect,gobo shake
 Function: Dyeing, strobe, zoom, light beam effect
 Pan: 540° (16bit) Tilt: 270° (16bit)
 DMX socket: 3-pin IN/OUT
 Power socket: Power Con IN
 Dimensions: 460*250*290mm

SKU: 982

LED



Light

IP20



10W LED Moving Head Spot

Input power: AC100-240V 50/60Hz
 Power consumption: 22W
 Output LUX: 1500 LUX at 3 meters
 LED: 1 PCS 10W high power white Cree LED
 DMX Channel: 9/11 channels
 Pan:X axis 540 degree ; Tilt:Y axis 270 degree
 Control mode: DMX512/Master-slave/Auto/Sound
 Display: LCD display
 Color wheel: 7 color+open
 Gobo Wheel: 7 gobo+open, gobo-flow effect,gobo shake
 Feature: 8 internal program, sound mode can control by DMX512
 Beam angle: 13 degree
 Net weight: 2.5kg
 Size: 140*160*290 cm

SKU: 984

LED



Light

IP20



36*18W RGBWA+UV LED Moving Head+Zoom Light

Input Voltage: AC90-260V 50/60Hz
 LED: 36 *18W 6in1 RGBWA+UV LED moving
 Power Consumption: 650W
 Control Channel: 18/15 DMX channels
 Control Signal: DMX512, master-slave and sound activated or auto operation
 Power connection: Powercon In DMX data In/ Out: XLR 3pin(XLR 5pin is optional)
 Packing Dimensions: 450*320*430mm
 Weight: 9 kg

SKU: 983

LED



Light

IP20



6pcs LED Moving Head

Voltage: AC100V~240V/50~60Hz
 Machine power: 120W
 Lamp beads: 15W, RGBW four-in-one LED lamp beads
 Lamp life: more than 50,000 hours
 Lens: Lens Aspheric lens Supports DMX signal priority recognition, signal retention when DMX signal is interrupted
 Beam angle: 1.5°
 Spot angle: minimum 6°, maximum 51°
 Color Rotation System: Color Rotation System: RGBW 4-in-1 Rotation, Macro Function Color System
 Strobe: 1-30 times / sec electronic strobe and random strobe
 Scanning system: horizontal 540° / 1.5 seconds, vertical 180° / 0.5 seconds

SKU: 986

LED



Light

IP20



LED MOVING HEAD LB40

SKU: 66437

Light Source: 1*40W White Laser 30*0.2W 3-IN-1 RGB LEDs
 Optics: Ø160mm Front lens 1.1° Beam angle
 PAN: 2 modes 1. 360° Continuous movement 2. 540°(8/16 bit)
 TILT: 2 modes 1. 360° Continuous movement 2. 270°(8/16 bit)
 Color System: Color wheel with 17 dichroic colors 6-Color wheel with variable direction and speed control
 Gobo System: 1 Static gobo wheel with 19 gobos plus open
 Control System: 23/25 DMX channels USITT DMX-512 master-slave, sound or auto, IR Remote control, RDM
 Prism 1: 8-Facet circular prism with variable speed
 Prism 2: 3 different prisms, 5-Facet linear prism/16-facet circular prism/
 8+16-facet circular prism with variable speed and direction
 Display System: 1.44" TFT LCD display
 Product Dimensions: 207(D)*268(W)*423.7(H)



MOVING HEAD LASER 2WRGBW 4in1

SKU: 66108

Rated voltage: AC100~240V 50/60Hz
 Power consumption: ≤100W
 Scanner: 2W, 3W 25kpps, 4W 30K, scan angle: max±30°;
 Input signal: ±5V; Linearity distortion <2%
 Motor: 3 phase 42 motor 2pcs
 Scan: X axis 540° rotation, Y axis 270° rotation
 Modulation: analog
 Beam diameter and divergence: 3*6.5mm; 1.5mrad
 Control mode: music(black out)/ automatic/master-slave/DMX-512(6/40CH)/ILDA
 Control interface: 3 pin DMX512/25DB ILDA
 DMX effect: Single pattern mode, and with the function of unique blanking, strobe, rotation, movement, billowing, zoom
 Weight: 9.5 kg



LED MOVING HEAD LB100

SKU: 66436

Light Source: 1*100W White Laser 30*0.2W 3-IN-1 RGB LEDs
 Optics: Ø160mm Front lens 1.1° Beam angle
 PAN: 2 modes 1. 360° Continuous movement 2. 540°(8/16 bit)
 TILT: 2 modes 1. 360° Continuous movement 2. 270°(8/16 bit)
 Color System: Color wheel with 13 dichroic colors 6-Color wheel with variable direction and speed control
 Gobo System: 1 Static gobo wheel with 13 gobos plus open
 Control System: 23/25 DMX channels USITT DMX-512 master-slave, sound or auto, IR Remote control, RDM
 Prism 1: 3 different prisms, 5-Facet linear prism/8-Facet circular prism/4+8+16-facet circular prism with variable speed
 Prism 2: 3 different prisms, 6-Facet linear prism/16-facet circular prism/8+16-facet circular prism
 Display System: 1.44" TFT LCD display
 Product Dimensions: 61.8(D)*297.9(W)*513.7(H)mm



MOVING HEAD LASER 4W

SKU: 66362

Rated voltage: AC100~240V 50/60Hz
 Power consumption: ≤100W
 Scanner: 2W, 3W 25kpps, 4W 30K, scan angle: max±30°;
 Input signal: ±5V; Linearity distortion <2%
 Motor: 3 phase 42 motor 2pcs
 Scan: X axis 540° rotation, Y axis 270° rotation
 Modulation: analog
 Beam diameter and divergence: 3*6.5mm; 1.5mrad
 Control mode: music(black out)/ automatic/master-slave/DMX-512(6/40CH)/ILDA
 Control interface: 3 pin DMX512/25DB ILDA
 DMX effect: Single pattern mode, and with the function of unique blanking, strobe, rotation, movement, billowing, zoom
 Weight: 9.5 kg



120W LED Spot Wash Moving 7x 4W RGBW 4in1

SKU: 66208

voltage: AC100-240V, 50/60Hz Rated power: 180W
 Lamp Beads: 120W White light +7x 4W 4-in-1 RGBW
 Heat dissipation system: intelligent temperature control protection
 Lens: high precision optical lens group
 Beam Angle: 10 degrees
 Working mode: DMX512 signal/master/slave/self-walking/voice control
 Control mode: International DMX512, 15/20CH
 Panel display: 0.39 inch 4 digit tube +4 keys
 Scanning speed: horizontal 540°, vertical 270° / speed adjustable
 Scan fine tuning: 8/16Bit
 Scanning positioning: electronic automatic positioning
 Color Plate: 7 colors + white light with rainbow effect
 Pattern Plate: 8 patterns + white light, with pattern shake effect
 Prism: Honeycomb prism, rotatable, adjustable speed





200W LED Spot Moving Head

Input Voltage: AC100-240V 50/60Hz
 Power: 200W
 Light Source: 1 LED (white) 200 W,
 Beam Angle: 16°
 Colors: 7 + white, split colors, continuous scroll at variable speeds
 Rotation wheel (1): 6 + open (5 aluminum + 1 glass), rotating,
 interchangeable, slot-n-lock, continuous scroll at variable speeds
 Static wheel (2): 8 + open (8 stamped), continuous scroll at variable speeds
 Prism: 3-facet round, bidirectional rotation at variable speeds
 Strobe Rate: 0 to 15 Hz
 DMX Channels: 10 or 16
 Control mode : DMX 512, master-slave , sound , Auto
 DMX connector : 3-pin XLR connectors IN/OUT
 Dimension: 290x194x432mm



SKU: 681 3800156606814



90W LED Spot Moving Head Light

Voltage: 100-240V 50/60Hz
 Power: 120v 60Hz 148W(0.1A)max,2A inrush
 Beam angle: 14degrees
 Channel: 14ch
 Light source: 1PCS 90W high power White LEDs
 Life rated: more than 50,000hrs
 Size: 250*255*360mm
 Net weight: 6kg
 Carton size: 370*360*340mm



SKU: 985



120W LED Spot Pattern Moving Head

Input Voltage: AC100-240V 50/60Hz
 Power: 120W
 Light Source: 1 LED (white) 120 W,
 Beam Angle: 16°
 Colors: 7 + white, split colors, continuous scroll at variable speeds
 Rotation wheel (1): 6 + open (5 aluminum + 1 glass), rotating,
 interchangeable, slot-n-lock, continuous scroll at variable speeds
 Static wheel (2): 8 + open (8 stamped), continuous scroll at variable speeds
 Prism: 3-facet round, bidirectional rotation at variable speeds
 Strobe Rate: 0 to 15 Hz
 Control mode : DMX 512, master-slave , sound , Auto
 Cooling : Efficient low noise fan cooling system
 DMX connector : 3-pin XLR connectors IN/OUT



SKU: 684 3800156606845



7x40w LED Wash Moving Head RGBW Mixing Color

Input: 110-240 V, 50/60 Hz
 Power: 320W
 Light source: 7* 40W RGBW 4in1 mixing color LED wash moving head
 Control mode:DMX512,Auto,Master-slave,Sound
 Channel:17ch/12ch
 2DMX Modes:STD(17ch)/HSI(12ch)
 Function:the dyeing effect,stroke,zoom, the beam light effect
 Pan:540°(16bit)Electric correction
 Tilt:270°(16bit)Electric correction
 Zoom range:9°~ 50°
 Dimmer:0-100% dimmer
 Size:240x300x405mm



SKU: 682



300W LED Moving Head

LED source: 300W LED ; 8000K white LED,16*10W RGBW
 Working Time (hours): 50000
 Fixed gobo wheel: 8 fixed gobos + open and bi-direction rotation
 Color Temperature(CCT): 6000K (Daylight Alert)
 Pan X: 540 degree, Tilt Y: 270 degree
 Channel: 25ch/18ch Dimmer from 0-100%, Strobe
 Beam angle: 3 degree 1 rotate gobo wheel (7 gobos + open) and 1 fixed
 gobo wheel (8 gobos + open)
 1 Color wheel: 7 main colors + open with rainbow effect 2 Prism disk,
 Rotation prism,
 Focus Temperature protect function powercon in & out, color screen,
 Silent fan, good housing Pan/Tilt 0-255 speed controllable



SKU: 126



12x10w LED Moving Head RGBW

Voltage: AC 110-240V 50/60 Hz
 Power: 150W
 LED QTY: 12*10W RGBW 4in1 LED Moving Head Light
 Lumens: 4500+, Lux @2m 40500+
 Control: Master-Slave / Auto / Sound / DMX
 Channel control: 15CH
 Dimmer: 0-100%
 Flash: 0-20Hz
 Pan / Tilt: User -selectable Pan / Tilt ranges
 Pan/ Tilt: 540 degrees / 270 degrees
 Fine Turning: 8-16 bit
 Color: Black / White
 Size: 300x245x385mm



SKU: 688

NEW PRODUCT



150W Beam LED Moving Head With Halo

SKU: 66304

Power: 150W
 Light Source: High Power 1*100W LED
 Lighting Life: 50000 hours
 Color temperature: 7000K-8000K
 Beam Angle: 2.5 degrees
 Display mode: LCD display, lamp temperature display, Chinese and English display, reversible display
 Working mode: DMX512 mode, self-propelled mode, voice control mode and master-slave mode
 DMX Channel Mode: 17 DMX
 Pan: 540 Degree (16 Bit) Electrodynamic Correction
 Tilt: 270 Degrees (16 Bits) Electro-dynamic Correction
 Dimming Level: 0-100% Perfect Linear Dimming System
 Product Weight : 12.5kg

NEW PRODUCT



280W 10R BEAM SPOT WASH MOVING HEAD

SKU: 66352

Lamp: 280W YODN LAMP (10R) beam spot wash moving
 Channel mode: 24 /16 CH DMX512 Channel
 Pan scan540°(16bit) Electric correction
 Tilt scan270° (16bit) Electric correction
 Color wheel: one color wheel, 14 kinds of color chips in one color wheel
 Gobo: 14 static gobos, 9 rotation gobos;
 Effect Wheel: Rotation eight prism, effect move , frost
 Lens: optical system achanical focue beam angle 04°
 Power Input: 100-240V50/60Hz
 Power Dissipation400W
 IP level: IP20
 Net weight: 18kg

NEW PRODUCT



360 Beam Module RGB+240PCS White LED Strip Strobe Light

SKU: 66415

Voltage: 100-240V50/60Hz Power: 360W
 Light source: 200 W white module LED
 Peripheral auxiliary light: 30×0.5W RGB 3-in-1 leds
 Beam Angle: 1.8°
 Outlet lens diameter: 160mm
 Color disk: 15 colors + white light, half color effect
 Fixed Pattern Plate: 17 fine patterns (14 solid patterns +3 color patterns)
 Prism: 1pc 16 prism, 1pc 24 prism, prism can be superimposed
 Control panel: Built-in color LCD panel, 4 mechanical keys
 Control channel: 19 DMX512 channels
 Electronic dimming: 16-bit
 X-axis operating angle: 540° Y-axis operating angle: 270°
 Power socket: Power connector input/output
 Signal input/output: three core cannon socket
 Product size: 298×237×524mm

NEW PRODUCT



400W Led Zoom Moving Head

SKU: 66225

Voltage Rated voltage AC100V-240V
 Rated frequency: 50/60HZ
 Color temperature: 2800K-6000K
 Service life: 50000 hours
 Color: with 2 colors + white light
 Dimming: 1-100% linear adjustment.
 Display index: 90
 Number of channels: 11CH
 Control mode: master-slave, self-propelled, standard DMX512
 Projection light range: X direction 540°, Y direction 250°,
 Spot angle: 5-60°.
 Number of motors: 4 ultra-quiet motors in total.
 Protection class: IP20
 Weight: 12Kg
 Size: 33×25×52 cm

NEW PRODUCT



30W LED Logo Lightcontroller

SKU: 139

Voltage: AC110-240V, 50/60HZ
 Consumption: 30W
 Light source: One pcs LED White 30W
 IP rating: IP20
 Housing material: Black Iron shell
 Mode of control: Auto, Remote
 Movement: Rotated(Forward/backward), Stop
 Net weight: 1.4kg

NEW PRODUCT



LED 150W Spot Moving Head

SKU: 66222

LED source: 150W LED
 Control mode: DMX512, Master/slave, Sound, Auto mode
 DMX Channel: 16ch/20ch
 Dimmer: from 0-100%, Strobe
 Beam angle: 15 degree
 1 rotate gobo wheel: (6 gobos + open) and 1 fixed gobo wheel
 (6 gobos + water ripple + open) + 1 water ripple wheel
 1 Color wheel: 7 main colors + open with rainbow effect
 Prism: 3-facet prism, Rotation prism, Focus
 Pan X: 540 degree,
 Tilt Y: 270 degree
 Pan/Tilt: 0-255 speed controllable

NEW PRODUCT



8x10w RGBW LED Lifting-Ball

SKU: 66445

Light source: 8x10W RGBW 4-in-1 beads, 96pcs RGB 3-in-1 beads
 Power: 100W
 Size: 20cmLift
 Stroke: 3 metres
 Control mode: DMX512/Artnet mode
 Channel: 15/64 channels optional
 Voltage: AC100V-240V/50-60HZ
 Power: 150W
 Size: 170*130*330mm

NEW PRODUCT



Mirror Glass Ball

SKU: 191 20 cm
 SKU: 193 30 cm
 SKU: 194 60 cm
 SKU: 195 70 cm
 SKU: 196 80 cm
 SKU: 197 120 cm

Application: concert, night club, theater, party,
 wedding event, hotel, building
 Material: Glass

NEW PRODUCT



Mini Battery bubble machine remote control

SKU: 134

Voltage: AC110V-220V
 Frequency: 50-60Hz
 Power: AC/Batteries
 Control mode: Auto, Remote control
 Battery: 8x NO.5 crown cell
 Tank Capacity: 0.6L
 Bubble Output: 2400 bubble/min
 Net weight: 1.5kg
 Size: 240x230x215mm



300W Bubble Machine

SKU: 968

Voltage: AC 110/230V 50-60Hz ± 10%
 Power: 200W
 Bubble Oil Capacity: 2.5L
 Bubble covered area: 200 m2
 Control: Remote control (30) meters, manual
 Product Dimensions: 415*250*415mm
 Weight: 12 kg

NEW PRODUCT



Moving Head Beam 46

SKU: 66439

Source: 4*60W 4-IN-1 RGBW LEDs (6*30)*0.2W
 3-IN-1 SMD RGB LEDs
 Optics: 4PCS high efficiency lens 3.5°Projection angle
 Movement TILT: 2 modes 60° Continuous movement 240°
 Colors: Sophisticated 4 colors RGBW mixed
 Linear CTO 2500-8000K
 Strobe Effect: 1-25Hz shutter/strobe effect with variable speed
 Dimming System: 0-100% Smooth linear LED dimming
 Control System: 22/49/73 DMX channels USITT DMX-512
 Display System: 1.44" TFT LCD display
 Product Dimensions: 168(D)*600(W)*235.5(H)mm
 Net Weight: 14.2kg

NEW PRODUCT



Moving Head Beam 66

SKU: 66438

Source: 6*60W 4-IN-1 RGBW LEDs (6*30)*0.2W 3-IN-1 SMD
 RGB LEDs
 Optics: 6 pcs high efficiency lens 3.5°Projection angle
 Movement TILT: 2 modes 60° Continuous movement 240°
 Colors: Sophisticated 4 colors RGBW mixed
 Linear CTO 2500-8000K
 Strobe Effect: 1-25Hz shutter/strobe effect
 with variable speed
 Dimming System: 0-100% Smooth linear LED dimming
 Control System: 22/49/73 DMX channels USITT DMX-512
 Display System: 1.44" TFT LCD display
 Product Dimensions: 168(D)*900(W)*235.5(H)mm
 Net Weight: 14.2kg

NEW PRODUCT



Moving Head Beam 16

SKU: 66440

Power supply 100-240V 50/60Hz
 Power: 80W
 Lamp source: 1x60W 4-IN-1 RGBW LEDs 30x0.2W
 3-IN-1 SMD RGB LEDs
 Pan/Tilt: 76°
 Dimmer: 0-100% Smooth linear LED dimming
 Strobe: 1-25Hz shutter/strobe effect with variable speed
 DMX channels: 23/28 DMX channels USITT DMX-512
 Connections: 3-pin XLR DMX input/output
 Display: 1.44" TFT LCD display
 Operating modes: DMX512, master/slave, auto, sound
 Net Weight: 4.6KG
 Size: 224/224/262.5 mm



19x15W AURA LED Beam Moving Head Light Zoom RGBW

Input Voltage: AC90-260V 50/60Hz
 Power Consumption: 300W
 Zoom range: 8-28degree. Motor: 3pcs
 Control mode: DMX512, master-slave, Sound, Auto
 Channel: 14/25CHs
 Beam (Primary LED array): provide the main output
 Aura (Secondary background LED array): illuminate the front of the head, provide local diffuse light output and can be set to contrast with the beam output.
 Beam: RGBW color control with color temperature control
 Aura: RGB control ; Dimming: 0-100% smoothly dimmer
 Strobe: 20t/s strobe effect with variable speed and pulse effects
 540° PAN and 270° TILT movement
 Size: 410x320x470mm



SKU: 693

NEW PRODUCT



Moving Head Wash Strobe 712ES

Source Face 1: 7*12W 4-IN-1 LEDs (RGBW) 60*0.2W 3-IN-1 LEDs (RGB)
 Source Face 2: 324*0.5W 5730 LEDs (WW+CW) 9 Individual control rings
 Optics Face 1: High efficiency optic system 25° Beam angle 35° Field angle
 Optics Face 2: 120° Field angle High output
 PAN: 2 modes 1. 360° Continuous movement 2. 540° (8/16 bit)
 TILT: 2 modes 1. 360° Continuous movement 2. 270° (8/16 bit)
 Color System Face 1: RGBW for main light, CTO, 2800K-5600K
 Color System Face 2: Warm white+cold white, CTO, 2500K-4600K
 Strobe Effect: 0-25Hz LED shutter/strobe effect with variable speed
 Dimming System: 0-100% Smooth linear LED dimming
 Control System: 9/18 DMX channels USITT DMX-512
 Display System: 1.44" TFT LCD display
 Product Dimensions: 139(D)*297.9(W)*376.7(H)mm

SKU: 66441

Power CON IN



SKU: 679 Female



SKU: 960 Male

XLR 3PIN -Male , Female - LH P005A



SKU: 678 Male



SKU: 963 Female

Power CON OUT



SKU: 961 Female



SKU: 962 Male

Hook

SKU: 698 30mm
SKU: 699 50mm

Safety Rope



SKU: 697



Spark Firework Machine

Voltage: AC 110-240V 50/60 HZ
 Power: 400W
 Control: DMX, remote control
 Temperature: (-10/+50°C)
 Height: 1-5 m
 Spray direction: erect
 DMX Channel: 2
 NW: 9.5 kg



SKU: 902



Stage Fog Waterproof Spark Machine

Power: 400W
 Control: DMX, Remote control
 Temperature (-10/+50°C)
 Height: 1-4 meter
 Spray direction fall
 DMX Channel: 2
 Machine Size: 200x200x180mm
 NW: 6.5KG



SKU: 903



LPG Fire Machine

Voltage: AC110-240V 50/60HZ
 Power: 250W
 Spary Height: 1-2 meter
 Control: DMX512/Electric Control/remote control
 DMX Channel: 1
 Gas: LPG fire gas bottle
 Machine Size: 420x165x200mm
 NW: 7KG



SKU: 904



Firebolt Fire Machine

Voltage: AC110-240V 50/60HZ
 Power: 250W
 Spary Height: 1-4 meter
 Control: DMX512/remote control
 DMX Channel: 4
 Gas: LPG Gas bottle
 Machine Size: 50x35x27CM
 NW: 13KG



SKU: 905



Water Low Fog Machine

Voltage: AC110-240V 50/60HZ
 Power: 3000W
 Cover area: 150-200 square meter
 Control: DMX512/remote control/manual
 DMX Channel: 2
 Consumable materials: water+heavy fog liquid
 Capacity of fog tank: 3L
 Capacity of water tank: 15L
 Machine Size: 714x400x316mm
 GW: 52KG

SKU: 908



FOG



Fog Machine 1000W

Voltage: AC110 - 240V 50/60HZ
 Power: 1000W
 Control: remote control/wire control
 Re-heating time: 5 mins
 Capacity of oil tanks 1 L
 Size: 360x200x130mm
 NW: 4KG

SKU: 912



FOG



Dry Ice Machine 3000W

Voltage: AC110-240V 50/60HZ
 Power: 3000W
 Cover area: 100-200 square meter
 Control: Manual
 Consumable materials: Dry ice and water
 Machine Size: 660x 370x580mm
 NW: 16KG

SKU: 909



FOG



Fog Machine 1500W

Voltage AC110 240V 50/60HZ
 Power: 1500W
 Control: remote control/DMX 512
 Re-heating time: 5 mins
 Capacity of oil tanks 3 L
 Size 510x260x150mm
 NW: 6KG

SKU: 913



FOG



Fog Machine 900W

Voltage AC220V-240V 50/60HZ
 Power: 900W
 Control: remote control/wire control
 Re-heating time 5 mins
 Capacity of oil tanks 1.5L
 Body color: black with hanging bracket
 Machine Size: 36.5x18.5x17cm
 NW 3KG

SKU: 910



FOG



LED Fog Machine 1500W

Voltage: AC110-240V 50/60HZ
 Power: 1520W
 Control: remote control/wire control/ time
 Re-heating time: 5 mins
 Capacity of oil tanks: 2.5 L
 Machine Size: 540x330x260mm
 NW: 6KG

SKU: 914



Light



FOG



900W Fog Machine Remote

Voltage: AC220V-240V 50/60HZ
 Power: 900W
 Control: remote control/wire control
 Re-heating time: 40s
 Capacity of oil tanks: 1.5kl
 Body color: black .with hanging bracket
 Machine Size: 530×270×320cm
 Weight: 3KG

SKU: 910



FOG



Cold Spark Machine 750W

Voltage: AC110-120,50/60Hz or AC220-230,50/60Hz
 Maximum power: 650W
 Preheating time: about 3-5min
 Spray height: 1-5M adjustable
 Control mode: DMX and wireless remote control
 DMX Channel: 2 channels (customizable)
 Temperature control mode: electronic constant temperature control
 Heating method: electromagnetic heating
 Net weight: 5.9KG
 Product size: 205x205x265mm

SKU: 66412



FOG MACHINE 3000W

Voltage: AC110-240V 50/60HZ
 Power: 3000W
 Control: DMX512/remote control
 Re-heating time: 5 mins
 Capacity of oil tanks: 5L
 Size: 68×31×20CM
 NW: 13KG

SKU: 915



FOG



Twin-tube column machine

Operating voltage: 220-240 V, 50/60 Hz
 Current limit insurance parameters: 15 A, 250 V
 Total power: 3000 W
 Warm-up time: about 8 minutes
 Oil drum volume: 3.0L
 Functions: Remote control, DMX-512, OLED control
 Single blast time: 10 seconds
 Maximum smoke output: approximately 78,000 cubic feet per minute
 DMX channels: 11
 Net weight: 20.5kg
 Machine size: 562x417x278 mm

SKU: 66411



Smoke machine 1500W

Use voltage: AC 220V, 50 HZ, 10A
 Power: 1500W
 Output: 40000cuft/min
 Warm-up time: 4 Min
 Oil drum volume: 3.0 L
 Control method: remote control, DMX-512, OLED control
 DMX channel value: 1
 Net weight: 9.25 KG
 Machine size: 525mmX350mmX233mm

SKU: 66408



FOG



LED Air Column Smoke Machine

Using voltage: AC 220V, 50/60HZ, 10A
 Power: 1500W
 Output: 6000cuft/min
 Preheating time: 4Min
 Oil barrel volume: 3L
 Control method: remote control, DMX-512, OLED screen control
 LED color: RGB
 LED type: Single Color
 Total power of single lamp bead: 3W
 Total number of lamp beads: 18 (6 red, green and blue)
 DMX channel value: 8
 Machine size: 460x320x235mm

SKU: 66410



600w Double Haze Machine

Voltage: AC 220V-240V 50/60Hz
 Limiting insurance: 5A/250V
 Power: 600W
 Tank Volume: 1.7L
 3 Fans angle: Adjustable
 Output of the wind turbine regulation: Support
 DMX-512: Support
 Controller: LCD controller LCD controller
 Preheating time: 0 second set-up time
 Product size: LW H 460x320x300 mm

SKU: 66379



HAZE



Haze machine 550W

SKU: 66409

Using Voltage AC 220V ,50/60HZ,7A
 Power 550W
 Output 6000cuft/min
 Preheating time 1Min
 Oil drum volume 0.8L
 Control Remote control, network port, digital tube control
 DMX channel: 2
 Product weight 3.9KG
 Machine size 332x160x258MM



HAZE



Hanging Type Haze Machine

Voltage: AC 110~240V 50/60HZ
 Power: 1000W
 Warm-up time: 30 sec
 Control: DMX512/ Remote control/Manual
 Use consumables: Water based haze liquid
 Capacity of oil tank: 2L
 Size: 440x340x340mm

SKU: 917



HAZE



Haze machine 1500W

SKU: 66407

Using voltage AC 220V ,50/60HZ
 Fuse: 10A,250V
 Power: 1500W
 Preheating time 1Min
 Maximum output fuel consumption: about 60 min/L
 Screen type: OLED
 Control method DMX-512 control remote control
 DMX channel value: 2
 Net weight: 12KG
 Machine Size: 480*343*280mm
 Function: keep the smoke coming



HAZE



Oil Based Haze Machine

Voltage: AC 110-240V 50/60HZ
 Power: 650W
 Re-heating time: 0 second
 Capacity of oil tank: 2.5L
 Control: DMX-512, remote control, Manual
 Machine size: 590x450x450mm
 NW: 23KG

SKU: 918



HAZE



Haze machine 2000W

SKU: 66406

Using voltage AC 220V ,50/60HZ,10A
 Power 2000W
 Output 16000cuft/min
 Preheating time 1Min
 Oil drum volume 6L
 Control method remote control DMX-512 OLED control
 DMX channel value: 2
 Net weight: 18KG
 Machine size: 517.5x260x220mm



HAZE



Hand Confetti Machine

Voltage: AC110~240V 50/60HZ
 Confetti capacity: 0.5kg
 Control: Manual
 Use consumables: Bullion paper/Color paper
 Gas: Co2/N2
 Weight: 7kg
 Size: 970x300x210mm

SKU: 906



Confetti



LED RGB 6x3W CO2 Gun

Spray Height: 6-7 meters

SKU: 66121



RGB



LED Electric Confetti Machine

Voltage: AC110-240V 50/60HZ
 Power: 1236W
 Control: DMX 512, remote control
 Height of ejection: 6-8M
 DMX Channel: 7
 Confetti capacity: 0.5KG
 Size: 280x280x550mm
 NW: 8KG

SKU: 907



Light



Confetti



CO2 LED CONFETTI GUN

Spray distance: 6-8 meters
 Control mode: manual (lithium-ion battery)
 with lamp high- voltage
 Tube length: 3 meters
 Weight: 5 kg
 Size: 760 x355 x270 mm, (3 meters tube)

SKU: 66413



LED RGB CO2 Machine

LEDs: 12x3w RGB 3 in 1
 Voltage: AC220/110V 50/60HZ
 Power: 250W
 Control: DMX512, remote control
 DMX channels: 9
 Column height: 8-10 m
 Machine Size: 310x310x430 mm
 Weight: 7.0KG

SKU: 664



RGB



IP20



LED CO2 GUN

Control: manual control
 Power: 35W
 Color: 7 color
 Jet distance: 6-7 m net
 Weight: 4.5 kg
 Size: 660x245 x350mm

SKU: 66414



Power Supplies

Metal 5V output



Watts	200W	300W
Input Voltage	220V	220V
Output Voltage	DC:5V	DC:5V
Current	40A	60A
Material	Metal	Metal
Dimension	190x80x30mm	190x80x30mm

SKU: 6191 200W 3800156661912

SKU: 6192 300W 3800156661929



DC 5V



IP20

Accessories



4G Module

for LED Multimedia Players

4G module can be used for all Optonica multimedia players. The 4G module, combined with external Sim card, enables you to access you're Optonica multi media player even when there is no Wi-Fi or LAN network available by using the 4G network. The compact module is plug and play, no further drivers are required.

- 4G module
- Access media player anywhere anytime
- Antenna included

SKU: 949



IP20



Wireless DMX512 receiver transmitter system

Terminal: XLR, DMX512

Connection: 2.4Ghz wireless signal transmission

Encoding: 126 auto-synchronizing channels

Frequencies: 16 individual frequencies allowing operation of several transmitters simultaneously.

Range: Distance up to 700m

SKU: 66378



IP20

Light Sensor

for Brightness Adjustment

Accessory light probe with the following features:

- Monitor the brightness of the environment to achieve automatic adjustment of screen brightness.
- Connect the sending card and sending box, asynchronous card or multi-function card.
- Marking the 5 meter line, can be extended to 100 meters;
- In the outdoor use, three defense;
- No external power supply is required.



SKU: 951



IP20



OPTONICA COMFORT PRODUCTS



WiFi E27 SMART CAMERA BULB

Video resolution: HD
Frame rate: 25fps
View angle: 360 degrees (Horizontal)
90 degrees (Vertical)
Motion detection: About 5 meters
Night vision: About 5 meters
Max memory: Up to 128Gb (Not Include)
App: JXLCAM

SKU: 227



E27



IP20



WiFi SMART CAMERA BULB

Video resolution: HD
Frame rate: 25fps
View angle: 360 degrees (Horizontal)
90 degrees (Vertical)
Motion detection: About 5 meters
Night vision: About 5 meters
Max memory: Up to 128Gb (Not Include)
App: JXLCAM

SKU: 244



EU Plug Socket




IP20



Window cleaning
Robot



Window cleaning
Robot



Cleaning speed 2 minutes / m2
Power 80W
Size 300x150x120mm
Cleaning Modes 3 modes

SKU: 757



Cleaning speed 2 minutes / m2
Power 80W
Size 250x250x9.5mm
Cleaning Modes 3 modes
UPS 20min

SKU: 758



Air Purifier & Humidifier

Breathe Cleaner and Healthier Air

7 Stage Air Purification + Humidifier
UV Lamp and IONIZER + WIFI

CADR(PM2.5)	450m ³ /h
Power	85W
Area	~50 m ²
Size	400x230x620mm
Purification	Pre-filter, Cold-catalyst, Formaldehyde removal filter (Honeycomb activated carbon filter Optional), Antibacterial filter, UV Sterilization, HEPA filter, Anion release.
SKU: 733	3800156607330



Air Purifier

Breathe Cleaner and Healthier Air

6 Stage Air Purification
UV Lamp and IONIZER

CADR(PM2.5)	150m ³ /h
Power	43W
Area	~30 m ²
Size	330x180x505mm
Purification	Cold-catalyst, Formaldehyde removal filter (Honeycomb activated carbon filter Optional), Antibacterial filter, UV Sterilization, HEPA filter, Anion release.
SKU: 731	3800156607316



Air Purifier & Humidifier

Breathe Cleaner and Healthier Air

6 Stage Air Purification + Humidifier
UV Lamp and IONIZER

CADR(PM2.5)	300m ³ /h
Power	65W
Area	~38 m ²
Size	360x195x565(mm)
Purification	Cold-catalyst, Formaldehyde removal filter (Honeycomb activated carbon filter Optional), Antibacterial filter, UV Sterilization, HEPA filter, Anion release.
SKU: 732	3800156607323



Air Purifier

Breathe Cleaner and Healthier Air

7 Stage Air Purification
UV Lamp and IONIZER

CADR(PM2.5)	320m ³ /h
Power	80W
Area	~40 m ²
Size	370x195x605mm
Purification	Pre-filter, Cold-catalyst, Formaldehyde removal filter (Honeycomb activated carbon filter Optional), Antibacterial filter, UV Sterilization, HEPA filter, Anion release.
SKU: 734	3800156607347





LED FLOOR LIGHT
20W - Remote Control



Watts	20W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	500lm	Dimension	130x1045 mm
Beam Angle	120°	Dimmable	YES

SKU: 237
RGB+3000K

DIY modular assembly
Multiple mode changes



LED FLOOR LIGHT
17W - Remote Control



Watts	17W	CRI	Ra>80
Input Voltage	AC : 220-240V	IP Rating	IP20
Flux	400lm	Dimension	φ23.5x1462 mm
Beam Angle	120°	Dimmable	YES

SKU: 238
RGB+3000K

DIY modular assembly
Multiple mode changes



LED FLOOR LIGHT 5V
8W - Remote Control



* AC Adapter NOT Included

Watts	8W	CRI	Ra>80
Input Voltage	DC 5V 2A	IP Rating	IP20
Flux	220lm	Dimension	Φ30x1047 mm
Beam Angle	120°	Dimmable	YES

SKU: 239
RGB+6000K

DIY modular assembly
Multiple mode changes



POWER BANK - WATERPROOF
10000 mAh



Battery: 10000MAh
Rated Power: 37Wh/3.7V
Input Micro :5V/2A
Input Type-C: 5V/3A
Output USB1/2 t: 5V/3A
Output Type-C : 5V/3A
Solar Panel:1.2W
Size: 159*78*19.5mm
Flashlight:2W LED

SKU: 7691 Black Body



POWER BANK - WATERPROOF
20000 mAh



Battery: 20000MAh
Rated Power: 74wh/3.7V
Input Micro :5V/2A
Input Type-C: 5V/3A
Output USB1/2 t: 5V/3A
Output Type-C : 5V/3A
Solr Panel:1.2W
Product Size: 167*86*33.5mm
Flashlight:4w Led

SKU: 7692 Black Body



POWER BANK
10000 mAh



Battery: 10000mAh
Rated Power: 3.7V/37Wh
Input Micro :1 DC 5V/2A | 9V/2A | 12V/1.5A
Input Type-C :2 DC 5V/3A | 9V/2A | 12V/1.5A
Output1 Type-C DC 5V/3A | 9V/2A | 12V/1.5A
Output2 USB-A/B DC 4.5V/5A | 5V/4A | 9V/2A
Product Size: 140*69*15.5mm

SKU: 7693 White Body
SKU: 7694 Black Body

PD 22.5W



POWER BANK
20000 mAh



Battery: 20000mAh
Rated Power: 3.7V/74Wh
Input Micro :1 DC 5V/2A | 9V/2A | 12V/1.5A
Input Type-C :2 DC 5V/3A | 9V/2A | 12V/1.5A
Output1 Type-C DC 5V/3A | 9V/2A | 12V/1.5A
Output2 USB-A/B DC 4.5V/5A | 5V/4A | 9V/2A
Product Size: 140*69*27.5mm

SKU: 7695 Black Body

PD 22.5W

SMART CAMERA ROBOTIC VACUUM CLEANER

SKU: 752




BRUSHLESS VACUUM MOTOR+ROLLER BRUSH

Clean thoroughly



1 Side Brush	2 Power Button	3 Camera	4 Power Switch
5 Glass Cover	6 Anti-drop Sensor	7 Charging Connect	8 Universal Wheel
9 Battery Cover	10 Wheel	11 Roller Brush	12 Mop

Working Time Per Charge: 80-120mins



ANTI-DROP SENSORS

Keep machine safety away from stairs

ANTI-COLLISION SENSORS

Effective protect machine and furniture



EASY CLIMBING

Moves over thresholds

GO TO CLEAN UNDER THE FURNITURE

Without omission



AUTOMATIC CHARGING

Back to charging dock automatically when battery is low

BREAKPOINT RESUME OPERATION

After charging, machine returns to breakpoint, continue to clean the remaining area.



SMART GYRO ROBOTIC VACUUM CLEANER

SKU: 753



**GYROSCOPE NAVIGATION
MULTIPLE CLEANING MODES**

AUTO CLEANING ROBOTIC VACUUM CLEANER

SKU: 754



ROADROVER WHEELS

Climbing ability reach 2cm
With cross-country wheel,
Easy go crossing the obstacle



10 PAIRS OF INFRARED ANTI-COLLISION SENSORS



AUTOMATIC DOCK AND CHARGING



STRONG SUCTION

Up to 1000PA, no dust can hide from it



VARIOUS GROUND TYPE APPLICATION

Suitable for various floor type, low pile carpet, tile, wood floor, etc



**Portable Party Bluetooth Speaker
2x8.0 inch**

Output Power: 20W RMS / 400W P.M.P.O
Version BT : V5.0+EDR
Function: BT/FM/USB/TF/AUX/MIC IN/TWS
Built-in USB MP3 Player
Remote Control
Woofer : 8"*2
Channel : Stereo
Signal to noise ratio : ≥80dB
MIC input
AUX 3.5mm Input
USB charging : DC 5V
Charging Time : 5-6 Hours
Playtime : 2-4 Hours
Battery capacity : 2400mAh
Size : 250x245x615mm



SKU: 9551



**Portable Party Bluetooth Speaker
2x8.0inch**

Output Power: 2x20W RMS / 800W P.M.P.O
Version BT : V5.2+EDR
Function: BT/FM/USB/TF/AUX/MIC IN/TWS
Built-in USB MP3 Player
Remote Control
Woofer : 8"*2
Channel : Stereo
Signal to noise ratio : ≥80dB
2 pcs Wireless MIC
AUX 3.5mm Input
Charging : DC 9V
Charging Time : 5-6 Hours
Playtime : 2-4 Hours
Battery capacity : 7.4V 3600mAh
Size : 315x277x667mm



SKU: 9553



**Portable Party Bluetooth Speaker
15 inch**

Output Power: 2x20W RMS / 800W P.M.P.O
Version BT : V5.0+EDR
Function: BT/FM/USB/TF/AUX/MIC IN/TWS
Built-in USB MP3 Player
Remote Control
Woofer : 15"
Channel : Stereo
Signal to noise ratio : ≥80dB
Wireless MIC
AUX 3.5mm Input
Charging : DC 9V
Charging Time : 5-6 Hours
Playtime : 2-4 Hours
Battery capacity : 7.4V 3000mAh
Size : 420x330x610mm



SKU: 9552



**Portable Party Bluetooth Speaker
2x3.0inch**

Output Power: 2x6W RMS / 150W P.M.P.O
Version BT : V5.0
Function: BT/FM/USB/TWS
Woofer : 3"*2
Signal to noise ratio : ≥80dB
5 Lighting Modes
Built-in USB MP3 Player
USB charging : DC 5V
Charging Time : 5-6 Hours
Playtime : 2-4 Hours
Battery capacity : 1200mAh
Size : 128x128x280mm



SKU: 9554


Charging Hub
USB 5xTYPE-A and 1xTYPE-C

Type-C Port Output:
 5.0V DC, 3.0A
 9.0V DC, 2A 12V DC, 1.5A, Max.18W

USB Output (A1):
 5.0V DC, 3A, Max. 15W
 9.0V DC, 2A, Max.18W
 12V DC, 1.5A, Max 18W

USB Output (A2/A3/A4/A5):
 5.0V DC, 2.4A, Max. 24W
 All Ports Total - 42W Max



SKU: 7641

5 in 1 Type-C Hub

1*HDMI 4K60Hz
 2* USB 3.0
 1*LAN Ethernet port
 1*PD USB-C



SKU: 9521



SKU: 9522

4 in 1 Type-C Hub

1*HDMI 4K30Hz
 1* USB 3.0
 1*LAN Ethernet port
 1*PD USB-C


Multi-Charger USB HUB
USB 4xTYPE-A and 1xTYPE-C

Type-C Port Output:
 5.0V DC, 3.0A
 9.0V DC, 2.2A 12V DC, 1.67A, Max.18W

USB Output (A1):
 5.0V DC, 3A, Max. 15W
 9.0V DC, 2A, Max.18W
 12V DC, 1.5A, Max 18W

USB Output (A2/A3/A4):
 5.0V DC, 2.4A, Max. 12W
 All Ports Total - 32W Max



SKU: 7642

1000 Mbps Gigabit Lan to USB-A Adapter
Aluminum


SKU: 9523



SKU: 9524

1000 Mbps Gigabit Lan to USB-C Adapter
Aluminum

Power Extension Cord
4x Sockets and 2xUSB TYPE-A

Power Supply : 220-240V
 Current: Max. 16A
 Schuko Sockets: 4
 USB Ports: 2xUSB Type A
 USB Charger Output: 5VDC/2.1A
 Cable Length: 1.4m(3x1.5mm²)



SKU: 7643

USB 3.0 Type-A to 4*USB3.0 HUB
Plastic
 4* USB 3.0


SKU: 9525


USB 3.0 Type-C to 4*USB3.0 HUB
Plastic
 4* USB 3.0


SKU: 9526



3 in 1 Wireless Charging Station
Apple iPhone/AirPods/iWatch
Samsung Phone/Buds/Watch



Wireless Charging IP20

3-in-1 Wireless Charging

Compact Design

Phone Stand

SKU: 9500 For iPhone
SKU: 9501 For Samsung

3 in 1 Multifunction Desk Lamp
Wireless Charging



Wireless Charging IP20

3-in-1 Wireless Charging

Phone Stand

SKU: 9512 Black Body

6 in 1 Multi-function Charging Station
Match multiple devices



Wireless Charging IP20

for phone for iWatch for AirPods

SKU: 9502 Black Body
SKU: 9503 White Body

3 USB Quick Charger
36W Max Power PD + 3USB



IP20

quick charge 3 USB ports PD 20W smart chip

SKU: 9510 Black Body
SKU: 9511 White Body

Wireless Charger Pad
Qi Standard



Compact Design Wireless Charging IP20

● Universal input: 5.0V=2A Universal output: 5.0V 1A
● Fast charge input: 9.0V 2A Fast charge output: 9.0V 1.2A

SKU: 9508 Black Body
SKU: 9509 White Body

Car Wireless Charger Stand
36W Max Power




Wireless Charging IP20

10W Wireless charging Steady Large area induction coil

SKU: 9506 Gold Body
SKU: 9507 Silver Body

Wireless Charging Clock supports iOS and Android



SKU: 9514 Clock

Solar Portable Bluetooth Speaker + Lamp
Solar Panel Power: 5V/3.5W



- SOS Emergency Light
- Power Bank Function
- USB Ports

Battery
3.7V 6Ah

SKU: 223
CCT
6000K 4500K 3000K



Bluetooth FM Transmitter Car Charger With MP3 Player

SKU: 9504 FM Transmitter



3 in 1 Magnetic USB Cable
Type-C, Micro USB, For Apple



SKU: 9516 Charging Cable

Solar Portable Bluetooth Speaker + Lamp
Solar Panel Power: 5V/3.5W



- SOS Emergency Light
- Power Bank Function
- USB Ports

Battery
3.7V 6Ah


SKU: 224
CCT
6000K 4500K 3000K



CCT Selfie Ring Light
10W 5V USB - Dimmable



Watts 10W
Input Voltage 5V USB
Flux 800lm
Beam Angle 120°
Dimmable YES



SKU: 9515 Selfie Ring Light



Solar Portable Bluetooth Speaker + Lamp
Solar Panel Power: 5V/3.5W



- SOS Emergency Light
- Power Bank Function
- USB Ports

Battery
3.7V 6Ah

SKU: 228
CCT
6000K 4500K 3000K





Travel Adaptor - UK to EU

Cooper

Input Voltage	AC : 250V	IP Rating	IP20
Working Current	10A Max	Dimension	35x35x68 mm
Material	Cooper	Body Color	White

SKU: 9517



Travel Adaptor - UK to EU

Iron

Input Voltage	AC : 250V	IP Rating	IP20
Working Current	10A Max	Dimension	35x35x68 mm
Material	Iron	Body Color	White

SKU: 9518



CABLE FOR POWER SUPPLY
0.75mm 2PIN

SKU: 6040



100cm



CABLE FOR POWER SUPPLY
0.75mm 3PIN

SKU: 6041



100cm



CABLE FOR POWER SUPPLY
0.75mm 3PIN

SKU: 6042



100cm



SKU: 7601 - 3 Sockets 1.5m 16A
SKU: 7602 - 3 Sockets 3m 16A



SKU: 7607 - 3 Sockets 1.5m 16A
SKU: 7608 - 3 Sockets 3m 16A



SKU: 7613 - 4 Sockets 5m 16A



SKU: 7614 - 6 Sockets 10m 16A



SKU: 7603 - 4 Sockets 1.5m 16A
SKU: 7604 - 4 Sockets 3m 16A



SKU: 7609 - 4 Sockets 1.5m 16A
SKU: 7610 - 4 Sockets 3m 16A



SKU: 7615 - 3 Sockets 1.5m 16A



SKU: 7616 - 5 Sockets 1.5m 16A



SKU: 7605 - 5 Sockets 1.5m 16A
SKU: 7606 - 5 Sockets 3m 16A



SKU: 7611 - 5 Sockets 1.5m 16A
SKU: 7612 - 5 Sockets 3m 16A



SKU: 7617 - 3 Sockets 3m 16A



SKU: 7618 - 5 Sockets 3m 16A

Reel: 1000W(4.35A)
Unreel: 3200W(13.91A)



SKU: 7623 - 4 Sockets 25m 16A

Reel: 1100W(4.8A)
Unreel: 3200W(13.91A)



SKU: 7624 - 4 Sockets 10m 16A



IP44

SKU: 7631 - Schuko Male 16A



IP44

SKU: 7632 - Schuko Female 16A



IP44

SKU: 7625 - 2 Sockets 5m 16A



IP44 Timer

SKU: 7626 - 2 Sockets 5m 16A



SKU: 7633 - Schuko Male 16A



SKU: 7634 - Schuko Female 16A



SKU: 7635 - 2 Sockets Adapter 16A



IP44

SKU: 7637 - 2 Sockets Adapter 16A




SKU: 7621 - 1 Sockets 10m 16A
SKU: 7622 - 1 Sockets 20m 16A



SKU: 7636 -3 Sockets 16A

SKU:	Page No.	SKU:	Page No.						
15126	244	15838	344	15898	348	66230	515	5611-M	112
15127	244	15839	344	16302	297	66302	484	5612-M	112
15128	244	15840	344	16701	116	66304	530	5624-M	112
15129	244	15841	344	16702	116	66305	517		
15130	243	15842	344	16703	117	66351	511		
15131	243	15843	344	16704	117	66352	531		
15401	311	15844	344	16705	116	66362	527		
15402	311	15845	344	16706	116	66364	472		
15511	107	15846	344	16707	117	66366	484		
15512	107	15847	344	16708	117	66367	482		
15513	107	15848	345	16709	116	66368	482		
15514	107	15849	345	16710	116	66371	516		
15515	107	15850	345	16711	117	66372	521		
15516	107	15851	345	16712	177	66373	521		
15517	107	15852	345	66018	474	66374	520		
15518	107	15853	345	66019	474	66375	521		
15519	107	15854	345	66020	475	66376	520		
15541	106	15855	345	66021	484	66377	520		
15542	106	15856	345	66022	472	66378	545		
15544	106	15857	345	66023	485	66379	540		
15545	106	15858	345	66025	478	66400	516		
15547	106	15859	346	66026	478	66401	495		
15548	106	15860	346	66027	478	66402	495		
15801	342	15861	346	66028	478	66403	495		
15802	342	15862	346	66102	516	66404	494		
15803	342	15863	346	66103	510	66405	494		
15804	342	15864	346	66104	517	66406	541		
15805	342	15865	346	66106	510	66407	541		
15806	342	15866	346	66107	509	66409	541		
15807	342	15867	346	66108	527	66410	539		
15808	342	15868	346	66109	509	66411	539		
15809	342	15869	346	66110	509	66412	539		
15810	342	15870	346	66120	517	66413	543		
15811	342	15871	346	66121	543	66414	543		
15812	342	15872	346	66122	514	66415	530		
15813	342	15873	346	66123	514	66416	511		
15814	342	15874	347	66124	515	66417	511		
15815	342	15875	347	66125	515	66420	483		
15816	343	15876	347	66126	514	66421	483		
15817	343	15877	347	66127	505	66436	526		
15818	343	15878	347	66173	480	66437	526		
15819	343	15879	347	66201	485	66438	533		
15820	343	15880	347	66202	485	66439	533		
15821	343	15881	347	66203	485	66440	533		
15822	343	15882	347	66206	482	66441	534		
15823	343	15883	347	66207	482	66442	508		
15824	343	15884	347	66208	482	66443	508		
15825	343	15885	347	66208	526	66444	508		
15826	343	15886	347	66209	477	66445	532		
15827	343	15887	347	66211	488	66447	498		
15828	343	15888	347	66212	488	66488	487		
15829	343	15889	348	66213	499	66489	498		
15830	343	15890	348	66214	496	66490	498		
15831	349	15891	348	66215	489	66491	494		
15832	349	15892	348	66216	489	66492	499		
15833	349	15893	348	66217	496	66494	496		
15834	349	15894	348	66218	489	66496	485		
15835	349	15895	348	66222	531	66502	488		
15836	349	15896	348	66225	531	66503	499		
15837	344	15897	348	66226	510				





OPTONICA

www.optonicaled.com